



Version General Specifications Version 13

Issue 1, Jan-2013



Document Summary

Document Item	Current Value
Document Title	Version 13, GS1 General Specifications
Date Last Modified	Jan-2013
Current Document Issue	Issue 1
Status	Ratified
Document Description	The GS1 General Specifications are the core standards document describing how barcodes and identification keys should be used to comply with GS1 standards. They are used throughout the GS1 System.

Disclaimer

WHILST EVERY EFFORT HAS BEEN MADE TO ENSURE THAT THE GUIDELINES TO USE THE GS1 STANDARDS CONTAINED IN THE DOCUMENT ARE CORRECT, GS1 AND ANY OTHER PARTY INVOLVED IN THE CREATION OF THE DOCUMENT HEREBY STATE THAT THE DOCUMENT IS PROVIDED WITHOUT WARRANTY, EITHER EXPRESSED OR IMPLIED, REGARDING ANY MATTER, INCLUDING BUT NOT LIMITED TO THE OF ACCURACY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND HEREBY DISCLAIM ANY AND ALL LIABILITY, DIRECT OR INDIRECT, FOR ANY DAMAGES OR LOSS RELATING TO OR RESULTING FROM THE USE OF THE DOCUMENT. THE DOCUMENT MAY BE MODIFIED, SUBJECT TO DEVELOPMENTS IN TECHNOLOGY, CHANGES TO THE STANDARDS, OR NEW LEGAL REQUIREMENTS. SEVERAL PRODUCTS AND COMPANY NAMES MENTIONED HEREIN MAY BE TRADEMARKS AND/OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE COMPANIES. GS1 IS A REGISTERED TRADEMARK OF GS1 AISBL.

Log of Changes in GS1 General Specifications

Gens Specs Change Notifications	Impact on Section	Summary of Change
Errata	1	Deletion of out of date / incorrect sections / statement
GSCN for 09-092 GSCN for 09-092 GSCN for 09-138 GSCN for 10-300 GSCN for 11-129 GSCN for 11-154 GSCN for 12-176 GSCN for 12-181 GSCN for 12-231	2	Packaging Component ID Managing Multiple Bar Codes Patient & Caregiver ID National Healthcare Reimbursement Number Clarify the use of GRAI for ordering Errata updates for GLN 'Party' changes Patient & Caregiver Short Name Updates Add the word 'Primary' to GTIN Allocation Rule 2.4 Updates for Global Coupon Number
GSCN for 09-092 GSCN for 09-138 GSCN for 10-300 GSCN for 11-173 GSCN for 11-212 GSCN for 12-092 GSCN for 12-176 GSCN for 12-191 GSCN for 12-231	3	Packaging Component ID Patient & Caregiver ID National Healthcare Reimbursement Number Allowable Character Set Day of Month 70 Series text clarification Patient & Caregiver Short Name Updates AI for Local Region Updates for Global Coupon Number
GSCN for 09-092 GSCN for 09-092 GSCN for 09-138 GSCN for 10-300 GSCN for 11-129 GSCN for 11-131 GSCN for 12-176 GSCN for 12-191 GSCN for 12-231	4	Packaging Component ID Managing Multiple Bar Codes Patient & Caregiver ID National Healthcare Reimbursement Number Clarify the use of GRAI for ordering AI Data Titles Patient & Caregiver Short Name Updates AI for Local Region Updates for Global Coupon Number

Gens Specs Change Notifications	Impact on Section	Summary of Change
GSCN for 09-092 GSCN for 09-138 GSCN for 11-068 GSCN for 11-069 GSCN for 11-141 GSCN for 11-142 GSCN for 11-173 GSCN for 12-023 GSCN for 12-176 GSCN for 12-178	5	Managing Multiple Bar Codes Patient & Caregiver ID Bar Code Conformance Global Verification Template Updates Symbol Specification Tables for GS1 DataBar in General Distribution GS1 DataBar and ISO alignment Allowable Character Set 2D Verification Template Patient & Caregiver Short Name Updates EAN/UPC Symbol Height
GSCN for 09-092 GSCN for 11-068	6	Managing Multiple Bar Codes Bar Code Conformance
GSCN for 10-300 GSCN for 11-068 GSCN for 11-173	7	Bar Code Conformance Allowable Character Set National Healthcare Reimbursement Number
GSCN for 09-092 GSCN for 09-092 GSCN for 09-138 GSCN for 10-300 GSCN for 12-176 GSCN for 12-191 GSCN for 12-231	8	Packaging Component ID Managing Multiple Bar Codes Patient & Caregiver ID National Healthcare Reimbursement Number Patient & Caregiver Short Name Updates AI for Local Region Updates for Global Coupon Number

Who Should Read These Specifications

Technical experts working with the GS1 System should read these specifications. They provide a global reference document covering all technical aspects of the GS1 System. Their primary objective is to define the international standard upon which individual GS1 Member Organizations can develop user documentation.

Electronic Data Interchange

The use of Electronic Data Interchange (EDI) is an integral part of the GS1 System philosophy. Full details on the EDI standards are contained in EANCOM and GS1 XML. EANCOM is an implementation guideline of the EDIFACT standards (Electronic Data Interchange for Administration, Commerce and Transport) developed under the auspices of the United Nations.

Navigator

These specifications have been developed as a reference document aimed primarily at GS1 Member Organisations (who also produce local language user manuals) and system engineers developing software based upon GS1 System standards. All aspects of the GS1 System are summarized in Section 1, which is recommended for those wishing to become familiar with the GS1 System logic and terminology.

Each application section mandates the use of system features defined elsewhere in this document, such as Check Digits, Element Strings, data carriers, and bar code symbol placement.

The sections of these GS1 General Specifications are:

- **Section 1. Basics and Principles of the GS1 System:** Provides an introduction to the core components of the GS1 System
- **Section 2 Application Identification:** Provides a definition for each GS1 application using a template format. Each application is uniquely identified and contains a description, the associated GS1 Key, its definition and links to relevant data structures and attributes (Section 3), rules (Section 4), carrier specifications (Section 5), placement (section 6), and unique processing requirements (Section 7).
- **Section 3 GS1 Application Identifier Definitions:** Describes the meaning, structure, and function of the GS1 element strings so they can be correctly processed in users' application programs
- **Section 4 Application Rules:** Provides the rules for use of GS1 Keys in their application environments. Differences in industries are included as well as the data relationship rules for Application Identifier use.
- **Section 5 Data Carriers:** Provides a detailed description of the data carriers that are endorsed by GS1. It includes symbol specification tables for use in the supply chain operational environment as well as the related bar code production and quality assessment required to achieve excellent scan rates.
- **Section 6 Symbol Placement Guidelines:** Provides guidance on symbol placement as well as transport label standards and tag standards
- **Section 7 AIDC Validation Rules:** Provides rules for validating and processing GS1 Element Strings without human intervention. Check digit and calendar date algorithms are also included.
- **Section 8 GS1 Standards Glossary of Terms:** A standard vocabulary used throughout the GS1 System

Table of Contents

1. Basics and Principles of the GS1 System	13
1.1. The GS1 General Specifications	14
1.1.1. Introduction	14
1.1.2. Who Should Read These Specifications	14
1.1.3. Foundational Standards	15
1.1.4. Maintenance Responsibility and Management	15
1.1.5. The BarCodes Technology Group (BTG)	15
1.2. GS1 System Principles	15
1.3. Identification System Policies	15
1.3.1. Mandatory Identifiers	15
1.3.2. Non-GS1 Identifiers	15
1.3.3. GS1 Company Prefix	16
1.3.4. Carrier Independence	16
1.3.5. GS1 Business Messages	16
1.4. GS1 Prefixes, GS1-8 Prefixes and GS1 Company Prefixes	16
1.4.1. Global, Open Versus Restricted	16
1.4.2. GS1 Prefixes	17
1.4.3. GS1-8 Prefixes	17
1.4.4. GS1 Company Prefix	18
1.5. GS1 Company Prefix Allocation	18
1.6. Allocation	19
1.6.1. Acquisitions and Mergers	19
1.7. Sunrise and Sunset Dates	20
2. Application Identification	21
2.1. Trade Items	22
2.1.1. Introduction	22
2.1.2. Fixed Measure Trade Items – Open Supply Chain	25
2.1.3. Fixed Measure – Trade Items Packed in Several Physical Units NOT Scanned at POS	51
2.1.4. Fixed Measure - Direct Part Marking	52
2.1.5. Variable Measure Trade Items Not Crossing a Point-of-Sale	56
2.1.6. Fixed Measure – Restricted Distribution	63
2.1.7. Variable Measure Trade Items Scanned at POS	70
2.1.8. Trade Item Extended Packaging	73
2.2. Logistic Units	75
2.2.1. Individual Logistic Units	76
2.2.2. Multiple Logistic Units – Global Identification Number for Consignment	78
2.2.3. Multiple Logistic Units – Global Shipment Identification Number	79
2.3. Assets	80
2.3.1. Global Returnable Asset Identifier (GRAI): AI (8003)	80
2.3.2. Global Individual Asset Identifier (GIAI): AI (8004)	82
2.4. Locations	83
2.4.1. Introduction	83

2.4.2.	For communication between trading partners, a GLN should be used following the rules defined in Section 4.EDI and Global Data Synchronization (GDS).....	84
2.4.3.	Application Overview.....	84
2.4.4.	Global Location Number to Identify a Physical Location: AI (414).....	86
2.4.5.	Ship to – Deliver to Global Location Number: AI (410).....	87
2.4.6.	Bill to - Invoice to Global Location Number: AI (411).....	88
2.4.7.	Purchased from Global Location Number: AI (412).....	89
2.4.8.	Ship for - Deliver for - Forward to Global Location Number: AI (413).....	90
2.4.9.	Global Location Number of the Invoicing Party: AI (415).....	92
2.5.	Service Relationships.....	93
2.5.1.	Global Service Relation Number – Provider: AI (8017).....	93
2.5.2.	Global Service Relation Number – Recipient: AI (8018).....	94
2.5.3.	Service Relation Instance Number: AI (8019).....	96
2.6.	Special Applications.....	96
2.6.1.	Coupons.....	96
2.6.2.	Allocating GS1 System Coupon Data.....	97
2.6.3.	Coupon Identification for Restricted Geographic Distribution (GS1 Prefix 99).....	97
2.6.4.	GS1 Common Currency Coupon Identification (GS1 Prefixes 981 to 983).....	99
2.6.5.	GS1 US Coupon Code Identification for Use in North America (U.P.C. Prefix 5).....	101
2.6.6.	GS1 US Coupon Extended Bar Code: AI (8100 - 8102).....	102
2.6.7.	Coupon Code Identification for Use in North America (AI 8110).....	103
2.6.8.	Refund Receipts.....	104
2.6.9.	Electronic Serial Identifier for Cellular Mobile Telephones (CMTI): AI (8002).....	105
2.6.10.	Payment Slips.....	106
2.6.11.	Customer Specific Articles.....	109
2.6.12.	Custom Trade Item.....	114
2.6.13.	Global Document Type Identifier for Document Control.....	116
2.6.14.	Internal Applications Using GS1-128 Symbology.....	122
2.6.15.	Digital Coupons.....	122
2.6.16.	Consumer Trade Item Production Control.....	124
3.	GS1 Application Identifier Definitions.....	127
3.1.	Introduction.....	128
3.2.	GS1 Application Identifiers in Numerical Order.....	128
3.3.	GS1 Application Identifiers starting with digit 0.....	133
3.3.1.	Identification of a Logistic Unit: AI (00).....	133
3.3.2.	Identification of a Fixed Measure Trade Item (GTIN): AI (01).....	134
3.3.3.	Identification of a Variable Measure Trade Item (GTIN): AI (01).....	135
3.3.4.	Identification of Fixed Measure Trade Items Contained in a Logistic Unit: AI (02).....	136
3.3.5.	Identification of Variable Measure Trade Items Contained in a Logistic Unit: AI (02).....	136
3.4.	GS1 Application Identifiers starting with digit 1.....	137
3.4.1.	Batch or Lot Number: AI (10).....	137
3.4.2.	Production Date: AI (11).....	138
3.4.3.	Due Date for Amount on Payment Slip: AI (12).....	138
3.4.4.	Packaging Date: AI (13).....	139

3.4.5.	Best Before Date: AI (15)	140
3.4.6.	Expiration Date: AI (17)	140
3.5.	GS1 Application Identifiers starting with digit 2	141
3.5.1.	Product Variant: AI (20)	141
3.5.2.	Serial Number: AI (21)	142
3.5.3.	Secondary Data for Specific Health Industry Products: AI (22)	142
3.5.4.	Additional Product Identification Assigned by the Manufacturer: AI (240)	143
3.5.5.	Customer Part Number: AI (241)	143
3.5.6.	Made-to-Order Variation Number: AI (242)	144
3.5.7.	Packaging Component Number: AI (243)	144
3.5.8.	Secondary Serial Number: AI (250)	145
3.5.9.	Reference to Source Entity: AI (251)	145
3.5.10.	Global Document Type Identifier (GDTI): AI (253)	146
3.5.11.	GLN Extension Component: AI (254)	147
3.5.12.	Global Coupon Number (GCN): AI (255)	147
3.6.	GS1 Application Identifiers starting with digit 3	148
3.6.1.	Variable Count: AI (30)	148
3.6.2.	Trade Measures: AIs (31nn, 32nn, 35nn, 36nn)	148
3.6.3.	Logistic Measures: AIs (33nn, 34nn, 35nn, 36nn)	150
3.6.4.	Kilograms per Square Metre: AI (337n)	151
3.6.5.	Count of Trade Items Contained in a Logistic Unit: AI (37)	151
3.6.6.	Amount Payable - Single Monetary Area: AI (390n)	152
3.6.7.	Amount Payable and ISO Currency Code: AI (391n)	153
3.6.8.	Amount Payable for a Variable Measure Trade Item – Single Monetary Area: AI (392n) ...	153
3.6.9.	Amount Payable for a Variable Measure Trade Item and ISO Currency Code: AI (393n) ..	154
3.7.	GS1 Application Identifiers starting with digit 4	155
3.7.1.	Customer's Purchase Order Number: AI (400)	155
3.7.2.	Global Identification Number for Consignment (GINC): AI (401)	155
3.7.3.	Global Shipment Identification Number (GSIN): AI (402)	156
3.7.4.	Routing Code: AI (403)	157
3.7.5.	Ship to - Deliver to Global Location Number: AI (410)	157
3.7.6.	Bill to - Invoice to Global Location Number: AI (411)	158
3.7.7.	Purchased from Global Location Number: AI (412)	158
3.7.8.	Ship for - Deliver for - Forward to Global Location Number: AI (413)	159
3.7.9.	Identification of a Physical Location - Global Location Number: AI (414)	160
3.7.10.	Global Location Number of the Invoicing Party: AI (415)	160
3.7.11.	Ship to - Deliver to Postal Code within a Single Postal Authority: AI (420)	161
3.7.12.	Ship to - Deliver to Postal Code with Three-Digit ISO Country Code: AI (421)	161
3.7.13.	Country of Origin of a Trade Item: AI (422)	162
3.7.14.	Country of Initial Processing: AI (423)	162
3.7.15.	Country of Processing: AI (424)	163
3.7.16.	Country of Disassembly: AI (425)	163
3.7.17.	Country Covering Full Process Chain: AI (426)	164
3.7.18.	Country Subdivision of Origin Code for a Trade Item: AI (427)	164
3.8.	GS1 Application Identifiers starting with digit 7	165

3.8.1.	Seven Series AIs - Cautionary Note	165
3.9.	GS1 Application Identifiers starting with digit 8.....	170
3.9.1.	Roll Products - Width, Length, Core Diameter, Direction, Splices: AI (8001)	170
3.9.2.	Cellular Mobile Telephone Identifier: AI (8002).....	171
3.9.3.	Global Returnable Asset Identifier (GRAI): AI (8003)	172
3.9.4.	Global Individual Asset Identifier (GIAI): AI (8004)	172
3.9.5.	Price per Unit of Measure: AI (8005).....	173
3.9.6.	Identification of the Components of a Trade Item: AI (8006)	173
3.9.7.	International Bank Account Number (IBAN): AI (8007).....	174
3.9.8.	Date and Time of Production: AI (8008).....	174
3.9.9.	Global Service Relation Numbers (GSRN): AIs (8017, 8018)	175
3.9.10.	Service Relation Instance Number (SRIN): AI (8019).....	176
3.9.11.	Payment Slip Reference Number: AI (8020).....	177
3.9.12.	GS1-128 Coupon Extended Bar Code: AIs (8100 - 8102).....	177
3.9.13.	Coupon Code Identification for Use in North America (AI 8110)	178
3.9.14.	Extended Packaging URL: AI (8200)	178
3.10.	GS1 Application Identifiers starting with digit 9.....	179
3.10.1.	Information Mutually Agreed Between Trading Partners: AI (90)	179
3.10.2.	Company Internal Information: AIs (91 - 99)	179
3.11.	Compatibility of EPCglobal Tag Data Standard and GS1 General Specifications	180
4.	Application Rules and Management Practices.....	181
4.1.	Introduction.....	182
4.2.	Rules for Keys	182
4.2.1.	GTIN Rules.....	182
4.2.2.	SSCC Rules	183
4.2.3.	Assets Rules.....	183
4.2.4.	GLN Rules.....	183
4.2.5.	GSRN Rules	183
4.3.	GTIN Rules.....	184
4.3.1.	Allocating the Numbers	184
4.4.	SSCC Rules	191
4.4.1.	Allocating Serial Shipping Container Codes	191
4.5.	Allocating GS1 System Asset Identifiers.....	192
4.5.1.	General Rule	192
4.5.2.	Change of Asset Ownership.....	193
4.5.3.	Information Associated with Asset Identifiers.....	194
4.6.	GLN Rules.....	194
4.6.1.	Allocating Global Location Numbers	194
4.6.2.	Information Associated with a Global Location Number	196
4.6.3.	GLN Allocation Rules	196
4.7.	GSRN Rules.....	196
4.7.1.	Allocating Global Service Relation Numbers	196
4.8.	GDTI Rules.....	198
4.8.1.	Application Rules.....	198

4.9.	GINC Rules	199
4.9.1.	Allocating Global Identification Numbers for Consignment.....	199
4.10.	GSIN Rules	199
4.10.1.	Allocating Global Shipment Identification Numbers	199
4.11.	GCN Rules	200
4.11.1.	Allocating Global Coupon Numbers	200
4.12.	Data Relationships	200
4.12.1.	Invalid Pairs of Element Strings	200
4.12.2.	Mandatory Association of Element Strings	202
4.13.	Human Readable Interpretation (HRI) Rules	205
4.13.1.	Healthcare Human Readable Interpretation Rules	207
4.13.2.	Manual Date Marking	209
4.14.	Multiple Bar Code Management Practices for Consumer Trade Items (cross-sector)	209
4.14.1.	Multiple Bar Code Management Practices for Consumer Trade Items (All Sectors).....	209
4.14.2.	GS1 Multiple Bar Code Management Practice for General Retail	210
4.14.3.	GS1 Multiple Bar Code Management Practices for Healthcare	210
5.	Data Carriers.....	216
5.1.	Introduction.....	217
5.1.1.	International Standards	219
5.1.2.	Symbology Identifiers	220
5.2.	Linear Bar Codes - EAN/UPC Symbology Specifications.....	221
5.2.1.	Symbology Characteristics.....	221
5.2.2.	Reference Decode Algorithm	232
5.2.3.	Human Readable Interpretation	236
5.3.	Linear Bar Codes - ITF-14 Symbology Specifications	245
5.3.1.	Symbology Characteristics.....	245
5.4.	Linear Bar Codes - GS1-128 Symbology Specifications	252
5.4.1.	GS1-128 Symbology Characteristics	252
5.4.2.	GS1-128 Bar Code Structure	253
5.4.3.	GS1-128 Symbology Character Assignments.....	254
5.4.4.	Dimensional Requirements	262
5.4.5.	Reference Decode Algorithm	262
5.4.6.	Symbol Quality	265
5.4.7.	GS1-128 Symbology Application Parameters.....	266
5.5.	Bar Code Production and Quality Assessment.....	269
5.5.1.	Introduction.....	269
5.5.2.	GS1 System Symbol Specification Tables.....	270
5.5.3.	Bar Code Production	292
5.6.	Linear Bar Codes – GS1 DataBar.....	318
5.6.1.	GS1 DataBar	318
5.7.	Two Dimensional Bar Codes – GS1 DataMatrix Symbology.....	331
5.7.1.	Introduction.....	331
5.7.2.	GS1 DataMatrix Features and Symbol Basics.....	332
5.7.3.	GS1 DataMatrix Symbology	333

5.8.	Composite Bar Codes	337
5.8.1.	Composite Symbology Introduction	337
5.8.2.	Symbol Structure	338
5.8.3.	Human Readable Interpretation of Composite Symbols	344
5.8.4.	Data Transmission and Symbology Identifier Prefixes	345
5.8.5.	Width of a Module (X).....	346
5.8.6.	Print Quality	346
5.8.7.	Advice for Selecting a Symbology.....	346
5.8.8.	Sample Composite Symbols	347
5.9.	Two Dimensional Bar Codes – GS1 QR Code Symbology	349
5.9.1.	Introduction.....	349
5.9.2.	GS1 QR Code Features and Symbol Basics	349
5.9.3.	Summary of additional features.....	351
5.9.4.	GS1 QR Code Symbology	352
5.10.	Appendix: Rules for Encoding/Decoding Element Strings in GS1 Symbologies using GS1 Application Identifiers	356
5.10.1.	The Basic Structure of GS1 Bar Codes using GS1 Application Identifiers and Concatenation.....	356
5.10.2.	Concatenation	357
6.	Symbol Placement Guidelines.....	360
6.1.	Introduction.....	361
6.2.	General Placement Principles.....	361
6.2.1.	Number of Symbols.....	361
6.2.2.	Scanning Environment	361
6.2.3.	Orientation	362
6.3.	General Placement Guidelines for Point-of-Sale	365
6.3.1.	Number of Symbols.....	365
6.3.2.	Identifying the Back of the Trade Item	366
6.3.3.	Symbol Placement	366
6.4.	Placement Guidelines for Specific Package Types	370
6.4.1.	Bags	372
6.4.2.	Blister Packs.....	372
6.4.3.	Bottles and Jars.....	373
6.4.4.	Boxes.....	374
6.4.5.	Cans and Cylinders	375
6.4.6.	Carded Items	375
6.4.7.	Egg Cartons.....	376
6.4.8.	Jugs	377
6.4.9.	Large, Heavy, or Bulky Items	377
6.4.10.	Multipacks.....	379
6.4.11.	Publishing Items	380
6.4.12.	Thin Items or Containers	382
6.4.13.	Trays.....	383
6.4.14.	Tubes.....	383
6.4.15.	Tubs.....	384

6.4.16.	Unpackaged Items	385
6.4.17.	Sets (Grouping of Individually Bar Coded Items)	387
6.4.18.	Sporting Goods	388
6.4.19.	Textured Surfaces	399
6.5.	Symbol Placement for Clothing and Fashion Accessories	399
6.5.1.	Information Zones Concept	400
6.5.2.	Hangtag (Hanging Label) Format	401
6.5.3.	Sewn-On (Joker) Label Format	403
6.5.4.	Sewn-In Label Formats	405
6.6.	Plastic Packaged Products Label Location Guidelines	406
6.6.2.	Boxed Products Label Formats	408
6.6.3.	Banded Products Label Formats	411
6.7.	GS1 Logistics Label Design	413
6.7.1.	Scope	413
6.7.2.	Concepts	413
6.7.3.	Label Design	414
6.7.4.	Technical Specifications	415
6.7.5.	Label Examples	416
6.7.6.	EPCglobal Seal Application Guidelines	420
6.8.	Placement Labels Used in General Distribution	420
6.8.1.	General Rule	421
6.8.2.	Recommendation to Include a Bar Code on Two Sides	423
6.8.3.	Add-On Symbols	424
6.9.	Symbol Placement for Regulated Healthcare Trade Items	425
6.9.1.	Blister Cells	425
6.9.2.	Products Requiring Variable Data On Primary and Secondary Packaging	425
7.	AIDC Validation Rules	426
7.1.	Introduction	427
7.2.	Synopsis of Message Processing	428
7.2.1.	Analysis of the Data Carrier and Plausibility Test for Element Strings	429
7.2.2.	Symbology Identification	430
7.2.3.	Prefix in Internal Table	430
7.2.4.	Item Identification	430
7.2.5.	Application Identifier (AI) in Internal Table	430
7.2.6.	Length of Data 14 Digits	430
7.2.7.	Check Digit Calculation and other system checks	430
7.2.8.	Move Element String to Message Field	431
7.3.	Validation of the Electronic Message Regarding System Consistency	431
7.4.	Validation of the Electronic Message Regarding User Requirements	432
7.5.	Conversion of Weights and Measures in User Applications	433
7.6.	Linkage of GTINs in a Database	434
7.6.1.	The Principle	435
7.6.2.	Extended Example of a Trade Item Hierarchy	435
7.6.3.	Linkage of GTINs in a Non-Relational Database by Trade Item Manufacturer	436

7.7.	Elements Strings Represented in Data Carriers	437
7.7.1.	Element Strings Represented in GS1 System Data Carriers.....	437
7.7.2.	Element Strings Represented in a GS1 Symbology using GS1 Application Identifiers	439
7.8.	Secondary Data for specific Health Industry Products	439
7.9.	Processing of Data from a GS1 Symbology using GS1 Application Identifiers	441
7.9.1.	General.....	442
7.9.2.	Element Strings with Pre-Defined Lengths Using Application Identifiers.....	442
7.9.3.	The Function 1 Symbol Character (FNC1).....	442
7.9.4.	National Healthcare Reimbursement Number (NHRN)	442
7.10.	Check Digit Calculations	443
7.10.1.	Standard Check Digit Calculations for GS1 Data Structures	443
7.10.2.	Check Digit Calculation for Price/Weight Fields.....	444
7.10.3.	Check Digit Calculation for the Four-Digit Price Field.....	445
7.10.4.	Check Digit Calculation for the Five-Digit Price Field	445
7.11.	GTIN-12 and RCN-12 in a UPC-E Bar Code	446
7.12.	The GS1 Subset of International Standard ISO/IEC 646.....	448
7.13.	Determination of Century in Dates	449
8.	GS1 Standards Glossary of Terms.....	450
8.1.	GS1 Glossary Terms and Definitions.....	451
8.2.	GS1 Abbreviations	463
8.3.	Legacy (Retired) Terms	464



1. **Basics and Principles of the GS1 System**

- The GS1 General Specifications
- GS1 System Principles
- Identification System Policies
- GS1 Prefixes, GS1-8 Prefixes and GS1 Company Prefixes
- GS1 Company Prefix Allocation
- Allocation
- Sunrise and Sunset Dates

WHILST EVERY EFFORT HAS BEEN MADE TO ENSURE THAT THE GUIDELINES TO USE THE GS1 STANDARDS CONTAINED IN THE DOCUMENT ARE CORRECT, GS1 AND ANY OTHER PARTY INVOLVED IN THE CREATION OF THE DOCUMENT HEREBY STATE THAT THE DOCUMENT IS PROVIDED WITHOUT WARRANTY, EITHER EXPRESSED OR IMPLIED, REGARDING ANY MATTER, INCLUDING BUT NOT LIMITED TO THE OF ACCURACY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND HEREBY DISCLAIM ANY AND ALL LIABILITY, DIRECT OR INDIRECT, FOR ANY DAMAGES OR LOSS RELATING TO OR RESULTING FROM THE USE OF THE DOCUMENT. THE DOCUMENT MAY BE MODIFIED, SUBJECT TO DEVELOPMENTS IN TECHNOLOGY, CHANGES TO THE STANDARDS, OR NEW LEGAL REQUIREMENTS. SEVERAL PRODUCTS AND COMPANY NAMES MENTIONED HEREIN MAY BE TRADEMARKS AND/OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE COMPANIES. GS1 IS A REGISTERED TRADEMARK OF GS1 AISBL.

1.1. The GS1 General Specifications

1.1.1. Introduction

The GS1 System originated in the United States and was established in 1973 by the Uniform Product Code Council, known until recently as the Uniform Code Council, Inc. (UCC) and since 2005 as GS1 US. The UCC originally adopted a 12-digit identification number, and the first ID numbers and bar codes in open trade were being scanned in 1974. Following the success of this U.P.C. System, the European Article Numbering Association, previously known as EAN International, but launched as GS1 in 2005, was established in 1977 to develop a compatible system for use outside North America. The EAN System was designed as a superset of the UCC System and principally used 13-digit numbers. As a consequence of using certain bar codes and data structures, the GS1 System has expanded.

The GS1 System provides for the use of unambiguous numbers to identify goods, services, assets, and locations worldwide. These numbers can be represented in bar codes to enable their electronic reading wherever required in business processes. The system is designed to overcome the limitations of using company, organisation, or sector specific coding systems, and to make trading much more efficient and responsive to customers.

These identification numbers are also used in Electronic Data Interchange (EDI), XML electronic messaging, Global Data Synchronization (GDSN), and GS1 Network Systems. This document provides information about syntax, assignment, allocation and Automatic Data Capture (ADC) standards for GS1 identification numbers.

In addition to providing unique identification numbers, the GS1 System provides for supplementary information, such as best before dates, serial numbers, and batch numbers, which can appear in bar code form. Currently, bar codes are used as the data carriers, but other technologies, such as radio frequency tags are being developed within EPCglobal as carriers of GS1 data. Changes take place only after wide consultation and are subject to a significant migration period.

By following the principles and design of the GS1 System, users can design applications to process GS1 System data automatically. The system logic guarantees that data captured from GS1 endorsed bar codes produces unambiguous electronic messages, and processing can be fully pre-programmed.

The GS1 System is designed for use in any industry or trade sector, and any changes to the system are introduced so as not to negatively affect current users.

In February 2005, GS1 was officially launched as the successor to the organisations previously known as EAN and UCC. This document is the concise definition and explanation of the use of the GS1 System standards within Automatic Identification and Data Capture (AIDC) technologies, and supersedes all previous AIDC technical documents provided and/or published by GS1 or its predecessor organisations. The document takes immediate effect as the agreed GS1 foundational standards including Application, Identification, and Data Carrier components and principles. Every organisation using GS1 System standards is requested to conform fully to the *GS1 General Specifications*.

1.1.2. Who Should Read These Specifications

The primary audiences of the *GS1 General Specifications* are GS1 Member Organisations and technically oriented users and suppliers.

These specifications provide a global reference document covering all technical aspects of the GS1 System. Their primary objective is to define the international standard upon which individual GS1 Member Organisations can develop user documentation. They are maintained in English and translated into local language by Member Organisations.

1.1.3. Foundational Standards

These *GS1 General Specifications* are the foundation for GS1 Electronic Messaging:

- Electronic Data Interchange (EDI)
- XML
- GDSN
- Net Solutions

The definitions in the *GS1 General Specifications* are the foundation of the [GS1 Global Data Dictionary](#).

1.1.4. Maintenance Responsibility and Management

The GS1 Global Standards Management Process (GSMP) is the mechanism to approve the adoption of additions and changes to the *GS1 General Specifications*. The process is fully defined in the [Global Standards Management Process Manual](#).

1.1.5. The BarCodes Technology Group (BTG)

The BarCodes Technology Group (BTG) provides advice and guidance from the solution provider community regarding practical implementation issues and technical applications. In addition, BTG provides expertise for testing and trial implementations.

1.2. GS1 System Principles

The GS1 System embodies an open architecture approach. It has been carefully designed for modular expansion with minimal disruption to existing applications. Enterprise Resource Planning (ERP) and other supply chain application software drive implementation of the system. New user driven applications can be expected, and this document will be updated accordingly.

The maintenance of these specifications will be the responsibility of GS1 and will be in line with the [GS1 Architecture Principles](#).

1.3. Identification System Policies

The GS1 identification system provides the world a globally unique and unambiguous identification system for physical entities, parties, and relationships exchanged in the supply chain. The policies that follow apply to all sectors making use of the GS1 Company Prefix in association with GS1 Keys and the Application Identification System. These policies provide for the long term integrity of the GS1 identification system so vital to the global supply chain.

1.3.1. Mandatory Identifiers

All GS1 standards shall incorporate GS1 identification standards as mandatory identifiers exclusive of all other mandatory identifiers.

1.3.2. Non-GS1 Identifiers

Non-GS1 identifiers may only be used with GS1 standards as additional identifiers (not alternates).

Implementations using non-GS1 identifiers as primary identifiers are not compliant with GS1 standards.

1.3.3. GS1 Company Prefix

The GS1 Company Prefix is used exclusively within GS1 identification standards that may be expressed in GS1 approved bar code applications, in GS1 eCom messages, for global data synchronization, network registration, and in EPC Tags within the header values reserved for the GS1 System. See Section 1.5 for further details on the GS1 Company Prefix Allocation.


1.3.4. Carrier Independence

GS1 Identification Keys are defined and utilized per GS1 definitions independent of data carrier (e.g., bar code, Radio Frequency Identification (RFID), business message).

1.3.5. GS1 Business Messages

GS1 business messages or GS1 standards-based applications use GS1 Identification Keys for identification exclusive of GS1 data carrier features. Examples of data carrier features include use of:

- Modulo 103 GS1-128 Symbol Check Character to secure data capture
- Function 1 Symbol Character (FNC1) in the second position of GS1-128 Bar code or an Electronic Product Code (EPC) header value to discriminate between GS1 data content and data carrier overhead
- FNC1 as separator character or EPC parsing value to parse a decoded data string into significant data parts

 **Exception:** If an EPC user is using GS1 System and non-GS1 System headers to support an application, this policy does not apply, and advice should be sought on the use of EPC headers to provide uniqueness among multiple numbering systems.

1.4. GS1 Prefixes, GS1-8 Prefixes and GS1 Company Prefixes

1.4.1. Global, Open Versus Restricted

1.4.1.1. Global, Open Numbers (Unrestricted Distribution)

Global, Open is an identification number used in unrestricted distribution which signifies that such system data may be applied on goods to be processed anywhere in the world without restraint as to such things as country, company, and industry.

1.4.1.2. Restricted Circulation Numbers

Restricted Circulation Numbers are GS1 identification numbers used for special applications in restricted environments, defined by the local GS1 Member Organisation (e.g., restricted within a country, company, or industry). They are allocated by GS1 for either internal use by companies or to GS1 Member Organisations for assignment based on business needs in their country (e.g., Variable Measure Trade Item identification, coupons).

- RCN-12 is a 12-digit Restricted Circulation Number
- RCN-13 is a 13-digit Restricted Circulation Number
- RCN-8 is an 8-digit Restricted Circulation Number beginning with GS1-8 Prefix 0 or 2.

A Variable Measure Number identifies Variable Measure Trade Items for scanning at the Point of Sale. It is defined per GS1 Member Organisation rules.

- VMN-12 is a 12-digit Restricted Circulation Number encoded in UPC-A Symbols to allow scanning of Variable Measure Trade Items at the Point-of-Sale. It is defined per target market specific rules that are associated with U.P.C. Prefix 2.
- VMN-13 is a 13-digit Restricted Circulation Number encoded in EAN-13 Symbols to allow scanning of Variable Measure Trade Items at the Point-of-Sale. It is defined per target market specific rules that are associated with GS1 Prefixes 20 through 29.

1.4.2. GS1 Prefixes


The GS1 Prefix is a number with two or more digits, administered by the GS1 Global Office, which is allocated to GS1 Member Organisations or for Restricted Circulation Numbers. The main purpose of the GS1 Prefix is to allow decentralisation of the administration of identification numbers.

GS1 Prefixes are shown in Figure 1.4.2 – 1

Figure 1.4.2 – 1

Synopsis of GS1 Prefixes	
GS1 Prefixes	Significance
000 - 019	GS1 Prefix* (used to create U.P.C. Company Prefixes)
02	GS1 Variable Measure Trade Item identification for restricted distribution
030 - 039	GS1 Prefix
04	GS1 restricted circulation number within a company
05	GS1 US coupon identification
060 - 099	GS1 Prefix (used to create U.P.C. Company Prefixes)
100 - 139	GS1 Prefix
140 - 199	Reserve
20 - 29	GS1 restricted circulation number within a geographic region
300 - 969	GS1 Prefix
970 - 976	Reserve
977	ISSN standard numbering (serial publications)
978 - 979	ISBN standard numbering (books)
980	GS1 identification of Refund Receipts
981-984	GS1 coupon identification for common currency areas
985 - 989	Reserved for further GS1 coupon identification
99	GS1 coupon identification

* Starting from GS1 Company Prefix 00 00100 to avoid collision with GTIN-8 Identification Numbers.

 **Note:** GS1 Company Prefixes 00 00000 and 00 01000 to 00 07999 have specific application for Locally Assigned Codes (LACs) or Retailer Zero-Suppressed Codes (RZSCs).

1.4.3. GS1-8 Prefixes

The GS1-8 Prefix is a one-, two-, or three-digit index number, administered by GS1, that is allocated to GS1 Member Organisations for the creation of GTIN-8s or for Restricted Circulation Numbers. GS1-8 Prefixes are only ever used to create GTIN-8s or RCN-8s.

GS1-8 Prefixes are shown in Figure 1.4.3 – 1

Figure 1.4.3 – 1

Synopsis of GS1-8 Prefixes	
GS1-8 Prefixes	Significance
0	Velocity Codes
100 - 139	GS1 Prefix
140 - 199	Reserve
2	GS1 restricted circulation number within a company
300 - 969	GS1 Prefix
97 - 99	Reserve

1.4.4. GS1 Company Prefix

The GS1 Company Prefix is a part of GS1 data structures. It consists of a GS1 Prefix, which is administered by GS1, and a Company Number, which is assigned by a GS1 Member Organisation.

1.5. GS1 Company Prefix Allocation

A GS1 Company Prefix gives access to all the applications using GS1 System identification standards.

The GS1 Company Prefix may not be sold, leased, or given, in whole or in part, for use by any other company. This restriction applies to all GS1 Identification Keys even those which are constructed without a GS1 Company Prefix. This requirement applies to GS1 Identification Keys which have been assigned individually by a GS1 Member Organisation to an individual user company.

See Section 1.6. for additional guidelines in the following sections apply when a company changes legal status as a result of an acquisition, merger, partial purchase, split, or “spin-off.”

A GS1 Company Prefix assigned to a member of any Member Organisation entitles that member to create any of the GS1 Identification Keys:

- Global Trade Item Number (GTIN)
- Global Location Number (GLN)
- Serial Shipping Container Code (SSCC)
- Global Returnable Asset Identifier (GRAI)
- Global Individual Asset Identifier (GIAI)
- Global Service Relation Number (GSRN)
- Global Document Type Identifier (GDTI)
- Global Shipment Identification Number (GSIN)
- Global Identification Number for Consignment (GINC)
- Global Coupon Number (GCN)

1.6. Allocation

The normal requirements on the re-use of GS1 identification numbers apply to all organisations at all times. The additional guidelines in the following sections apply when a company changes legal status as a result of an acquisition, merger, partial purchase, split, or “spin-off.”

GS1 Member Organisations may adapt the following guidelines if the law of the country makes it absolutely necessary.

Companies should notify their GS1 Member Organisation of any legal status change within one year of that change to facilitate a smooth transition.

1.6.1. Acquisitions and Mergers

If a company is being acquired by or merged with another company and has stock on hand, the stock's existing Global Trade Item Numbers (GTINs) should be kept. Products that are produced after the acquisition or merger may keep the GTIN allocated before the acquisition if the acquiring company maintains the GS1 Member Organisation membership.

A merger implies that someone has taken over a company and has assumed responsibility for the company's GS1 Company Prefix as well as their assets and locations. Products that the acquired company produced under its GS1 Company Prefix can still be produced using the same prefix after the merger, since the acquiring company has control of the acquired company's GS1 Company Prefix.

If it so desires, the acquiring company can label all acquired products using their existing GS1 Company Prefix. The importance of ensuring trading partners are informed of any changes in a timely manner cannot be overemphasized. A company should be careful when centralizing the allocation of all numbers under one GS1 Company Prefix, thus changing the GTIN of the existing products, which are otherwise unchanged. Centralizing the allocation of all numbers under a single GS1 Company Prefix should be an exception, as it results in additional work and data file maintenance for customers.

1.6.1.1. Partial Purchase

If a company purchases a division of a company whose GS1 Company Prefix is used in divisions not purchased, then the acquiring company must change the Global Trade Item Numbers (GTINs) for products in the purchased division as well as any related Global Location Numbers (GLNs), within one year.

The rules concerning the use of the seller's GTINs and other GS1 Identification Keys should be taken into consideration when drawing up the purchase contract.

At the earliest opportunity, the buyer should phase in new numbers from its own range of numbers for items whose brand name it has acquired. The buyer will be able to do this, for example, when packaging is redesigned or reprinted.

If a company sells an asset to another company, then the asset identifier should ideally be replaced by another Global Individual Asset Identifier (GIAI) or Global Returnable Asset Identifier (GRAI) within one year or be removed from the physical item.

During a company sale and for four years following the selling company must not reallocate the original numbers to other items.

1.6.1.2. Split or Spin-Off

When a company splits into two or more separate companies it is necessary for each GS1 Company Prefix assigned to the original company to be transferred to only one of the new companies. Any company left without a GS1 Company Prefix will need to apply to a GS1 Member Organisation to obtain one. The decision about which of the new companies should take the original GS1 Company Prefixes should be made in such a way as to minimize the number of additional Global Trade Item

Numbers (GTINs) required. The decision should be part of the legal arrangements of the new companies.

It is not necessary for existing stocks of items to be renumbered. However, when any of the split or spin-off companies has trade items that are numbered with a GS1 Company Prefix that it no longer holds, the company should renumber those items using its own GS1 Company Prefix when new labelling or packaging is produced. Customers should be notified well in advance of the changes.

Split or spin-off companies that retain a GS1 Company Prefix must keep a record of the GTINs created that have been allocated to items they no longer own. They must not re-use these GTINs for a period of at least four years after the company that split away owning those items last supplied goods identified by those GTINs. Therefore, the company that did not retain the GS1 Company Prefix has to keep the company that now maintains it informed of the dates on which goods were last supplied using that GS1 Company Prefix or to guarantee a date by which the number change will be made.

1.7. Sunrise and Sunset Dates

Expansion of both the breadth and reach of the GS1 system requires the introduction of new data carrier technologies and messaging techniques. While these are potentially disruptive, their use in GS1 Global, Open standards requires an agreed date at which they are globally accepted for use. This date is referred to as a Sunrise Date. Its use is accompanied by associated rules that may be unique to the circumstances. A Sunrise Date is agreed by user/members and approved by the GS1 Management Board.

Conversely, as a data carrier or messaging standard is no longer cost effective as determined by users and approved by the GS1 Management Board, it may be declared obsolete and removed from the *GS1 General Specifications*. This is termed the Sunset Date. It is accompanied by associated rules that may be unique to the circumstances.



2. Application Identification

- Trade Items
- Logistic Units
- Assets
- Locations
- Service Relationships
- Special Applications

WHILST EVERY EFFORT HAS BEEN MADE TO ENSURE THAT THE GUIDELINES TO USE THE GS1 STANDARDS CONTAINED IN THE DOCUMENT ARE CORRECT, GS1 AND ANY OTHER PARTY INVOLVED IN THE CREATION OF THE DOCUMENT HEREBY STATE THAT THE DOCUMENT IS PROVIDED WITHOUT WARRANTY, EITHER EXPRESSED OR IMPLIED, REGARDING ANY MATTER, INCLUDING BUT NOT LIMITED TO THE OF ACCURACY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND HEREBY DISCLAIM ANY AND ALL LIABILITY, DIRECT OR INDIRECT, FOR ANY DAMAGES OR LOSS RELATING TO OR RESULTING FROM THE USE OF THE DOCUMENT. THE DOCUMENT MAY BE MODIFIED, SUBJECT TO DEVELOPMENTS IN TECHNOLOGY, CHANGES TO THE STANDARDS, OR NEW LEGAL REQUIREMENTS. SEVERAL PRODUCTS AND COMPANY NAMES MENTIONED HEREIN MAY BE TRADEMARKS AND/OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE COMPANIES. GS1 IS A REGISTERED TRADEMARK OF GS1 AISBL.

2.1. Trade Items

2.1.1. Introduction

A trade item is any item (product or service) upon which there is a need to retrieve pre-defined information and that may be priced, or ordered, or invoiced at any point in any supply chain. This definition covers services and products, from raw materials through to end user products, all of which may have pre-defined characteristics.

The identification and marking of trade items enables the automation of the Point-of-Sale (through Price Look Up (PLU) files), of goods receiving, inventory management, automatic re-ordering, sales analysis, and a wide range of other business applications.

If the item is of variable measure, the respective measure or price information will often be of critical importance to business applications. Attributes relating to trade items (e.g., dates, lot number) are also available as standardised Element Strings.

Each trade item that is different from another in design and/or content is allocated a unique identification number, which remains the same as long as it is traded. The same identification number is given to all trade items sharing key characteristics. Such numbers must be treated in their entirety throughout the supply chain.

The serialised identification of trade items, which enables total connectivity of information and communication systems, is achieved through the use of Application Identifier AI (01) GTIN and AI (21) Serial Number.

Different standard solutions apply depending on the nature of the item and the scope of the user's applications. The following sections determine the identification and symbol marking rules applicable to a particular trade item.

2.1.1.1. Physical or Non-Physical Trade Items

Non-physical trade items are usually called services. Services may be identified with standard numbers for open trade applications or in restricted distribution environments.

2.1.1.2. Open or Restricted Distribution

The main benefit of the GS1 System for trade items is that it provides a unique and unambiguous identification number for every trade item, which is applicable worldwide in open environments. In addition, the system provides for other number series that may be exclusively used for restricted distribution (e.g., national use, company internal use). Restricted distribution identification numbers are available to GS1 Member Organisations' members to help them develop solutions applicable within their territory.

2.1.1.3. Fixed or Variable Measure

Fixed Measure Trade Items are those that are always produced in the same version and composition (e.g., type, size, weight, contents, and design). Like a Fixed Measure Trade Item, a Variable Measure Trade Item is an entity with pre-defined characteristics, such as the nature of the product or its contents. Unlike a Fixed Measure Trade Item, a Variable Measure Trade Item has at least one characteristic that varies whilst other characteristics of the trade item remain the same. The variable characteristic may be weight, dimension, number of items contained, or volume information. The complete identification of a Variable Measure Trade Item consists of both an identification number and information about the variable data.

2.1.1.4. General Retail Consumer Trade Item, Regulated Healthcare Retail Consumer Trade Item or Non-Retail Trade Item

Scanning at the Point-of-Sale (POS) is a major application of the GS1 System, and trade items that are intended to cross a Point-of-Sale are subject to specific rules. Scanning of trade items are broken into three groups based on the application and sector.

- **General Retail Consumer Trade Items** use omnidirectional linear bar codes that are read by high-volume Omnidirectional Retail POS scanners or linear hand held scanners. This scanning environment cannot read 2D Matrix symbols.
- **Regulated Healthcare Retail Consumer Trade Items** require 2D Matrix symbols but these cannot be deployed for high-volume Omnidirectional Retail POS. Regulated Healthcare Retail Consumer Trade Items marked with 2D Matrix symbols are intended to be read in lower-volume retail scenarios or hospital pharmacies or in high volume applications such as distribution centres.
- **Non-Retail Trade Items** are any trade item that does not cross Retail POS. Commonly, these trade items will appear in mixed scanning environments (laser, image based, etc.) depending on the application and industry sector. Typical examples include standard trade items groupings, direct part marked items, etc.

2.1.1.5. Books and Serial Publications

Published material (newspapers, magazines, and books) requires special consideration due to the following factors:

- A solution for published material should address the requirement to process returns (sorting and counting) to wholesalers and publishers. This implies the reading of a supplementary number that is not required for item identification.
- The international systems, ISSN and ISBN, already handle the numbering of publications and books.

2.1.1.6. Single Item or Grouping of Items

A trade item may be a single, non-breakable unit or a standard and stable grouping of a series of single items. Such groupings of items may be present in a wide variety of physical forms, such as a fibreboard case, a covered or banded pallet, a film wrapped tray, or a crate with bottles. Trade items consisting of a single unit are identified with a Global Trade Item Number (GTIN). Standard groupings of identical or different units, each identified with a GTIN, are identified with a separate GTIN.

2.1.1.7. Regulated Healthcare Trade Items (RHTI)

Regulated Healthcare Trade Items (RHTI) are pharmaceutical or medical device trade items that are sold or dispensed in a controlled environment such as in a retail pharmacy, hospital pharmacy, etc.

2.1.1.7.1. Marking Levels of Regulated Healthcare Trade Items

For Regulated Healthcare Trade Items (RHTI) three levels of identification have been developed:

- Minimum Level of AIDC Marking
- Enhanced Level of AIDC Marking
- Highest Level of AIDC Marking

The identification solution for each of these levels may differ between the category of “pharmaceuticals” (which includes biologics, vaccines, controlled substances, clinical trial pharmaceuticals, and therapeutic nutritional products) versus the category of “medical devices” (which

includes all classes of medical devices) and may also differ by configuration or packaging level (trade items direct marked, primary packaging, secondary packaging, case/shipper, pallet, logistics unit). The standards in Section [2.1.2.5](#) define the data required by packaging level and by product type. For purposes of AIDC marking the Brand Owner is responsible for determining the proper assignment of each particular regulated healthcare retail consumer trade item to either the pharmaceutical or medical device category in accordance with local regulatory requirements.

2.1.1.7.2. National Healthcare Reimbursement Numbers

National Healthcare Reimbursement Number (NHRN) is the term for identification numbers used on pharmaceutical and/or medical devices, where required by national or regional regulatory organizations, for product registration purposes and/or for the management of reimbursement. For compliance with a national/regional regulatory or industry requirement where the GTIN will not meet the current need, the trade item shall be identified with GTIN and the applicable National Healthcare Reimbursement Number Application Identifier.

See Sections 2.1.2.4, 2.1.2.5 and 3.8.1.6 for a complete description of the structure and rules of use of the Application Identifier for National Healthcare Reimbursement Number (NHRN).

2.1.1.8. Small Medical / Surgical Instruments (Non-Retail Trade Items)

Application Description

Within this application are the rules and recommendations for the direct part marking (DPM) of small medical / surgical instruments for the Automatic Identification and Data Capture (AIDC) management of instruments within the micro-logistics cycle of use, cleaning and sterilization, see section [2.1.4](#).

Small medical / surgical instruments shall be identified with GTIN and AI (21) Serial Number in all future brand owner / source marking cases.

The use of GTIN and AI (21) Serial Number is also preferred for all hospital / instrument owner marking. However, recognizing that some existing in-house legacy systems use GS1 asset identifiers (GIAI or GRAI, see Section [2.3](#)), hospital / instrument owners may use GIAI or GRAI for marking.

At no time should two different identification numbers be marked on a single instrument.

GS1 Key

Definition

- The GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-14 is the 14-digit GS1 Identification Key composed of an Indicator digit (1-9), GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GRAI is the GS1 Identification Key used to identify Returnable Assets. The key is comprised of a GS1 Company Prefix, Asset Type, Check Digit, and optional serial number.
- The GIAI is the GS1 Identification Key used to identify an Individual Asset. The key is comprised of a GS1 Company Prefix and an Individual Asset Reference.

Rules

- All the GTIN Allocation Rules described in Section 4.
- All the GIAI and GRAI Application Rules described in Section 4.

- If the AIDC marking on the instrument can be seen and scanned when placed in the protective packaging after sterilization, the protective packaging will not have to be AIDC marked.

Attributes

Required

When using GTIN-12, GTIN-13, or GTIN-14 to identify a small medical / surgical instrument, to complete the identification the presence of an Element String, AI (21), representing a serial number is mandatory.

To manage GS1 Healthcare data requirements within GS1 EPCglobal RFID tags, see Section 3.11 of the General Specifications and EPCglobal Tag Data Standard.

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

Small Medical / Surgical Instruments (Non-Retail Trade Items) should be marked with GS1 DataMatrix Symbology. See Section 2.1.4 Fixed Measure Direct Part Marking for more detail.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 8, GS1 System Symbol Specification Table 7.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.1.9. Single Trade Items Composed of Several Physical Parts

Because of its physical nature, a trade item may be packed in separate physical parcels. For example, furniture equipment may be composed of several pieces (e.g., a sofa and two armchairs, which cannot be ordered or sold separately). A specific standard solution is available to identify and symbol mark each component of a trade item composed of several physical parts.

2.1.2. Fixed Measure Trade Items – Open Supply Chain

Fixed Measure Trade Items are those that are always produced in the same version and composition (e.g., type, size, weight, contents, design). The identification number identifies the item unambiguously. Every trade item that is different from another in any respect is assigned a separate Global Trade Item Number (GTIN). The GS1 Prefixes 000 to 019, 030 to 039, 060 to 099, 100 to 139, 300 to 969, and 977 to 979 are used for all GTINs described in Section 1.4.

2.1.2.1. General Retail Consumer Trade Items

A General Retail Consumer Trade Item that is intended to be read at high-volume POS. The General Retail Consumer Trade Item must carry a bar code from the EAN/UPC Symbology family and in

limited circumstances (see Note below) a symbol from the GS1 DataBar Retail POS Family*. Therefore, these trade items support only GTIN-8, GTIN-12, or GTIN-13s.

Some Point-of-Sale scanning systems may be able to handle symbologies other than the EAN/UPC Symbology. However, in an open environment, it is not possible to predict the type of scanner that will be used. Therefore, items that may be scanned at Point-of-Sale must be marked with an omni-directional bar code.

* GS1 DataBar has been approved for bilateral use between trading partners from 2010. In 2014 GS1 DataBar becomes an open symbology and all scanning environments must be able to read these symbols. GTIN data string

A GTIN may be an eight, twelve, thirteen or fourteen-digit number as explained in sections [2.1.2](#), [2.1.2.1.3](#), [2.1.2.1.4](#), [2.1.2.1.5](#), [2.1.2.1.6](#), and [2.1.2.4](#) below. These numbers will be unique when they incorporate a GS1 Prefix, GS1-8 Prefix or GS1 Company Prefix as required, and if they are always treated as a data string of numbers plus a final Check Digit. The Check Digit is explained in section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the number is correctly composed.

Figure 2.1.2.1.1 - 1

GTIN	GTIN format
GTIN-8	N7 + C
GTIN-12	N11 + C
GTIN-13	N12 + C
GTIN-14	N13 + C

* N - numeric digit
C - Check Digit

When any of these GTINs is encoded in a data carrier that must encode a fixed-length data string of 14-digits, the GTINs less than 14-digits in length must be prefixed by leading zeroes that simply act as filler characters. The presence or lack of these leading zeroes does not change the GTIN concerned. These series of GTINs may be stored with or without leading zeroes in the same database field, depending on the requirements of the particular application.

Note: A GTIN-12 may start with one, two or three leading zeros. For the list of GS1 Prefix use see Section 1.4.

2.1.2.1.1. GTIN-12 and GTIN-13

Application Description

Figure 2.1.2.1.2 - 1

GTIN-12 / GTIN-13 Data Structure														
GS1 Company Prefix											Item Reference		Check Digit	
	→											←		
(GTIN-13)	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃	
(GTIN-12)	0	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	

The GS1 Company Prefix is allocated by a GS1 Member Organisation to a system user. It makes the ID number unique worldwide but does not identify the origin of the item. GS1 Company Prefixes starting with GS1 Prefixes 000 to 019, 030 to 039, 060 to 099, 100 to 139, 300 to 969, or 977 to 979 in the first three digits are used in this Element String.

The Item Reference is assigned by the system user, who must observe the rules in Section 4.

The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the number is correctly composed.

GS1 Key

Definition

- The GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

All the GTIN Allocation Rules described in Section 4.

Attributes

Required

Not Applicable

Optional

For all the Application Identifiers (AI) that can be used with a GTIN, see Section 3.

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

The data carriers for this Element String are:

- UPC-A Bar Code (carrying a GTIN-12)
- EAN-13 Bar Code (carrying a GTIN-13)
- GS1 DataBar Retail POS Family (carrying GTIN-12 or GTIN-13)*

EAN-13 and UPC-A is generally referenced as a common symbology called EAN/UPC.

The system recognises this Element String by the symbology identifier **JE0** and **Je0*** and the GS1 Prefixes starting with 000 to 019, 030 to 039, 060 to 099, 100 to 139, 300 to 969, or 977 to 979.

The data transmitted from the bar code reader means that one Fixed Measure Trade Item with a GTIN-13 or GTIN-12 has been captured.

*GS1 DataBar has been approved for bilateral use between trading partners from 2010.

In 2014 GS1 DataBar becomes an open symbology and all scanning environments must be able to read these symbols.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 2, GS1 System Symbol Specification Table 1, and Figure 5.5.2.7 - 4, GS1 System Symbol Specification Table 3.

Symbol Placement

All the Symbol Placement Guidelines are defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.2.1.2. GTIN-12 Carried by a UPC-E Bar Code**Application Description**

Only U.P.C. Company Prefixes beginning with zero can be used to construct UPC-E Bar Codes. Distribution of a U.P.C. Company Prefix in this range is restricted to proven need only (e.g., for items whose packaging does not include enough available space to permit the use of any other bar code). Companies with these prefixes are encouraged to manage their finite resource carefully.

Some GTIN-12s beginning with the U.P.C. Prefix 0 may be represented in a small symbol called the UPC-E Bar Code. The GTIN-12 is condensed into a bar code consisting of six symbol character positions. For application processing, the GTIN-12 must be transformed into its full length by the bar code reader software or by the application software. There is no six-digit UPC-E Bar Code.

See Chapter 7.11 for UPC-E Bar Code options.

GS1 Key**Definition**

The 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

All the GTIN Allocation Rules described in Section 4.

Attributes**Required**

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification**Carrier Choices**

The UPC-E Bar Code is a bar code of the EAN/UPC Symbology representing a GTIN-12 in six explicitly encoded digits using zero-suppression techniques.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 2, GS1 System Symbol Specification Table 1.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.2.1.3. GTIN-8

Application Description

The GTIN-8 is available for items whose packaging does not include enough available space to permit the use of an EAN-13 or UPC-A Symbol. GTIN-8s are individually assigned by GS1 Member Organisations on request. Figure 2.1.2.1.3 - 1 shows the data structure of a GTIN-8.

Figure 2.1.2.1.3 - 1

GTIN-8 Data Structure							
GS1-8 Prefix →			← Item Reference				Check Digit
N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈

The GS1-8 Prefix is a one-, two-, or three-digit index number, administered by the GS1 Global Office. It does not identify the origin of the item. GS1 Prefixes 100 to 139 and 300 to 969 in positions N₁ to N₃ are used in this Element String.

The Item Reference is assigned by the GS1 Member Organisation. The GS1 Member Organisations provide procedures for obtaining GTIN-8s.

The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the number is correctly composed.

GS1 Key

Definition

The 8-digit GS1 Identification Key composed of a GS1-8 Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

In addition to the GTIN Allocation Rules described in Section 4, the following guidelines should be observed:

Before deciding to use a GTIN-8 as opposed to a GTIN-13 or GTIN-12, companies, working jointly with their printer, should consider options such as:

- Whether the bar code can be reduced in size (e.g., printed at a lower X-dimension, taking into account the minimum bar code print quality requirements (see Section 5.5)).
- Whether the label or artwork can reasonably be changed to enable the printer's recommended size of a EAN-13 or UPC-A Bar Code or a symbol from the GS1 DataBar Retail POS Family* to be included (e.g., redesigning the label and increasing the label size, especially when the existing label is small in comparison with the pack area, or using an additional label). The label includes the total printed design surface whether or not it is separately affixed.
- Whether a truncated bar code can be used. A truncated bar code (normal length, but reduced in height) may only be used if there is absolutely no possibility of printing a full size bar code. Truncation removes the omni-directional scanning capability. A bar code with excessive truncation will not be of any practical use. Users considering this option should consult their customers to see if an acceptable compromise can be reached.

Pack size constraints allow several possible options:

- The use of a GTIN-8 is authorised when the EAN-13 or UPC-A Bar Code or a symbol from the GS1 DataBar Retail POS Family* in the size required as a result of print quality studies exceeds either 25 percent of the printed label area or 12.5 percent of the total printable area.
- The use of a GTIN-8 is authorised when either the largest side of the printed label is less than 40 centimetres² or the total printable area is less than 80 centimetres².
- The use of a GTIN-8 is authorised on cylindrical products with a diameter less than 3 centimetres.

Attributes**Required**

Not Applicable

Optional

For all the Application Identifiers (AI) that can be used with a GTIN, see Section 3.

Rules

Not Applicable

Data Carrier Specification**Carrier Choices**

The data carriers for a GTIN-8 are the EAN-8 Bar Code or a symbol from the GS1 DataBar Retail POS Family*.

The system recognises this Element String by the symbology identifier **JE4 or Je0*** and by N₁ not being 0 or 2. The data transmitted from the bar code reader means that one Fixed Measure Trade Item with a GTIN-8 has been captured.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 2, GS1 System Symbol Specification Table 1.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.


*GS1 DataBar has been approved for bilateral use between trading partners from 2010.

In 2014 GS1 DataBar becomes an open symbology and all scanning environments must be able to read these symbols.

2.1.2.1.4. Hardcover Books and Paperbacks: ISBN, GTIN-13, and GTIN-12

Application Description

When identifying books and paperbacks a company may identify them in the same manner as any other retail trade items (see Section 2.1.2.1). However, the recommended option is to use the International Standard Book Number (ISBN numbering system). The GS1 Prefixes 978 and 979 have been allocated to ISBN (<http://www.isbn-international.org/>), which allocates numbers from these 'Bookland' prefixes.

- 
Note: ISBNs shall not be allocated to non-book products even if the products are related to a book (e.g., teddy bears, coffee mugs, T-shirts, etc. related to a book launch). Such non-book products shall be identified and bar coded in the same manner as any other retail trade item (see Section 2.1.2.1). A standard grouping of identical book items would normally be identified according to Section 2.1.2.6.2. However, an ISBN may also be used to create a 14-digit GTIN with an Indicator to identify a grouping of identical book items (refer to Section 2.1.2.6.2) provided that the publisher that issues the 14-digit GTIN is a member of a GS1 organisation or is authorised to act through an agreement between its local GS1 Member Organisation and the local organisation representing publishers.

GS1 Key

Definition

The Global Trade Item Number (GTIN) is the GS1 Identification Key used to identify trade items. The key comprises a GS1 Company Prefix, an Item Reference and a Check Digit.

Rules

All the GTIN Allocation Rules described in Section 4.

Attributes

Required

Not Applicable

Optional

Some publishers may wish to communicate additional information in a bar code in order to meet their internal requirements. For example, publishers may wish to include an edition variant (e.g., unchanged reprint, price increase), which is not distinguished by the ISBN, GTIN-13, or GTIN-12. The GS1 System provides an additional two- or five-digit symbol, called an Add-On Symbol that can be included on the item just to the right of the main bar code.

A two-digit or five-digit serial number provides more information about a particular publication of the printed item, but it is not required for the identification of the title itself.

This figure shows the format of a two-digit Add-On:

Figure 2.1.2.1.4 - 1

Supplementary Information
N ₁ N ₂

The supplementary information consists of numeric data of any structure and meaning. It is the publisher's responsibility to define the numbering scheme.

The data carrier for this Element String is the two-digit Add-On Symbol.

The system recognises this Element String by the Symbology Identifier **JE1**. The two-digit Add-On Symbol must be jointly used with a UPC-A, UPC-E or EAN-13 Bar Code. It is never scanned alone, and the data from both bar codes can be used together for processing.

This figure shows the format of a five-digit Add-On:

Figure 2.1.2.1.4 - 2

Supplementary Information				
N ₁	N ₂	N ₃	N ₄	N ₅

The supplementary information consists of numeric data of any structure and meaning. It is the publisher's responsibility to define the numbering scheme.

The data carrier for this Element String is the five-digit Add-On Symbol.

The system recognises this Element String by the Symbology Identifier **JE2**. The five-digit Add-On Symbol must be jointly used with a UPC-A, UPC-E or EAN-13 Bar Code. It is never scanned alone, and the data from both bar codes can be used together for processing.

Rules

Add-On Symbols involve the following constraints:

- They should not contain information that should rightly be looked up using the item's GTIN-13 (or GTIN-12).
- The reading of the Add-On Symbol by the retailer's Point-of-Sale system is optional.
- The use of the Add-On Symbol is the responsibility of each publisher.

Data Carrier Specification

Carrier Choices

Books and paperbacks should be marked with an EAN-13, UPC-A, or UPC-E Bar Code that complies with the print quality specifications applicable to all GS1 System bar codes. The EAN/UPC 2-digit or 5-digit Add-on symbols are options used with the above EAN/UPC symbols.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 2, GS1 System Symbol Specification Table 1.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.4.

Unique Application Processing Requirements

For description of processing requirements, see Section 7.

2.1.2.1.5. Serial Publications: ISSN, GTIN-13, and GTIN-12

Application Description

When identifying serial publications, companies should first attempt to identify them in the same manner as any other trade item: using the GTIN-13 or GTIN-12 Data Structure.

The second option involves using a special GS1 Company Prefix (assigned by a GS1 Member Organisation within its territory), the publication number, and the price of the publication (provided that the national legislation allows this). With this option, the price is placed in clearly defined positions and is directly usable in the country of publication. However, as soon as the item leaves the country, the

price has no direct significance, and the GTIN must be interpreted in a general way without being broken down internally.

The third option is to make use of the ISSN numbering system. The GS1 Prefix 977 is used for encoding the ISSN assigned to a particular item without its Check Digit.

Figure 2.1.2.1.5 - 1

GS1 Prefix	ISSN (without its Check Digit)	Variant	Check Digit
9 7 7	N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀	N ₁₁ N ₁₂	N ₁₃

The variant digits N₁₁ and N₁₂ may be used to express variants of the same title for issues with a different price or to identify different issues of a daily within one week. Normal title takes value 00.

GS1 Key

Definition

The Global Trade Item Number (GTIN) is the GS1 Identification Key used to identify trade items. The key comprises a GS1 Company Prefix, an Item Reference and a Check Digit.

Rules

All the GTIN Allocation Rules described in Section 4.

Attributes

Required

Not Applicable

Optional

Some publishers may wish to communicate additional information in a bar code in order to meet their internal requirements.

A two-digit or five-digit serial number provides more information about a particular publication of the printed item, but it is not required for the identification of the title itself.

This figure shows the format of a two-digit Add-On:

Figure 2.1.2.1.5 - 2

Serial Number Publications
N ₁ N ₂

GS1 recommends the use of the following number assignment:

- Dailies (or more generally publications with several issues a week): The publications of each day of the week are considered separate trade items that must be identified with a separate identification number represented in an EAN-13, UPC-A, or UPC-E Symbol. The two-digit serial number should only be used to represent the applicable week, which, together with the GTIN-13 or GTIN-12, establishes the day within the year.
- Weeklies: Number of the week (01 – 53)
- Bi-weeklies: Number of the first week of the respective period (01 – 53)
- Monthlies: Number of the month (01 – 12)
- Bi-monthlies: Number of the first month of the respective period (01 – 12)

- Quarterlies: Number of the first month of the respective period (01 – 12)
- Seasonal period: First digit = last digit of the year; second digit = 1 spring, 2 summer, 3 autumn, 4 winter
- Bi-annual period: First digit = last digit of the year; second digit = number of the first season of the respective period
- Annuals: First digit = last digit of the year; second digit = 5
- Special intervals: Consecutively numbered from 01 to 99

The serial number is carried by a two-digit Add-On Symbol that is placed to the right of the symbol and parallel to it. The Add-On Symbol must comply with the print quality specifications applicable to all GS1 System bar codes. For example, the X-dimension applied to the main bar code must also be applied to the Add-On Symbol.

Serial publications can also use a five-digit serial number carried by a five-digit Add-On Symbol. The reading of the Add-On Symbol at a Point-of-Sale is optional. The Add-On Symbol must not be used to encode information that should be contained within the Global Trade Item Number (GTIN). The Add-On Symbol provides additional information about a particular publication of a printed item, and it is the publisher’s responsibility to define the numbering scheme.

This figure shows the format of a five-digit Add-On:

Figure 2.1.2.1.5 - 3

Supplementary Information				
N ₁	N ₂	N ₃	N ₄	N ₅

Information that can be encoded in the five-digit Add-On Symbol includes the actual date of issue, in order to differentiate between successive issues.

The five-digit Add-On Symbol is placed to the right of the main bar code and parallel to it. The Add-On Symbol must comply with the print quality specifications applicable to all GS1 System bar codes. For example, the X-dimension applied to the main symbol also must be applied to the Add-On Symbol.

Rules

When using a five-digit Add-On Symbol, a two-digit Add-On Symbol cannot also be used.

Data Carrier Specification

Carrier Choices

Serial Publications should be marked with an EAN-13, UPC-A, or UPC-E Bar Code that complies with the print quality specifications applicable to all GS1 System bar codes. The EAN/UPC 2-digit or 5-digit Add-on symbols are options used with the above EAN/UPC symbols.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.4.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.2.1.6. Trade Item Groupings

Application Description

Two kinds of groupings are defined:

- Pre-defined assortments

A standard trade item grouping that comprises a fixed configuration of two or more different retail consumer items, each identified with a Global Trade Item Number (GTIN). Any change in the configuration of the assortment is considered a new trade item.

- Dynamic assortments

A standard trade item grouping that comprises a fixed count of a changing assortment of two or more different retail consumer trade items, each identified with a unique GTIN. All of the retail consumer trade items and their GTINs will have been communicated to the retailer before trading takes place. The retailer has accepted that the supplier may change the assortment without any prior notice.

GS1 Key

Definition

The Global Trade Item Number (GTIN) is the GS1 Identification Key used to identify trade items. The key comprises a GS1 Company Prefix, Item Reference and Check Digit or a GS1-8 Prefix, Item Reference, and Check Digit

Rules

All the GTIN Allocation Rules described in Section 4. In addition the GTIN-8 is only available for trade item groupings whose packaging does not include available space to permit the use of an EAN-13 or UPC-A Symbol. See section [2.1.2.1.4](#).

Attributes

Required

Not Applicable

Optional

All the Application Identifiers (AI) that can be used with a GTIN (see Section 3).

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

A standard trade item grouping that is intended to cross the Point-of-Sale in a retail outlet must carry a bar code of the EAN/UPC Symbology or GS1 DataBar Retail POS Family*. Therefore, these trade items support GTIN-8s, GTIN-12s or GTIN-13s. Allowable symbols are EAN-8, EAN-13 and UPC-A.

*GS1 DataBar has been approved for bilateral use between trading partners from 2010.

In 2014 GS1 DataBar becomes an open symbology and all scanning environments must be able to read these symbols.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.2.2. Loose Produce Trade Items Scanned at POS**Application Description**

Loose Produce trade items are trade items which may be identified with a GTIN. How the retail POS price is determined by the retailer using the GTIN, point-of-sale (POS) data, and POS processing is left to the discretion of the retailer. From a brand owner's perspective, the trade item is a fixed measure trade item identified with a GTIN with no additional attributes.

GS1 Key**Definition**

- The GTIN-8 is the 8-digit GS1 Identification Key composed of a GS1-8 Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

Reference GTIN Allocation Rules in Section 4

Reference Human Readable Interpretation Rules in Section 4.12

Attributes**Required**

Not applicable

Optional

For all the Application Identifiers (AI) that can be used with a GTIN, see Section 3.

Rules

Not applicable.

Data Carrier Specification**Carrier Choices**

The data carriers for this Element String are:

- UPC-A Bar Code (carrying a GTIN-12)
- EAN-8 Bar Code (carrying GTIN-8)
- EAN-13 Bar Code (carrying a GTIN-13)
- GS1 DataBar Retail POS Family (carrying GTIN-12 or GTIN-13)*

EAN-13 and UPC-A is generally referenced as a common symbology called EAN/UPC.

The system recognises this Element String by the symbology identifier **JE0** and **Je0*** and the GS1 Prefixes starting with 000 to 019, 030 to 039, 060 to 099, 100 to 139, 300 to 969, or 977 to 979.

The data transmitted from the bar code reader means that one Fixed Measure Trade Item with a GTIN-13 or GTIN-12 has been captured.

*GS1 DataBar has been approved for bilateral use between trading partners from 2010.

In 2014 GS1 DataBar becomes an open symbology and all scanning environments must be able to read these symbols.

The GS1 DataBar symbols encode a 14-digit numeric string. When encoding GTIN-8, GTIN-12 or GTIN-13 in GS1 DataBar symbols zero-fill with six, two, or one zeros to the left of the GTIN.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 2, GS1 System Symbol Specification Table 1

Symbol Placement

There are no specified rules for symbol placement on loose produce scanned at POS.

Unique Application Processing Requirements

Not applicable

2.1.2.3. Trade Items Intended for General Distribution and POS

Trade items intended for general distribution and Point-of-Sale scanning must carry a bar code of the EAN/UPC Symbology family. Therefore, these trade items support GTIN-12s or GTIN-13s (see Section [2.1.2.1.14](#)).

2.1.2.4. Healthcare Primary Packaging (Non-Retail Trade Items)

Application Description

Healthcare Primary Packaging trade items are pharmaceutical and medical products or their packages presented to support the Point-of-Care (direct consumption based on right product, dose, and route of administration). Because the product is never scanned at retail POS the use of symbologies beyond EAN/UPC and the use of GTIN-14 data structure is permitted. These products, which may be packaged in a sterile packaging system or in a non-sterile packaging system, are only marked when the package is intended for dispensing to the consumer in a hospital or equivalent facility (e.g. field hospital, nursing home, home healthcare). See Section 4.13.1 (Multiple Bar Code Management Practices for Consumer Trade Items – All Sectors), then 4.13.3 (Multiple Bar Code Management Practices for Healthcare) if the product is intended for scanning at general retail and also must meet regulatory requirements for this application section based on multiple market use.

If an item is a Regulated Healthcare Retail Consumer Trade Item and also a Non-Retail Trade Item then the bar code marking for Regulated Healthcare Retail Consumer Trade Items is required at a minimum.

GS1 Key

Definition

- The GTIN-8 is the 8-digit GS1 Identification Key composed of a GS1-8 Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

- The GTIN-14 is the 14-digit GS1 Identification Key composed of an Indicator digit (1-9), GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

All the GTIN Allocation Rules described in Section 4.

If the regulated healthcare retail consumer trade item to be marked on the Primary Packaging does not also have Secondary Packaging, then the Primary Packaging markings in this section do not apply and are replaced by the required markings in the Secondary Packaging section (2.1.2.5).

Example: a bottle of 50 pharmaceutical tablets (the Primary Package) is not enclosed into a carton (which would represent the Secondary Packaging). In this instance, the Secondary Packaging markings are required on the Primary Packaging level.

If the required AIDC marks are placed directly on the part, then those AIDC marks (e.g., bar code, human readable interpretation) satisfy the requirements for Primary Package marking and those marks are functional (scannable) through the primary packaging, then no additional AIDC marks are required on the Primary Package.

If the product to be marked has Primary Packaging that is a blister pack containing several individual Pharmaceutical items, for instance a blister pack of 12 pills or tablets, the following rules apply:

- GTIN is the only required mark.
- In addition to the GTIN Allocation Rules described in Section 4, see Section 2.1.2.1.2 for rules on deploying GTIN-8.

Attributes

Required

Figure 2.1.2.4 - 1

AIDC Marking level for Regulated Healthcare Trade Items	Key	Batch/Lot Number - AI (10)	Expiration Date – AI (17)	Serial Number – AI (21)	Other
Minimum (Pharmaceutical only)	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	No	No	No	None
Enhanced (med device only)	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	Yes	Yes	No	None
Highest – Pharmaceutical brand owner AIDC marking	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	No	No	No	No
Highest – Medical Device - brand owner AIDC marking	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	Yes	Yes	Yes	Active Potency AI (7004) for Kits with Pharmaceuticals
Highest – Hospital AIDC marking of Pharmaceutical	GTIN-8, GTIN -12, GTIN -13, or GTIN -14	No	Yes, AI (7003) if needed for short life items	Yes	None

AIDC Marking level for Regulated Healthcare Trade Items	Key	Batch/Lot Number - AI (10)	Expiration Date – AI (17)	Serial Number – AI (21)	Other
Highest –Hospital AIDC marking of certain medical devices (see Section 2.1.1.8)	GRAI, AI (8003), or GIAI, AI (8004), is optional if GTIN, AI (01), + Serial Number, AI (21), is not marked on the product.	No	No	GRAI, AI (8003), or GIAI, AI (8004), is optional if GTIN, AI (01), + Serial Number, AI (21), is not marked on the product.	

To manage healthcare data requirements within GS1 EPCglobal RFID tags, see Section 3.11 and the most recent version of the EPCglobal Tag Data Standard.

Optional

For compliance with a national/regional regulatory or industry requirement where the GTIN will not meet the need, a Regulated Healthcare Trade Item may be identified with GTIN and AIs (710), AI (711), and AI (712) National Healthcare Reimbursement Number. See Section 3.8.1.6 for details on the use of AI (710), AI (711), and (712).

Rules

All the GTIN Allocation Rules described in Section 4.

National Healthcare Reimbursement Number AI (710), AI (711), and AI (712) must always be used with the GTIN.

Human Readable Interpretation

For Human-Readable Interpretation Rules see Section 4.12. For HRI Rules specific to Regulated Healthcare Retail Consumer Trade Items, see Section 4.12.1.

Data Carrier Specification

Carrier Choices

Figure 2.1.2.4 - 2

Preferred Option(s) (this is the long-term direction for AIDC marking)	GS1 DataMatrix Symbology GS1-128 Symbology GS1 DataBar Symbology NOTE: If a product package serves multiple markets and in one market the specifications in Section 2.1.2.1 apply, then the specification for 2.1.2.1 must be followed for encoding GTIN (at a minimum) and the rules for use of multiple symbols in Section 5.5 apply.
Option in addition to the bar code	GS1 EPCglobal RFID tag. GS1 expects the bar code as the minimum requirement for packaging however EPC RFID is an approved AIDC carrier which can be deployed in addition to the bar code.
Other Acceptable Options (GS1 strongly supports existing options for symbol marking as a guiding principle and therefore supports all previous AIDC marking specifications)	The following symbols have been permitted by GS1 and therefore could appear on some existing packages. For that reason, GS1 does not want to preclude them as an option, particularly where GTIN without additional data (Minimum ID) is required. With that said, symbols that allow all the data to be concatenated into one symbol are the preferred option:- EAN/UPC Symbology family (UPC-A, UPC-E, EAN-8 and EAN-13) may be used to encode the GTIN-8, GTIN-12 or GTIN-13 Identification. ITF-14 Symbols may be used where printing conditions require the application of a less demanding symbology. It may not be used when attribute information is required. ITF-14 Symbols can encode the GTIN-8, GTIN-12, or GTIN-13 of the item. It is not used to

	<p>encode attribute information.</p> <p>GS1 Composite Component is also used in combination with linear symbols by GS1 and therefore remains a legitimate option however, GS1 DataMatrix is preferred based on its ability to encode all information in one symbol and do so efficiently in terms of print speed and panel size.</p>
--	--

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5 Figure 5.5.2.7 - 7, GS1 System Symbol Specification Table 6.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.2.5. Healthcare Secondary Packaging (Regulated Healthcare Retail Consumer Trade Items)

A Regulated Healthcare Retail Consumer Trade Item (RHRCTI) trade item not intended to be scanned in high volumes per consumer transaction at retail but does require additional data beyond GTIN to support regulatory requirements. This means, these trade items support:

GTIN-8, GTIN-12, or GTIN-13 data structures

GTIN attributes such as Batch/Lot Number, Expiration Dates, or Serial Numbers

May be marked with 2D matrix bar codes that require imaging-based scanners or linear symbologies such as GS1 DataBar or GS1-128.

If an item is a General Retail Consumer Trade Item and Regulated Healthcare Retail Consumer Trade Item then the bar code marking for general retail is required at a minimum.

GS1 Key

Definition

- The GTIN-8 is the 8-digit GS1 Identification key composed of a GS1-8 Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

In addition to the GTIN Allocation Rules described in Section 4, see Section [2.1.2.1.3](#) for rules on deploying GTIN-8.

Attributes

Required

Figure 2.1.2.5 - 1

AIDC Marking level for Regulated Healthcare Trade Items	Key	Batch/Lot Number - AI (10)	Expiration Date – AI (17)	Serial Number – AI (21)	Other
Minimum – Pharmaceutical & medical device	GTIN-8, GTIN-12, or GTIN-13	Yes	Yes	No	None
Enhanced – Pharmaceutical & medical device	GTIN-8, GTIN-12, or GTIN-13	Yes	Yes	No	None
Highest – Brand owner AIDC marking	GTIN-8, GTIN-12, or GTIN-13	Yes	Yes	Yes	Potency AI (7004) (for Pharmaceutical, and for medical device Kits with Pharmaceuticals)
Highest – Hospital AIDC marking of pharmaceuticals	GTIN-8, GTIN-12, or GTIN-13	No	Yes, AI (7003) if needed for short life items	Yes	None
Highest - Hospital AIDC marking of certain medical devices (see Section 2.1.1.8)	GRAI, AI (8003), or GIAI, AI (8004), is optional if GTIN, AI (01), + Serial Number, AI (21), is not marked on the product.	No	No	GRAI, AI (8003), or GIAI, AI (8004), is optional if GTIN, AI (01), + Serial Number, AI (21), is not marked on the product.	

To manage healthcare data requirements within GS1 EPCglobal RFID tags, see Section 3.11 and the most recent version of the EPCglobal Tag Data Standard.

Optional

For compliance with a national/regional regulatory or industry requirement where the GTIN will not meet the need, a Regulated Healthcare Trade Item may be identified with GTIN and AIs (710), AI (711), and AI (712) National Healthcare Reimbursement Number. See Section 3.8.1.6 for details on the use of AIs (710), AI (711), and AI (712).

Rules

National Healthcare Reimbursement Number AI (710), AI (711), and AI (712) must always be used with the GTIN.

Data Carrier Specification

Carrier Choices

See the “Data Carrier Specification Carrier Choices” recommendations on Preferred Options, Options in Addition to the Bar Code and Other Acceptable Options found at the end of Section [2.1.2.4](#).

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5 Figure 5.5.2.7 - 7, GS1 System Symbol Specification Table 6.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.2.6. Trade Items Intended for General Distribution Scanning Only

Every trade item that is different from another in any respect is assigned a unique Global Trade Item Number (GTIN). This includes groupings of retail and non-retail trade items that are also trade items and non-retail single units.

For example, each of the packaging types in Figure 2.1.2.6 - 1, if traded, is assigned a separate GTIN.

Figure 2.1.2.6 - 1

Trade Item	GTIN Numbering Options			
	GTIN-8	GTIN-12	GTIN-13	GTIN-14
Single Product A	X	X	X	
50 x Product A (standard case)		X	X	X
50 x Product A (display case)		X	X	X
100 x Product A (standard case)		X	X	X
Single Product B	X	X	X	
50 x Product A 50 x Product B		X	X	

2.1.2.6.1. Identification of a Trade Item that is a Single Product

Application Description

The manufacturer or supplier has the option of assigning a unique GTIN-8, GTIN-12, GTIN-13 or in the case of regulated healthcare trade items, GTIN-14 to a trade item that is a single product as shown in Figure 2.1.2.5 - 1.

Restricted Circulation Numbers (RCNs) must not be used in this Element String.

GS1 Key

Definition

- The GTIN-8 is the 8-digit GS1 Identification key composed of a GS1-8 Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

- For regulated healthcare trade items the GTIN-14 is the 14-digit GS1 Identification Key composed of an Indicator digit (1-9), GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

In addition to the GTIN Allocation Rules described in Section 4, the following guidelines should be observed: GTIN-8 can only be used when all other pack size constraints are met.

Before deciding to use a GTIN-8 as opposed to a GTIN-12, GTIN-13, or in the case of regulated healthcare trade items, GTIN-14, companies, working jointly with their printer, should consider options such as:

- Whether the bar code can be reduced in size (e.g., printed at a lower X-dimension, taking into account the minimum bar code print quality requirements (see Section 5.5)).
- Whether the label or artwork can reasonably be changed to enable the printer's recommended size of a EAN-13 or UPC-A Bar Code to be included (e.g., redesigning the label and increasing the label size, especially when the existing label is small in comparison with the pack area, or using an additional label). The label includes the total printed design surface whether or not it is separately affixed.
- Whether a truncated bar code can be used. A truncated bar code (normal length, but reduced in height) may only be used if there is absolutely no possibility of printing a full size bar code. Truncation removes the omni-directional scanning capability. A bar code with excessive truncation will not be of any practical use. Users considering this option should consult their customers to see if an acceptable compromise can be reached.

Pack size constraints allow several possible options:

- The use of a GTIN-8 is authorised when the EAN-13 or UPC-A Bar Code in the size required as a result of print quality studies exceeds either 25 percent of the printed label area or 12.5 percent of the total printable area.
- The use of a GTIN-8 is authorised when either the largest side of the printed label is less than 40 centimetres² or the total printable area is less than 80 centimetres².
- The use of a GTIN-8 is authorised on cylindrical products with a diameter less than 3 centimetres.

Attributes

Required

For Regulated Healthcare Consumer Trade Items the following levels of AIDC marking are specified.

Figure 2.1.2.6.1 - 1

AIDC Marking level for Regulated Healthcare Trade Items	Key	Batch/Lot Number - AI (10)	Expiration Date – AI (17)	Serial Number – AI (21)	Other
Minimum	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	Yes	Yes	No	None
Enhanced	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	Yes	Yes	No	None
Highest – Brand owner AIDC marking	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	Yes	Yes	Yes	Potency AI (7004) for Pharmaceutical, and for medical device Kits with Pharmaceutical (cases only for both situations)
Highest – Hospital AIDC marking of Pharmaceutical	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	No	AI (7003) for short-life products	Yes	None
Hospital AIDC Marking of Medical Devices	No	No	No	No	None

To manage healthcare data requirements within GS1 EPCglobal RFID tags, see Section 3.11 and the most recent version of the EPCglobal Tag Data Standard.

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

Symbols from the EAN/UPC Symbology family (UPC-A, UPC-E, may be used to encode the GTIN-12, EAN-13 to encode the GTIN-13 and, if the size requirements are met, EAN-8 to encode the GTIN-8) of the trade item grouping.

ITF-14 Symbols may be used where printing conditions require the application of a less demanding symbology. ITF-14 Symbols can encode the GTIN-12, or GTIN-13 of the item.

The GS1-128 Symbology with Application Identifier (01) may be used to encode a GTIN that identifies the trade item if the printing conditions allow. The choice of this symbology is particularly relevant if there is a need to encode attribute information in addition to the identification number.

For healthcare, the following carrier selections take precedence over the Carrier Choices above and apply to all regulated healthcare retail consumer trade items.

Figure 2.1.2.6.1 - 2

<p>Preferred Option(s) (this is the long-term direction for AIDC marking)</p>	<p>First preference: GS1-128 Symbology. After Jan 2010, GS1 DataBar is permitted for use on all trade items and therefore may be encountered in general distribution however use of GS1-128 is preferred as the scanners in the field today pervasively support it.</p> <p>Second preference: When one linear symbol cannot accommodate the field length of the data (exceeds 48 characters), two symbols should be used.</p> <p>Third option: Where the package or label size does not permit the use of the first two options, GS1 DataMatrix Symbology are permitted but should be avoided wherever possible if the package could be scanned by a mounted conveyORIZED scanner.</p>
<p>Option in addition to the bar code</p>	<p>See the “Data Carrier Specification Carrier Choices” recommendations on Options in Addition to the Bar Code at the end of Section 2.1.2.4</p>
<p>Other Acceptable Options (GS1 strongly supports existing options for symbol marking as a guiding principle and therefore supports all previous AIDC marking specifications)</p>	<p>See the “Data Carrier Specification Carrier Choices” recommendations on Other Acceptable Options found at the end of Section 2.1.2.4</p>

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

For multi-sector use except for Retail or Regulated Healthcare Trade Items see Section 5.5, Figure 5.5.2.7 – 3, GS1 System Symbol Specification Table 2.

For Regulated Healthcare Non-Retail Consumer Trade Items see Section 5.5, Figure 5.5.2.7-9 GS1 System Symbol Specification Table 8.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.2.6.2. Identification of Uniform Groupings of Trade Items

Application Description

A uniform grouping of trade items is a standard and stable grouping of identical trade items. The manufacturer or supplier has the option of either assigning a unique GTIN-13 or GTIN-12 to each grouping or assigning a unique GTIN-14. These 14-digit GTINs incorporate the GTIN of the trade item (less its Check Digit) contained in each grouping. The Check Digit for each GTIN-14 is then recalculated.

The Indicators have no meaning. The digits do not have to be used in sequential order, and some may not be used at all. The GTIN-14 structure for standard trade item groupings creates extra numbering capacity. Indicators can be re-used.

Figure 2.1.2.6.2 – 1

Format of the Element String	
Global Trade Item Number (GTIN)	
Indicator	GTIN of Contained Trade Items (Without Check Digit)
GTIN-8 based	N ₁ 0 0 0 0 0 N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃ N ₁₄
GTIN-12 based	N ₁ 0 N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃ N ₁₄
GTIN-13 based	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃ N ₁₄

The Indicator is a digit with a value of 1 to 8. It is assigned as required by the company that constructs the identification number. It can provide up to eight separate GTIN-14s to identify groupings of trade items.

For packaging configuration hierarchies which include a retail consumer trade item identified with a GTIN-13, GTIN-12, or GTIN-8, this GTIN must always be one of the relevant levels of packaging contained, usually the lowest level (see note below related to GTIN-14 assignment on the primary packaging). Restricted Circulation Numbers must not be used in this Element String.

Note: For regulated healthcare trade items on the primary packaging, the phrase “usually the lowest level” shall be interpreted as allowing for the use of GTIN-14 on packaging configurations below the retail consumer trade item level, if one exists. This interpretation may not be applied to other trade item categories such as Do It Yourself (DIY) or Foodservice.

Any product package which will encounter scanning or product listing for sale at Point-of-Sale shall be identified according to retail point of sale specifications.

When a GTIN change at the retail consumer trade item level is required, the GTIN change must be made at all configuration levels above the retail consumer trade item level. Where there is an association between primary packaging and retail consumer trade item levels and GTIN -14 assignment is used on the primary packaging, the GTIN-14 assigned to the primary packaging is based on the retail level GTIN. There are three scenarios to consider for the relationship of these GTIN assignments:

- If changes to the Primary Packaging drive the change of the GTIN assigned to the retail consumer trade item level, the GTIN of the Primary Packaging will change.
- If changes to retail consumer trade item level GTIN are not caused by a change in primary packaging, the GTIN at the primary package level may or may not change per the discretion of the brand owner
- If additional retail level package(s) are introduced beyond the original retail package or replace the original retail package, the GTIN-14 on the primary packing may remain tied to the original retail level GTIN.

The Check Digit is explained in Section 7.10. Its verification, usually carried out automatically by the bar code reader, ensures that the number is correctly composed.

Figure 2.1.2.6.2 - 2
Different Uniform Groupings of the Same Trade Item

Indicator	GTIN of Trade Item Contained in the Grouping, Less Its Check Digit	New Check Digit	Description	Quantity
	061414112345	2	Trade item	Single
1	061414112345	9	Standard trade item grouping	A grouping
...
8	061414112345	8	Standard trade item grouping	Another grouping

Indicators 1 to 8 may be used to create new GTIN-14s. When these eight Indicators have been used, further groupings must be identified with either a GTIN-13 or GTIN-12. (Indicator digit 9 is reserved for Variable Measure Trade Items). (See Section [2.1.5](#))

GS1 Key

Definition

- The GTIN-8 is the 8-digit GS1 Identification key composed of a GS1-8 Prefix, Item Reference, and Check Digit used to identify trade items
- The GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-14 is the 14-digit GS1 Identification Key composed of an Indicator digit (1-9), GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

All the GTIN Allocation Rules described in Section 4.

Attributes

Required

For Regulated Healthcare Consumer Trade Items the following levels of AIDC marking are specified:

Figure 2.1.2.6.2 - 3

AIDC Marking level for Regulated Healthcare Trade Items	Key	Batch/Lot Number - AI (10)	Expiration Date – AI (17)	Serial Number – AI (21)	Other
Minimum	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	Yes	Yes	No	None
Enhanced	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	Yes	Yes	No	None
Highest – Brand owner AIDC marking	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	Yes	Yes	Yes	Potency AI (7004) for Pharmaceutical, and for medical device Kits with Pharmaceutical (cases only for both situations)
Highest – Hospital AIDC marking of Pharmaceutical	GTIN-8, GTIN-12, GTIN-13, or GTIN-14	No	AI (7003) for short-life products	Yes	None
Hospital AIDC Marking of Medical Devices	No	No	No	No	None

To manage healthcare data requirements within GS1 EPCglobal RFID tags, see Section 3.11 and the most recent version of the EPCglobal Tag Data Standard.

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

For multi-sector use except for Regulated Healthcare Retail Consumer Trade Items symbols from the EAN/UPC Symbology family (UPC-A, UPC-E, and EAN-13) may be used to encode the GTIN-12 or GTIN-13 of the trade item grouping. If used, the GTIN-8 is encoded in an EAN-8 Bar Code. GTIN-8 can only be used when all other pack size constraints are met, see Section [2.1.2.1.3](#). The system recognises this Element String by the symbology identifier **JE0**.

ITF-14 Symbols may be used on groupings of trade items where printing conditions require the application of a less demanding symbology. ITF-14 Symbols can encode the GTIN-12, GTIN-13, or GTIN-14 of the item. The system recognises this Element String by the symbology identifier **J11** and the number of digits decoded (14).

The GS1-128 Symbology with Application Identifier (01) may be used to encode a GTIN-12, GTIN-13, or GTIN-14 that identifies the trade item if the printing conditions allow. The choice of this symbology is

particularly relevant if there is a need to encode attribute information in addition to the identification number. The system recognises this Element String by the symbology identifier **JC1** and the Application Identifier.

For healthcare the carrier selections noted at the end of Section [2.1.2.6.1](#) take precedence over the Carrier Choices above and apply to all Regulated Healthcare Retail Consumer Trade Items.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

For multi-sector use other than Regulated Healthcare Trade Items see Section 5.5, Figure 5.5.2.7 - 3, GS1 System Symbol Specification Table 2.

For Regulated Healthcare Non-Retail Consumer Trade Items see Section 5.5, Figure 5.5.2.7 - 9, GS1 System Symbol Specification Table 8.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.2.6.3. Identification of Mixed Groupings of Trade Items

Application Description

A mixed grouping of trade items is a standard and stable grouping of two or more different trade items.

For example:

- Product C is a mixed grouping of Product A (GTIN 'A') and Product B (GTIN 'B'), and is identified with either a GTIN-12 or GTIN-13, GTIN 'C.'
- GTIN 'C' could then be used to construct a GTIN-14 for a standard trade item grouping comprised of Product C.

As shown in Figure 2.1.2.3.3 - 1, the GTIN-12s 614141234561 and 614141345670 identify the two trade items in the assortment identified by the GTIN 614141456789.

Figure 2.1.2.6.3 - 1

Indicator	GTIN of Trade Item Less Its Check Digit	Check Digit	Description	Quantity
	061414123456 061414134567	1 0	Retail consumer trade item (Product A) Retail consumer trade item (Product B)	Single Single
	061414145678	9	Retail consumer trade item (Product C)	Assortment
1	061414145678	6	Standard trade item grouping	A grouping of the assortment
...
8	061414145678	5	Standard trade item grouping	Another grouping of the assortment
The Indicators 1 to 8 may be used to create new GTIN-14s. When these eight Indicators have been used, further groupings must be identified with either a GTIN-13 or GTIN-12. (Indicator digit 9 is reserved for Variable Measure Trade Items). (See Section 2.1.5)				

GS1 Key

Definition

- The GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-14 is the 14-digit GS1 Identification Key composed of an Indicator digit (1-9), GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items

Rules

All the GTIN Allocation Rules described in Section 4; in addition, the GTIN-14 is valid for mixed groupings only when the trade item contained is an assortment of two or more different trade items.

Attributes

Required

Not Applicable

Optional

Not Applicable

Data Carrier Specification

Carrier Choices

Symbols from the EAN/UPC Symbology family (UPC-A, UPC-E, and EAN-13) may be used to encode the GTIN-12 or GTIN-13 of the trade item grouping. The system recognises this Element String by the symbology identifier **JE0**.

ITF-14 Symbols may be used on groupings of trade items where printing conditions require the application of a less demanding symbology. ITF-14 Symbols can encode the GTIN-12, GTIN-13, or GTIN-14 of the item. The system recognises this Element String by the symbology identifier **J11** and the number of digits decoded (14).

The GS1-128 Symbology with Application Identifier (01) may be used to encode a GTIN-12, GTIN-13, or GTIN-14 that identifies the trade item if the printing conditions allow. The choice of this symbology is particularly relevant if there is a need to encode attribute information in addition to the identification number. The system recognises this Element String by the symbology identifier **JC1** and the Application Identifier

For healthcare, the carrier selections noted at the end of Section [2.1.2.4](#) take precedence over the Carrier Choices above and apply to all Regulated Healthcare Retail Consumer Trade Items.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

For multi-sector use other than Regulated Healthcare Trade Items see Section 5.5, Figure 5.5.2.7 - 3, GS1 System Symbol Specification Table 2.

For Regulated Healthcare Non-Retail Consumer Trade Items see Section 5.5, Figure 5.5.2.7 – 9, GS1 System Symbol Specification Table 8.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.3. Fixed Measure – Trade Items Packed in Several Physical Units NOT Scanned at POS

Application Description

The trade item that does not cross a Point-of-Sale, due to its nature, is packed in several physical units. Each individual component consists of the Global Trade Item Number (GTIN) of the trade item, the sequence number of the particular component, and the total number of components of the trade item. If an attribute appears on more than one component, its value must be the same. See Section 3, Identification of the Components of a Trade Item: AI (8006).

GS1 Key

Definition

The Global Trade Item Number (GTIN) is the GS1 Identification Key used to identify trade items. The key is comprised of a GS1 or U.P.C. Company Prefix followed by an Item Reference Number and a Check Digit.

Rules

All the GTIN Allocation Rules described in Section 4.

Attributes

Required

See in Section 3.2 the List for all GS1 Application Identifier, Identification of the Components of a Trade Item: AI (8006).

Optional

Not Applicable

Rules

The use of the Element String AI (8006) to identify a trade item excludes the application of the Element String AI (01) on the same unit.

This solution is not applicable for trade items crossing Point-of-Sale.

Data Carrier Specification

Carrier Choices

For multi-sector use except for Regulated Healthcare Retail Consumer Trade Items, the only data carrier used to represent each individual component using the Application Identifier AI (8006) is the GS1-128 Bar Code Symbology.

For healthcare, the following carrier selections take precedence over the Carrier Choices above and apply to all Regulated Healthcare Retail Consumer Trade Items.

Figure 2.1.3 - 1

Preferred Option	GS1-128 Symbology
Option in addition to the bar code	See the “Data Carrier Specification Carrier Choices” recommendations on Options in Addition to the Bar Code at the end of Section 2.1.2.4

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 3, GS1 System Symbol Specification Table 2.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.1.4. Fixed Measure - Direct Part Marking

Application Description

Direct part marking (DPM) refers to the process of marking a symbol directly onto an item using an intrusive or non-intrusive method instead of applying a label or using another indirect marking process.

GS1 Key

Definition

GTIN-12, GTIN-13, GTIN-14 (see Section 3).

Rules

GTIN Allocation rules are described in Section 4.

Attributes

Required

For Regulated Healthcare Consumer Trade Items the following levels of AIDC marking are specified:

Figure 2.1.4 - 1

AIDC Marking level for Regulated Healthcare Trade Items	Key	Batch/Lot Number - AI (10)	Expiration Date – AI (17)	Serial Number – AI (21)	Other
Highest – Brand owner AIDC marking of certain medical devices	GTIN-12, GTIN-13, or GTIN-14	No	No	Yes	None
Highest - Hospital AIDC marking of certain medical devices (see Section 2.1.1.8)	GRAI, AI (8003), or GIAI, AI (8004), is optional if GTIN, AI (01), + Serial Number, AI (21), is not marked on the product.	No	No	GRAI, AI (8003), or GIAI, AI (8004), is optional if GTIN, AI (01), + Serial Number, AI (21), is not marked on the product.	

To manage healthcare data requirements within GS1 EPCglobal RFID tags, see Section 3.11 and the most recent version of the EPCglobal Tag Data Standard.

Optional

See Section 3 for all the Application Identifiers (AIs) that can be used with a GTIN. Since the GTIN identifies a grouping of items, the optional attributes apply to the grouping as well.

Rules

All the GTIN Allocation Rules described in Section 4.

Data Carrier Specification

Carrier Choices

The use of GS1 DataMatrix in direct part marking applications is endorsed by GS1 for those applications that require permanent marking for cradle-to-grave history of the part’s lifecycle.

Some sources express the height of the 2D cell in terms of a Y dimension. For GS1 DataMatrix the cells are considered the same size under optimal print conditions so that X = Y.

Consult System Symbol Specification Table 7: 2D Symbols Using GS1 DataMatrix, Figure 5.5.2.7 - 8, for minimum and maximum printing densities and other sizing requirements.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 8, GS1 System Symbol Specification Table 7

Symbol size is determined by the amount of data and the number of rows and columns required encoding the data for the printing density selected (see Figures 5.7.3.2 - 1 and 5.7.3.2 - 2).

For healthcare, the following carrier selection applies to Regulated Healthcare Retail Consumer Trade Items.

Figure 2.1.4 - 2

Preferred Option	GS1 DataMatrix Symbology
Option in addition to the bar code	See the “Data Carrier Specification Carrier Choices” recommendations on Options in Addition to the Bar Code at the end of Section 2.1.2.4

Figure 2.1.4 - 3

Example of GS1 DataMatrix Symbol Encoded with GTIN and AIs (17) and (10) per Section 2.1.2.4

(17) 050101 (10) ABC123



(01) 04012345678901

Figure 2.1.4 - 4

Example of GS1 DataMatrix Symbol Encoded with GTIN and Serial Number AI (21)

(21) ABCDEFG123456789



(01) 04012345678901

Symbol Placement

General principles on placement of bar codes are described in Section 6.

The majority of uses for these symbols will be on very small items with curved surfaces such as vials, ampoules, and very small bottles. For guidance in locating these symbols on curved surfaces, refer to Section 6.2.

Unique Application Processing Requirements

Use GS1 DataMatrix if:

- The use of GS1 DataMatrix is allowed in the application specification.
- The marking method will not produce an acceptable linear symbol but will produce an acceptable GS1 DataMatrix (e.g., dot peen marking and high-speed ink jet).
- A GS1 Identification Key plus attribute Element String are to be encoded
- GS1 DataMatrix is the only symbology that will fit on the item at the application specified X-dimension.
- Low contrast signal is expected from the application.
- The use of 2D (two-dimensional) array scanners and/or vision systems are specified exclusively for the application and can read GS1 DataMatrix.

Marking Methods

It is important to analyse the selected method of marking in relation to several considerations:

- Finishes that cause an excess of shadowing or glare
- Surfaces that do not provide sufficient contrast - less than 20 percent difference in surface reflectance
- Safety critical parts that can not be marked with intrusive methods
- Marking method must comply with the users requirements
- Location of the symbol should not be:
 - In direct air/water (streams, etc.)
 - On sealing surfaces
 - On surfaces subject to wear or exposure to heavy contact

Intrusive (Subtractive Methods)

Intrusive marking refers to methods that remove or alter the material of the host.

- Abrasive blast
- Dot peen
- Electro-chemical marking, colouring, or etching
- Engraving/milling
- Fabric embroidery/weaving
- Direct laser marking
- Laser shot peening
- Laser Inducted Surface Improvement (LISI)
- Gas Assisted Laser Etch (GALE)
- Laser Induced Vapor Deposition (LIVD)

Non-Intrusive (Additive Methods)

Non-Intrusive marking does not affect the host material; it usually involves the addition of material.

- Cast, forge, mold
- Inkjet
- Laser bonding
- Liquid metal jet
- Silk screen
- Stencil

Host (Substrate) Surface

Direct part marking of GS1 DataMatrix should be reserved for surfaces no rougher than 250 micro inches (millionths of an inch) and for surfaces that are no smoother than 8 micro inches. Surfaces that fall outside these parameters need to be re-surfaced or marked using an alternative method.

Consideration of the surface colour must be taken. A minimum 20 percent difference in contrast between the host and the symbol is required.

Altering the cell size in relation to the surface roughness should provide adequate contrast on cast surfaces.

(Cell size = (0.00006 X roughness) + 0.0067); (see Figure 2.1.4 - 3)

Figure 2.1.4 - 5

Average Roughness	Cell Size Minimum
0,508 micrometers (20 micro inches)	0.1905 mm (0.0075 in.)
1,524 micrometers (60 micro inches)	0.2286 mm (0.009 in.)
3,048 micrometers (120 micro inches)	0.381 mm (0.015 in.)
5,08 micrometers (200 micro inches)	0.508 mm (0.020 in.)
7,62 micrometers (300 micro inches)	0.635 mm (0.025 in.)
10,668 micrometers (420 micro inches)	0.762 mm (0.030 in.)

Substrate Surface Thickness

A minimum host surface thickness is recommended as is a maximum marking depth. Both are outlined in the table below.

Figure 2.1.4 - 6

Method	Min. Thickness	Max Marking Depth
Dot Peen	1.016 mm (0.04 in.)	0.102 mm (0.004 in.)
Laser Shot peening	0.508 mm (0.020 in.)	0.051 mm (0.002 in.)
Laser Bonding	0.025 mm (0.001 in.)	Surface Mark
Abrasive Blast	0.076 mm (0.003 in.)	0.008 mm (0.0003 in.)
Electro-Chemical Colouring	0.508 mm (0.02 in.)	0.051 mm (0.002 in.)
Laser Etch	0.762 mm (0.03 in.)	0.076 mm (0.003 in.)
LISI	1.016 mm (0.04 in.)	0.102 mm (0.004 in.)
Laser Engraving	1.27 mm (0.05 in.)	0.127 mm (0.005 in.)
Electro-Chemical Etch	2.54 mm (0.100 in.)	0.254 mm (0.01 in.)
Micro-Milling	31.75 mm (1.250 in.)	3.175 mm (0.125 in.)

Human Readable Interpretation

For Human-Readable Interpretation Rules see Section 4.12. For HRI Rules specific to Regulated Healthcare Retail Consumer Trade Items, see Section 4.12.1.

2.1.5. Variable Measure Trade Items Not Crossing a Point-of-Sale

Application Description

Trade items may be of variable measure either because the production process does not guarantee consistency in weight, size, or length (e.g., carcasses of meat, whole cheeses) or because the items are created to meet a special order that states a quantity (e.g., textiles ordered by the metre, glass ordered by the square metre).

Only trade items that are sold, ordered, or produced in quantities, which can vary continuously, are covered by the rules outlined in this section. Trade items that are sold in discrete and pre-defined bands (e.g., as a nominal weight) are treated as Fixed Measure Trade Items.

A trade item must be considered a Variable Measure Trade Item if its measure is variable at any point in the supply chain. For example, a supplier may sell and invoice chickens in standardised cases of 15 kilograms each; therefore, the quantity of contained chickens will vary. The customer, a retailer in this example, may need to know the exact number of chickens contained in each case in order to organise the distribution to his stores. In this example, the supplier should source mark the trade item by using a variable measure Global Trade Item Number (GTIN) and the variable count Element String.

See Section 3 for the use of AI (242) Variable Made-to-Order Number and its use in the Maintenance, Repair and Operations (MRO) industrial supply sector.

Figure 2.1.5 - 1

Format of the Element String					
Global Trade Item Number (GTIN)					
Indicator	GS1 Company Prefix			Item Reference	Check Digit
(GTIN-12)	9	0	N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃		N ₁₄
(GTIN-13)	9		N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃		N ₁₄

The Check Digit is explained in Section 7.10. Its verification, usually carried out automatically by the bar code reader, ensures that the number is correctly composed. The symbology identifier shows whether or not the Check Digit has been validated. If it has not, the Check Digit verification must be programmed in the application software.

Any trade item of a given composition where the quantity/measure information cannot be pre-determined for any reason is a Variable Measure Trade Item. The most frequent types are shown in Figure 2.1.5 - 2.

Figure 2.1.5 - 2

Type	Item Description
A	Items traded in bulk, neither portioned nor pre-packed for retail sale, ordered in any quantity, and that are delivered as non-standardised trade items (e.g., fish, fruit, vegetables, cables, carpets, timber, fabrics) The identification number denotes the item as a trade entity containing any quantity of the given product and, if applicable, the form of packaging. Weight or dimensions complete the identification of the individual unit.

Type	Item Description
B	Trade items ordered and delivered by piece (wrapped or unwrapped) and invoiced by weight or measure because weight or measure varies due to the nature of the product or due to the manufacturing process (e.g., whole cheese, sides of bacon, beef carcasses, fish, sausages, ham, chicken, cauliflower, motion picture films) The identification number denotes the item as a particular pre-defined entity and, if applicable, denotes the form of packaging. Price or weight or dimensions complete the identification of the individual item.
C	Portioned trade items, pre-packed for sale by weight to the consumer, not standardised in quantity. (e.g., meat, cheese, vegetables, fruit, fillets of fish, sliced poultry, cold cuts) The identification number denotes the item type according to business practice and the form in which it is packed. Price or weight completes the identification of the individual unit.
D	Standardised trade items with selectable dimensions where GS1 System standard numbering does not make sense to cover the multiplicity of all variations (e.g., wooden planks, carpeting) The identification number denotes the pre-defined basic trade item. The applicable dimension(s) completes the identification of the individual unit.
E	Standardised composition of a fixed number of trade items that are Type B or Type C (e.g., a trade item containing 10 chickens (Type B)) The identification number denotes the standardised trade item as an entity and, if applicable, its form of packaging. The total weight of all items contained completes the identification of the particular trade item.
F	Trade items made to customer specifications, restricted in use to the Maintenance, Repairs and Operations industrial supply sector, and sold business-to-business. The identification number denotes a base custom item. The specific variation is identified by the Variation Made-to-Order Number. (See in Section 3.2 the List for all GS1 Application Identifier).

GS1 Key

Definition

The GTIN-14 is the 14-digit GS1 Identification Key composed of an Indicator digit (9), GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

The GTIN-14 with the Indicator 9 is used to identify a Variable Measure Trade Item. The presence of the variable measure information is mandatory for the complete identification of a particular Variable Measure Trade Item. The digit 9 in the first position is an integral part of the GTIN.

The GTIN-14 Data Structure beginning with Indicator 9 is not used on an item intended to cross the Point-of-Sale. Numbering of variable measure fresh food trade items intended to cross Point-of-Sale is defined in Section [2.1.7.2](#).

Attributes

Required

The GTIN-14 identifies a Variable Measure Trade Item with respect to its fixed attributes or characteristics. To complete the identification of a Variable Measure Trade Item, the presence of an Element String representing a trade measure is mandatory.

See in Section 3.2 the List for all GS1 Application Identifier, Identification of a Variable Measure Trade Item (GTIN): AI (01).

Optional

Applicable trade measures depend on the nature of the product. They may be a quantity, a weight, or any dimension.

- An Element String with Application Identifier (30) is used if the variable measure of the trade item is the number of items contained. In order to generate a short bar code, always enter an

even number of digits in the data field count of items by inserting a leading zero. Concatenation of this Element String with the GTIN of the item enhances the accuracy of the application (see in Section 3.2 the List for all GS1 Application Identifier, Variable Count: AI (30)).

- An Element String with Application Identifiers (AIs) (31nn), (32nn), (35nn), and (36nn) is used if the variable measure of the respective trade item is weight, dimension, area, or volume. Only one Element String of a given unit of measure may be applied on a particular item. Several Element Strings containing trade measures are possible on a particular item if the item is available in either unit of measure and if the applicable unit of measure is not distinguished for ordering and billing. This might apply if weight must be expressed in kilograms and pounds (see in Section 3.2 the List for all GS1 Application Identifier, Trade Measures: AIs (31nn, 32nn, 35nn, 36nn)).



Note: The fourth (and last) digit of the AI indicates the implied decimal point position. The value 0 means that the measurement is expressed in the basic unit of measure associated with the AI (e.g., kilograms). A value of 1 decreases the measurement by a factor of 10, a value of 2 by a factor of 100, and so on. For example, this enables metric weights to be represented from 999 kilograms to 1/1000 of a milligram.

- An Element String with Application Identifier (8001) contains the pre-defined variable fields of a roll product and it may be used for those variable roll products where the standard trade measures AI (31nn), (32nn), (35nn), (36nn) are not sufficient. The GTIN-14 can denote a basic roll product.

Rules

An Element String with Application Identifier (30) should never be used to indicate the quantity contained in a Fixed Measure Trade Item. However, if it appears on a Fixed Measure Trade Item, it should not invalidate the trade item identification.

An Element String with Application Identifier (8001) must never be used together with other Element Strings representing standard trade measures.

Data Carrier Specification

Carrier Choices

Variable Measure Trade Items not crossing a Point-of-Sale should be marked with an ITF-14 Bar Code or GS1-128 Bar Code Symbolology.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 3, GS1 System Symbol Specification Table 2.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

Examples of Variable Measure Trade Item Numbering and Symbols

In the examples in the subsections that follow, the following factors apply:

- In order to be illustrative, all examples show the same presentation (e.g., price list, order, delivery, invoice, and recording in a data file).
- GS1-128 Bar Codes are used.

- The examples are given to demonstrate the correct use of a given Application Identifier when used. When AI (02) is not used, information about the shipment must be received using Electronic Data Interchange (EDI) or other means prior to its physical receipt.

Example 1: Traded by Piece

The following example shows the order and delivery of an item traded by piece and invoiced by weight.

- The supplier’s catalogue contains one entry: one salami weighing ~ 500 grams
- The order for 100 units is delivered in three boxes. Each box is marked with an SSCC (Serial Shipping Container Code) and, optionally, with information on the content of the box, expressed as follows:
 - AI (02) indicates the variable measure Global Trade Item Number (GTIN) of the units contained within the box.
 - AI (3101) indicates the total weight of the items contained within the box.
 - AI (37) indicates the count of items contained within the box.
- The three boxes may be stored on a pallet that may itself be marked with an SSCC and, optionally, with information on the contents of the pallet, expressed as follows:
 - AI (02) indicates the variable measure GTIN of the units contained within the pallet.
 - AI (3101) indicates the total weight of the items contained within the pallet.
 - AI (37) indicates the count of items contained within the pallet.
- The invoice refers to the GTIN and quantity delivered and shows the total weight and the price per kilogram. The GTIN and quantity of the invoice match the GTIN and quantity of the order.

Figure 2.1.5 - 3

Process	Description	Element Strings Used / Symbol Marking of the Items
Supplier’s catalogue	1 Salami ~ 500 g	GTIN 97612345000018
Order	100 salamis	100 x 97612345000018
Delivery	three logistic units Unit 1 = 33 salamis, 16.7 kg Unit 2 = 33 salamis, 16.9 g Unit 3 = 34 salamis, 17.1 kg	Unit 1: 00 376123450000010008 02 97612345000018 3101 000167 37 33 Unit 2: 00 376123450000010015 02 97612345000018 3101 000169 37 33 Unit 3: 00 376123450000010022 02 97612345000018 3101 000171 37 34
	If delivery is made on a pallet	Pallet: 00 376123450000010039 02 97612345000018 3101 000507 37 0100
Invoice	GTIN of items and the total weight (50.7 kg) + the price per kg	100 x 97612345000018; 50.7 kg x price per kg

Data File Logistic Units	Identification of Logistic Unit (SSCC)	GTIN of Contained Trade Items	Total Trade Weight of Content (Grams)	Number of Units Contained
Either pallet	376123450000010039	97612345000018	50700	100
or individual units	376123450000010008	97612345000018	16700	33

Data File Logistic Units	Identification of Logistic Unit (SSCC)	GTIN of Contained Trade Items	Total Trade Weight of Content (Grams)	Number of Units Contained
	376123450000010015	97612345000018	16900	33
	376123450000010022	97612345000018	17100	34

Data File Trade Items	GTIN of Trade Item	Total Trade Weight (Grams)	Number of Trade Items
One record per identification number	97612345000018	50700	100

An Element String with an Application Identifier (410) represents the Global Location Number (GLN) of the recipient of a logistic unit. The GLN refers to the address where a particular transport unit identified with an SSCC is to be delivered. This Element String is used in single leg transport operations. A logistic unit may include a bar code carrying the GLN of the unit's intended destination. When scanning this Element String, the data transmitted may be used to retrieve the related address and/or to sort the item by destination.

Example 2: Traded by Standard Grouping

The following example shows the order and delivery of an item traded by standard grouping and invoiced by weight.

- The supplier's catalogue contains one entry: one case of 20 steaks weighing ~ 200 grams each.
- The order is for three cases. Each case delivered is marked with the Global Trade Item Number (GTIN) of a single case followed by the actual weight of the items contained.
- The three cases may be stored on a pallet that may itself be marked with an SSCC (Serial Shipping Container Code) and, optionally, with information on the contents of the pallet, expressed as follows:
 - AI (02) indicates the variable measure GTIN of the units contained within the pallet.
 - AI (3102) indicates the total weight of the items contained within the pallet.
 - AI (37) indicates the count of cases contained within the pallet.
- The invoice refers to the GTIN and quantity delivered and shows the total weight and the price per kilogram. The GTIN and quantity of the invoice match the GTIN and quantity of the order.

Figure 2.1.5 - 4

Process	Description	Element Strings Used / Symbol Marking of the Items
Supplier's catalogue	1 case of 20 steaks ~ 200 g vacuum packed	GTIN 97612345000117
Order	Three cases	3 x 97612345000117
Delivery	Three trade items Unit 1: weight = 4.150 kg Unit 2: weight = 4.070 kg Unit 3: weight = 3.980 kg	Unit 1: 01 97612345000117 3102 000415 Unit 2: 01 97612345000117 3102 000407 Unit 3: 01 97612345000117 3102 000398
	If delivery is made on a pallet	Pallet: 00 376123450000010091 02 97612345000117 3102 001220 37 03

Process	Description	Element Strings Used / Symbol Marking of the Items
Invoice	GTIN of items and the total weight (12.20 kg) + the price per kg	3 x 97612345000117; 12.2 kg x price per kg

Data File Logistic Units	Identification of Logistic Unit (SSCC)	GTIN of Contained Trade Items	Total Trade Weight of Content (Grams)	Number of Units Contained
Pallet	376123450000010091	97612345000117	12200	3

Data File Trade Items	GTIN of Trade Item	Total Trade Weight	Number of Trade Items
One Record	97612345000117	12200	3

Example 3: Traded in Bulk

The following example shows an order and delivery of an item traded in bulk.

- The supplier’s catalogue contains one entry: cabbage unwrapped sold in bulk by kilogram.
- The order is for 100 kilograms. It is delivered in two cases. Each case is marked with the Global Trade Item Number (GTIN) of the cabbage followed by the actual weight of the items contained.
- The two cases may be stored on a pallet that may itself be marked with an SSCC (Serial Shipping Container Code).
- The invoice refers to the GTIN as ordered and shows the total weight and the price per kilogram. The delivered weight may be verified as being close to the ordered quantity.

Figure 2.1.5 - 5

Process	Description	Element Strings Used / Symbol Marking of the Items
Supplier’s catalogue	Cabbage unwrapped sold in bulk by kilogram	GTIN 97612345000049
Order	100 kg of cabbage	100 kg x 97612345000049
Delivery	Two trade items Unit 1: weight = 42.7 kg Unit 2: weight = 57.6 kg	Unit 1: 01 97612345000049 3101 000427 Unit 2: 01 97612345000049 3101 000576
	If delivery is made on a pallet	Pallet: 00 376123450000010107
Invoice	GTIN of item and the total weight (100.3 kg) + the price per kg	97612345000049 100.3 kg x price per kg

Data File Logistic Units	Identification of Logistic Unit (SSCC)	GTIN of Contained Trade Items	Total Trade Weight of Content (Grams)	Number of Units Contained
Pallet	376123450000010107	97612345000049 97612345000049	42700 57600	1 1

Data File Trade Items	GTIN of Trade Item	Total Trade Weight (Grams)	Number of Trade Items
One record per trade item	97612345000049	42700	1
	97612345000049	57600	1

Example 4: Traded by Standard Grouping

The following example shows an order of standardised Variable Measure Trade Items by case that are invoiced by the number of pieces delivered.

- The supplier’s catalogue contains one entry: one case of ~ 10 cabbages sold by piece.
- The order is for two cases. Each case delivered is marked with the Global Trade Item Number (GTIN) of a single case followed by the actual count of the items contained.
- The two cases may be stored on a pallet that may itself be marked with an SSCC (Serial Shipping Container Code) and, optionally, with information on the contents of the pallet, expressed as follows:
 - AI (02) indicates the variable measure GTIN of the units contained within the pallet.
 - AI (30) indicates the total count of the items contained within the pallet.
 - AI (37) indicates the count of cases contained within the pallet.
- The invoice refers to the GTIN as ordered and delivered and the total count of items.

Figure 2.1.5 - 6

Process	Description	Element Strings Used / Symbol Marking of the Items
Supplier's catalogue	Case containing ~10 cabbages sold by pieces	GTIN 97612345000285
Order	Two cases	2 x 97612345000285
Delivery	Unit 1: 11 pieces Unit 2: 12 pieces	Unit 1: 01 97612345000285 30 11 Unit 2: 01 97612345000285 30 12
	If delivery is made on a pallet	Pallet: 00 376123450000010138 02 97612345000285 30 23 37 02
Invoice	GTIN of the trade item and the total quantity	2 x 97612345000285 23 pieces x price per piece

Data File Logistic Units	Identification of Logistic Unit (SSCC)	GTIN of Contained Trade Items	Total Number of Pieces Contained in the Trade Item	Number of Units Contained
Pallet	376123450000010138	97612345000285	23	2

Data File Trade Items	GTIN of Trade Item	Total Number of Pieces	Number of Trade Items
One Record	97612345000285	23	2

Example 5: Traded in Bulk

The following example shows a product that can be purchased from a supplier or sold to a customer by any length in metres.

- The supplier’s catalogue contains one entry: cable T49 sold in metres.
- The order is for one length of cable of 150 metres. The delivered package is marked with the Global Trade Item Number (GTIN) of the cable followed by the actual length of cable contained.
- The invoice refers to the GTIN as ordered and delivered and the total length.

Figure 2.1.5 - 7

Process	Description	Element Strings Used / Symbol Marking of the Items
Supplier's catalogue	Cable T49 sold in any length in MTR	GTIN 97612345000063
Order	One trade item of 150 MTR	97612345000063 x 150 MTR
Delivery	One trade item, 150 MTR	01 97612345000063 3110 000150
Invoice	GTIN of the trade item and the total quantity	1 x 97612345000063 150 x price per MTR

Data File Trade Items	GTIN of Trade Item	Total Trade Length (Metres)
One record	97612345000063	150

2.1.6. Fixed Measure – Restricted Distribution

This section describes applications where the item identification is defined only in a closed environment. Therefore, the distribution of trade items marked in this way is restricted to a given geographic region or for use within a company. However, within their closed environment these items may be processed along with trade items identified with Global Trade Item Numbers (GTINs) defined for open trade.

The regulations established by GS1 Member Organisations for their country or assigned area should be observed for the allocation of these Restricted Circulation Numbers.

When assigned to company internal use, the structure and management of the numbers represented in the Element Strings of this section are the responsibility of the user. Number changes and re-use of expired numbers must be managed by the user based on his requirements.

When centrally administrated within a geographic area, the GS1 Member Organisation determines the structure and manages number allocation based on user requirements.

These identification numbers are known as Restricted Circulation Numbers and may be 8, 12, or 13 digits in length. Eight-digit numbers are known as RCN-8s, 12-digit numbers as RCN-12s, and 13-digit numbers as RCN-13s.

Restricted circulation Fixed Measure Trade Items are defined only in a closed environment. Therefore, the distribution of trade items marked in this way is restricted to a given geographic region or for use within a company. These items are either marked in the store by the retailer or are marked at the source by the supplier.

GS1 Member Organisations may assign one or several of the GS1 Prefixes 02, 20 through 29 for the identification of Fixed Measure Trade items with RCN-13s, or RCN-12s for use within a given geographic region or for use within a company.

2.1.6.1. Company Internal Numbering – RCN-8 Prefix 0 or 2

Application Description

This Element String uses an RCN-8 Prefix of 0 or 2. It provides two million identification numbers, which can be assigned for internal use in a company. When the RCN-8 Prefix is 0, the Element String is sometimes called a Velocity Code because it is quicker to key enter.

This Element String is for internal use in a company. The numbers are assigned by individual companies and do not provide unique identification if they leave the company premises.

Figure 2.1.6.1 - 1



Format of the Element String							
RCN-8 Prefix	Item Reference						Check Digit
N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈

The RCN-8 Prefixes 0 or 2 are system identifiers that show that the item identification number is under the sole control of the assigning company and that it is for internal item distribution.

The Item Reference is allocated by the company that uses the Element String. The positions N₂ to N₇ may contain any digit.

The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the number is correctly composed.

The data transmitted from the bar code reader means that one Fixed Measure Trade Item with a GTIN-8 has been captured.

- 
Note: In addition to trade item identification, this Element String may be used for any purpose that is supported by the company's equipment supplier.
- 
Note: In some environments where numbers may have to be key entered, the EAN-8 Bar Code carrying RCN-8s (and the RCN-8 Prefix 0) may be confused with the numbers carried by a UPC-E Bar Code. If such a risk exists, it is preferable to use the RCN-8 Prefix 2 capacity for internal use.

GS1 Key

Definition

Not Applicable

Rules

Not Applicable

Attributes

Required

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

The data carrier for this Element String is the EAN-8 Bar Code. The system recognises this Element String by the symbology identifier **JE4** and by N₁ being 0 or 2.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

Not Applicable

2.1.6.2. Company Internal Numbering – RCN-13 GS1 Prefix 04 (RCN-12 U.P.C. Prefix 4)

Application Description

Any company in the world may use this Element String for company internal trade item numbering. If the RNC-12 U.P.C. Prefix 4 is being applied, the user company may structure the trade item number.

Although this Element String is mainly used for the identification of trade items, it may be used for any purpose as long as it is kept within a restricted environment.

This Element String is for a company’s internal use. Because any company may use this Element String, it does not provide unique identification of a trade item if it leaves the company’s premises.

Figure 2.1.6.2 - 1

Format of the Element String												
GS1 Prefix		Item Reference										Check Digit
0	4	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃

The GS1 Prefix 04 is a system identifier showing that the identification number is under the sole control of the assigning company and that it is for internal trade item distribution.

The Item Reference is assigned by the company that uses the Element String. Positions N₃ to N₁₂ may contain any digit.

The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the number is correctly composed.

The data transmitted from the bar code reader means that one Fixed Measure Trade Item with a RCN-13 or RCN-12 has been captured.

GS1 Key

Definition

Not Applicable

Rules

Not Applicable

Attributes**Required**

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification**Carrier Choices**

The data carrier for this Element String is the UPC-A Bar Code.

The system recognises this Element String by the symbology identifier **JE0**.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

Not Applicable

2.1.6.3. Company Internal Numbering – RCN-12 U.P.C. Prefix 0 (LAC and RZSC)**Application Description**

The U.P.C. Company Prefix 0 includes a reserved capacity for company internal numbering, using Local Assigned Codes (LACs) or Retailer Zero-Suppression Codes (RZSCs), which are carried by a UPC-E Bar Code. U.P.C. Company Prefixes 000000 and 001000 to 007999 are used in this feature. For details, see Figure 2.1.6.3 – 1.

Although this Element String is mainly used for the identification of trade items in restricted distribution, it may be used for any purpose as long as it is kept within a restricted environment.

This Element String is for a company's internal use. Because any company may use this Element String, it does not provide unique identification of a trade item if it leaves the company's premises.

Figure 2.1.6.3 - 1

UPC-E Bar Code Option for the Identification of GTINs for Company Internal Distribution

GTIN-12 Identification Number of Trade Item											Check Digit	Represented in UPC-E Symbol Positions							
N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	1	2	3	4	5	6		
(0)	0	0	1	0	0	0	0	0	0	5	2	0	1	0	0	0	'5'		
(0)	0	0	7	9	9	9	0	0	0	9	7	0	7	9	9	9	'9'		
LAC version = 35000 UPC-E Bar Code Applications																			
(0)	0	0	1	0	0	0	0	0	1	0	4	0	1	1	0	0	'0'		
(0)	0	0	5	0	0	0	0	0	9	9	2	0	5	9	9	9	'0'		
RZSC version = 4500 UPC-E Bar Code Applications																			
(0)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	'0'		
(0)	0	0	0	0	0	0	0	0	9	9	7	0	0	9	9	9	'0'		
Velocity version = 1000 UPC-E Bar Code Applications																			

In Figure 2.1.6.3 - 1, each number position must only contain the digits shown in the upper and lower lines of each section and those in-between. On decoding, the extension to full length is determined by the value of the number in single quotes in the column represented in UPC-E Bar Code positions.

The Check Digit, calculated as described in Section 7.10, applies to the entire length of the RCN-12. In the UPC-E Bar Code, it is implicitly represented by the parity combination of the six symbol characters that are actually encoded. The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the number is correctly composed

GS1 Key

Definition

Not Applicable

Rules

Not Applicable

Attributes

Required

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification**Carrier Choices**

The data carrier for this Element String is the UPC-A Bar Code.

The system recognises this Element String by the symbology identifier **JE0** and GS1 Prefix 00 with the digits 01 to 07 in the next two positions.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable


Unique Application Processing Requirements

It is possible to create false UPC-E Bar Code if the encodation rules are not properly observed. Whether the digits represented in a UPC-E Bar Code can be expanded correctly to an RCN-12 may be verified by the tests shown in section 7.11.

2.1.6.4. GS1 Prefixes 02, 20 to 29 - Restricted Circulation**Application Description**

The GS1 Prefixes 02, 20 to 29 are reserved for identification purposes within a restricted geographic area. Each GS1 Member Organisation is entitled to assign the prefixes to be used for these Element Strings in its country or assigned area:

- For the identification of Variable Measure Trade Items or Fixed Measure Trade Items
- For internal numbering of Variable Measure Trade Items or Fixed Measure Trade Items by a particular company

 **Note:** Suppliers manufacturing their own label products for several different customers should use unique GS1 System numbering to distinguish their customers. If this is not done, the supplier will not be able to use Electronic Data Interchange (EDI) or electronic catalogues.

Although this Element String is mainly used for the identification of trade items, it may be used for any purpose as long as it is kept within a restricted environment.

This Element String is for use within a GS1 Member Organisation's geographic region. The GS1 Member Organisation may assign a company a GS1 Prefix for use externally throughout a region or may assign the prefix for use internally within a region. The numbers are never unique if they leave the region and, if assigned for a company's internal use, are not unique if they leave the company or region.

Figure 2.1.6.4 - 1

Format of the Element String												
GS1 Prefix		Item Reference										Check Digit
2	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃

The GS1 Prefix must be in the series 20 to 29. A particular prefix may be assigned either for use on Fixed Measure Trade Items for restricted distribution or for Variable Measure Trade Items (see Section 2.1.7).

The Item Reference is assigned by the company that uses the Element String. Positions N₃ to N₁₂ may contain any digit.

The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the number is correctly composed.

The data transmitted from the bar code reader means that one Fixed Measure Trade Item with a RCN-13 or RCN-12 has been captured.

GS1 Key

Definition

Not Applicable

Rules

Not Applicable

Attributes

Required

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

The data carrier for this Element String is an EAN-13 Bar Code.

The system recognises this Element String by the symbology identifier **JE0** and the GS1 Prefix assigned by the relevant GS1 Member Organisation.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

Not Applicable

2.1.7. Variable Measure Trade Items Scanned at POS

Note: The GS1 DataBar Omnidirectional and Omnidirectional Stacked shall only carry GTIN. GS1 DataBar Expanded Symbols shall encode GTIN with AI (01). Restricted Circulation Numbers (RCNs) shall not be encoded with AI (01) as RCNs are not GTINs.

2.1.7.1. Variable Measure Fresh Food Trade Items Scanned at Point-of-Sale Using GTIN

Application Description

Like a Fixed Measure Trade Item, a Variable Measure Trade Item is an entity with pre-defined characteristics, such as the nature of the product or its contents. Unlike a Fixed Measure Trade Item, a Variable Measure Trade Item has one measure that varies continuously while other characteristics remain the same. The variable measure may be weight, length, number of items contained, or volume.

GS1 Key

Definition

- The GTIN-12 is the 12-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.
- The GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

Reference Fresh Food GTIN Allocation Rules in Section 4

Reference Human Readable Interpretation Rules in Section 4

Attributes

Required

See Section 3.2, a Variable Count or a Trade Measure (AIs 30, 31nn, 32nn, 35nn, 36nn)

Optional

- See in Section 3.2 - GS1 Application Identifiers in Numerical Order for a complete list of all GS1 Application Identifiers.
- For more details related to Application Identifiers for Fresh Foods, refer to the Fresh Foods Implementation Guide.

Rules

Reference Human Readable Interpretation Rules in Section 4.12

Data Carrier Specification

Carrier Choices

- GS1 DataBar Expanded
- GS1 DataBar Expanded Stacked



Note: The GS1 DataBar symbols encode a 14-digit numeric string. When encoding GTIN-12 or GTIN-13 in GS1 DataBar symbols, zero-fill with two or one zeros to the left of the GTIN.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 2, GS1 System Symbol Specification Table 1,

Symbol Placement

None

Unique Application Processing Requirements

None

2.1.7.2. Variable Measure Trade Items Scanned at POS Using Restricted Circulation Numbers

Application Description

Restricted circulation Variable Measure Trade Items are those sold in random quantity against a fixed price per unit quantity and intended to cross a Point-of-Sale (e.g., apples sold at a fixed price per kilogram).

These items are either marked in the store by the retailer or are marked at the source by the supplier. National solutions are available for this purpose.

GS1 Member Organisations should assign one or several of the GS1 Prefixes 02, 20 through 29 for the identification of Variable Measure Trade Items in their territory. GS1 Member Organisations should make part of this capacity available to user companies for company internal applications.

The data fields available after the relevant GS1 Prefix (defined by the GS1 Member Organisation for their territory) can be structured in a variety of ways to represent the product type, net weight, calculated price, or number of units. Equipment is commercially available for automatically weighing items, calculating an item price from the unit price, and printing the information as a bar code label. The scanning equipment and applications can then be programmed to use the prefix as an instruction to decode the ensuing data fields according to the particular structure adopted.

The first row in Figure 2.1.7 - 1 shows the structure specified by GS1 US for North America. The same structure is used by many other GS1 Member Organisations. The next two rows do not show predetermined structures. Examples of recommended structures are given in Figure 2.1.7 - 2. GS1 Member Organisations choose appropriate structures for use within their geographic area.

Figure 2.1.7 - 1 Format of the Element String

GS1 Prefix	Item Reference	Price Verifier-Digit	Item Price	Check Digit
0 2	N ₃ N ₄ N ₅ N ₆ N ₇	N ₈	N ₉ N ₁₀ N ₁₁ N ₁₂	N ₁₃
0 2	N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂			N ₁₃
2 N ₂	N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂			N ₁₃

The Item Reference is usually assigned by the company that scans the Element String at its Point-of-Sale. However, some countries may specify their own standard numbering systems for variable measure products administered by their GS1 Member Organisation or by a trade association.

The Price verifier-digit is the result of a special calculation, and its verification ensures correct reading of the price. For details, see Section 7.10 Security of reading this Element String without a Price verifier-digit depends on the Element String's Check Digit (see Section 7.10).

The item price is the price of the trade item in the relevant currency with an implied decimal point defined by the trading partners or the relevant GS1 Member Organisation. A different format is

required for each position of the implied decimal point. Multiple formats require an unambiguous way to differentiate each format, and separate GS1 Prefixes may be assigned to accomplish this.

The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the data corresponds with the verification rules.

Figure 2.1.7 - 2

Examples of Alternative Data Structures		
Item Reference	Price verifier-digit	Item price
Item Reference		Item price
Item Reference	Measure verifier-digit	Item measure
Item Reference		Item measure

When the price (or weight) of an item is encoded using this Element String, a Price verifier-digit or a Measure verifier-digit should be used. The Measure verifier-digit is calculated from the digits in the item measure field in the same way that the Price verifier-digit is calculated from the item price digits (see Section 7).

The item measure is a measurement of the trade item with a defined unit of measure and an implied decimal point position. The unit of measure and decimal point position are defined within the relevant geographic area for each GS1 Prefix and/or format code. The item measure may be weight only if local weights and measures regulations permit.

The data transmitted from the bar code reader means that data about a Variable Measure Trade Item has been captured. The bar code reader normally performs the Price verifier-digit and the Measure verifier-digit calculation. Failing this, the calculation must take place in the application software.


Although each GS1 Member Organisation and/or user is free to develop a solution for numbering Variable Measure Trade Items, the GS1 System provides recommended structures that provide a degree of equipment standardisation. These formats may include an Item Reference, the retail price of the item, and a Price check-digit. The recommended structures are shown in Figure 2.1.7 - 3.

Figure 2.1.7 - 3

GS1 Prefix	Recommended Data Structures (Exact Structure Determined by GS1 Member Organisation)	Check Digit
0 2	I I I I I V P P P P	C
or	I I I I V P P P P	C
2 0 - 29	I I I I I I P P P P	C
	I I I I I P P P P	C

The GS1 Prefix is administered by each GS1 Member Organisation and denotes the format and meaning of a particular Element String, where:

- **I..I** = Item Reference
- **V** = Price check-digit calculated according to the algorithm specified in Section 7
- **P..P** = Price in local currency
- **C** = Check Digit calculated according to the standard algorithm in Section 7.10

 **Note:** The price field may contain zero, one, or two implied decimal places depending on the monetary unit used. The decimal point, which is not included in the bar code, must nevertheless be taken into account by the marking equipment when printing the Human Readable Interpretation on the label.

GS1 Member Organisations may choose to implement a national solution for Variable Measure Trade Items branded by the supplier for retail. Any national branded variable measure solution requires GS1 Member Organisations to manage the allocation of the item number at a national level.

GS1 Key

Definition

Not Applicable

Rules

Not Applicable

Attributes

Required

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

The data carriers for this Element String are: UPC-A Bar Codes and EAN-13 Bar Codes.

The system recognises this Element String by the symbology identifier **JE0**, the GS1 Prefix 02 or 20 to 29, and the structure defined by the GS1 Member Organisation in which it is operating.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

Not Applicable

2.1.8. Trade Item Extended Packaging

The information obtained from a consumer trade item's packaging can be extended when consumers using mobile devices scan bar codes on the package which leads them to more information or an application. This standard provides a standardized packaging solution which will lead to brand owner authorized information.

Independent of whether a trade item is retail or non-retail, fixed or variable measure, if it is sold to the end consumer and utilizes GTIN-based identification, then it is within the scope of this application.

GTIN is the primary GS1 Key used to access GS1 B2C Trusted Source Data infrastructure and all GS1 application standards for consumer trade items require GTIN, therefore this standard makes normative reference to the Sections in the GS1 General Specifications related to consumer trade items in Figure 2.1.8 - 1. In addition to using GTIN and indirect mode to reach trusted data, the URL AI (8200) with GTIN can be used to reach brand owner authorized information or applications via direct mode. GTIN and AI (8200) are encoded as separate data elements in the bar code but once decoded they are processed in a standard fashion by concatenating the following three strings: the contents of AI (8200), followed by a slash (/) character, followed by the GTIN expressed as 14 numeric digits. For example, where a trade item's GTIN, when expressed as 14 digits is 01234567890128 and the URL for direct mode access to information is <http://example.com/01234567890128>.

When encoded in the symbol, the sequence for encoding is (01) 01234567890128 (8200) <http://example.com>, but when processed the URL, a slash, and the GTIN are combined to arrive at <http://example.com/01234567890128>.

The example provided is not intended to constrain the brand owner to the use of http URL schema, the .com top-level domain, or the specific structure of URL illustrated. Any URL may be used, and in processing the slash character and 14-digit GTIN are appended.

These values are also expressed in Non-HRI text on the label (see Section 4.12, Rule 9). If GTIN attributes beyond AI (8200) are encoded together with GTIN and PRODUCT URL they are processed and expressed in text on the label as <http://brandownerassignedURL.com/gtin/serialnumber> where serial number equals up to 20 alphanumeric digits.

Figure 2.1.8 - 1

Section	Title	General Retail POS	Regulated Healthcare Retail POS	Regulated Healthcare Non-retail POC
2.1.2.1	General Retail Consumer Trade Items	Yes		
2.1.2.2	Loose Produce Trade Items Scanned at POS	Yes		
2.1.2.3	Trade Items Intended for General Distribution and POS	Yes		
2.1.2.4	Healthcare Primary Packaging (Non-Retail Trade Items)			Yes
2.1.2.5	Healthcare Secondary Packaging (Regulated Healthcare Retail Consumer Trade Items)		Yes	
2.1.2.6.1	Trade Items Intended for General Distribution Scanning Only/ Identification of a Trade Item that is a Single Product			Yes
2.1.7.1	Variable Measure Fresh Food Trade Items Scanned at Point-of-Sale Using GTIN	Yes		

GS1 Key

Definition

- For all applications above, GTIN-8 is the 8-digit GS1 Identification key composed of a GS1-8 Prefix, Item Reference, and Check Digit used to identify trade items.
- For all applications above, GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- For all applications above, GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

- For regulated healthcare non-retail applications above, GTIN-14 is the 14-digit GS1 Identification Key composed of an Indicator digit (1-9), GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

All existing rules in the Sections which appear in Figure 2.1.8 - 1 apply as described in each section.

Attributes

Required

Not applicable

Optional

For the purpose of indirect mode, all attributes in the Sections which appear in Figure 2.1.8 - 1 apply as described in each section.

For the purpose of direct mode, AI (8200) must be used in combination with GTIN when brand owners provide extended packaging information or applications.

Rules

All rules in the Sections which appear in Figure 2.1.8 - 1 apply as described in each section.

Data Carrier Specification

Carrier Choices

For the purpose of supporting indirect mode, all carrier choices in the Sections which appear in Figure 2.1.8 - 1 apply as described in each section.

For the purpose of direct mode, in addition to the symbol required for indirect mode, when AI (8200) is used, GS1 DataMatrix and GS1 QR Code are the only approved data carriers. In the case of regulated healthcare consumer trade items, only GS1 DataMatrix is approved.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

To determine the appropriate specifications for printing and quality control, see the System Symbol Specification Table(s) referred to in each Application Standard shown in Figure 2.1.8 -1. See note below Figure 5.5.2.7 – 2.1 related to reverse and mirror-image representation constraint.

Symbol Placement

None defined.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.2. Logistic Units

A logistic unit is an item of any composition established for transport and/or storage that needs to be managed through the supply chain.

Tracking and tracing logistic units in the supply chain is a major application of the GS1 System. Scanning the standard identification number, marked on each logistic unit, allows the physical movement of units to be individually tracked and traced by providing a link between the physical movement of items and the associated information flow. It also opens up the opportunity to implement a wide range of applications, such as cross docking, shipment routing, and automated receiving.

Logistic units are identified with a GS1 identification number called the SSCC (Serial Shipping Container Code). The SSCC is the only GS1 Key that shall be used as the identifier of a logistic unit. The SSCC ensures that logistic units are identified with a number that is unique worldwide.

If, in addition to being a logistic unit, the item is regarded as a trade item by the brand owner, it may additionally be identified with a GTIN. The combination of a GTIN and a serial number must not replace the SSCC as the identifier of a logistic unit.

If, in addition to being a logistic unit, the item is part of a consignment and or a shipment, it may also be associated with the GINC and or the GSIN.

Attribute information, such as a Global Identification Number for Consignment , AI (401), may be optionally encoded using internationally agreed data structures and a bar code symbology that allow unambiguous interpretation.

2.2.1. Individual Logistic Units

Application Description

A logistic unit is an item of any composition established for transport and/or storage that needs to be managed through the supply chain. The identification and symbol marking of logistic units enables a large number of user applications. In particular, the SSCC (Serial Shipping Container Code) provides a link between the physical logistic unit and information pertaining to the logistic unit that is communicated between trading partners using Electronic Data Interchange (EDI).

The SSCC Element String AI (00) is used for the identification of logistic units (see Section 3). Each individual logistic unit is allocated a unique number, which remains the same for the life of the logistic unit. When assigning an SSCC, the rule is that an individual SSCC number must not be reallocated within one year of the shipment date from the SSCC assignor to a trading partner. However, prevailing regulatory or industry organisation specific requirements may extend this period.

In principle, the SSCC provides a unique reference number that can be used as the key to access information regarding the logistic unit in computer files. However, attributes relating to the logistic unit (e.g., ship to information, logistic weights) are also available as standardised Element Strings.

GS1 Key

Definition

The SSCC is the GS1 Identification Key used to identify logistics units. The key is comprised of an Extension Digit, the GS1 Company Prefix, Serial Reference, and Check Digit. Refer to Section 3 for details of the SSCC and associated data elements.

Rules

All SSCC Rules described in Section 4.

Attributes

Required

Identification of a Logistic Unit: AI (00) (See Section 3.2 for List of all GS1 Application Identifier), if Fixed Measure AI (02) or Routing Code AI (403) are used when:

- A logistic unit is a grouping of trade items, it is sometimes useful to indicate the Global Trade Item Number (GTIN) of the contained items in association with the SSCC. See Section 3.2 for List of all GS1 Application Identifier, Identification of Trade Items Contained in a Logistic Unit - Fixed Measure: AI (02) and Count of Trade Items Contained in a Logistic Unit: AI (37).
- Use of AI (02) and AI (37) with SSCC AI (00) is not the preferred option for regulated healthcare trade items. For Regulated Healthcare Trade Items, AI (02) + AI (37) is limited to bilateral use between trading partners for exception handling during a migration period to

eCom (EDI) implementation or if the product is sold as a non-regulated trade item within a retail distribution channel for certain markets. SSCC is the approach selected by healthcare and provides the appropriate level of identification when associated with eCom messaging to provide traceability inclusive of count for trade items contained. SSCC when associated with eCom is required for identification purposes to reach our extended goals for traceability.

- The routing code, AI (403), is assigned by a parcel carrier. It is intended to provide a migration path to the adoption of a yet to be defined international, multi-modal solution. See Section 3.2 for List of all GS1 Application Identifier, Routing Code: AI (403).

Optional

The use of attribute information on logistic units is optional. However, when used, attribute information should be processed with the SSCC that identifies the logistic unit.

- The Element String Ship to - Deliver to Global Location Number: AI (410) has been designed to allow the automatic sortation of logistic units using the Global Location Number (GLN). See Section 3.2 for List of all GS1 Application Identifier.
- The Element String Ship for - Deliver for - Forward to Global Location Number: AI (413), has been designed to allow the cross docking of logistic units using the Global Location Number (GLN). It is used in conjunction with the Element String AI (410) to indicate the cross docking station and the final destination of the logistic unit. See Section 3.2 for List of all GS1 Application Identifier.
- The Element String Ship to - Deliver to Postal Code Within a Single Postal Authority: AI (420) has been designed to allow the automatic sortation of logistic units using the postal code in a single postal area. See Section 3.2 for List of all GS1 Application Identifier.
- The Element String Ship to - Deliver to Postal Code with Three-Digit ISO Country Code: AI (421) has been designed to allow the automatic sortation of logistic units using the postal code. As the postal code is prefixed by the ISO country code, it may be used internationally. See Section 3.2 for List of all GS1 Application Identifier.

Rules

Refer to Section 4 for the mandatory associations.

Data Carrier Specification

Carrier Choices

The mandatory data carrier used to represent GS1 System individual logistic units is the GS1-128 Bar Code Symbolology.

For healthcare, see the “Data Carrier Specification Carrier Choices” recommendations on Options in Addition to the Bar Code at the end of Section [2.1.2.4](#).

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 6, GS1 System Symbol Specification Table 5.

Symbol Placement


All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.2.2. Multiple Logistic Units – Global Identification Number for Consignment

Application Description

- Consignments can comprise one or many logistic units. If the consignment comprises more than one physical object there is no requirement that they are attached together. A consignment number identifies a logical grouping. When a consignment number is read the message is that this physical unit should be associated with any other physical units carrying the same consignment number. Individual physical units carry the SSCC as described in the previous section.
 - The Global Identification Number for Consignment is assigned by the freight forwarder or carrier of the transport units and is referenced in the relevant transport messages and documents HWB (house waybill) etc. It may be used as a communication reference by all parties in the transport chain, such as in Electronic Data Interchange (EDI) messages where it can be used as a consignment reference and/or freight forwarders or carriers loading list. See Section 3.2 for List of all GS1 Application Identifier, Global Identification Number for Consignment (GINC): AI (401).
-  **Note:** Shipment and consignment are terms which may be used interchangeably within the transport and logistics sector however for the purposes of clarity, when referring to multiple logistic unit identification for trade, GS1 uses the term shipment and when referring to multiple logistic unit identification for transport, GS1 uses the term consignment

GS1 Key

Definition

The Global Identification Number for Consignment, AI (401), identifies a logical grouping of goods (one or more physical entities) that has been consigned to a freight forwarder or carrier and is intended to be transported as a whole.

Refer to Section 3.2 for List of all GS1 Application Identifier for detailed information.

Rules

The data transmitted means that the Element String denoting a Global Identification Number for Consignment has been captured. The Global Identification Number for Consignment may be processed as stand-alone information where applicable or with other identification data appearing on the same unit.

See Section 4.9.

Attributes

Required

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

The data carrier used to represent the GS1 Global Identification Number for Consignment is the GS1-128 Bar Code Symbology.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 3, GS1 System Symbol Specification Table 2, and Figure 5.5.2.7 - 7, GS1 System Symbol Specification Table 6.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.2.3. Multiple Logistic Units – Global Shipment Identification Number

Application Description

- Shipments can comprise one or many logistic units. If the shipment comprises more than one physical object there is no requirement that they are attached together. A shipment number identifies a logical grouping. When a shipment number is read the message is that this physical unit should be associated with any other physical units carrying the same shipment number. Individual physical units carry the SSCC as described in the previous section.
- The Global Shipment Identification Number is assigned by a seller (sender) of the goods and is referenced in the despatch advice and bill of lading, etc.. It is a globally unique number that identifies a logical grouping of physical units in a transport shipment. It may be used as a communication reference by all parties in the transport chain, such as in Electronic Data Interchange (EDI) messages where it can be used as a shipment reference and/or a consignor's loading list. See Section 3.2 for List of all GS1 Application Identifier, Global Shipment Identification Number (GSIN): AI (402).
- Note: Shipment and consignment are terms which may be used interchangeably within the transport and logistics sector however for the purposes of clarity, when referring to multiple logistic unit identification for trade, GS1 uses the term shipment and when referring to multiple logistic unit identification for transport, GS1 uses the term consignment.

GS1 Key

Definition

The Global Shipment Identification Number (bill of lading) is a number assigned by a seller (sender) of the goods. It provides a globally unique number that identifies a logical grouping of physical units for the purpose of a transport shipment

Rules

The data transmitted means that the Element String denoting a shipment identification number has been captured. The Global Shipment Identification Number may be processed as stand-alone information where applicable or with other identification data appearing on the same unit.

See Section 4.10.

Attributes

Required

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification**Carrier Choices**

The data carrier used to represent GS1 Global Shipment Identification Number is the GS1-128 Bar Code Symbology.

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 3, GS1 System Symbol Specification Table 2, and Figure 5.5.2.7 - 7, GS1 System Symbol Specification Table 6.

Symbol Placement

All the Symbol Placement Guidelines defined in Section 6.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.3. Assets

The GS1 System provides a method for the identification of assets. The object of asset identification is to identify a physical entity as an inventory item.

Each company holding a GS1 Company Prefix may assign asset identifiers to the assets or trade items supplied to their customers.

Each company holding a GS1 Company Prefix may assign a Global Returnable Asset Identifier (GRAI) or Global Individual Asset Identifier (GIAI). If the asset is manufactured on behalf of a company best practice may dictate that the manufacturing company applies the GRAI or GIAI during the manufacturing process on behalf of this customer.



Note: Where assets of the same type need to be ordered a GTIN is required for the ordering process. There is no conflict when a GTIN and a GRAI (GS1 Company Prefix, Asset Type and Check Digit) have the same digits, because the data carrier (EDI qualifier, GS1 Bar Code with GS1 Application Identifier, or EPC/RFID) will distinguish between the two GS1 Identification Keys.

The GS1 System asset identifiers act as keys to access the characteristics of an asset stored in a computer file and/or to record movements of assets.

Asset identifiers may be used for applications, such as the location and usership of a given asset (e.g., a personal computer or returnable transport item) or for complex applications, such as recording the characteristics of a returnable asset (e.g., a reusable beer keg), its movements, its life-cycle history, and any relevant data for accounting purposes.


2.3.1. Global Returnable Asset Identifier (GRAI): AI (8003)

Application Description

A Returnable Asset is a reusable package or transport equipment of a certain value, such as a beer keg, a gas cylinder, a plastic pallet, or a crate. The GS1 System identification of a Returnable Asset, the Global Returnable Asset Identifier (GRAI), enables tracking as well as recording of all relevant data.

The Element String comprises the GRAI (see Section 3.2 for List of GS1 Application Identifier). The GRAI is composed of the GS1 Company Prefix of the company assigning the asset identifier and of the Asset Type. The latter is assigned to uniquely identify, together with the GS1 Company Prefix, a particular kind of asset. The GRAI remains the same for all identical Returnable Assets. Although consecutive numbering is recommended, the structure is left to the discretion of the assigning company. An optional serial number may be used to distinguish Individual Assets within a given asset type.

A typical application using this Element String is in tracking returnable beer kegs. The owner of the beer keg applies a bar code carrying a GRAI to the keg using a permanent marking technique. This bar code is scanned whenever the keg is supplied full to a customer and scanned again when it is returned. This scanning operation allows the beer keg owner to automatically capture the life-cycle history of a given keg and to operate a deposit system, if desired.

 **Note:** This Element String identifies a physical entity as a Returnable Asset. When such a physical entity is used to transport or to contain a trade item, the Element String AI (8003) must never be used to identify the transported or contained trade item.

GS1 refers to GRAI in the Section [2.1.1.8](#) which deals with small medical or surgical instruments for the Automatic Identification and Data Capture (AIDC) management of instruments within the micro-logistics cycle of use, cleaning and sterilization. See Section [2.1.1.8](#) for more details.

GS1 Key

Definition

The GS1 Identification Key used to identify Returnable Assets. The key is comprised of a GS1 Company Prefix, Asset Type, Check Digit, and optional serial number.

The structure of the Element String for a Global Returnable Asset Identifier (GRAI) can include two parts: the mandatory Asset Type Identification and an optional serial number (see Section 3.2 for List of GS1 Application Identifier).

Rules

See Section 4, Application Rules.

Attributes

The attributes of the asset should be established on a computer file using the GS1 System asset identifier as the key to the information. Examples of the type of information held include the full name and address of the party who owns the asset, the value of the asset, the location of the asset, and the life-cycle history of the asset.

Required

Not Applicable.

Optional

The owner of the asset assigns the optional serial number. It denotes an Individual Asset within a given Asset Type. The field is alphanumeric and is used to distinguish Individual Assets with the same Asset Types.

See Section 3.2 for List of all GS1 Application Identifier, Global Returnable Asset Identifier (GRAI): AI (8003).

Rules

See Section 4, Application Rules (none is currently identified).

Data Carrier Specification

Carrier Choices

For multi-sector use other than for small medical / surgical instruments the only data carrier used to represent GS1 System asset identifiers is the GS1-128 Bar Code Symbology. When encoding an asset identifier for small medical / surgical instruments see section [2.1.1.8](#).

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 3, GS1 System Symbol Specification Table 2.

Symbol Placement

Not Applicable.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.3.2. Global Individual Asset Identifier (GIAI): AI (8004)

Application Description

In the GS1 System, an Individual Asset is considered a physical entity made up of any characteristics.

This Element String identifies a particular physical entity as an asset. It must not be used for other purposes and must be unique for a period well beyond the lifetime of the relevant asset records. Whether or not, the assigned Global Individual Asset Identifier (GIAI) may remain with the physical item when changing hands depends on the particular business application. If it remains with the physical item, then it must never be re-used.

The GIAI comprises the GS1 Company Prefix of the company assigning the asset identifier and an Individual Asset Reference (see Section 3). The Individual Asset Reference is alphanumeric. Its structure is left to the discretion of the company applying the Element String.

This Element String might, for example, be used to record the life-cycle history of aircraft parts. By symbol marking the GIAI, AI (8004), on a given part, aircraft operators are able to automatically update their inventory database and track assets from acquisition until retirement.

GS1 refers to GIAI in the Section [2.1.1.8](#) which deals with small medical or surgical instruments for the Automatic Identification and Data Capture (AIDC) management of instruments within the micro-logistics cycle of use, cleaning and sterilization. See Section [2.1.1.8](#) for more details.

GS1 Key

Definition

The GS1 Identification Key used to identify an Individual Asset. The key is comprised of a GS1 Company Prefix and an Individual Asset Reference (see Section 3.2 for List of all GS1 Application Identifier).

Rules

See Section 4, Application Rules.

Attributes

The attributes of the asset should be established on a computer file using the GS1 System asset identifier as the key to the information. Examples of the type of information held include the full name and address of the party who owns the asset, the value of the asset, the location of the asset, and the life-cycle history of the asset.

Required

None is currently standardized.

Optional

None is currently standardized.

Rules

See Section 4, Application Rules (none is currently identified).

Data Carrier Specification**Carrier Choices**

For multi-sector use other than for small medical / surgical instruments the only data carrier used to represent GS1 System asset identifiers is the GS1-128 Bar Code Symbology. For small medical / surgical instruments see section [2.1.1.8](#).

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 3, GS1 System Symbol Specification Table 2.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.4. Locations

GS1 System has defined two broad classes of entities that are identified with a Global Location Number: Physical Locations and Parties. The distinguishing characteristic between the two is one is always an object or point in the physical world (structure, building, or a specific location within a site) and the other is a business or business function (a party to a transaction, a group, or organisation, including regulatory and other public sector agencies), which may be associated with a physical location.

2.4.1. Introduction

A Global Location Number (GLN) is used to identify any location that needs to be uniquely identified for use in the supply chain.

The GLN makes possible the unique and unambiguous identification of physical locations and parties used in the supply chain. Identification in this manner is a prerequisite to efficient Electronic Commerce between trading partners (e.g., Electronic Data Interchange (EDI), electronic catalogues). The GLN is a 13-digit number created by a GS1 Company Prefix, a Location Reference and a Check Digit. Note that when a U.P.C. Prefix is used to generate the GLN, the U.P.C. Prefix should be considered as having a leading zero (see Section 1.3 for a full definition of the GS1 Company Prefix).

Within the GS1 System, the GLN and the Global Trade Item Number (GTIN) are two distinct data identifiers. There is no conflict when a GTIN and a GLN have the same digits, because the data carrier (EDI, machine readable symbol, or radio frequency) will distinguish between the two identifiers. For example, when GLNs are used in Automatic Identification and Data Capture (AIDC) and EDI, the context (Application Identifiers and qualifiers) will prevent any misinterpretation. Each company or organisation that is a member of a GS1 Member Organisation may use GLNs to identify locations under the terms of its membership. For full contact details of the GS1 Member Organisations worldwide, visit www.gs1.org.

Although in some countries the national GLN database is administered by the GS1 Member Organisation, it remains the responsibility of the company issuing the numbers to keep business partners informed of all relevant GLNs related to the trading relationship. Special care is needed if ownership of the company changes (see Section 1.7).

In business operations, location numbers are of no value if they are not associated with business attributes. The attributes of the location ideally should be established as part of master data management using the GLN as the key to the information.

These attributes, in conjunction with transactional data, answer the three questions of who, what, and where.

The GLN is designed to improve the efficiency of communication with trading partners and add value to the trading partners involved as well as to consumers.


For communication between trading partners, a GLN should be used following the rules defined in Section 4.

2.4.2. EDI and Global Data Synchronization (GDS)

Electronic Data Interchange (EDI) ideally uses Global Location Numbers (GLNs) to identify all trading partners and physical locations involved. The mailbox or network address for companies has traditionally been identified with a GLN to support EDI applications. The EDI standards promoted by the GS1 System (EANCOM, GS1 Business Messaging Standards (XML)) make full use of GLNs to simplify the automation of business messaging. Any GLN related Application Identifier should have an equivalent field (data element) in EDI messages.

GLNs and associated information of trading partners are communicated at the start of the relation through the party information message (PARTIN). GLNs are then used during the trading relationship in any other business message, such as invoice, order, pay, or deliver.

National data pools and the global registry that links them for the purpose of global data synchronisation mandate the use of GLNs to identify each party that provides information to any data pool or who requires information about products and locations.


 **Note:** The GS1 General Specifications do not provide details on business messages or the Global Data Synchronisation Network (GDSN). For further information, please consult the relevant GS1 standard.

2.4.3. Application Overview

The Global Location Number (GLN) provides a unique and unambiguous identification of physical locations and parties used in the supply chain or participating in a business process.

Physical Location - A site (an area, a structure or group of structures) or an area within the site where something was, is, or will be located.

Party – Any legal entity or organisation (including regulatory and other public bodies), business function, group, or individual actor; a participant in one or more business processes.

 **Note:** A party may have an address associated with it whereas a physical location always has a geographical address.


A geographical address is a collection of information expressing a specific location on the Earth's surface. Most commonly a postal delivery address; but could be any geographical coordinate system such as latitude & longitude.

2.4.3.1. Physical Location

The identification of physical locations is an essential element for supply chain visibility. A GLN assigned to a physical location always has a permanent and identifiable geographical address regardless of any business process roles conducted at the site. If the GLN + GLN Extension Component are used to identify locations within the site, each sub-location identification shall follow the same reassignment rules defined in section 4 for the site GLN.

The following figure illustrates just one likely example; it is not the only normative solution.

Figure 2.4.3.1 - 1 Physical Locations in a Logistic Process



Physical Location Extension

Business processes causes objects (products, assets, or other equipment) to move from one physical location to another. The ability to have visibility to these movements is an essential element in any supply chain.

These physical locations can be a site such as a distribution centre or a specific location within the site such as a selling floor; it can even be as granular as a specific area on a shelf. The GLN + GLN Extension Component provides a method for identifying locations at a very granular level.

The use of GLN + GLN Extension Component restricted to physical locations. The GLN Extension Component may be communicated to trading partners, by mutual agreement.

The GLN Extension Component may used to identify internal physical locations within a location identified with a GLN (e.g., stores, factories, buildings). A company may choose to assign a unique GLN, without an extension component, as a way to identify these locations

Physical Location Data Carriers

There are two data carriers, other than human readable, used to represent a GLN or GLN + GLN Extension Component: the GS1-128 Bar Code and an EPC RFID Tag.

For more information on EPC carriers see the EPC Tag Data Standard (latest revision).

For more information on bar code carriers, see Section 2.4.4 Global Location Number to Identify a Physical Location: AI (414)


2.4.3.2 Party

Parties require identification within electronic business networks (e.g., Electronic Data Interchange (EDI) networks, electronic catalogues). The use of Global Location Numbers (GLNs) in these areas is driven by the exact party role within a given business process requirement. The GLN can be used as a GS1 Identification Key to access master data associated with a given business transaction.

The figure below illustrates an example of a high level business process between a supplier and the supplier's customer. Certainly both the supplier and the customer would have allocated a GLN to identify their respective enterprise. Beyond that GLNs are used to identify the customer's purchasing or buying organisation, the supplier's order contact, supplier's billing contact, and the customer's payable department.

These GLNs identify parties to different business processes and transactions.

Figure 2.4.3.1 - 2 Party Locations in Business Processes



2.4.4. Global Location Number to Identify a Physical Location: AI (414)

Application Description

An Element String with an Application Identifier AI (414) identifies a physical location. This implies that this Element String is represented in a data carrier on the location itself. Physical locations may, for example, be a room, a door of a warehouse, an x-ray room in a hospital, or a control point.

This Element String may be used to record and confirm presence at a given location for any purpose. An equivalent field will hold this information in Electronic Messages.

A typical application using this Element String is the identification of a warehouse dock as a delivery point. The driver is directed to a given warehouse dock and the Global Location Number (GLN) identifying the warehouse dock, and the Global Trade Item Number (GTIN) or SSCC (Serial Shipping Container Code) identifying the goods are scanned whenever a delivery is made to the location. The Electronic Message from the scanner is then used to automatically update the warehouse's stock management system of the delivery.

GS1 Key

Definition

The Global Location Number (GLN) is the GS1 Identification Key used to identify physical locations or parties. The key is comprised of a GS1 Company Prefix, Location Reference, and Check Digit.

Rules

All the GLN Allocation Rules described in Section 4.

Attributes

Required

See Section 3.2 for List of all GS1 Application Identifier, Identification of a Physical Location - Global Location Number: AI (414).

Optional

The extension component may be used to identify internal physical locations within a location identified with a GLN (e.g., stores, factories, buildings). The use of GLN Extension Component is restricted to physical locations.

The GLN Extension Component may be communicated to trading partners, by mutual agreement.

The GS1 Application Identifier (254) is used to represent the GLN Extension Component in conjunction with AI (414).

For more information, see Section 3.2 for List of all GS1 Application Identifiers.

Rules

See Section 4, Mandatory Association of Element Strings.

Data Carrier Specification

Carrier Choices

The Global Location Number (GLN) is used to identify a physical location and, when required, may be carried by a bar code using the appropriate Application Identifier. The data carrier used to represent the GLN is the GS1-128 Bar Code Symbolology.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

When encoding the Global Location Number (GLN), GS1-128 Bar Codes should be printed at an X-dimension between 0.249 mm (0.0098 in.) and 1.016 mm (0.0400 in.). However, if the GLN is carried by a bar code on a GS1 logistic label, the recommendations contained in Section [2.2](#) apply.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.4.5. Ship to – Deliver to Global Location Number: AI (410)

Application Description

An Element String with an Application Identifier AI (410) represents the Global Location Number (GLN) of the recipient of a logistic unit. The GLN refers to the address where a particular transport unit identified with an SSCC is to be delivered. This Element String is used in single leg transport operations. A logistic unit may include a bar code carrying the GLN of the unit's intended destination.

When scanning this Element String, the data transmitted may be used to retrieve the related address and/or to sort the item by destination.

GS1 Key

Definition

The Global Location Number (GLN) is the GS1 Identification Key used to identify physical locations or parties. The key is comprised of a GS1 Company Prefix, Location Reference, and Check Digit.

Rules

All the GLN Allocation Rules described in Section 4.

Attributes

Required

See Section 3.2 for List of all GS1 Application Identifier, Ship to - Deliver to Global Location Number: AI (410).

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

The data carrier used to represent the Global Location Number (GLN) is the GS1-128 Bar Code Symbology.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

When encoding the Global Location Number (GLN), GS1-128 Bar Codes should be printed at an X-dimension between 0.249 mm (0.0098 in.) and 1.016 mm (0.0400 in.). However, if the GLN is carried by a bar code on a GS1 logistics label, the recommendations contained in Section [2.2](#) apply.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.4.6. Bill to - Invoice to Global Location Number: AI (411)

Application Description

An Element String with Application Identifier AI (411) represents the Global Location Number (GLN) of the addressee of an invoice. The GLN refers to the name and address of the business partner to which an entity shall be invoiced and includes accounting-related information that may be used wherever required.

GS1 Key

Definition

The Global Location Number (GLN) is the GS1 Identification Key used to identify physical locations or parties. The key is comprised of a GS1 Company Prefix, Location Reference, and Check Digit.

Rules

All the GLN Allocation Rules described in Section 4.

Attributes

Required

See Section 3.2 for List of all GS1 Application Identifier, Bill to - Invoice to Global Location Number: AI (411).

Optional

Not Applicable

Rules

See Section 4.

Data Carrier Specification

Carrier Choices

The data carrier used to represent the Global Location Number (GLN) is the GS1-128 Bar Code Symbology.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

When encoding the Global Location Number (GLN), GS1-128 Bar Codes should be printed at an X-dimension between 0.249 mm (0.0098 in) and 1.016 mm (0.0400 in). However, if the GLN is carried by a bar code on a GS1 logistic label, the recommendations contained in Section [2.2](#) apply.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For description of processing requirements, see Section 7.

2.4.7. Purchased from Global Location Number: AI (412)

Application Description

In business it is sometimes important to know from where a particular item was purchased. Applied on a trade item, an Element String with Application Identifier AI (412) provides the Global Location Number (GLN) of the company from which the respective trade item has been purchased.

GS1 Key

Definition

The Global Location Number (GLN) is the GS1 Identification Key used to identify physical locations or parties. The key is comprised of a GS1 Company Prefix, Location Reference, and Check Digit.

Rules

All the GLN Allocation Rules described in Section 4.

Attributes**Required**

See Section 3.2 for List of all GS1 Application Identifier, Purchased from Global Location Number: AI (412).

Optional

Not Applicable

Rules

See Section 4.

Data Carrier Specification**Carrier Choices**

The data carrier used to represent the Global Location Number (GLN) is the GS1-128 Bar Code Symbology.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

When encoding the Global Location Number (GLN), GS1-128 Bar Codes should be printed at an X-dimension between 0.249 mm (0.0098 in.) and 1.016 mm (0.0400 in.). However, if the GLN is carried by a bar code on a GS1 logistic label, the recommendations contained in Section [2.2](#) apply.

Symbol Placement

Not Applicable

Unique Application Processing Requirements


For description of processing requirements, see Section 7.

2.4.8. Ship for - Deliver for - Forward to Global Location Number: AI (413)**Application Description**

An Element String with Application Identifier AI (413) is used by the consignee for determining the internal or subsequent final destination of a physical unit.

Cross docking is a typical application using this Element String. Here, a bar code carrying the Element String AI (410) is placed on a logistic unit at the point of creation to direct the goods to the intermediate destination (e.g., a distribution centre). The Element String AI (413) is also carried by the bar code to direct the goods to their final destination (e.g., a retail store served by the distribution centre).

Figure 2.4.8 - 1 Example of a Cross Docking Application



GS1 Key

Definition

The Global Location Number (GLN) is the GS1 Identification Key used to identify physical locations or parties. The key is comprised of a GS1 Company Prefix, Location Reference, and Check Digit.

Rules

All the GLN Allocation Rules described in Section 4.

Attributes

Required

See Section 3.2 for List of all GS1 Application Identifier, Ship for - Deliver for - Forward to Global Location Number: AI (413).

Optional

Not Applicable

Rules

See Section 4.

Data Carrier Specification

Carrier Choices

The data carrier used to represent the Global Location Number (GLN) is the GS1-128 Bar Code Symbology.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

When encoding the Global Location Number (GLN), GS1-128 Bar Codes should be printed at an X-dimension between 0.249 mm (0.0098 in.) and 1.016 mm (0.0400 in.). However, if the GLN is carried by a bar code on a GS1 logistics label, the recommendations contained in Section 2.2 apply.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.4.9. Global Location Number of the Invoicing Party: AI (415)**Application Description**

An Element String with Application Identifier AI (415) is used to indicate the Global Location Number (GLN) of the invoicing party. The GLN is mandatory information for the payment slip application (see Section [2.6.10](#)).

GS1 Key**Definition**

The Global Location Number (GLN) is the GS1 Identification Key used to identify physical locations or parties. The key is comprised of a GS1 Company Prefix, Location Reference, and Check Digit.

Rules

All the GLN Allocation Rules described in Section 4.

Attributes**Required**

See Section 3.2 for List of all GS1 Application Identifier, Global Location Number of the Invoicing Party: AI (415).

Optional

Not Applicable

Rules

See Section 4, Mandatory Association of Element Strings.

Data Carrier Specification**Carrier Choices**

The data carrier used to represent the Global Location Number (GLN) is the GS1-128 Bar Code Symbology.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

When encoding the Global Location Number (GLN), GS1-128 Bar Codes should be printed at an X-dimension between 0.249 mm (0.0098 in.) and 1.016 mm (0.0400 in.). However, if the GLN is carried by a bar code on a GS1 logistics label, the recommendations contained in Section [2.2](#) apply.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.5. Service Relationships

Application Description

The Global Service Relation Number (GSRN) is a non-significant number used to identify the relationship between an organisation offering services and the individual entities providing or benefitting from the services. The GSRN provides unique and unambiguous identification. It is the key to accessing information, stored on computer systems, relevant to service(s) provided and received and in some cases, these services could be recurring. The GSRN may also be used for referencing information transferred via Electronic Data Interchange (EDI).

When using the GSRN, often two types of relationships may need to be captured in one transaction:

1. the relationship between the organisation offering the service and the actual recipient of the service.
2. the relationship between the organisation offering the service and the actual provider of the service.

It should be noted that the GSRN is not meant to identify a single service as a trade item, neither is it used to identify a physical unit as a trade item. It may identify a physical unit for service purposes (e.g., a computer with a service agreement).

2.5.1. Global Service Relation Number – Provider: AI (8017)

An Element String with Application Identifier AI (8017) represents the Global Service Relation Number of a relationship between the organisation offering the service and the provider of the service.

Some examples of how the GSRN can be used to identify the service relationships are:

- A medical procedure, where it could be used to identify an individual medical provider by role. For identification of the individual provider of care, the hospital or the appropriate authority generates a GSRN with AI (8017) for each of its caregivers and encodes it in an appropriate GS1 Data Carrier (bar code) symbol on the caregiver's ID card, work station, work order, etc. In this case, the GSRN would ensure non-significant identification management, securing identification uniqueness and also allowing linkage to local rule management systems.
- A service agreement, where it could be used to manage agreed upon services, such as maintenance services for a television or computer
- A loyalty program required to identify the service relationship between the loyalty program and the service provider (i.e. company providing merchandise due to use of loyalty points).
- Hospital administration can identify the service relationship between hospital and the doctor, nurses, etc.

GS1 Key

Definition

The Global Service Relation Number is the GS1 Identification Key used to identify the relationship between an organisation offering services and the recipient or provider of services. The key is comprised of a GS1 Company Prefix, Service Reference and Check Digit.

Rules

See Section 4, GSRN Allocation Rules.

Attributes

Required

See Section 3.2 for the List of all GS1 Application Identifiers, Global Service Relation Number AI (8017) and AI (8018).

Optional

Application Identifier AI(8019) Service Relation Instance Number, Section 3.2

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

The data carriers for the Global Service Relation Number (GSRN) are the GS1-128 and GS1 DataMatrix Symbolologies.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 12 GS1 System Symbol Specification Table 11

Symbol Placement

No standard placement is required.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.5.2. Global Service Relation Number – Recipient: AI (8018)

An Element String with Application Identifier AI (8018) represents the Global Service Relation Number of a relationship between the organisation offering the service and the recipient of the service.


Some examples of how the GSRN can be used to identify the service relationships are:

- A hospital admission, where it could be used to identify a subject of care globally and uniquely for AIDC purposes and establish an identification uniqueness that does not harm privacy. For identification of the subject of care (patient) the hospital generates a GSRN with AI (8018) for each of its patients and encodes it in an appropriate GS1 Data Carrier (bar code) on the patient's wristband as well as his or her corresponding medical record, pathology samples, etc. The GSRN may then be used as the key to link multiple or specific instances of treatment, room charges, medical tests, and patient charges.
- A membership in a frequent flyer programme, where it could be used to record awards, claims, and preferences
- A membership in a loyalty scheme, where it could be used to record visits, purchase value, and awards
- A membership in a club, where it could be used for recording entitlements, use of facilities, and subscriptions
- A loyalty program required to identify the service relationship between the loyalty program and the recipient of the loyalty program (the end user or customer who earns loyalty points).
- Patient Admission to a hospital can identify the service relationship between the hospital and the patient.

- Utility networks, such as those providing electricity, gas or water, where it could be used to identify the relationship between network service providers and suppliers of utility products.

A GSRN could be used to give students access to other libraries that have formed a cooperative lending agreement. A typical application is the identification of membership in a student library. The library would issue all members a card that includes a unique GSRN identifying the relationship between the library and a student. The library would then scan the GSRN whenever a book was lent or returned. The Electronic Message from the scanner would then be used to automatically update the library's stock management database. See Figure 2.5.2 – 1 for an example of how the service relationship identifier would appear on this membership card.

Figure 2.5.2 - 1



GS1 Key

Definition

The Global Service Relation Number is the GS1 Identification Key used to identify the relationship between an organization offering services and the recipient or provider of services. The key is comprised of a GS1 Company Prefix, Service Reference and Check Digit.

Rules

See Section 4, GSRN Allocation Rules.

Attributes

Required

See Section 3.2 for the List of all GS1 Application Identifiers, Global Service Relation Number AI (8017) and AI (8018).

Optional

Application Identifier AI (8019) Service Relation Instance Number, Section 3.2.

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

The data carriers for the Global Service Relation Number (GSRN) are the GS1-128 and GS1 DataMatrix Symbologies.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 5, GS1 System Symbol Specification Table 4.

Symbol Placement

No standard placement is required.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.5.3. Service Relation Instance Number: AI (8019)

When a product or service is administered (e.g., a particular treatment is given) it can easily be associated with the patient by scanning the Global Trade Item Number (GTIN) of the product or service as well as the caregiver's GSRN (bar coded with AI (8017)) and the patient's GSRN (bar coded with AI (8018)). If the subject of care identification needs to, optionally, be made more granular with a sequence indicator corresponding to each encounter during the episode of care, attribute data in the form of a Service Relation Instance Number (Application Identifier AI (8019), see Section 3.2) may be added. This would, for example, allow differentiation of subject of care identification captured from an identification band, both before and after its replacement (i.e. radiology examination). If the treatment plan requires different instances of care, such as chemotherapies, and when a record should be captured for each instance, the SRIN linked to the GSRN may be used.

2.6. Special Applications

2.6.1. Coupons

A coupon is a voucher that can be redeemed at the Point-of-Sale for a cash value or free item. Coupon identification is organised at the local level. Determining the data structure of a coupon is, therefore, the responsibility of the GS1 Member Organisations for their area of jurisdiction.

The purpose of coupon numbering and symbol marking is to automate and speed up coupon handling procedures at the Point-of-Sale. Moreover, coupon issuers and retailers may be able to reduce the costs involved in sorting coupons, administering manufacturers' payments, and producing reports on redemption.

All GS1 System coupon standards presented here allow for coupon validation (e.g., to check whether the item(s) covered by the coupon is within the customer's order).

If either validation or value look up is performed, manufacturers must advise their distributors and retailers of the impending issue of a coupon so that retailers' files can be updated to process the information at the Point-of-Sale.

A GS1 System coupon number is used for numbering promotional coupons for manufacturers and retailers as well as tokens with monetary value, such as gift tokens, book tokens, food stamps, record vouchers, luncheon vouchers, and social security tokens.

The structure of GS1 System coupon numbers ensures uniqueness against all other GS1 System numbers only when used within the monetary area of the appropriate GS1 Member Organisation(s).

2.6.2. Allocating GS1 System Coupon Data

2.6.2.1. General Rule

GS1 System coupon identification specifications are flexible and have been designed to cater to current and future requirements.

Due to the nature of coupon numbering, a range of national solutions is offered, each of which is defined by the respective GS1 Member Organisation. National coupon solutions are not unique worldwide and must be operated in the restricted area defined by the GS1 Member Organisation.

In the interest of consistency and to avoid misinterpretation by equipment vendors, when defining national specifications, GS1 Member Organisations should include appropriate mention of all GS1 System coupon data structures.

Coupon reference numbers must not be re-used for a period of three years.

2.6.2.2. Recommendation on Allocating Coupon Reference Numbers

The exact method used to allocate GS1 System coupon reference numbers is left to the discretion of the issuing organisation. However, the GS1 US Coupon Code must be unique for each individual promotion.

For ease of administration, coupon reference numbers should be allocated sequentially.

2.6.3. Coupon Identification for Restricted Geographic Distribution (GS1 Prefix 99)

Application Description

A coupon is a voucher with a cash value that is deducted at the Point-of-Sale. It is sometimes associated with a specific trade item. Coupon identification is organised on a national level and is therefore not unique worldwide. The specification of the coupon data structure in the Element String is the responsibility of each GS1 Member Organisation.

The internationally agreed standard for GS1 System coupon numbers is shown in Figure 2.6.3 - 1.

Figure 2.6.3 - 1

GS1 Prefix	Coupon Data (Structure Determined by GS1 Member Organisation)	Check Digit
9 9	N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂	N ₁₃

The GS1 Prefix 99 denotes the Element String for GS1 coupon identification.

The structure of the coupon data field is determined according to the needs of a particular country. Mandatory components are the coupon issuer number and the coupon reference number. Other useful data are the redemption value in real or encoded format and codes for the decimal point or tax rates.

The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the data corresponds with the verification rules.

The data transmitted from the bar code reader means that the data of a coupon has been captured. Processing of coupons at a Point-of-Sale usually consists of validity checks and deduction of its value.

Within this agreed standard for GS1 System coupon numbers, each GS1 Member Organisation is free to develop a national coupon solution. Four recommended structures provide a degree of equipment standardisation. These recommended structures are shown in Figure 2.6.3 - 2.

Figure 2.6.3 - 2

GS1 Prefix	Recommended Coupon Data Structures (Exact Structure Determined by GS1 Member Organisation)	Check Digit
9 9	Y Y Y Y R R R V V V	C
9 9	Y Y Y R R R V V V V	C
9 9	Y Y Y Y Y R R R T T	C
9 9	Y Y Y Y Y R R R R R	C

Where:

- Y** = Coupon issuer number (issued by the GS1 Member Organisation)
- R** = Coupon reference number (allocated by a coupon issuer)
- V** = Redemption value
- T** = Value code (standardised by the GS1 Member Organisation)
- C** = Check Digit calculated according to the standard algorithm

The GS1 Member Organisations or retailers may require that the third digit of the coupon numbers (990 to 999) be programmable in order to cope with specific demands such as:

- Taxable or non-taxable coupons
- Different currencies
- Indication of the decimal position

GS1 Key

Definition

Not Applicable

Rules

Not Applicable

Attributes

Required

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

A coupon with the GS1 Prefix 99 is carried by the EAN-13 Bar Code.

The system recognises this Element String by the symbology identifier **JE0** and the GS1 Prefix.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.6.4. GS1 Common Currency Coupon Identification (GS1 Prefixes 981 to 983)

A coupon is a voucher with a cash value that is deducted at the Point-of-Sale. It is sometimes associated with a specific trade item. Coupon identification is normally organised on a national level using the GS1 Prefix 99. However, for a common currency area, coupon identification is organised between participating countries. Determining the coupon data structure in the Element String is the responsibility of all the GS1 Member Organisations in the common currency area.

The GS1 Prefixes 981 to 983 have been released for use with coupons expressing a value in a common currency.

The structure of the coupon data positions is determined according to the needs of a particular set of countries. Mandatory components are the coupon issuer number and the coupon reference number. Further useful data is the redemption value in real or encoded format and numbers for the decimal point or tax rates.

The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the data corresponds with the verification rules.

The internationally agreed standard for GS1 Common Currency Coupon Codes is shown in Figure 2.6.4 - 1.

Figure 2.6.4 - 1

GS1 Prefix	Coupon Data (Structure Determined by GS1 MOs in Common Currency Area)	Check Digit
9 8 1 - 9 8 3	N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂	N ₁₃

Within this structure, GS1 Member Organisations in a common currency area should develop a common coupon solution that is valid throughout the common currency area.

2.6.4.1. Use of GS1 Common Currency Coupon Code for the Euro

Application Description

At present the only application of GS1 Prefixes 981, 982 and 983 is for the euro. The euro is a new currency that began to replace the national currencies of some countries in the European Union.

Within the euro area, coupon issuer numbers are administered by:

GS1 BELGIUM • LUXEMBOURG
 Rue Royale 29
 1000 Brussels
 Belgium
 Tel: + 32.2.229.18.80
 Fax: + 32.2.217.43.47
 Contact: info@gs1belu.org


See Figure 2.6.4.1 - 1 for the coupon data structure in the euro area.

Figure 2.6.4.1 - 1

GS1 Prefix	Coupon Data			Check Digit
9 8 1	Y ₁ Y ₂ Y ₃ Y ₄	R ₁ R ₂	E E , E	C
9 8 2	Y ₁ Y ₂ Y ₃ Y ₄	R ₁ R ₂	E , E E	C
9 8 3	Y ₁ Y ₂ Y ₃ Y ₄	R ₁ R ₂	E , E E	C

Where:

- Y = Coupon issuer number (issued by a GS1 Member Organisation)
- R = Coupon reference number (allocated by a coupon issuer)
- E = Redemption value (expressed in euro); value 000 indicates free gift
- C = Check Digit calculated according to the standard algorithm

 **Note:** The only difference between the two structures is the position of the implied decimal point.

GS1 Key

Definition

Not Applicable

Rules

Not Applicable

Attributes

Required

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

A coupon with the GS1 Prefix 981, 982 or 983 is carried by the EAN-13 Bar Code.

The system recognises this Element String by the symbology identifier **JE0** and the GS1 Prefix. The data transmitted from the bar code reader means that the data of a common currency coupon has been captured. Processing of coupons at a Point-of-Sale usually consists of validity checks and deduction of its value.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.6.5. GS1 US Coupon Code Identification for Use in North America (U.P.C. Prefix 5)

Application Description

GS1 US coupon identification consists of the actual coupon identification data and supplementary information represented in a GS1-128 Coupon Extended Bar Code. The *Application Standard for GS1 US Coupon Codes* provides detailed information on data contents and applied codes.












- 
Note: GS1 US coupon identification is used in the United States and Canada and cannot be used beyond their boundaries.

Figure 2.6.5 - 1

Format of the Element String				
U.P.C. Prefix	Company Number	Family Code	Value Code	Check Digit
5	N ₂ N ₃ N ₄ N ₅ N ₆	N ₇ N ₈ N ₉	N ₁₀ N ₁₁	N ₁₂

- 
 The U.P.C. Prefix 5 denotes the Element String for GS1 US coupon identification.
 - 
 The Company Number is that of the company issuing the coupon for redemption if a product symbol marked with the same Company Number in the item identification number has been purchased.
 - 
 The Family Code is used to validate the coupon.
 - 
 The Value Code is the redemption value of the coupon in encoded format.
 - 
 The Check Digit is explained in Section 7.10. Its verification, carried out automatically by the bar code reader, ensures that the data corresponds with the verification rules.
 - 
 The data carrier for this Element String is the UPC-A Bar Code.
 - 
 The system recognises this Element String by the symbology identifier **JE0** and the U.P.C. Prefix 5.
- 
Note: The Company Number N₂ to N₆ uses the implied U.P.C. Prefix 0 (zero). If the coupon is applicable to a Global Trade Item Number (GTIN) beginning with a U.P.C. Prefix other than zero, an AI (8100) to (8102) (GS1-128 Coupon Extended Bar Code) must be present.
- 
 U.P.C. Prefix 5 is reserved for use in North America only! GS1 US Coupon Code is constructed using the U.P.C. Company Prefix assigned to a given organisation. For U.P.C. Company Prefixes beginning with a digit other than zero, the presence of one of the Element Strings AI (8100), (8101), or (8102) is required.
 - 
 See the *Application Standard for GS1 US Coupon Codes* for detailed information on GS1 US coupon code data content and applied numbers.

GS1 Key

Definition

Not Applicable

Rules

Not Applicable

Attributes**Required**

Not Applicable

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification**Carrier Choices**

A coupon with the U.P.C. Prefix 5 is carried by the UPC-A Bar Code.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

Not Applicable

2.6.6. GS1 US Coupon Extended Bar Code: AI (8100 - 8102)**Application Description**

Element Strings AI (8100) to AI (8102) represents supplementary data related to a particular GS1 US Coupon Code using the U.P.C. Prefix 5. They are never used as a stand-alone Element String.

The Element String AI (8100) enables the representation of an Offer Code and the extension of the use of GS1 US Coupon Codes to companies whose U.P.C. Company Prefix does not begin with the U.P.C. Prefix 0.

The Element String AI (8101) enables the representation of an Offer Code and expiration data, and extends the use of GS1 US Coupon Codes to companies whose U.P.C. Company Prefix does not begin with the U.P.C. Prefix 0.

The Element String AI (8102) enables the extension of the use of GS1 US Coupon Codes to companies whose U.P.C. Company Prefix does not begin with the U.P.C. Prefix 0.

See the *Application Standard for GS1 US Coupon Codes* for detailed information on data content and applied numbers.

GS1 Key**Definition**

Not Applicable

Rules

Not Applicable

Attributes

Required

See Section 3.2 for List of all GS1 Application Identifier, GS1-128 Coupon Extended Bar Code: AIs (8100 - 8102).

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification

Carrier Choices

The GS1 US Coupon Extended Bar Code, AIs (8100 to 8102), is carried by the GS1-128 Bar Code Symbology.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 5, GS1 System Symbol Specification Table 4.

Symbol Placement

Not Applicable


Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.6.7. Coupon Code Identification for Use in North America (AI 8110)

Application Description

The current U.P.C. Prefix 5 coupon system (Section [2.6.5](#)) dates back to 1985. Along the way, there have been significant changes in the system itself, such as the addition of the Coupon Extended Code in 1997 (Section [2.6.6](#)). Over 200 billion paper coupons are processed annually.

 **Note:** This application, identified using AI (8110), will lead to the replacement of the U.P.C. Prefix 5 system in 2011. The new system will initially be rolled out in the form of paper coupons.

See the *U.S. Coupon Application Guideline using GS1 DataBar Expanded Symbols* for detailed information on GS1 U.S. coupon code data content and migration.

A stimulus for change is the fact that GS1 US has begun issuing variable-length GS1 Company Prefixes and retailers are expected to accept imported products identified with GS1 Company Prefixes. Both changes will lead to an increasing number of coupon mis-redemptions if the full Company Prefix is not processed. This will impact retailers, manufacturers, and coupon processing agents.

The new coupon format has a large number of fields (many of them optional) for specifying the more complex coupon offers in use today. Data encoded in the coupon bar code is used to identify the source (typically a manufacturer) producing the coupon, the conditions for fulfilling the offer and the specific save value offered to the consumer.

2.6.8. Refund Receipts

Application Description

Refund Receipts are vouchers produced to automate payment for returned empty containers.

Refund Receipts automate and expedite the handling of empty containers (e.g., bottles, crates) that have a refund value in a retail store.

When customers return empty containers (that have a refund value), the containers have to be checked and valued. This process can be done manually or by automated equipment capable of handling empty containers. When the returned containers have been valued, a Refund Receipt is printed and given to the customer. The customer presents the Refund Receipt at the store checkout, and the corresponding amount is refunded in cash or deducted from the customer's bill.

An EAN-13 Bar Code can be printed on the Refund Receipt to encode the required data including a security number and the monetary value.

The structure of Refund Receipts ensures uniqueness against all other GS1 System ID numbers only when used within the restricted environment defined by the appropriate GS1 Member Organisation.

The GS1 Prefix 980 has been released for use with Refund Receipt data.

The internationally agreed standard for GS1 System Refund Receipt data is shown in 2.6.8 - 1.

Figure 2.6.8 – 1

GS1 Prefix	Refund Receipt Data (Structure Determined by GS1 Member Organisation)	Check Digit
980	N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂	N ₁₃

Within this structure, each GS1 Member Organisation develops its own national Refund Receipt solution. The recommended structure shown in Figure 2.6.6 – 2 provides some degree of equipment standardisation.

Figure 2.6.8 – 2

GS1 Prefix	Recommended Structure	Check Digit
980	S S S S S V V V V	C

Where: **S** = security number.

This number is used to provide some security in the handling of the Refund Receipt. For example, it consists of a sequential number, which is incremented by 1, for each ticket generated. In this case, the Point-of-Sale system will be able to recognise a Refund Receipt that had already been refunded. The security number can also include a two-digit machine number and a three-digit sequential number, in the case where several machines are available to the customers at the same location.

V = monetary value of the refund. The scale factor (decimal places) will depend on the currency used.

C = Check Digit. Calculated according to the standard algorithm

GS1 Key

Definition

Not Applicable

Rules

Refund Receipt specifications are flexible and have been designed to cater for current and future requirements.

Due to the nature of Refund Receipt identification, several national solutions are offered, each of which is defined by the respective GS1 Member Organisation. National Refund Receipt solutions are not unique worldwide and must be operated in the restricted circulation defined by the GS1 Member Organisation.

Data Carrier Specification**Carrier Choices**

EAN-13 Bar Codes are used with Refund Receipts.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.6.9. Electronic Serial Identifier for Cellular Mobile Telephones (CMTI): AI (8002)**Application Description**

The purpose of an electronic serial identifier, AI (8002), for cellular mobile telephones (CMTI) is to uniquely identify a cellular phone within a given jurisdiction.

The information from the bar code can be used to automate and speed up the capture of CMTIs. CMTIs are usually assigned by a national or pluri-national authority. Issuing authorities must ensure that the electronic serial identifier is unique for each cellular phone. However, because electronic serial identifiers are assigned by different issuing authorities, they are not unique worldwide. An electronic serial identifier, AI (8002), is assigned by the appropriate national or pluri-national body and can be carried by a bar code placed directly on the cellular phone. The electronic serial identifier, AI (8002), is unique for each cellular telephone within the jurisdiction of the issuing body.

GS1 Key**Definition**

Not Applicable

Rules

Not Applicable

Attributes**Required**

See Section 3.2 for List of all GS1 Application Identifier, Cellular Mobile Telephone Identifier: AI (8002).

Optional

Not Applicable

Rules

Not Applicable

Data Carrier Specification**Carrier Choices**

The electronic serial identifier for Cellular Mobile Telephones (CMTI), AI (8002), is carried by the GS1-128 Bar Code.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 5, GS1 System Symbol Specification Table 4.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

Not Applicable

2.6.10. Payment Slips**Application Description**

A Payment slip is that part of a paper invoice used to facilitate payment. Payment slips cover a wide range of payment demands, such as telephone bills, electricity bills, and insurance renewals. The Payment slip is normally issued by a service provider (the invoicing party) to a final customer (the invoicee) and represents a payment demand. Normally the Payment slip would outline in Non-HRI text:

- Details of the customer
- Details of the service provider
- A detailed invoice for the service(s) provided
- A reference number
- The amount payable
- The payment conditions (e.g., pay before date, where to pay)

GS1 Key**Definition**

Not Applicable

Rules

Not Applicable

Attributes**Required**

- **Global Location Number of the Invoicing Party** – The Application Identifier (AI) to indicate the Global Location Number (GLN) of the invoicing party is AI (415) (see Section 3). The GLN of the invoicing party identifies the issuer of the payment slip. It is used as a key to access database information about the invoicing party (normally held by the payment receiving agency). The same GLN is used for all payment slips issued by the invoicing party under

identical payment conditions. The GLN of the invoicing party is used by the payment receiving agency to reference the characteristics of the contract with the invoicing party, such as:

- Whether the payment can be accepted
- Contact details of the invoicing party
- Action to take if the due date has expired
- Transfer arrangement of funds to the invoicing party's bank

A different GLN shall be used whenever the payment conditions are different. For more information, see Section 4.

- **International Bank Account Number (IBAN): AI (8007)** – The Application Identifier to indicate the International Bank Account Number (IBAN) is AI (8007). See Section 3.2 for List of all GS1 Application Identifier.

The bank account identifier of the invoicing party is defined in ISO 13616. It is used to identify where to send the payment and, in the receiving country, which bank holds the account for international bank payment.

- **Payment Slip Reference Number: AI (8020)** – The Application Identifier to indicate a payment slip reference number is AI (8020). See Section 3.2 for List of all GS1 Application Identifier.

By their nature, payment slips need to be individually tailored for the invoicee and, therefore, require a unique reference number, the payment slip reference number, AI (8020). Reminder notices should use the same number as the original notice. The payment slip reference number, AI (8020), is issued by the invoicing party and is a unique number in the system. Payment slip reference numbers, AI (8020), should be sequentially allocated.

The payment slip reference number, AI (8020), uniquely identifies the payment slip when used in conjunction with the Global Location Number (GLN) of the invoicing party. It is used to communicate details of payment among all the partners involved: invoicing party, invoicee, payment receiving agency, and banks. It is also used to access locally held information.

- **Amount Payable** – There are two Application Identifiers to indicate the amount payable:
 - AI (390n) = amount payable for a single monetary area. See Section 3.2 for List of all GS1 Application Identifier.
 - AI (391n) = amount payable with ISO three-digit currency code. See Section 3.2 for List of all GS1 Application Identifier.

(n = indicates the implied decimal point position)

If the amount payable is expressed in a bar code, AI (391n) should be used, as this ensures the currency of the payment can be automatically processed and verified by the system. However, if the currency is unambiguously implied by the system, AI (390n) may be used. To avoid ambiguity, only one AI encoding the amount payable shall be used, and the currency must be clearly indicated in human readable form.

Scanning systems should have the facility to override the amount payable. This functionality is required should the invoicee wish to make the minimum required payment, which could be less than the total amount due. The amount due is attribute information and, when used, must be processed with the Global Location Number (GLN) of the invoicing party.

- **Due Date for Amount on Payment Slip** – The Application Identifier to indicate the due date is AI (12). See Section 3.2 for List of all GS1 Application Identifier.

The due date indicates the date by which the invoice should be paid (by the invoicee). It is attribute information and, when used, must be processed with the Global Location Number (GLN) of the invoicing party.

- Note:** The due date must be represented in the YYMMDD format in the bar code; however, the Human Readable Interpretation can be presented in whatever form is appropriate.

Optional

Not Applicable

Rules

See Section 4, Mandatory Association of Element Strings.

Data Carrier Specification

Carrier Choices

The GS1-128 Bar Code is used with Payment slips. They in no way replace the need for the Human Readable Interpretation.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

To facilitate efficient scanning, all bar codes shall be printed at an X-dimension between 0.249 mm (0.0098 in.) and 0.495 mm (0.0195 in.) and be a minimum of 12.70 mm (0.500 in.) in height. See Section 5.5, Figure 5.5.2.7 - 5, GS1 System Symbol Specification Table 4.

Symbol Placement

No standard placement. Figure 2.6.10 - 1 is an example of numbering and symbol marking for payment slips.

Figure 2.6.10 - 1

ABC-Electric Company	Mr A.N. Customer	PAY TO: 5412345678908
Electricity consumption for	45 Sunrise Drive	REF NO.: ABC123
period:	Cape Town, TX	
1 January 2001	765444	
to		
31 March 2001		
Amount Payable South African Rand		
12.50		 (415)5412345678908(3911)710125
DUE DATE 25 April 2001		(12) 010425 (8020) ABC123

- Example: (415) 5412345678908** – AI (415) indicates the Global Location Number (GLN) of the invoicing party.
 The GLN is a fixed length 13-digit number terminated by a standard Check Digit. The rules for allocating GLNs ensure that this number is unique worldwide. GLNs are used by the payment receiving agent to distinguish between payment slips that can and cannot be accepted.
- Example: (12) 010425** – AI (12) indicates the due date by which the payment should made.

The due date is always encoded YYMMDD; however, other formats may be used for the Human Readable Interpretation equivalent. The use of the due date is optional, but if used, the payment receiving agent and the invoicing party should agree about what action will be taken if the due date has expired.

- **Example: (3911) 710125** – AI (3911) indicates the amount payable with ISO currency number. From ISO 4217, “710” indicates South African Rand.

It is strongly recommended to use the ISO currency number when encoding this optional data element. The fourth digit of this AI is the decimal point indicator. For example, the digit 1 in this position would indicate one digit after the decimal point; a 2 would indicate two digits after the decimal point.

- **Example: (8020) ABC123** – AI (8020) indicates the payment slip reference number.

The payment slip reference number, AI (8020), is a mandatory data element for this application. It is processed with the GLN of the invoicing party and provides a unique reference for all communications between the payment agent and the invoicing party.

Unique Application Processing Requirements

Not Applicable

2.6.11. Customer Specific Articles

2.6.11.1. Introduction

The GS1 System guidelines for trade items (see Section [2.1](#)) state that each item of trade is assigned a non-significant number that uniquely identifies the item in an unrestricted environment. The same number is used to identify a series of identical items, with every variant being allocated a separate unique identification number whenever the variation is apparent and significant between partners in the supply chain or to the final user.

This system enables the use of Automatic Data Capture (ADC) and Electronic Data Interchange (EDI) in an open environment, globally. However, in a number of business sectors, because of the vast number of possible manifestations of certain made-to-order articles, pre-allocation of Global Trade Item Numbers (GTINs) at the lowest level is not feasible.

For organisations that trade in such made-to-order products, GS1 in association with trade representatives has developed the following guidelines. They have been designed to improve supply chain efficiency by enabling ADC and, in particular, efficient ordering via EDI.

These guidelines are fully compatible with, and should be treated as a special case of, the GS1 System recommendations for the numbering and symbol marking of trade items.

2.6.11.2. Application Overview

2.6.11.2.1. Definition

A customer specific article (CSA) is broadly defined as any item where the supplier defines all possible manifestations of the article from which the customer may choose, and pre-allocation of article numbers at the lowest level is not feasible. CSAs are never made for stock, and hence are always made to order. However, made-to-order articles are not necessarily customer specific, but could be standard.

A typical example of a CSA is a chair that is available in 300 different types of upholstery for the seat, back, and armrest. This list of available upholstery could also be used for other types of furniture the supplier offers. There are 27,000,000 ordering possibilities for this chair (300 x 300 x 300). Typically

the supplier's catalogue lists a generic style of chair as well as the 300 different upholstery options. The customer chooses the style of chair and selects upholstery for the seat, back, and armrest.

On receipt of order, the supplier produces the customer specific chair and makes it available to the customer. Because the supplier defines the customer's options, and because the customer must specify his or her choices based on those options, the order contains all the information the supplier requires to manufacture the chair. This example highlights four separate process steps:

- The supplier makes available all the possible manifestations of an article.
- The customer specifies the actual article required using the supplier catalogue.
- The supplier manufactures the article in accordance with the customer's specifications.
- The CSA is delivered.
- The GS1 System has formalized this process, enabling efficient Automatic Data Capture (ADC) and Electronic Data Interchange (EDI) throughout the supply chain. The CSA data model is based on the assumption that the supplier defines the possible components (either in a paper or electronic catalogue) and the customer specifies the actual article required.


The processes for identifying and ordering the article are dealt with separately. Although these processes are closely related, each requires separate consideration in an open system.

2.6.11.2.2. Customer Specific Articles Data Flow

The data flow model is organised on a series of assumptions designed to ensure that the model is independent of the type of article and the sector: It is a generic model. Because many different procedures may be applied by various manufacturers, the generic model is meant to be a general guide. By using this model, companies can communicate in a standard way and (re)organise the automated handling of customer specific article (CSA) specification according to this guideline.

The model assumes that the supplier informs the customer of all available ordering options and specifications. This is achieved by means of an electronic catalogue (see Figure 2.6.11.2.2 - 1). From this catalogue the customer can determine which article(s) to order. In the order message the base article number and the chosen specifications are communicated.

Figure 2.6.11.2.2 - 1



In the order confirmation, the supplier may confirm that the article ordered can be manufactured (that is, that the buyer has made a correct combination of specifications). This should be the case assuming the customer has up-to-date database information. The order confirmation may also be used to notify the customer of the assigned article number. The assigned article number may be used in all subsequent communications. For example, the despatch advice and invoice messages use the assigned article number and, if required, the order number plus the order line number to establish an unambiguous link with the CSA.

The article produced may not be numbered with a string of numbers representing the base article number plus the applicable specifications (see Section [2.6.11.4.5](#)).

2.6.11.3. Allocating System Numbers for Customer Specific Articles

2.6.11.3.1. General Rule

Each different product must be identified by a unique number. This implies that each variant of a product is assigned a different number. For example, each different size or colour of a garment has its own individual identification number. Article numbers should be sequentially allocated for this purpose

2.6.11.3.2. Ordering of Customer Specific Articles

The ordering process of customer specific articles (CSAs), the customer specification process, is based on a supplier's catalogue definitions. Internal identification systems are often manual and become increasingly complex and prone to error as the number of trading partners increases. In addition, the use of internal codes can be cumbersome, inflexible, and prone to duplication among different suppliers. These recommendations, which are based on the open systems principle, seek to avoid internally-based systems. Catalogue products using GS1 System identification numbers are guaranteed to be uniquely identifiable worldwide.

A customer specific articles *EANCOM* user profile for the price catalogue (PRICAT), orders (ORDERS), and the response to order (ORDRSP) messages have been published that use the numbering system outlined in the following subsections.

2.6.11.4. Base Article Number

A supplier assigned base article number is given to each generic product type for ordering purposes. A GTIN-13 is used for this functionality. The GTIN-13 is defined by the supplier and must be unique with respect to all other GS1 System identification numbers. Because it does not identify an item, the base article number will never be carried by a bar code on an article. It is solely used for ordering purposes.

The base article number indicates to the customer that a number of supplier defined questions have to be answered by the customer. These specifications (questions and associated answers), which are relevant to a base article number, are communicated via an electronic catalogue. The specifications available for each different article are defined by the supplier.

2.6.11.4.1. Specifications

Specifications are linked to the different base article numbers for the purposes of ordering. The same specifications may be used with different base article numbers. Specifications fall into one of the categories described in the following subsections.

2.6.11.4.2. Option

An option is a specification with a discrete value that is pre-defined by the supplier and associated with a base article number.

Each option may be identified with a GTIN-13. The GTIN-13 is defined by the supplier and must be unique with respect to all other GS1 System identification numbers. An ID number of an option will never be carried by a bar code on an article. It solely is used for communication purposes.

Options, such as red leather seat covers, may be valid for different base articles.

2.6.11.4.3. Parameter

A parameter is a specification within a range of values (e.g., dimensions) ranging from a minimum to a maximum and including a step size.

Each parameter may be identified with a GTIN-13. The GTIN-13 is defined by the supplier and must be unique with respect to all other GS1 System identification numbers. The parameter identification will never be carried by a bar code on an article. It is solely used for ordering purposes.

Parameters should be communicated using the standard EANCOM syntax and should be related to a base article number.

2.6.11.4.4. Part

A part is a physical article that may also be ordered separately.

Parts are identified within Global Trade Item Numbers (GTINs). The GTIN-13 for the part may be used in association with a base article number to create a composite, an article made up of one or more individual parts.

A part may be associated with a number of different base articles.

2.6.11.4.5. External References

An external reference is often required for a customer-designed or custom-made item. External references are specified through a separate, non-EDI communication channel, such as a fax or CAD/CAM drawing. A secondary source can be used to communicate a set of customer-defined specifications (not pre-defined by the supplier).

2.6.11.4.6. Data Carrier

GS1 System identification numbers used to identify customer specific articles (CSAs) for ordering purposes may never be carried by a bar code on the physical article. However, suppliers may wish to utilise bar code scanning as part of the order process. This may be achieved by representing base articles and identification numbers in machine readable form in a paper catalogue. GS1-128 Bar Codes, utilising an Application Identifier for internal applications, should be used for this purpose.

2.6.11.5. Identification of the Physical Article Actually Produced

Application Description

In environments with automated systems the physical article needs to be identified and the identification of the produced article is required in machine readable form (as a bar code). The identification of the physical article must be communicated from the supplier to the customer. Both supplier and customer should be able to use the same identification number and each need to keep a record of this number.

For open systems, the most appropriate identification number is the GTIN-13. Identifying a physical article with a GTIN-13 and a bar code allows customer specific articles (CSAs) to be integrated within a system that manages all other items identified using the GS1 System. During order confirmation, the supplier assigns GTIN-13 to the product. It is not necessary to pre-assign numbers to all possible articles, only to those that are actually produced.

Each different product must be identified by a unique number. This implies that each variant of a product is assigned a different number. For example, each different size or colour of a garment has its own individual identification number. Article numbers should be sequentially allocated for this purpose.

GS1 Key

Definition

The Global Trade Item Number (GTIN) is the GS1 Identification Key used to identify trade items. The key is comprised of a GS1 or U.P.C. Company Prefix followed by an Item Reference Number and a Check Digit.

Rules

All the GTIN Allocation Rules described in Section 4; in addition, the main bar code on books and paperbacks must not be reduced in height.

Attributes

Required

Not Applicable

Optional

Not Applicable

Data Carrier Specification

Carrier Choices

The bar code requirements for customer specific articles (CSAs) are the same as those for trade items. The data carrier used to carry the GS1 System identification number of a physical article shall be one of the following:

- EAN-13, or UPC-A Bar Code
- ITF-14 Bar Code
- GS1-128 Bar Code (attribute information always uses GS1-128 Bar Codes)

With CSAs, the choice of data carrier is left to the discretion of the organisation responsible for issuing the GS1 System identification number. Trade items that will be scanned at a Point-of-Sale always should be marked using the EAN/UPC Symbology.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, Figure 5.5.2.7 - 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.

2.6.12. Custom Trade Item

2.6.12.1. Allocating System Numbers for Custom Trade Items

2.6.12.1.1. General Rule

Customer Specific Items, as described in the previous section, (Section 2.6.11) are configured from a wide variety of known parameters. Things like colour, size, model, and various materials are listed and uniquely identified. A Customer Specific Item is created when a selection is made from each category, sufficient to create the item. Customer Specific Items may be intended for the end consumer (e.g. furniture) and can be marked with a GTIN and data carrier appropriate for Point of Sale (POS).

Custom made-to-order trade items are different than Customer Specific Items, however, in that they are one-of-a-kind, made-to-order items that are strictly sold from business to business. Their use is approved for the Maintenance, Repair and Operations (MRO) environment, also known as industrial supplies. Examples include custom abrasive belts, special adhesives, and made-to-order cutting tools needed for a specific machine and cutting application. Their specifications may be called out in a series of blue prints or other technical documents.

Each different product must be identified by a unique number. If a trade item is a stock trade item, it is assigned the appropriate fixed measure GTIN. If any trade item, custom or not, will be scanned at POS, then it must be assigned a GTIN-12, GTIN-8, or GTIN-13 and represented in a bar code symbology approved for POS. At the discretion of the supplier, it is always acceptable to use a GTIN-12, GTIN-8 or GTIN-13 to identify a trade item, whether custom or not. In other words, a supplier or manufacturer is not required to use the method described below to identify a custom item. They may give each and every different trade item a unique GTIN. However, this will deplete their pool of possible GTIN more quickly.

This method of assigning unique product identification uses a base GTIN-14, Indicator Digit 9 which signifies a GTIN with a variable component (i.e. it is a custom, made-to-order item), followed by a Made-to-Order Variation Number. The Made-to-Order Variation Number is a variable length, numeric field up to six digits. This allows each base GTIN-14, Indicator Digit 9 to be used for 1,000,000 different custom variations. Multiple items, made to the same specifications could have the same combination of the base GTIN-14, Indicator Digit 9 and Made-to-Order Variation Number.

2.6.12.1.2. Ordering of Custom Trade Items

A supplier or manufacturer may indicate in their paper or electronic catalogue that certain items can be ordered based on customer specifications. A GTIN-14, Indicator Digit 9 can be assigned to denote that it is possible to order a customized version of this trade item. However, in this case, no physical item exists. When the order is accepted for the made-to-order custom item, a Made-to-Order Variation number is assigned to this specific version. Multiples of this same item may be ordered at one time. It is the combination of the GTIN-14, indicator digit 9 and the Made-to-Order Variation Number that uniquely identifies the custom items.

2.6.12.1.2.1. Custom Trade Item Number

A GTIN-14, Indicator Digit 9 indicates a variable measure trade item. Additional information is needed to complete the identification of the trade item. A custom trade item number is the combination of a GTIN-14, Indicator Digit 9, and the Made-to-Order Variation Number. This combination is used in electronic business transactions and in bar code representation. When many items with the exact same specifications are manufactured at one time, they will each carry the same combination of GTIN-14, Indicator Digit 9 and Made-to-Order Variation Number.

2.6.12.1.2.2. Base GTIN-14

To indicate that a trade item is available in a custom format, a base GTIN-14, Indicator Digit 9, is used. A base GTIN-14, Indicator Digit 9 may appear in the supplier's paper or electronic product catalogue to indicate the possibility of a custom item. This GTIN does not identify a specific trade item, but a general category of possible custom trade items. The description indicates that this is a custom, made-to-order item. A manufacturer may create one GTIN-14, Indicator Digit 9 to represent any and all made-to-order trade items, or they may assign one for each category of custom items (Custom Abrasive Belts, Custom Abrasive Pads, etc.). Further a manufacturer may choose to create a GTIN-14 Indicator Digit 9 for sub-categories (Custom Abrasive Belts, 1 to 2 Inches Wide; Custom Abrasive Belts, 2 to 3 Inches Wide, and so on).

2.6.12.1.2.3. Made-to-Order Variation Number

Once the specifications for a custom trade item are agreed upon between the customer and the manufacturer, the manufacturer will assign a Made-to-Order Variation Number to that custom item. A Made-to-Order Variation number is always used with a GTIN-14, Indicator Digit 9.

The Made-to-Order Variation Number is communicated from the manufacturer to the customer during the Request for Quote / Response to Request for Quote process or on a Purchase Order Acknowledgement or by some other mutually agreed upon method. In a bar code representation, Application Identifier AI (242) is used to denote a Made-to-Order Variation Number. The Made-to-Order Variation Number is numeric and variable length up to, and including, six digits.

A Made-to-Order Variation Number will never appear alone, but must always be associated with the appropriate GTIN-14, Indicator Digit 9. Further, a Made-to-Order Variation Number may not be used with GTIN-8, GTIN-12, GTIN-13, and GTIN-14 Indicator Digit 1 through 8.

The use of a GTIN-14, Indicator Digit 9 and a Made-to-Order Variation Number is only approved for the Maintenance, Repair, Operations and Production (MROP) industrial supply sector.

2.6.12.1.2.4. Data Carrier

GS1 System identification numbers used to identify custom made-to-order items in the manufacturing, pick, pack, shipping, receiving and inventory management process may be carried by a bar code on the physical article. This may be achieved by representing identification numbers in machine readable form. GS1 Bar Codes, utilising Application Identifiers should be used for this purpose.

2.6.12.2. Identification of the Physical Article Actually Produced

Application Description

In environments with automated systems the physical article needs to be identified and the identification of the produced article is required in machine readable form (e.g. as a bar code). The identification of the physical article must be communicated from the supplier to the customer. Both supplier and customer should be able to use the same identification number and each need to keep a record of this number.

For open systems, the appropriate identification number for a custom trade item is the base GTIN-14 Indicator Digit 9, followed by a Made-to-Order Variation Number. During order confirmation, the supplier assigns the Made-to-Order Variation Number to this version of the product.

Products made to the same specifications can carry the same combination GTIN-14, Indicator Digit 9, and Made-to-Order Variation Number.

GS1 Key

Definition

The Global Trade Item Number (GTIN) is the GS1 Identification Key used to identify trade items. The base GTIN-14, Indicator Digit 9 in combination with the Made-to-Order Variation Number comprises the key for a custom trade item. The base GTIN-14 is comprised of Indicator Digit 9, GS1 Company

Prefix followed by an Item Reference Number and a Check Digit. The Made-to-Order Variation number is variable length, numeric, up to and including six digits.

Attributes

Required

Not Applicable

Optional

Not Applicable

Data Carrier Specification

Carrier Choices

The combination of a GTIN-14, Indicator Digit 9, and a Made-to-Order Variation Number, can be carried by using the appropriate Application Identifiers in the following symbologies:

- GS1-128
- GS1 DataBar
- GS1 DataMatrix

AI (01) is used for the GTIN-14, Indicator Digit 9, plus AI (242) for the Made-to-Order Variation Number when the item is considered a trade item. The combination of AI (02) plus AI (242) and AI (37) Count of Trade Items Contained in a Logistic Unit, is used in conjunction with an (00) Serial Shipping Container Code when marking a logistics unit of custom trade items.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

See Section 5.5, - Figure 5.5.2.7 – 2, GS1 System Symbol Specification Table 1.

Symbol Placement

Not Applicable

2.6.13. Global Document Type Identifier for Document Control

Application Description

The term “document” is applied broadly to cover any paper(s) or digital file(s). The Global Document Type Identifier (GDTI) can be used to identify any type of document including but not limited to:

- commercial documents (e.g. invoice, purchase order);
- documents that infer a right (e.g., proof of ownership);
- documents that infer an obligation (e.g., notification or call for military service);
- identification documents (e.g. driver’s license, passport); and
- images

The issuer of the document is normally responsible for the identification of the document which may be physical or virtual; such as a database record. Such documents typically require storage of the appropriate information contained on the document.

Examples of documents that can be identified with the GDTI include, but are not limited to:

- Land registration papers
- Tax demands
- Proof of shipment/receipt forms

- Custom's clearance forms
- Insurance policies
- Internal invoices.
- National press documents
- Educational papers
- Transporting company documents
- Mail companies documents
- Among others

GS1 Key

Definition

The Application Identifier to indicate the Global Document Type Identifier (GDTI) is AI (253) (see Section 3.2 for List of all GS1 Application Identifier).

Rules

The GDTI is assigned by the document issuer. The GDTI is used as a key to access database information that is required for document control purposes (normally held by issuing organisation). The same GDTI is used for all document classes that are issued with an identical purpose. This can then be used to reference the characteristics of the document, such as:

- The issuer of the document
- The exact right or obligation the document imposes
- The document type (e.g., insurance policy, governmental paper)

A different GDTI shall be used whenever characteristics of the document are different.

Attributes

Required

Not Applicable

Optional

By their nature, each document needs to be individually tailored for the intended recipient and, therefore, requires a unique reference number in addition to the GDTI. Any duplicates of a document should use the same number as the original. The serial component is optional and assigned by the document issuer and is a unique number in a series of documents issued under the same GDTI. Ideally the serial component should be sequentially allocated for each new document generated.

The serial component is used to communicate exact details pertinent to the individual document, such as:

- The name and address of the recipient
- The cross-reference to individual details

Refer to Section 3 for detailed information.

Data Carrier Specification

Carrier Choices

The GS1-128 Bar Code is used for documents that require control. The bar code in no way replaces the need for the Human Readable Interpretation.

Symbol X-Dimension, Minimum Symbol Height, and Minimum Symbol Quality

To facilitate efficient scanning, all bar codes shall be printed at an X-dimension between 0.249 mm (0.0098 in.) and 0.495 mm (0.0195 in.) and be a minimum of 12.70 mm (0.500 in.) in height. See Section 5.5, Figure 5.5.2.7 - 5, GS1 System Symbol Specification Table 4.

Symbol Placement

No standard placement. The following are examples of numbering and symbol marking for document control:

Example 1: Legally Required Declaration Prior to Travel

This example shows how GS1-128 Bar Codes can be used to automate the capture of information for traveller who enters or leaves the country.

Figure 2.6.13 - 1 Legally Required Travel Declaration



Declaration of Luggage and Money of Travellers







(253) 770721248998412345678901

Name:			
Address:			
Date of Entrance:			
Items to Declare:			
Amount	Description	Value	Customs Value
I have read the instructions and declare the truth:			
Date and Signature:			
			Doc Type: 12345678901

Example 2: Insurance Policy

This example shows how GS1-128 Bar Codes can be used to automate the capture of information on insurance policies. This standard solution provides benefit for the insurer, the insured, and any potential beneficiaries as well as facilitates the automation of any monitoring and inspection of the requirement to fulfil the legal norms.


Figure 2.6.13 - 2 Insurance Policy

Policy Number: 67890543210987		
Branch: Bogotá	Date of Policy: March 23, 2005	
Name: Name of Insured		
Age: 24	Valid From: March 23, 2005	
	Valid To: March 22, 2007	
Contract Cover: Life	Value: 10,000	
<div style="border: 1px solid black; height: 60px; width: 100%;"></div>		
 <p style="font-size: 1.2em; margin-top: 5px;">(253) 770999800010067890543210987</p>		

Example 3: Application Form


This example shows how GS1-128 Bar Codes can be used to automate the capture of information on application forms. Many organisations require their clients to complete an application form.

Figure 2.6.13 - 3 Membership Application Form



Este formulario es GRATUITO. Solicítalo directamente en IAC. El trámite Transmisionero.

Mira una muestra de cómo se ve en Internet, así sea en muchos formatos más fáciles de usar.



Solicitud de Servicios

TIPOS DE SERVICIOS

Para que su empresa pueda identificar productos, servicios o localizaciones, el Instituto Colombiano de Codificación y Automatización Comercial IAC Colombia le ofrece varias opciones. Escoga la que más le convenga según sus necesidades.

1. SER MIEMBRO DE IAC
Al ser miembro del Instituto, su empresa podrá obtener los siguientes beneficios:

- » Asignación de Código único para su empresa, con el cual podrá identificar entre 1 y 100.000 productos, servicios o localizaciones (los códigos asignados como localizaciones sirven para identificar ubicaciones o buzones para EDI).
- » Voz y voto en la Asamblea Anual de Miembros de IAC Colombia.
- » Uso gratuito de CABASnet: El primer Catálogo Electrónico de Productos.
- » Tarifas especiales en los cursos, seminarios y consultorías que realiza el Instituto.
- » Recorridos técnicos por TecnoEAV, el único modelo real y didáctico de una Cadena de Abastecimiento en Colombia.
- » Navegar en el área privada de nuestra página Web www.iaccolombia.org, en la cual puede acceder a la información especializada que le ofrece el Instituto.
- » Tarifas preferenciales para pasar en el Directorio de Soluciones Logísticas para la Cadena de Abastecimiento.

2. SER CLIENTE DE IAC
Al escoger esta opción Usted puede elegir entre cuatro opciones dependiendo de sus necesidades:


2a. Cliente Código de empresa: Con este tipo de vinculación su empresa adquirirá el código EAN+UCC mediante el cual podrá identificar entre 1 y 100.000 productos, servicios o localizaciones. Renovación anual.

2b. Cliente pago por 10 años: Con este tipo de vinculación su empresa adquirirá el código EAN+UCC mediante el cual podrá identificar entre 1 y 100.000 productos, servicios o localizaciones. Renovación cada 10 años. Válido sólo para empresas con activos inferiores a 99.9 millones de pesos.

2c. Cliente Código CTIN: Con este tipo de vinculación su empresa adquirirá UN código para UN solo producto o UN solo servicio. Si más adelante usted desea identificar UNO adicional, debe diligenciar un formato que IAC le suministrara y cancelar el valor vigente. Código de carácter vitalicio.

2d. Cliente Código Identificación de Documentos: Con este tipo de vinculación su empresa adquirirá UN código para identificar UN solo documento. Si más adelante usted desea identificar UNO adicional, debe diligenciar un formato que IAC le suministrara y cancelar el valor vigente.

El subconjunto de datos OPERA DEL DOCUMENTO que se identifica Codifica



(253) 77012340000117654321

Example 4: Freight-Forwarding Authorisation

This example shows how GS1-128 Bar Codes can be used to automate the capture of information on freight-forwarding forms. Many organisations require documentary evidence that goods have been dispatched prior to making payment.

Figure 2.6.13 - 4 Freight-Forwarding Authorisation

<p>Suppliers or Forwarders Principals</p> <p>ID-Number barcoded (automated access to database)</p> <hr/> <p>Consigned to order of</p> <p>Human readable information (no meaning for access to database)</p> <p>Notify address</p> <hr/> <p>Conveyance from /via</p> <hr/> <p>Destination</p>	<p style="font-size: 2em; font-weight: bold;">FIATA FCT</p> <div style="border: 1px solid black; padding: 5px; display: flex; justify-content: space-between;"> Emblem No. 123 456 CH </div> <p>(253)761234500008123456</p> <p>ID-Number human readable (manual access to database)</p>										
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">Marks and numbers</th> <th style="width: 25%;">Number and kind of packages</th> <th style="width: 25%;">Description of goods</th> <th style="width: 10%;">Gross weight</th> <th style="width: 15%;">Measurement</th> </tr> </thead> <tbody> <tr> <td colspan="5" style="text-align: center; height: 100px; vertical-align: middle; font-size: 4em; opacity: 0.5;">specimen</td> </tr> </tbody> </table>	Marks and numbers	Number and kind of packages	Description of goods	Gross weight	Measurement	specimen					
Marks and numbers	Number and kind of packages	Description of goods	Gross weight	Measurement							
specimen											
<p style="text-align: center;">according to the declaration of the consignor</p> <p>The goods and instructions are accepted and dealt with subject to the General Conditions printed overleaf.</p> <p>Acceptance of this document or the invocation of rights arising therefrom acknowledges the validity of the following conditions, regulations and exceptions also of the trading conditions printed overleaf, except where the latter conflict with conditions 1-6 below.</p> <ol style="list-style-type: none"> 1. The undersigned are authorized to enter into contracts with carriers and others involved in the execution of the transport subject to the latter's usual terms and conditions. 2. The undersigned do not act as Carriers but as Forwarders. In consequence they are only responsible for the careful selection of third parties, instructed by them, subject to the conditions of Clause 3 hereunder. 3. The undersigned are responsible for delivery of the goods to the holder of this document through the intermediary of a delivery agent of their choice. They are not responsible for acts or omissions of Carriers involved in the execution of the transport or of other third parties. The undersigned Forwarders will, on request, assign their rights and claims against Carriers and other parties. 4. Insurance of the goods will only be effected upon express instructions in writing. 5. Unforeseen and/or unforeseeable circumstances entitle the undersigned to arrange for deviation from the envisaged route and/or method of transport. 6. Unforeseen and/or unforeseeable disbursements and charges are for the account of the goods. <p>Insurance through the intermediary or the undersigned Forwarders</p> <p><input type="checkbox"/> Not covered</p> <p><input type="checkbox"/> Covered according to the attached Insurance Policy/Certificate</p> <p>All disputes shall be governed by the law and within the exclusive jurisdiction of the courts at the place of issue.</p> <p>For delivery of the goods please apply to:</p> <p>Freight and charges prepaid to:</p> <p>thence for account of goods, lost or not lost.</p>		<p>We, the Undersigned Forwarders in accordance with the instructions of our Principals, have taken charge of the abovementioned goods in good external condition at:</p> <p>for despatch and delivery as stated above or order against surrender of this document properly endorsed.</p> <p>In witness thereof the Undersigned Forwarders have signed originals of this FCT document, all of this tenor and date. When one of these has been accomplished, the other(s) will lose their validity.</p> <p>Place and date of issue</p> <hr/> <p>Stamp and signature</p>									
<p style="writing-mode: vertical-rl; transform: rotate(180deg);">Text authorized by FIATA. COPYRIGHT FIATA / Zurich - Switzerland 5.96</p>		12									

Unique Application Processing Requirements

For description of processing requirements, see Section 7.

2.6.14. Internal Applications Using GS1-128 Symbology

In addition to the GS1 Prefixes noted above, the GS1 System makes available Application Identifiers for internal applications. Like all other data structures using Application Identifiers, internal application AIs may only be carried by GS1-128 Bar Codes.

2.6.14.1. Information Mutually Agreed Between Trading Partners: AI (90)

Element String AI (90) may be used to represent any information that has been mutually agreed between two trading partners. The agreement may include the use of FACT DIs (Data Identifiers). If a FACT DI is used, it should appear immediately after the AI (90), followed by the appropriate data. The use of FACT DIs gives little security to users.

The bar code carrying this Element String should be removed from any item that leaves the jurisdiction of the trading partners. Failure to remove the symbol may cause problems if another trading partner using the same AI for a separate internal application scans the item.

2.6.14.2. Company Internal Information: AIs (91 to 99)

Element Strings AI (91) to (99) may contain any internal information relevant to a company's internal applications.

The bar code containing these Element Strings should be removed from any item that leaves the jurisdiction of the company. Failure to remove the symbol may cause problems if a trading partner using the same AI for a separate internal application scans the item.

2.6.15. Digital Coupons


2.6.15.1. Application Description

A digital coupon is an electronic presentation, that is distributed and presented without manifesting as "paper" or in other hard-copy form, and that can be exchanged for a financial discount or for loyalty points when making a purchase

GS1 global standards enable efficient digital coupon processes for the benefit of:

- Brands who can execute offers in the same way in multiple countries and with multiple retailers. Brands can have more relevant/targeted marketing and campaign opportunities tied to specific factors (ex. Location, consumer, products, interest, and interaction with media)
- Mobile Industry and Solution Providers who will have a baseline and one standard to implement rather than multiple
- Retailers who can accept offers from coupon issuers in one rather than multiple ways and can understand how to configure (and possibly upgrade) the POS system. Retailers can also accept digital coupons acquired from multiple distributions channels, process them in a uniform and standard way, and integrate where appropriate with their loyalty system.
- Consumers who will have a consistent and a satisfying experience when they manage their coupon offers (digital coupons are searchable, sort-able, allowing customers to browse by merchant, category, offer date, and other criteria).

The following diagram illustrates the Digital Coupon Management Process. The process is specified in detail in the Digital Coupon Management Standard Specification Document.



2.6.15.2. Relation with existing coupon specifications

The Digital Coupons specification will co-exist in the foreseeable future with coupon specifications described in sections 2.6.1 to 2.6.7. that are restricted to national or common currency regional applications specified by the respective GS1 Member Organisations.

2.6.15.3. Identification requirements

The Digital Coupon Management Process specifies the following identification requirements:

- Parties, e.g. Offer Issuer, Digital Coupon Enabler, Retailer, shall be identified with a GLN
- Digital Coupons are always related to offers and promotions on products or services. Products as well as services shall be identified with a GTIN
- Digital Coupons may be managed in conjunction with loyalty cards. If appropriate, consumer loyalty cards accounts may be identified with a GSRN

Digital Coupons shall be identified by a Global Coupon Number assigned by the Coupon Issuer. The GCN comprises a GS1 Company Prefix followed by a Coupon Reference. It may be supplemented by an optional serial number.

GS1 Key

Definition

The Global Coupon Number (GCN) is the GS1 Identification Key that provides a globally unique identification for a coupon, with an optional serial number.

The Application Identifier to indicate the Global Coupon Number (GCN) is AI (255) (see Section 3.2 for List of all GS1 Application Identifier).

Rules

All the GCN Application Rules described in Section 4.

Attributes

Required

Not Applicable

Optional

Not Applicable

Data Carrier Specification

Carrier Choices

Data Carrier specifications for the GCN were out of scope and therefore not addressed when this standard was developed. Local implementations may choose to use the GS1 DataBar to carry the coupon identifier, as it is the only carrier that is capable of holding the identifier structure that is approved for POS use within the GS1 System.

Symbol Placement

Not applicable

2.6.16. Consumer Trade Item Production Control

This application standard utilizes GTIN and a GTIN attribute which are used by consumer trade item brand owners to ensure the proper association of packaging components during production of a finished consumer trade item. The attribute is called a Packaging Component Number (PCN). The PCN identifies a packaging component which is used by only one brand owner and is an attribute of the GTIN of the finished consumer trade item. For example, a bottle of cough syrup has a front and back label. It is critical the declarations on the labels match the product filled in the bottle. By using a different PCN on each label during packaging for a specific trade item identified with a GTIN, the brand owner can ensure the right labels are used to produce the product (GTIN to PCN associations). PCN may be encoded as a standalone symbol or the PCN and GTIN may be encoded together. Package components shared between two or more brand owners are not covered by this standard. Brand owners and their packaging component suppliers will have to manage this situation. The PCN is assigned by the brand owner.

GS1 Key

Definition

- GTIN-8 is the 8-digit GS1 Identification Key composed of a GS1-8 Prefix, Item Reference, and Check Digit used to identify trade items.
- GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
- GTIN-13 is the 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.
- For regulated healthcare non-retail applications, GTIN-14 is the 14-digit GS1 Identification Key composed of an Indicator digit (1-9), GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.

Rules

GTIN of the finished consumer trade item shall not be used to identify packaging components (e.g., bottle, bottle cap, front label, back label) for the purpose of trade item production control; however GTIN is specified as the GS1 Key for consumer trade item production control as the GTIN determines which packaging components are used in production.

Attributes

Required

Packaging Component Number

Rules

PCN shall not replace GTIN for pricing, ordering, or invoicing upstream packaging components from the brand owner's upstream suppliers. Per Section 4.11.2, PCN has a mandatory association with one or more finished consumer trade item GTIN(s). The PCN and GTIN may or may not be encoded in the same symbol.

PCN is used only on packaging components used by one brand owner.

There may be more than one PCN associated with one GTIN

One PCN may be associated with multiple GTINs

There shall only be one PCN per each packaging component for the lifespan of the packaging component and one packaging component may change while another does not. For example a front and back label would each have a unique PCN and the front label may change while the back label does not.

Over a GTIN's lifespan, there may be more than one PCN per packaging component (e.g., front label)

Optional

Not applicable

Data Carrier Specification

Carrier Choices

Symbol Options by consumer trade item type	Type of Consumer Trade Item		
	General Retail POS	Regulated Healthcare POS (retail)	Regulated Healthcare POC (non-retail)
GTIN and PCN in one symbol	GS1 DataBar	GS1 DataBar or GS1 DataMatrix	GS1 DataBar, GS1 DataMatrix, GS1-128, Composite Component
PCN standalone	GS1 symbol selection/size specifications left to the brand owner's discretion		
GTIN, PCN, & Extended Packaging URL in one symbol	* GS1 DataMatrix or GS1 QR Code	GS1 DataMatrix	GS1 DataMatrix

* For general retail consumer trade items where PCN is combined with AI (8200), GS1 DataMatrix or GS1 QR Code may be used according to the specifications in Figure 5.5.2.7 – 2.1 GS1 System Symbol Specification Table 1 Addendum

Symbol X-Dimensions, Minimum Symbol Height, and Minimum Symbol Quality

To determine the appropriate specifications for printing and quality control, see the System Symbol Specification Table(s) referred to in each Application Standard.

Symbol Placement

When the PCN is encoded together with GTIN, symbol placement rules for consumer trade item apply. If the production line scanning of the PCN prohibits use of this symbol placement, the PCN must be encoded in a separate bar code.

Unique Application Processing Requirements

For a description of processing requirements, see Section 7.



3.

GS1 Application Identifier Definitions

- Introduction
- GS1 Application Identifiers in Numerical Order
- GS1 Application Identifiers starting with digit 0
- GS1 Application Identifiers starting with digit 1
- GS1 Application Identifiers starting with digit 2
- GS1 Application Identifiers starting with digit 3
- GS1 Application Identifiers starting with digit 4
- GS1 Application Identifiers starting with digit 7
- GS1 Application Identifiers starting with digit 8
- GS1 Application Identifiers starting with digit 9
- Compatibility of EPCglobal Tag Data Standard and GS1 General Specifications

WHILST EVERY EFFORT HAS BEEN MADE TO ENSURE THAT THE GUIDELINES TO USE THE GS1 STANDARDS CONTAINED IN THE DOCUMENT ARE CORRECT, GS1 AND ANY OTHER PARTY INVOLVED IN THE CREATION OF THE DOCUMENT HEREBY STATE THAT THE DOCUMENT IS PROVIDED WITHOUT WARRANTY, EITHER EXPRESSED OR IMPLIED, REGARDING ANY MATTER, INCLUDING BUT NOT LIMITED TO THE OF ACCURACY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND HEREBY DISCLAIM ANY AND ALL LIABILITY, DIRECT OR INDIRECT, FOR ANY DAMAGES OR LOSS RELATING TO OR RESULTING FROM THE USE OF THE DOCUMENT. THE DOCUMENT MAY BE MODIFIED, SUBJECT TO DEVELOPMENTS IN TECHNOLOGY, CHANGES TO THE STANDARDS, OR NEW LEGAL REQUIREMENTS. SEVERAL PRODUCTS AND COMPANY NAMES MENTIONED HEREIN MAY BE TRADEMARKS AND/OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE COMPANIES. GS1 IS A REGISTERED TRADEMARK OF GS1 AISBL.

3.1. Introduction

This section describes the meaning, structure, and function of the GS1 System Element Strings so they can be correctly processed in users' application programmes. An Element String is the combination of a GS1 Application Identifier and a GS1 Application Identifier Data Field. The allowable character set to be used for GS1 Application Identifier Element Strings is defined in section 7.12. There are AIs that have additional syntax restrictions, e.g. numerical only; see below definition for each AI.

Automatic processing of Element Strings in business applications requires information about the type of transaction to which the transferred data refers. See Section 7 for an explanation of this process. Element Strings can be carried by GS1-128, GS1 DataBar Symbology, GS1 Composite, and GS1 DataMatrix and GS1 QR Code Symbols. The rules for use and interrelationships between the Application Identifiers are contained in Section 2 and 4.

When a pre-defined length GS1 Key and attributes are encoded together, the GS1 Key should appear before the attributes. In most cases pre-defined length element strings should be followed by non pre-defined element strings. The sequence of pre-defined and non pre-defined element strings should be at the discretion of the brand owner.

3.2. GS1 Application Identifiers in Numerical Order

Notes: *: The first position indicates the length (number of digits) of the GS1 Application Identifier. The following value refers to the format of the data content. The following convention is applied:

- N numeric digit
- X any character in figure 7.12 - 1
- N3 3 numeric digits, fixed length
- N..3 up to 3 numeric digits
- X..3 up to 3 characters in figure 7.12 - 1

** : If only year and month are available, DD must be filled with two zeroes.

***: The fourth digit of this GS1 Application Identifier indicates the implied decimal point position.

Example:

- 3100 Net weight in kg without a decimal point
- 3102 Net weight in kg with two decimal points

FNC1: All GS1 Application Identifiers indicated with (FNC1) are defined as of variable length and shall be delimited unless this Element String is the last one to be encoded in the symbol. The delimiter shall be a Function 1 Symbol Character in GS1-128 Symbology, GS1 DataBar Expanded Versions and GS1 Composite Symbology and should be a Function 1 Symbol Character in GS1 DataMatrix and GS1 QR Code Symbology.

Figure 3.2 - 1

AI	Data Content	Format*	FNC1 Required	Data Title
00	SSCC (Serial Shipping Container Code)	N2+N18		SSCC
01	Global Trade Item Number (GTIN)	N2+N14		GTIN
02	GTIN of Contained Trade Items	N2+N14		CONTENT
10	Batch or Lot Number	N2+X..20	(FNC1)	BATCH/LOT
11 (**)	Production Date (YYMMDD)	N2+N6		PROD DATE
12 (**)	Due Date (YYMMDD)	N2+N6		DUE DATE

AI	Data Content	Format*	FNC1 Required	Data Title
13 (**)	Packaging Date (YYMMDD)	N2+N6		PACK DATE
15 (**)	Best Before Date (YYMMDD)	N2+N6		BEST BEFORE or SELL BY
17 (**)	Expiration Date (YYMMDD)	N2+N6		USE BY OR EXPIRY
20	Variant Number	N2+N2		VARIANT
21	Serial Number	N2+X..20	(FNC1)	SERIAL
22	Secondary Data Fields	N2+X..29	(FNC1)	QTY /DATE /BATCH
240	Additional Item Identification	N3+X..30	(FNC1)	ADDITIONAL ID
241	Customer Part Number	N3+X..30	(FNC1)	CUST. PART NO.
242	Made-to-Order Variation Number	N3+N..6	(FNC1)	MTO VARIANT
243	Packaging Component Number	N3+X..20	(FNC1)	PCN
250	Secondary Serial Number	N3+X..30	(FNC1)	SECONDARY SERIAL
251	Reference to Source Entity	N3+X..30	(FNC1)	REF. TO SOURCE
253	Global Document Type Identifier (GDTI)	N3+N13+X..17	(FNC1)	GDTI
254	GLN Extension Component	N3+X..20	(FNC1)	GLN EXTENSION COMPONENT
255	Global Coupon Number (GCN)	N3+N13+N..12	(FNC1)	GCN
30	Count of Items (Variable Measure Trade Item)	N2+N..8	(FNC1)	VAR. COUNT
310 (***)	Net weight, kilograms (Variable Measure Trade Item)	N4+N6		NET WEIGHT (kg)
311 (***)	Length or first dimension, metres (Variable Measure Trade Item)	N4+N6		LENGTH (m)
312 (***)	Width, diameter, or second dimension, metres (Variable Measure Trade Item)	N4+N6		WIDTH (m)
313 (***)	Depth, thickness, height, or third dimension, metres (Variable Measure Trade Item)	N4+N6		HEIGHT (m)
314 (***)	Area, square metres (Variable Measure Trade Item)	N4+N6		AREA (m ²)
315 (***)	Net volume, litres (Variable Measure Trade Item)	N4+N6		NET VOLUME (l)
316 (***)	Net volume, cubic metres (Variable Measure Trade Item)	N4+N6		NET VOLUME (m ³)
320 (***)	Net weight, pounds (Variable Measure Trade Item)	N4+N6		NET WEIGHT (lb)
321 (***)	Length or first dimension, inches (Variable Measure Trade Item)	N4+N6		LENGTH (i)
322 (***)	Length or first dimension, feet (Variable Measure Trade Item)	N4+N6		LENGTH (f)
323 (***)	Length or first dimension, yards (Variable Measure Trade Item)	N4+N6		LENGTH (y)

AI	Data Content	Format*	FNC1 Required	Data Title
324 (***)	Width, diameter, or second dimension, inches (Variable Measure Trade Item)	N4+N6		WIDTH (i)
325 (***)	Width, diameter, or second dimension, feet (Variable Measure Trade Item)	N4+N6		WIDTH (f)
326 (***)	Width, diameter, or second dimension, yards (Variable Measure Trade Item)	N4+N6		WIDTH (y)
327 (***)	Depth, thickness, height, or third dimension, inches (Variable Measure Trade Item)	N4+N6		HEIGHT (i)
328 (***)	Depth, thickness, height, or third dimension, feet (Variable Measure Trade Item)	N4+N6		HEIGHT (f)
329 (***)	Depth, thickness, height, or third dimension, yards (Variable Measure Trade Item)	N4+N6		HEIGHT (y)
330 (***)	Logistic weight, kilograms	N4+N6		GROSS WEIGHT (kg)
331 (***)	Length or first dimension, metres	N4+N6		LENGTH (m), log
332 (***)	Width, diameter, or second dimension, metres	N4+N6		WIDTH (m), log
333 (***)	Depth, thickness, height, or third dimension, metres	N4+N6		HEIGHT (m), log
334 (***)	Area, square metres	N4+N6		AREA (m ²), log
335 (***)	Logistic volume, litres	N4+N6		VOLUME (l), log
336 (***)	Logistic volume, cubic metres	N4+N6		VOLUME (m ³), log
337 (***)	Kilograms per square metre	N4+N6		KG PER m ²
340 (***)	Logistic weight, pounds	N4+N6		GROSS WEIGHT (lb)
341 (***)	Length or first dimension, inches	N4+N6		LENGTH (i), log
342 (***)	Length or first dimension, feet	N4+N6		LENGTH (f), log
343 (***)	Length or first dimension, yards	N4+N6		LENGTH (y), log
344 (***)	Width, diameter, or second dimension, inches	N4+N6		WIDTH (i), log
345 (***)	Width, diameter, or second dimension, feet	N4+N6		WIDTH (f), log
346 (***)	Width, diameter, or second dimension, yard	N4+N6		WIDTH (y), log
347 (***)	Depth, thickness, height, or third dimension, inches	N4+N6		HEIGHT (i), log
348 (***)	Depth, thickness, height, or third dimension, feet	N4+N6		HEIGHT (f), log
349 (***)	Depth, thickness, height, or third dimension, yards	N4+N6		HEIGHT (y), log
350 (***)	Area, square inches (Variable Measure Trade Item)	N4+N6		AREA (i ²)

AI	Data Content	Format*	FNC1 Required	Data Title
351 (***)	Area, square feet (Variable Measure Trade Item)	N4+N6		AREA (f ²)
352 (***)	Area, square yards (Variable Measure Trade Item)	N4+N6		AREA (y ²)
353 (***)	Area, square inches	N4+N6		AREA (i ²), log
354 (***)	Area, square feet	N4+N6		AREA (f ²), log
355 (***)	Area, square yards	N4+N6		AREA (y ²), log
356 (***)	Net weight, troy ounces (Variable Measure Trade Item)	N4+N6		NET WEIGHT (t)
357 (***)	Net weight (or volume), ounces (Variable Measure Trade Item)	N4+N6		NET VOLUME (oz)
360 (***)	Net volume, quarts (Variable Measure Trade Item)	N4+N6		NET VOLUME (q)
361 (***)	Net volume, gallons U.S. (Variable Measure Trade Item)	N4+N6		NET VOLUME (g)
362 (***)	Logistic volume, quarts	N4+N6		VOLUME (q), log
363 (***)	Logistic volume, gallons U.S.	N4+N6		VOLUME (g), log
364 (***)	Net volume, cubic inches (Variable Measure Trade Item)	N4+N6		VOLUME (i ³)
365 (***)	Net volume, cubic feet (Variable Measure Trade Item)	N4+N6		VOLUME (f ³)
366 (***)	Net volume, cubic yards (Variable Measure Trade Item)	N4+N6		VOLUME (y ³)
367 (***)	Logistic volume, cubic inches	N4+N6		VOLUME (i ³), log
368 (***)	Logistic volume, cubic feet	N4+N6		VOLUME (f ³), log
369 (***)	Logistic volume, cubic yards	N4+N6		VOLUME (y ³), log
37	Count of Trade Items	N2+N..8	(FNC1)	COUNT
390 (***)	Applicable Amount Payable, local currency	N4+N..15	(FNC1)	AMOUNT
391 (***)	Applicable Amount Payable with ISO Currency Code	N4+N3+N..15	(FNC1)	AMOUNT
392 (***)	Applicable Amount Payable, single monetary area (Variable Measure Trade Item)	N4+N..15	(FNC1)	PRICE
393 (***)	Applicable Amount Payable with ISO Currency Code (Variable Measure Trade Item)	N4+N3+N..15	(FNC1)	PRICE
400	Customer's Purchase Order Number	N3+X..30	(FNC1)	ORDER NUMBER
401	Global Identification Number for Consignment (GINC)	N3+X..30	(FNC1)	GINC
402	Global Shipment Identification Number (GSIN)	N3+N17	(FNC1)	GSIN
403	Routing Code	N3+X..30	(FNC1)	ROUTE

AI	Data Content	Format*	FNC1 Required	Data Title
410	Ship to - Deliver to Global Location Number	N3+N13		SHIP TO LOC
411	Bill to - Invoice to Global Location Number	N3+N13		BILL TO
412	Purchased from Global Location Number	N3+N13		PURCHASE FROM
413	Ship for - Deliver for - Forward to Global Location Number	N3+N13		SHIP FOR LOC
414	Identification of a Physical Location - Global Location Number	N3+N13		LOC No
415	Global Location Number of the Invoicing Party	N3+N13		PAY TO
420	Ship to - Deliver to Postal Code Within a Single Postal Authority	N3+X..20	(FNC1)	SHIP TO POST
421	Ship to - Deliver to Postal Code with ISO Country Code	N3+N3+X..9	(FNC1)	SHIP TO POST
422	Country of Origin of a Trade Item	N3+N3	(FNC1)	ORIGIN
423	Country of Initial Processing	N3+N3+N..12	(FNC1)	COUNTRY - INITIAL PROCESS.
424	Country of Processing	N3+N3	(FNC1)	COUNTRY - PROCESS.
425	Country of Disassembly	N3+N3	(FNC1)	COUNTRY - DISASSEMBLY
426	Country Covering full Process Chain	N3+N3	(FNC1)	COUNTRY – FULL PROCESS
427	Country Subdivision of Origin	N3+X..3	(FNC1)	ORIGIN SUBDIVISION
7001	NATO Stock Number (NSN)	N4+N13	(FNC1)	NSN
7002	UN/ECE Meat Carcasses and Cuts Classification	N4+X..30	(FNC1)	MEAT CUT
7003	Expiration Date and Time	N4+N10	(FNC1)	EXPIRY TIME
7004	Active Potency	N4+N..4	(FNC1)	ACTIVE POTENCY
703s	Approval Number of Processor with ISO Country Code	N4+N3+X..27	(FNC1)	PROCESSOR # s
710	National Healthcare Reimbursement Number (NHRN) – Germany PZN	N3+X..20	(FNC1)	NHRN PZN
711	National Healthcare Reimbursement Number (NHRN) – France CIP	N3+X..20	(FNC1)	NHRN CIP
712	National Healthcare Reimbursement Number (NHRN) – Spain CN	N3+X..20	(FNC1)	NHRN CN
nnn*	National Healthcare Reimbursement Number (NHRN) – Country “A” NHRN	N3+X..20	(FNC1)	NHRN xxx
8001	Roll Products (Width, Length, Core Diameter, Direction, Splices)	N4+N14	(FNC1)	DIMENSIONS
8002	Cellular Mobile Telephone Identifier	N4+X..20	(FNC1)	CMT No

AI	Data Content	Format*	FNC1 Required	Data Title
8003	Global Returnable Asset Identifier (GRAI)	N4+N14+X..16	(FNC1)	GRAI
8004	Global Individual Asset Identifier (GIAI)	N4+X..30	(FNC1)	GIAI
8005	Price Per Unit of Measure	N4+N6	(FNC1)	PRICE PER UNIT
8006	Identification of the Components of a Trade Item	N4+N14+N2+N2	(FNC1)	GCTIN
8007	International Bank Account Number (IBAN)	N4+X..30	(FNC1)	IBAN
8008	Date and Time of Production	N4+N8+N..4	(FNC1)	PROD TIME
8017	Global Service Relation Number to identify the relationship between an organisation offering services and the provider of services	N4+N18	(FNC1)	GSRN - PROVIDER
8018	Global Service Relation Number to identify the relationship between an organisation offering services and the recipient of services	N4+N18	(FNC1)	GSRN - RECIPIENT
8019	Service Relation Instance Number (SRIN)	N4+N..10	(FNC1)	SRIN
8020	Payment Slip Reference Number	N4+X..25	(FNC1)	REF No
8100	GS1-128 Coupon Extended Code	N4+N6	(FNC1)	-
8101	GS1-128 Coupon Extended Code	N4+N1+N5+N4	(FNC1)	-
8102	GS1-128 Coupon Extended Code	N4+N1+N1	(FNC1)	-
8110	Coupon Code Identification for Use in North America	N4+X..70	(FNC1)	-
8200	Extended Packaging URL	N4+X..70	(FNC1)	PRODUCT URL
90	Information Mutually Agreed Between Trading Partners	N2+X..30	(FNC1)	INTERNAL
91 to 99	Company Internal Information	N2+X..30	(FNC1)	INTERNAL



***Note:** An example to illustrate future additional NHRNs. If additional NHRN AIs are required, a request for a new NHRN AI shall be made through the GS1 GSMP.

3.3. GS1 Application Identifiers starting with digit 0

3.3.1. Identification of a Logistic Unit: AI (00)

The Application Identifier (00) indicates that the GS1 Application Identifier data field contains an SSCC (Serial Shipping Container Code). The SSCC is used to identify logistic units (see Section 2.2).

The Extension digit is used to increase the capacity of the Serial Reference within the SSCC. It is assigned by the company that constructs the SSCC. The Extension digit ranges from 0-9.

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the SSCC – here the physical builder or the brand owner of the logistic unit (see Section 1.5). It makes the SSCC unique worldwide but does not identify the origin of the unit.

The structure and content of the Serial Reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each logistic unit.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.3.1 - 1

Format of the Element String					
SSCC (Serial Shipping Container Code)					
Application Identifier	Extension Digit	GS1 Company Prefix \longleftrightarrow Serial Reference			Check Digit
0 0	N ₁	N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃ N ₁₄ N ₁₅ N ₁₆ N ₁₇			N ₁₈

The data transmitted from the bar code reader means that the Element String denoting the SSCC of a logistic unit has been captured.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **SSCC**

3.3.2. Identification of a Fixed Measure Trade Item (GTIN): AI (01)

The Application Identifier (01) indicates that the GS1 Application Identifier data field contains a GTIN. The GTIN is used to identify trade items (see Section 4).

The GTIN for Fixed Measure Trade Items may be a GTIN-8, GTIN-12, GTIN-13 or a GTIN-14.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.3.2 – 1

Format of the Element String				
Global Trade Item Number (GTIN)				
Application Identifier	GS1-8 Prefix or GS1 Company Prefix \longleftrightarrow Item reference			Check Digit
(GTIN-8)	0 1	0 0 0 0 0 0	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇	N ₈
(GTIN-12)	0 1	0 0	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁	N ₁₂
(GTIN-13)	0 1	0	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂	N ₁₃
(GTIN-14)	0 1	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃		N ₁₄

The data transmitted from the bar code reader means that the Element String denoting the GTIN of a Fixed Measure Trade Item has been captured.

When indicating this Element String in the Non-HRI text section of a bar code label, the following data title should be used (see also Section 3.2): **GTIN**

3.3.3. Identification of a Variable Measure Trade Item (GTIN): AI (01)

3.3.3.1. Identification of a Variable Measure Trade Item (GTIN) Scanned at POS: AI (01)

The Application Identifier (01) indicates that the GS1 Application Identifier data field contains a GTIN. The GTIN is used to identify trade items (see Section 4).

The GTIN for variable measure trade Item scanned at POS can include a GTIN-12 or GTIN-13 Identification Number.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.3.3.1 – 1

		Format of the Element String													
		Global Trade Item Number (GTIN)												Check Digit	
	Application Identifier														
(GTIN-12)	0 1	0	0	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂
(GTIN-13)	0 1	0	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃

The data transmitted from the bar code reader means that the Element String denoting the GTIN of a Variable Measure Trade Item has been captured. This Element String must be processed together with the variable information of the same trade item (see 3.6.1 and 3.6.2 Optional Attributes).

When indicating this Element String in the Non-HRI text section of a bar code label, the following data title should be used (see also Section 3.2): **GTIN**

3.3.3.2. Identification of a Variable Measure Trade Item (GTIN) Not Scanned at POS: AI (01)

The Application Identifier (01) indicates that the GS1 Application Identifier data field contains a GTIN. GTINs with Indicator digit 9 are used to identify variable measure trade items not scanned at POS (see Section 4).

The GTIN for Variable Measure Trade Items is a special application of the GTIN-14 Data Structure. The digit 9 in the Indicator position indicates that the item identified is a Variable Measure Trade Item Not Scanned at POS.

Unlike GTIN-14s used to identify fixed measure trade items (see Section 2, Identification of Uniform Groupings of Trade Items), this GTIN-14 is not derived from the GTIN (without check digit) of the contained trade items.

The GTIN-14 must be processed in its entirety and not broken down into its constituent elements.

Each standard average measurement grouping must be assigned its own GTIN-14 according to the GTIN Allocation Rules.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.3.3 – 1

Format of the Element String				
Application Identifier	Global Trade Item Number (GTIN)			
	Indicator	GS1 Company Prefix Item Reference 		
0 1	9	N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃	N ₁₄	

The data transmitted from the bar code reader means that the Element String denoting the GTIN of a Variable Measure Trade Item has been captured. This Element String must be processed together with the variable information of the same trade item (see 3.6 Optional Attributes).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GTIN**

3.3.4. Identification of Fixed Measure Trade Items Contained in a Logistic Unit: AI (02)

The Application Identifier (02) indicates that the GS1 Application Identifier data field includes the GTIN of the contained trade items. The GTIN is used to identify trade items (see Section 4).

Note: This Element String may be used only on a logistic unit that is not itself a trade item and if all trade items that are contained at the same level have the same GTIN.

The GTIN of the trade items contained represents the identification number of the highest level of trade item contained in the logistic unit.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.3.4 – 1

Format of the Element String				
Application Identifier	GTIN of the Contained Trade Items			Check Digit
0 2	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃	N ₁₄		

The data transmitted from the bar code reader means that the Element String denoting the GTIN of Fixed Measure Trade Items contained in a logistic unit has been captured. This Element String must be processed together with the count of trade items, AI (37), which must appear on the same unit (see Section 3.6.5).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **CONTENT**

3.3.5. Identification of Variable Measure Trade Items Contained in a Logistic Unit: AI (02)

The Application Identifier (02) indicates that the GS1 Application Identifier data field includes the GTIN of the contained trade items. Indicator digit 9 is required for a GTIN-14 used for Variable Measure Trade Items.

Note: This Element String may be used only on a logistic unit that is not itself a trade item and if all trade items that are contained at the same level have the same GTIN. If the trade items are Variable Measure Trade Items, then this GTIN will be the implied item number that does not appear on the items contained.

The GTIN of the trade items contained represents the identification number of the highest level of items contained in the logistic unit.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.3.5 – 1

Format of the Element String		
Application Identifier	GTIN of the Contained Trade Item	Check Digit
0 2	9 N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃	N ₁₄

The data transmitted from the bar code reader means that the Element String denoting the GTIN of a Variable Measure Trade Item contained in a logistic unit has been captured. This Element String must be processed together with the count of trade items, AI (37), and a valid trade measure that must appear on the same unit (see Section 3.6.5).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **CONTENT**

3.4. GS1 Application Identifiers starting with digit 1

3.4.1. Batch or Lot Number: AI (10)

The Application Identifier (10) indicates that the GS1 Application Identifier data field contains a batch or lot number. The batch or lot number associates an item with information the manufacturer considers relevant for traceability of the trade item to which the Element String is applied. The data may refer to the trade item itself or to items contained. The number may be, for example, a production lot number, a shift number, a machine number, a time, or an internal production code. The data is alphanumeric and may include all characters contained in Figure 7.12 - 1.

Note: The batch or lot number is not part of the unique identification of a trade item.

Figure 3.4.1 - 1

Format of the Element String	
Application Identifier	Batch or Lot Number
1 0	X ₁ ————— variable length —————> X ₂₀

The data transmitted by the bar code reader means that the Element String denoting a batch or lot number has been captured. As this Element String is an attribute of a particular item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **BATCH/LOT**

3.4.2. Production Date: AI (11)

The Application Identifier (11) indicates that the GS1 Application Identifier data field contains a production date. The production date is the production or assembly date determined by the manufacturer. The date may refer to the trade item itself or to items contained.

The structure is:

- Year: the tens and units of the year (e.g., 2003 = 03), which is mandatory
- Month: the number of the month (e.g., January = 01), which is mandatory
- Day: the number of the day of the relevant month (e.g., second day = 02); if it is not necessary to specify the day, the field must be filled with two zeros

✔ **Note:** When it is not necessary to specify the day (the Day field is filled with two zeros), the resultant data string shall be interpreted as the last day of the noted month including any adjustment for leap years (e.g. “130200” is “2013 February 28”, “160200” is “2016 February 29”, etc.)

✔ **Note:** This Element String can only specify dates ranging from 49 years in the past to 50 years in the future. Determination of the correct century is explained in Section 7.13.

Figure 3.4.2 - 1

Format of the Element String			
Application Identifier	Production Date		
	Year	Month	Day
1 1	N ₁ N ₂	N ₃ N ₄	N ₅ N ₆

The data transmitted from the bar code reader means that the Element String denoting a production date has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **PROD DATE**

3.4.3. Due Date for Amount on Payment Slip: AI (12)

The Application Identifier (12) indicates that the GS1 Application Identifier data field contains the date by which an invoice should be paid. This data element represents an attribute of a payment slip reference number, AI (8020), and a Global Location Number (GLN) of the invoicing party.

The structure is:

- Year: the tens and units of the year (e.g., 1998 = 98), which is mandatory
- Month: the number of the month (e.g., January = 01), which is mandatory
- Day: the number of the day of the relevant month (e.g., second day = 02); if it is not necessary to specify the day, the field must be filled with two zeros

✔ **Note:** When it is not necessary to specify the day (the Day field is filled with two zeros), the resultant data string shall be interpreted as the last day of the noted month including any

adjustment for leap years (e.g. “130200” is “2013 February 28”, “160200” is “2016 February 29”, etc.)

- ✓ **Note:** This Element String can only specify dates ranging from 49 years in the past to 50 years in the future. Determination of the correct century is explained in Section 7.13.

Figure 3.4.3 - 1

Format of the Element String			
Application Identifier	Due Date		
	Year	Month	Day
1 2	N ₁ N ₂	N ₃ N ₄	N ₅ N ₆

The data transmitted from the bar code reader means that the Element String denoting a due date has been captured. This Element String must be processed together with a payment slip reference number, AI (8020), and a GLN of the invoicing party, AI (415).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **DUE DATE**

3.4.4. Packaging Date: AI (13)

The Application Identifier (13) indicates that the GS1 Application Identifier data fields contain a packaging date. The packaging date is the date when the goods were packed as determined by the packager. The date may refer to the trade item itself or to items contained.

The structure is:

- Year: the tens and units of the year (e.g., 2003 = 03), which is mandatory
- Month: the number of the month (e.g., January = 01), which is mandatory
- Day: the number of the day of the relevant month (e.g., second day = 02); if it is not necessary to specify the day, the field must be filled with two zeros

- ✓ **Note:** When it is not necessary to specify the day (the Day field is filled with two zeros), the resultant data string shall be interpreted as the last day of the noted month including any adjustment for leap years (e.g. “130200” is “2013 February 28”, “160200” is “2016 February 29”, etc.)

- ✓ **Note:** This Element String can only specify dates ranging from 49 years in the past to 50 years in the future. Determination of the correct century is explained in Section 7.13.

Figure 3.4.4 - 1

Format of the Element String			
Application Identifier	Packaging Date		
	Year	Month	Day
1 3	N ₁ N ₂	N ₃ N ₄	N ₅ N ₆

The data transmitted from the bar code reader means that the Element String denoting a packaging date has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **PACK DATE**

3.4.5. Best Before Date: AI (15)

The Application Identifier (15) indicates that the GS1 Application Identifier data fields contain a best before date. The best before date indicates the ideal consumption or best effective use date of a product. It is a statement about quality. It is often referred to as a sell by date or a minimum durability date.

The structure is:

- Year: the tens and units of the year (e.g., 2003 = 03), which is mandatory
- Month: the number of the month (e.g., January = 01), which is mandatory
- Day: the number of the day of the relevant month (e.g., second day = 02); if it is not necessary to specify the day, the field must be filled with two zeros

✔ **Note:** When it is not necessary to specify the day (the Day field is filled with two zeros), the resultant data string shall be interpreted as the last day of the noted month including any adjustment for leap years (e.g. “130200” is “2013 February 28”, “160200” is “2016 February 29”, etc.)

✔ **Note:** This Element String can only specify dates ranging from 49 years in the past to 50 years in the future. Determination of the correct century is explained in Section 7.13.

Figure 3.4.5 - 1

Format of the Element String			
Application Identifier	Best Before Date		
	Year	Month	Day
1 5	N ₁ N ₂	N ₃ N ₄	N ₅ N ₆

The data transmitted from the bar code reader means that the Element String denoting a best before date has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **BEST BEFORE** or **SELL BY**

3.4.6. Expiration Date: AI (17)

The Application Identifier (17) indicates that the GS1 Application Identifier data fields contain an expiration date. The expiration date is the date that determines the limit of consumption or use of a product. Its meaning is determined based on the trade item context (e.g., for food, the date will indicate the possibility of a direct health risk resulting from use of the product after the date, for pharmaceutical products, it will indicate the possibility of an indirect health risk resulting from the ineffectiveness of the product after the date). It is often referred to as "use by date" or "maximum durability date."

The structure is:

- Year: the tens and units of the year (e.g., 2003 = 03), which is mandatory
- Month: the number of the month (e.g., January = 01), which is mandatory
- Day: the number of the day of the relevant month (e.g., second day = 02); if it is not necessary to specify the day, the field must be filled with two zeros

✔ **Note:** When it is not necessary to specify the day (the Day field is filled with two zeros), the resultant data string shall be interpreted as the last day of the noted month including any adjustment for leap years (e.g. “130200” is “2013 February 28”, “160200” is “2016 February 29”, etc.).

✔ **Note:** This Element String can only specify dates ranging from 49 years in the past to 50 years in the future. Determination of the correct century is explained in Section 7.13.

Figure 3.4.6 - 1

Format of the Element String			
Application Identifier	Expiration Date		
	Year	Month	Day
1 7	N ₁ N ₂	N ₃ N ₄	N ₅ N ₆

The data transmitted from the bar code reader means that the Element String denoting an expiration date has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **USE BY or EXPIRY**

3.5. GS1 Application Identifiers starting with digit 2

3.5.1. Product Variant: AI (20)

This Element String may be used to distinguish a variant from the usual item if the variation is not sufficiently significant to require a separate Global Trade Item Number (GTIN) and the variation is relevant only to the brand owner and any third party acting on its behalf.

The product variant is only for use by the brand owner and any third party acting on its behalf and not for dealings with any other trading partners. The product variant shall not be used where the variation would trigger the allocation of a different GTIN per the GTIN Allocation Rules.

Although the Element String will not have meaning to all trading partners, the Element String may remain on the item throughout distribution.

Figure 3.5.1 - 1

Format of the Element String	
Application Identifier	Variant Number
2 0	N ₁ N ₂

The Application Identifier (20) indicates that the data field contains a variant number.

The variant number must only be assigned by the brand owner. It forms a subsidiary numbering facility that can be used in addition to the item's GTIN and allows the creation of 100 variants of a particular item.

The data transmitted from the bar code reader means that the Element String denoting a product variant has been captured. The product variant must be processed together with the GTIN of the same trade item. Beyond the brand owner and any third party acting on its behalf, it should be ignored.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **VARIANT**

3.5.2. Serial Number: AI (21)

The Application Identifier (21) indicates that the GS1 Application Identifier data field contains a serial number. A serial number is assigned to an entity for its lifetime. When combined with a GTIN, a serial number uniquely identifies an individual item. The serial number field is alphanumeric and may include all characters contained in Figure 7.12 - 1. The manufacturer determines the serial number.

Figure 3.5.2 - 1

Format of the Element String	
Application Identifier	Serial Number
2 1	X ₁ _____ variable length _____ → X ₂₀

The data transmitted from the bar code reader means that the Element String denoting a serial number has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **SERIAL**

3.5.3. Secondary Data for Specific Health Industry Products: AI (22)

GS1 has established 01 Jan 2013 as the global Sunset date for AI (22) as no continuing business rationale for it exists. After this date, GS1 will return AI (22) to the numbers available for assignment to new Application Identifier requirements.

Figure 3.5.3 - 1

Format of the Element String	
Application Identifier	Additional Item Identification
2 2	X ₁ _____ variable length _____ → X ₂₉

The Application Identifier (22) indicates that the data field contains the secondary data for specific health industry products (quantity, expiration date, and lot number). The secondary data fields are described in Section 7.8.

Note: This Element String was developed to accommodate an existing, non-GS1 System, standard used for specific healthcare products. The Element String is not recommended for new

applications or other industries. The use of the Element Strings denoting expiration date, AI (17), and batch or lot number, AI (10), are recommended instead.

Not recommended for use (see Section 7.8)

3.5.4. Additional Product Identification Assigned by the Manufacturer: AI (240)

The Application Identifier (240) indicates that the GS1 Application Identifier data field contains additional item identification. The purpose of this Element String is to enable identification data other than the Global Trade Item Number (GTIN) to be represented in a GS1 System data carrier. It is a cross-reference to previously used catalogue numbers. The additional item identification is considered an attribute of the GTIN (e.g., it facilitates migration to the GS1 System during a transitional period). However, it must not be used to replace the GTIN.

The additional item identification field is alphanumeric and may include all characters contained in Figure 7.12 - 1. Its content and structure are at the discretion of the company applying the Element String.

Figure 3.5.4 - 1

Format of the Element String	
Application Identifier	Additional Item Identification
2 4 0	X ₁ ————— variable length —————> X ₃₀

The data transmitted from the bar code reader means that the Element String denoting an additional item identification has been captured. This Element String must be processed together with the GTIN of the same trade item.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **ADDITIONAL ID**

3.5.5. Customer Part Number: AI (241)

The Application Identifier (241) indicates that the GS1 Application Identifier data field contains a customer part number. The purpose of this Element String is to enable identification data other than the Global Trade Item Number (GTIN) to be represented in a GS1 System data carrier. The Element String should only be used between trading partners that are currently using the customer part number for ordering and who have agreed on a timetable to convert to the GTIN for their business purposes. Therefore, the use of the GTIN and the AI (241) on trade items is for transitional use during the conversion. The customer part number must not be used in place of the GTIN.

The customer part number field is alphanumeric and may include all characters contained in Figure 7.12 - 1.

Figure 3.5.5 - 1

Format of the Element String	
Application Identifier	Customer Part Number
2 4 1	X ₁ ————— variable length —————> X ₃₀

The data transmitted from the bar code reader means that the Element String denoting a customer part number has been captured. This Element String must be processed together with the GTIN of the same trade item.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **CUST. PART NO.**

3.5.6. Made-to-Order Variation Number: AI (242)

The Application Identifier (242) indicates that the data field contains a Made-to-Order Variation Number. The data is variable length numeric up to and including six digits.

The Made-to-Order Variation Number provides the additional data needed to uniquely identify a custom trade item. (See Section 2.6.)

There is a mandatory association of AI 242 with a GTIN-14, Indicator Digit 9. This association indicates that the GTIN-14, Indicator Digit 9 represents a custom trade item when paired with AI 242.

A Made-to-Order Variation Number may not be used with the following GTINs: GTIN-8, GTIN-12, GTIN-13, and GTIN-14 Indicator Digit 1 through 8. The use of a GTIN-14, Indicator Digit 9 and a Made-to-Order Variation Number is only approved for the Maintenance, Repair, and Operation (MRO) industrial supply sector.

Figure 3.5.6 - 1

Format of the Element String	
Application Identifier	Made-to-Order Variation Number
2 4 2	N ₁ ————— variable length —————> N ₆

The data transmitted by the bar code reader means that the Element String denoting a Made-to-Order Variation Number has been captured. This Element String must be processed together with the GTIN of the trade item to which it relates (see Section 3.3.3).

When indicating this Element String in the Non-HRI text section of a bar code label, the following data title should also be used (see also Section 3.2): **MTO Variant**

3.5.7. Packaging Component Number: AI (243)

The Application Identifier (243) indicates the GS1 Application Identifier data field contains a Packaging Component Number (PCN). A PCN is assigned to the packaging component for its lifetime. When associated with a GTIN, a PCN uniquely identifies the relationship between a finished consumer trade item and one of its packaging components.

The current use case for PCN is for internal use only however the PCN may be considered in future use cases for open supply chain applications.

The Packaging Component Number field is alphanumeric and may include all characters contained in Figure 7.12 - 1.

Figure 3.5.7 - 1

Format of the Element String	
Application Identifier	Packaging Component Number
243	X ₁ ————— variable length —————> X ₂₀

The data transmitted from the bar code reader means that the Element String denoting a Packaging Component Number has been captured. As this Element String is an attribute of a particular item, it must be processed together with the GTIN of the trade item to which it relates

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **PCN**

3.5.8. Secondary Serial Number: AI (250)

The Application Identifier (250) indicates that the GS1 Application Identifier data field contains a secondary serial number. While the Element String using AI (21) (see Section 3.5.2) contains the serial number of the trade item, the Element String denoting a secondary serial number represents the serial number of a component of that item. The company applying the Element String determines which component the Element String refers to for a given trade item. The recognition of the meaning of the secondary serial number is accomplished via the GTIN and information provided by the issuer regarding the component to which the secondary serial number refers.

If this Element String is being used, the trade item must be symbol marked with the following Element Strings:

- AI (01): representing the GTIN of the trade item
- AI (21): representing the serial number of the trade item
- AI (250): representing the serial number of a component of the trade item

Only one Element String with AI (250) may be associated with a particular GTIN.

The secondary serial number field is alphanumeric and may include all characters contained in Figure 7.12 - 1. The number and to what component it relates is determined by the issuer.

Figure 3.5.8 - 1

Format of the Element String	
Application Identifier	Secondary Serial Number
2 5 0	X ₁ _____ variable length _____ → X ₃₀

The data transmitted from the bar code reader means that the Element String denoting a secondary serial number has been captured. This Element String must be processed together with the GTIN of the trade item to which it relates and the serial number of the trade item AI (21).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **SECONDARYSERIAL**

Note: The actual data title may be specified by the issuer of the data.

3.5.9. Reference to Source Entity: AI (251)

The Application Identifier (251) indicates that the GS1 Application Identifier data field consists of a reference to the original item. Reference to source entity is an attribute of a trade item used to refer to the original item from which the trade item was derived. The issuer of the trade item must indicate through other means the source entity to which the data refers.

For example, the original item could be an animal from which a carcass of beef is derived. This Element String would enable reference to the original animal, so that, if the animal was found to be contaminated, all derived products could be isolated. In addition, this Element String could also be

used for regulatory compliance when recycling parts from various white goods, such as refrigerators, where it is necessary to refer to the original appliance.

The reference to the source entity field is alphanumeric and may include all characters contained in Figure 7.12 -1.

Figure 3.5.9 - 1

Format of the Element String	
Application Identifier	Reference to Source Entity
2 5 1	X ₁ ————— variable length —————> X ₃₀

The data transmitted by the bar code reader means that the Element String denoting a reference to source entity has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **REF. TO SOURCE**

Note: The actual data title may be specified by the issuer of the data.

3.5.10. Global Document Type Identifier (GDTI): AI (253)

The Application Identifier (253) indicates that the GS1 Application Identifier data field contains the Global Document Type Identifier (GDTI). The GDTI used to identify a document type with an optional serial number.

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GDTI – here the document issuer (see Section 1.5). It makes the number unique worldwide.

The structure and content of the Document Type is at the discretion of owner of the GS1 Company Prefix to uniquely identify each type of document.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

The optional serial component is assigned to a single document for its lifetime. When combined with a GDTI, it uniquely identifies an individual document. The Serial Component field is alpha-numeric and may contain up to 17 characters. The issuer of the document determines the serial component.

Figure 3.5.10 – 1

Format of the Element String			
Application Identifier	Global Document Type Identifier (GDTI)		
	GS1 Company Prefix →	← Document Type	Check Digit
			Serial Component (Optional)
2 5 3	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂	N ₁₃	X ₁ — variable → X ₁₇

The data transmitted from the bar code reader means that the Element String denoting a GDTI has been captured.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GDTI**

3.5.11. GLN Extension Component: AI (254)

The Application Identifier (254) indicates that the data field contains an extension component of a Global Location Number (GLN). The use of AI (254) is optional, but when used it must appear in conjunction with AI (414), identification of a physical location.

The GS1 Company Prefix owner determines the extension component. Once determined, it is unchanged for the life of the associated GLN.

The GLN Extension Component field is alphanumeric and may include all characters contained in Figure 7.12 - 1.

Figure 3.5.11 - 1

Format of the Element String	
Application Identifier	GLN Extension Component
254	X_1 — variable length — X_{20}

The data transmitted from the reader means that the Element String denoting an extension component of a GLN has been captured. As this Element String is an attribute of a physical location, it must be processed together with the GLN, AI (414), to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GLN EXTENSION COMPONENT**

3.5.12. Global Coupon Number (GCN): AI (255)

The Application Identifier (255) indicates that the GS1 Application Identifier data field contains the Global Coupon Number (GCN). The GCN provides a globally unique identification for a coupon, with an optional serial number.

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GCN. It makes the number unique worldwide.

The structure and content of the coupon reference is at the discretion of the owner of the GS1 Company Prefix to uniquely identify each type of coupon.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

The optional serial component is assigned to an individual instance of a coupon. The combination of GS1 Company Prefix, Coupon Reference and Serial Component uniquely identifies an individual coupon. The Serial Component field is numeric and may contain up to 12 digits. The issuer of the Global Coupon Number determines the serial component.

Figure 3.5.12 - 1

Format of the Element String			
Application Identifier	Global Coupon Number (GCN)		
	GS1 Company Prefix	Coupon Reference	Check Digit
255	$N_1 N_2 N_3 N_4 N_5 N_6 N_7 N_8 N_9 N_{10} N_{11} N_{12}$	N_{13}	N_1 — variable — N_{12}

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GCN**

3.6. GS1 Application Identifiers starting with digit 3

3.6.1. Variable Count: AI (30)

The Application Identifier (30) indicates that the GS1 Application Identifier data field contains the number of items contained in a Variable Measure Trade Item. This Element String is used to complete the identification of a Variable Measure Trade Item and, therefore, should never be applied in isolation.

The Count of Items field represents the quantity contained in the respective trade item. It is of variable length and may have up to eight digits.


 **Note:** This Element String must not be used to indicate the contained quantity of a Fixed Measure Trade Item. However, if this Element String appears on a Fixed Measure Trade Item (in error) it should not invalidate the item identification but should be treated as redundant data.

Figure 3.6.1 – 1

Format of the Element String	
Application Identifier	Count of Items
3 0	N ₁ _____ variable length → N ₈

The data transmitted from the bar code reader means that the Element String denoting a quantity (count of items), which can be considered part of the identification of a Variable Measure Trade Item, has been captured. This Element String must be processed with the GTIN of the trade item to which it relates (see Section 3.3.3).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **VAR. COUNT**

3.6.2. Trade Measures: AIs (31nn, 32nn, 35nn, 36nn)

The Application Identifiers (digits A1 to A3 – see figure below) indicate that the GS1 Application Identifier data field contains the quantity or dimension of a Variable Measure Trade Item. It also denotes the unit of measure. These Element Strings are used to complete the identification of a Variable Measure Trade Item. They contain information such as the weight, size, volume, or dimension of a Variable Measure Trade Item and, therefore, should never be applied alone. Several Element Strings are possible if the variables required are dimensions or weights expressed in kilograms and pounds.

The Application Identifier digit A4 indicates the implied decimal point position, where, for example, the digit 0 means that there is no decimal point, and the digit 1 means that the decimal point is between N5 and N6. The Applicable Value field contains the variable measure that applies to the respective trade item.

Figure 3.6.2 - 1

Format of the Element String	
Application Identifier	Applicable Value
A ₁ A ₂ A ₃ A ₄	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆

The Application Identifiers used with this Element String are shown in the Figure below.

 **Note:** Other values of AI (3nnn) specify gross measures and logistic measures.

Figure 3.6.2 - 2

A ₁	A ₂	A ₃	Trade Measure	Unit of Measure
3	1	0	Net weight	Kilograms
3	1	1	Length or first dimension	Metres
3	1	2	Width, diameter, or second dimension	Metres
3	1	3	Depth, thickness, height, or third dimension	Metres
3	1	4	Area	Square metres
3	1	5	Net volume	Litres
3	1	6	Net volume	Cubic metres
3	2	0	Net weight	Pounds
3	2	1	Length or first dimension	Inches
3	2	2	Length or first dimension	Feet
3	2	3	Length or first dimension	Yards
3	2	4	Width, diameter, or second dimension	Inches
3	2	5	Width, diameter, or second dimension	Feet
3	2	6	Width, diameter, or second dimension	Yards
3	2	7	Depth, thickness, height, or third dimension	Inches
3	2	8	Depth, thickness, height, or third dimension	Feet
3	2	9	Depth, thickness, height, or third dimension	Yards
3	5	0	Area	Square inches
3	5	1	Area	Square feet
3	5	2	Area	Square yards
3	5	6	Net weight	Troy ounces
3	5	7	Net weight (or volume)	Ounces
3	6	0	Net volume	Quarts
3	6	1	Net volume	Gallons (U.S.)
3	6	4	Net volume	Cubic inches
3	6	5	Net volume	Cubic feet
3	6	6	Net volume	Cubic yards

The data transmitted from the bar code reader means that the Element String denoting a quantity, which can be considered part of the identification of a Variable Measure Trade Item, has been captured. This Element String must be processed together with the GTIN of the trade item to which it relates (see Section [3.3.3](#)).

When indicating this Element String in the Non-HRI text section of a bar code label, the Data Title in Section [3.2](#) should be used.

3.6.3. Logistic Measures: AIs (33nn, 34nn, 35nn, 36nn)

The Application Identifiers (A1 to A3 see Figure below) indicate that the GS1 Application Identifier data field contains the logistic quantity or dimension of a logistic unit or a Variable Measure Trade Item. They also denote the unit of measure.

Note: The GS1 System provides standards for logistic weights and measures in metric and other units of measure. In principle, a particular logistic measure should be applied in only one unit of measure on a given logistic unit. However, application of the same attribute in several units of measure does not impede the correct processing of the transmitted data.

The Application Identifier digit in field A4 indicates the implied decimal point position, where, for example, the digit 0 means that there is no decimal point, and the digit 1 means that the decimal point is between N5 and N6.

The Applicable Value field represents the measures of the respective unit.

Figure 3.6.3 - 1

Format of the Element String									
Application Identifier				Applicable Value					
A ₁	A ₂	A ₃	A ₄	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆

The Application Identifiers used with this Element String are shown in Figure below

Figure 3.6.3 – 2

A ₁	A ₂	A ₃	Definition of Logistic Measures	Unit of Measure
3	3	0	Logistic weight	Kilograms
3	3	1	Length or first dimension	Metres
3	3	2	Width, diameter, or second dimension	Metres
3	3	3	Depth, thickness, height, or third dimension	Metres
3	3	4	Area	Square metres
3	3	5	Logistic volume	Litres
3	3	6	Logistic volume	Cubic metres
3	4	0	Logistic weight	Pounds
3	4	1	Length or first dimension	Inches
3	4	2	Length or first dimension	Feet
3	4	3	Length or first dimension	Yards
3	4	4	Width, diameter, or second dimension	Inches
3	4	5	Width, diameter, or second dimension	Feet
3	4	6	Width, diameter, or second dimension	Yards
3	4	7	Depth, thickness, height, or third dimension	Inches
3	4	8	Depth, thickness, height, or third dimension	Feet
3	4	9	Depth, thickness, height, or third dimension	Yards
3	5	3	Area	Square inches

A ₁	A ₂	A ₃	Definition of Logistic Measures	Unit of Measure
3	5	4	Area	Square feet
3	5	5	Area	Square yards
3	6	2	Logistic volume	Quarts
3	6	3	Logistic volume	Gallons (U.S.)
3	6	7	Logistic volume	Cubic inches
3	6	8	Logistic volume	Cubic feet
3	6	9	Logistic volume	Cubic yards

The data transmitted from the bar code reader means that the Element String denoting a logistic measure has been captured. This Element String must be processed with the SSCC of the logistic unit or the GTIN of the Variable Measure Trade Item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the Data Title in Section [3.2](#) should be used.

3.6.4. Kilograms per Square Metre: AI (337n)

The Application Identifier (337) indicates that the GS1 Application Identifier data field contains the kilograms per square metre of a particular trade item.

The Application Identifier digit shown as “n” indicates the implied decimal point position, where, for example, the digit 0 means that there is no decimal point, and the digit 1 means that the decimal point is between N₅ and N₆.

The **Kilograms Per Square Metre** field contains the weight per area of the respective trade item. The unit of measure is kilograms.

Figure 3.6.4 - 1

Format of the Element String						
Application Identifier	Kilograms Per Square Metre					
3 3 7 n	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆

The data transmitted from the bar code reader means that the Element String denoting kilograms per square metre has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section [3.2](#)): **KG PER m²**

3.6.5. Count of Trade Items Contained in a Logistic Unit: AI (37)

The Application Identifier (37) indicates that the GS1 Application Identifier data field contains the number of trade items contained in a logistic unit. This Element String is a mandatory completion of AI (02) described in Sections [3.3.4](#) and [3.3.5](#).

The Count of Trade Items field contains the number of trade items contained in the respective logistic unit. This information refers to the identification number of the contained trade items.

Figure 3.6.5 – 1

Format of the Element String	
Application Identifier	Count of Trade Items
3 7	N ₁ ——— variable length ———> N ₈

The data transmitted from the bar code reader means that the Element String denoting a number of trade items contained in a logistic unit has been captured. This Element String must be processed together with the GTIN represented in AI (02) (see Sections [3.3.4](#) and [3.3.5](#)) appearing on the same logistic unit.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section [3.2](#)): **COUNT**

3.6.6. Amount Payable - Single Monetary Area: AI (390n)

The Application Identifier (390) indicates that the GS1 Application Identifier data field contains the amount payable of a payment slip.

The Application Identifier digit shown as “n” indicates the implied decimal point position, where the digit 0 means that there is no decimal point, and the digit 1 means that the decimal point is before the last position of the amount payable. See examples in Figure below.

The applicable amount payable contains the sum to be paid with the respective payment slip.

Figure 3.6.6 - 1

Format of the Element String	
Application Identifier	Applicable Amount Payable
3 9 0 n	N ₁ ——— variable length ———> N ₁₅

Note: To aid unambiguous processing, AI (391n), described in Section [3.6.7](#), should be used to indicate the currency in which the amount is expressed.

The Figure below shows examples of the decimal point indication.

Figure 3.6.6 - 2

Application Identifier	Encoded Value	Actual Value
3 9 0 2	1 2 3 4 5 6 7	1 2 3 4 5 . 6 7
3 9 0 1	1 2 3 4 5 6 7	1 2 3 4 5 6 . 7 0
3 9 0 0	1 2 3 4 5	1 2 3 4 5 . 0 0

The data string transmitted from the bar code reader means that the Element String denoting the amount payable of a payment slip has been captured. This Element String must be processed together with the payment slip reference number, AI (8020), and the GLN of the invoicing party, AI (415).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section [3.2](#)): **AMOUNT**

3.6.7. Amount Payable and ISO Currency Code: AI (391n)

The Application Identifier (391) indicates that the GS1 Application Identifier data fields consist of an ISO currency code and an applicable amount payable.

The Application Identifier digit shown as “n” indicates the implied decimal point position in the Applicable Amount Payable field, where the digit 0 means that there is no decimal point, and the digit 1 means that the decimal point is before the last position of the amount payable. See examples in the Figure below.

The ISO country code field contains the three-digit currency number of the numerical international standard ISO 4217 and indicates the currency in which the amount payable is expressed.

The applicable amount payable contains the sum to be paid with the respective payment slip.

Figure 3.6.7 - 1

Format of the Element String		
Application Identifier	ISO Currency Code	Applicable Amount Payable
3 9 1 n	N ₁ N ₂ N ₃	N ₄ _____ variable length _____ N ₁₈

Figure 3.6.7 – 2 shows examples of the decimal point indication.

Figure 3.6.7 - 2

Application Identifier	ISO Currency Code	Encoded Value	Actual Value
3 9 1 2	7 1 0 [*]	1 2 3 0	1 2 . 3 0
3 9 1 1	7 1 0 [*]	1 2 3 0	1 2 3 . 0 0
3 9 1 0	9 7 8 ^{**}	1 2 3	1 2 3 . 0 0

* South African Rand

**Euro

The data string transmitted from the bar code reader means that the Element String denoting the amount payable has been captured. This Element String must be processed together with the payment slip reference number, AI (8020), and the GLN of the invoicing party, AI (415).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **AMOUNT**

3.6.8. Amount Payable for a Variable Measure Trade Item – Single Monetary Area: AI (392n)

The Application Identifier (392) indicates that the GS1 Application Identifier data field contains the amount payable for a Variable Measure Trade Item.

The amount payable refers to an item identified by the Global Trade Item Number (GTIN) of a Variable Measure Trade Item and is expressed in local currency. This AI is an attribute of the GTIN and is always used in conjunction with it.

The Application Identifier digit shown as “n” indicates the implied decimal point position, where the digit 0 means that there is no decimal point, and the digit 1 means that the decimal point is before the last position of the amount payable. See examples in the Figure below.

The Applicable Amount Payable field contains the total to be paid for the Variable Measure Trade Item.

Figure 3.6.8 - 1

Format of the Element String	
Application Identifier	Applicable Amount Payable
3 9 2 n	N ₁ _____ variable length _____ N ₁₅

Figure 3.6.8 - 2

Application Identifier	Encoded Value	Actual Value
3 9 2 2	1 2 3 4 5 6 7	1 2 3 4 5 . 6 7
3 9 2 1	1 2 3 4 5 6 7	1 2 3 4 5 6 . 7 0
3 9 2 0	1 2 3 4 5	1 2 3 4 5 . 0 0

The data transmitted by the bar code reader means that the Element String denoting the amount payable of a Variable Measure Trade Item has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see Section 3.2): **PRICE**

3.6.9. Amount Payable for a Variable Measure Trade Item and ISO Currency Code: AI (393n)

The Application Identifier (393) indicates that the GS1 Application Identifier data field consists of an ISO currency code and an applicable amount payable. The amount payable refers to an item identified with the Global Trade Item Number (GTIN) of a Variable Measure Trade Item and is expressed in the indicated currency. This AI is an attribute of the GTIN and is always expressed in conjunction with it.

The Application Identifier digit shown as “n” indicates the implied decimal point in the Applicable Amount Payable Field, where the digit 0 means that there is no decimal point, and the digit 1 means that the decimal point is before the last position of the amount payable. See examples in the Figure below.

The ISO currency code field contains the three-digit currency number of the numerical international standard ISO/IEC 4217 and indicates the currency in which the amount payable is expressed.

The Applicable Amount Payable field contains the sum to be paid for the Variable Measure Trade Item.

Figure 3.6.9 - 1

Format of the Element String		
Application Identifier	ISO Currency Code	Applicable Amount Payable
3 9 3 n	N ₁ N ₂ N ₃	N ₄ _____ variable length _____ N ₁₈

Figure 3.6.9 - 2

Application Identifier	ISO Currency Code	Encoded Value	Actual Value
3 9 3 2	7 1 0*	1 2 3 0	1 2 . 3 0
3 9 3 1	7 1 0*	1 2 3 0	1 2 3 . 0 0
3 9 3 0	9 7 8**	1 2 3	1 2 3 . 0 0

* South African Rand

** Euro

The data transmitted by the bar code reader means that the Element String denoting the amount payable of a Variable Measure Trade Item has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **PRICE**

3.7. GS1 Application Identifiers starting with digit 4

3.7.1. Customer's Purchase Order Number: AI (400)

The Application Identifier (400) indicates that the GS1 Application Identifier data field contains the customer's purchase order number, restricted for use between two trading partners.

The Customer's Purchase Order Number field is alphanumeric and may include all characters contained in Figure 7.12 - 1. It contains the number of the purchase order assigned by the company that issued the order. The composition and content of the order number is left to the discretion of the customer. For example, the purchase order number may include release and line numbers.

Figure 3.7.1 - 1

Format of the Element String	
Application Identifier	Customer's Purchase Order Number
4 0 0	X ₁ ————— variable length —————> X ₃₀

The data transmitted by the bar code reader means that the Element String denoting a customer's purchase order number has been captured. This Element String may be processed as stand-alone information where applicable or processed together with the GS1 identification number of the same unit.

! **Important:** This Element String must be removed from the unit before the unit leaves the premises of the customer.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **ORDER NUMBER**

3.7.2. Global Identification Number for Consignment (GINC): AI (401)

The Application Identifier (401) indicates that the GS1 Application Identifier data field contains a Global Identification Number for Consignment (GINC). This number identifies a logical grouping of goods (one or more physical entities) that has been consigned to a freight forwarder and is intended to be transported as a whole. The consignment number must be allocated by a freight forwarder (or a carrier acting as a freight forwarder) or a consignor, but only if prior agreement of the freight forwarder is given. Typically AI (401) encodes a House Way Bill (HWB) Number.

According to the Multi Industry Scenario for Transport (MIST), a freight forwarder is a party that arranges the carriage of goods, including connected services and/or associated formalities, on behalf of a shipper or consignee. A carrier is a party that undertakes the transportation of goods from one point to another. A consignor is the party that sends the goods. A consignee is the party that receives the goods.

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GINC – here the carrier (see Section 1.5). It makes the number unique worldwide.

The structure and content of the consignment reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each consignment. It may contain all characters contained in Figure 7.12 - 1.

Figure 3.7.2 - 1

Format of the Element String						
Application Identifier	Global Identification Number for Consignment (GINC)					
	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">GS1 Company Prefix</td> <td style="text-align: center;">Consignment Reference</td> </tr> <tr> <td style="text-align: center;">→</td> <td style="text-align: center;">←</td> </tr> </table>	GS1 Company Prefix	Consignment Reference	→	←	
GS1 Company Prefix	Consignment Reference					
→	←					
4 0 1	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">$N_1 \dots$</td> <td style="text-align: center;">N_i</td> <td style="text-align: center;">$X_{i+1} \dots$</td> <td style="text-align: center;">variable length</td> <td style="text-align: center;">$X_j (j \leq 30)$</td> </tr> </table>	$N_1 \dots$	N_i	$X_{i+1} \dots$	variable length	$X_j (j \leq 30)$
$N_1 \dots$	N_i	$X_{i+1} \dots$	variable length	$X_j (j \leq 30)$		

The data transmitted by the bar code reader means the Element String denoting a GINC has been captured.

Note: If a new consignment is created, previously consignment number bar codes must be removed from the physical units.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GINC**

3.7.3. Global Shipment Identification Number (GSIN): AI (402)

The Application Identifier (402) indicates that the data field contains a Global Shipment Identification Number (GSIN).

The Global Shipment Identification Number (GSIN) is a number assigned by a consignor (seller) of goods. It provides a globally unique number that identifies a logical grouping of logistic units for the purpose of a transport shipment from that consignor (seller) to the consignee (buyer). It identifies the logical grouping of one or several logistic units each identified with an separate SSCC and containing trade items as being part of a specific seller / buyer relationship and that travels under one despatch advice and/or Bill of Lading. It may be used by all parties in the transport chain as a communication reference, for example, in Electronic Data Interchange (EDI) messages where it can be used as a shipment reference and/or a consignor’s loading list. The GSIN fulfils the requirements of the UCR (Unique Consignment Reference) of the World Customs Organisation (WCO).

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GSIN – here the shipper (sender) (see Section 1.5). It makes the number unique worldwide.

The structure and content of the shipper reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each shipment. It should be sequentially allocated.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.7.3 - 1

Format of the Element String					
Application Identifier	Global Shipment Identification Number (GSIN)				
	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">GS1 Company Prefix</td> <td style="text-align: center;">Shipper Reference</td> </tr> <tr> <td style="text-align: center;">→</td> <td style="text-align: center;">←</td> </tr> </table>	GS1 Company Prefix	Shipper Reference	→	←
GS1 Company Prefix	Shipper Reference				
→	←				
4 0 2	$N_1 N_2 N_3 N_4 N_5 N_6 N_7 N_8 N_9 N_{10} N_{11} N_{12} N_{13} N_{14} N_{15} N_{16}$	N_{17}			

The data transmitted by the bar code reader means that the Element String denoting a GSIN has been captured.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GSIN**

3.7.4. Routing Code: AI (403)

The Application Identifier (403) indicates that the GS1 Application Identifier data field contains a routing code. The routing code is assigned by the parcel carrier and is an attribute of the SSCC (Serial Shipping Container Code). It is intended to provide a migration path to the adoption of a yet-to-be-defined international, multi-modal solution. The routing code must not be used to encode information for which other Element Strings have been created (such as a ship to postal code).

The routing code field is alphanumeric and may include all characters contained in Figure 7.12 - 1. Its content and structure are at the discretion of the parcel carrier issuing the code. If parcel carriers wish to enter co-operative agreements with other parcel carriers, then a mutually agreed indicator is required to designate the structure of the routing code.

Figure 3.7.4 - 1

Format of the Element String	
Application Identifier	Routing Code
4 0 3	X ₁ ————— variable length —————> X ₃₀

The data transmitted from the bar code reader means that the Element String denoting a routing code has been captured. As this Element String is an attribute of a logistic unit, it must be processed together with the SSCC to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **ROUTE**

3.7.5. Ship to - Deliver to Global Location Number: AI (410)

The Application Identifier (410) indicates that the GS1 Application Identifier data field contains the Global Location Number (GLN) of the consignee. The GLN is used to identify physical locations or legal entities (see Section 2.4).

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GLN – here the addressee (see Section 1.5). It makes the number unique worldwide.

The structure and content of the Location Reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each location.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.7.5 – 1

Format of the Element String			
Application Identifier	GS1 Company Prefix →	← Location Reference	Check Digit
4 1 0	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂		N ₁₃

The data transmitted from the bar code reader means that the Element String denoting the GLN of the consignee of a physical item has been captured. This Element String may be processed as stand-alone information where applicable or processed together with the GS1 identification number to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **SHIP TO LOC**

3.7.6. Bill to - Invoice to Global Location Number: AI (411)

The Application Identifier (411) indicates that the GS1 Application Identifier data field contains the Global Location Number (GLN) of the addressee of an invoice. The GLN is used to identify physical locations or legal entities (see Section 2.4).

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GLN – here the addressee (see Section 1.5). It makes the number unique worldwide.

The structure and content of the Location Reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each location.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.7.6 - 1

Format of the Element String			
Application Identifier	GS1 Company Prefix →	← Location Reference	Check Digit
4 1 1	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂		N ₁₃

The data transmitted from the bar code reader means that the Element String denoting the GLN of the addressee of an invoice has been captured. This Element String may be processed as stand-alone information where applicable or processed together with the GS1 identification number to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **BILL TO**

3.7.7. Purchased from Global Location Number: AI (412)

The Application Identifier (412) indicates that the GS1 Application Identifier data field contains the Global Location Number (GLN) of the company from which the respective trade item has been purchased. The GLN is used to identify physical locations or legal entities (see Section 2.4).

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GLN – here the supplier (see Section 1.5). It makes the number unique worldwide.

The structure and content of the Location Reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each location.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.7.7 – 1

Format of the Element String													
Application Identifier	GS1 Company Prefix						Location Reference						Check Digit
4 1 2	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃

The data transmitted from the bar code reader means that the Element String denoting the GLN of the company that supplied the trade item has been captured. This Element String may be processed as stand-alone information where applicable or processed together with the GS1 identification number to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label the following Data Title should be used (see also Section 3.2): **PURCHASE FROM**

3.7.8. Ship for - Deliver for - Forward to Global Location Number: AI (413)

The Application Identifier (413) indicates that the GS1 Application Identifier data field contains the Global Location Number (GLN) of the internal or subsequent final destination. The GLN is used to identify physical locations or legal entities (see Section 2.4).

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GLN – here the final recipient (see Section 1.5). It makes the number unique worldwide.

The structure and content of the Location Reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each location.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Note: This Element String is for the internal use of the consignee and is not to be used by the carrier.

Figure 3.7.8 - 1

Format of the Element String													
Application Identifier	GS1 Company Prefix						Location Reference						Check Digit
4 1 3	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃

The data transmitted from the bar code reader means that the Element String denoting the GLN of the final recipient of a physical item has been captured. This Element String may be processed as stand-

alone information where applicable or processed together with the GS1 identification number to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **SHIP FOR LOC**

3.7.9. Identification of a Physical Location - Global Location Number: AI (414)

The Application Identifier (414) indicates that the GS1 Application Identifier data field contains the Global Location Number (GLN) of a physical location (see Section 2.4).

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GLN – here the holder of the physical location (see Section 1.5). It makes the number unique worldwide.

The structure and content of the Location Reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each location.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Figure 3.7.9 – 1

Format of the Element String													
Application Identifier	GS1 Company Prefix						Location Reference						Check Digit
4 1 4	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃

The data transmitted from the bar code reader means that the Element String denoting the GLN of a physical location has been captured from the location itself. This Element String may be processed as stand-alone information where applicable or processed together with the GS1 identification number to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **LOC NO.**

3.7.10. Global Location Number of the Invoicing Party: AI (415)

The Application Identifier (415) indicates that the GS1 Application Identifier data field contains the Global Location Number (GLN) of the invoicing party.

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GLN – here the invoicing party (see Section 1.5). It makes the number unique worldwide.

The structure and content of the Location Reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each location.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

Note: This Element String is mandatory on a payment slip. Together with the payment slip reference number, AI (8020), it uniquely identifies a payment slip.

Figure 3.7.10 - 1

Format of the Element String													
Application Identifier	GS1 Company Prefix						Location Reference						Check Digit
4 1 5	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃

The data transmitted from the bar code reader means that the Element String denoting the GLN of the invoicing party has been captured. This Element String must be processed together with the payment slip reference number, AI (8020), to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **PAY TO**

3.7.11. Ship to - Deliver to Postal Code within a Single Postal Authority: AI (420)

The Application Identifier (420) indicates that the GS1 Application Identifier data field contains the postal code of the addressee (national format).

The postal code field contains the postal code of the addressee as defined by the appropriate postal authority. It is left justified and must not contain any fill characters.

Figure 3.7.11 - 1

Format of the Element String	
Application Identifier	Postal Code
4 2 0	X ₁ — variable length → X ₂₀

The data transmitted from the bar code reader means that the Element String denoting the national version of a postal code of the addressee of the transport unit has been captured. This Element String is normally processed as stand-alone information.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **SHIP TO POST**

3.7.12. Ship to - Deliver to Postal Code with Three-Digit ISO Country Code: AI (421)

The Application Identifier (421) indicates that the GS1 Application Identifier data field contains the postal code of the addressee (international format).

The ISO country code field contains the three-digit country number of the numerical international standard ISO 3166.

The national postal code field, which follows the three-digit ISO country code, contains the postal code of the addressee as defined by the appropriate postal authority. It is left justified and must not contain any fill characters.

Figure 3.7.12 - 1

Format of the Element String		
Application Identifier	ISO Country Code	Postal Code
4 2 1	N ₁ N ₂ N ₃	X ₄ — variable length —> X ₁₂

The data transmitted from the bar code reader means that the Element String denoting the international version of a postal code of the addressee of the transport unit has been captured. This Element String is normally processed as stand-alone information.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **SHIP TO POST**

3.7.13. Country of Origin of a Trade Item: AI (422)

The Application Identifier (422) indicates that the GS1 Application Identifier data field contains the ISO country code of the country of origin of the trade item.

The ISO country code field contains the three-digit country number of the numerical international standard ISO 3166 that is the country of origin.



Note: The country of origin is normally the country in which the trade item has been produced or manufactured. However, due to a wide range of definitions for country of origin, which were created for different purposes, it is the manufacturer's responsibility to assign the correct country of origin.

Figure 3.7.13 - 1

Format of the Element String	
Application Identifier	ISO Country Code
4 2 2	N ₁ N ₂ N ₃

The data transmitted from the bar code reader means that the Element String denoting the ISO country code of the country of origin of the respective trade item has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **ORIGIN**

3.7.14. Country of Initial Processing: AI (423)

The Application Identifier (423) indicates that the GS1 Application Identifier data field contains the ISO country code(s) of the country or countries of initial processing of the trade item.

The ISO country code field contains the three-digit country code(s) from the numerical international standard ISO 3166 that indicates the country or countries of initial processing.

- Note:** The country of initial processing is normally the country in which the trade item has been produced or manufactured. However, in certain applications, such as livestock fattening, the country of initial processing may include up to five different countries, all of which should be indicated. It is the responsibility of the supplier to allocate the correct country code(s).

Figure 3.7.14 - 1

Format of the Element String	
Application Identifier	ISO Country Code(s)
4 2 3	N ₁ N ₂ N ₃ ... N ₁₅

The data transmitted from the bar code reader means that the Element String denoting the ISO country code(s) of the country or countries of initial processing of the respective trade item has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **COUNTRY – INITIAL PROCESS**

3.7.15. Country of Processing: AI (424)

The Application Identifier (424) indicates that the GS1 Application Identifier data field contains the ISO country code of the country of processing of the trade item.

The ISO country code field contains the three-digit country code of the numerical international standard ISO 3166 that is the country of processing.

- Note:** It is the responsibility of the processor of the trade item to allocate the correct country code.

Figure 3.7.15 - 1

Format of the Element String	
Application Identifier	ISO Country Code
4 2 4	N ₁ N ₂ N ₃

The data transmitted from the bar code reader means that the Element String denoting the ISO country code of the country of processing of the respective trade item has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **COUNTRY – PROCESS**

3.7.16. Country of Disassembly: AI (425)

The Application Identifier (425) indicates that the GS1 Application Identifier data field contains the ISO country code of the country of disassembly of the trade item.

The ISO country code field contains the three-digit country code of the numerical international standard ISO 3166 that is the country of disassembly.

- Note:** It is the responsibility of the party doing the disassembly of the trade item to allocate the correct country code.

Figure 3.7.16 - 1

Format of the Element String			
Application Identifier	ISO Country Code		
4 2 5	N ₁	N ₂	N ₃

The data transmitted from the bar code reader means that the Element String denoting the ISO country code of the country of disassembly of the respective trade item has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **COUNTRY – DISASSEMBLY**

3.7.17. Country Covering Full Process Chain: AI (426)

The Application Identifier (426) indicates that the GS1 Application Identifier data field contains the ISO country code of the country where all the processing of the trade item took place.

The ISO country code field contains the three-digit country code of the numerical international standard ISO 3166 that is the country of full processing.

- Note:** If this AI is used, the full processing of a trade item must have taken place in a single country. This is particularly important in certain applications (e.g., covering a livestock animal’s birth, fattening, and slaughter) where processing could take place in different countries. In situations like this, AI (426) may not be used. It is the responsibility of the supplier to allocate the correct country code.

Figure 3.7.17 - 1

Format of the Element String			
Application Identifier	ISO Country Code		
4 2 6	N ₁	N ₂	N ₃

The data transmitted from the bar code reader means that the Element String denoting the ISO country code of the country of full processing of the trade item has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **COUNTRY – FULL PROCESS**

3.7.18. Country Subdivision of Origin Code for a Trade Item: AI (427)

The Application Identifier (427) indicates that the GS1 Application Identifier data field contains the ISO based country subdivision code (e.g. provinces, states, cantons, etc) of a country’s local region origin of the trade item.

The ISO country subdivision code field contains up to three alphanumeric characters after separator of ISO 3166-2:2007 that is the principal subdivision of origin.

- Note:** This GS1 AI is applicable to standard trade item groupings where the contents originate from only one region.
- Note:** The local region of origin is the principal subdivision in which the trade item has been produced or manufactured. Determination of the principle subdivision is the brand owner's responsibility.

Figure 3.7.18 - 1

Format of the Element String	
Application Identifier	ISO Subdivision Code
427	X_1 — variable length — X_3

The data transmitted from the bar code reader means that the Element String denoting the ISO based country subdivision code of the trade item has been captured. This Element String must be processed together with the GTIN of the trade item and the country of origin, AI (422), to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **ORIGIN SUBDIVISION**

3.8. GS1 Application Identifiers starting with digit 7

3.8.1. Seven Series AIs - Cautionary Note

Application Identifiers issued in the 7 series represent a special case because they are restricted to:

- one or a small number of sectors (i.e. are not multi-sectoral) or
- a country or a region (i.e. are not global).

3.8.1.1. Stock Number (NSN): AI (7001)

The Application Identifier (7001) indicates that the GS1 Application Identifier data field contains a NATO stock number.

The NATO stock number is the number allocated to any item of supply in the NATO Alliance. It is the responsibility of the country that manufactures or controls the design of the item to allocate the number.

- Note:** This Element String is only for use within the context of the supply within the NATO Alliance. Use of it is subject to the rules and regulations of the Allied Committee 135 (AC/135), the NATO Group of National Directors on Codification.

Figure 3.8.1.1 - 1

Format of the Element String	
Application Identifier	NATO Supply Assigning Sequential Number Classification Country
7001	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃

The data transmitted from the bar code reader means that the Element String denoting a NATO stock number has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **NSN**

3.8.1.2. UN/ECE Meat Carcasses and Cuts Classification: AI (7002)

The Application Identifier (7002) indicates that the GS1 Application Identifier data field contains a UN/ECE meat carcasses and cuts classification code.

The UN/ECE meat carcasses and cuts code is an attribute of a Global Trade Item Number (GTIN) that denotes the trade description of the product. It is an alphanumeric, variable length code up to 30 characters.

Note: This Element String is only for use within the context of UN/ECE standards for the quality of meat carcasses and cuts (bovine, porcine, ovine, and caprine).

Figure 3.8.1.2 - 1

Format of the Element String	
Application Identifier	UN/ECE Product Classification
7 0 0 2	X ₁ _____ variable length _____ X ₃₀

The data transmitted from the bar code reader means that the Element String denoting a UN/ECE meat carcasses and cuts code has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **MEAT CUT**

3.8.1.3. Expiration Date and Time: AI (7003)

The Application Identifier (7003) indicates that the data fields contain expiration date and time.

The manufacturer determines the expiration date and time, which is relevant only for short duration and for items that will not be sent on long distances and not outside of the time zone. A typical application of AI (7003) is in hospitals or public pharmacies for special, customised, products which may have a "life duration" shorter than one single day. The life duration varies according the pharmaceutical substances used in the treatment. The precise expiration date and time is defined at the end of the manufacturing process, and can be bar coded on the product label as an attribute to the item's GTIN. Where there is no business requirement to express the expiration date to the nearest hour (or less), AI (17) Expiration Date should be used.

The structure is:

- **Year:** the tens and units of the year (e.g., 2007 = 07), which is mandatory
- **Month:** the number of the month (e.g., January = 01), which is mandatory
- **Day:** the number of the day of the relevant month (e.g., second day = 02), which is mandatory.
- **Hour:** the number of the hour based on local 24-hour time (e.g., 2 p.m. = 14), which is mandatory
- **Minutes:** the number of the minutes based on local time (e.g., 15 minutes. = 15); if it is not necessary to specify the minutes, the field must be filled with two zeros. Time will then be interpreted as ending on the hour (e.g., 14:00 = expiry time at 14:00)

Figure 3.8.1.3 - 1

Format of the Data Element					
Application Identifier	Expiration Date and Time				
	YY	MM	DD	HH	MM
7003	N ₁ N ₂	N ₃ N ₄	N ₅ N ₆	N ₇ N ₈	N ₉ N ₁₀

The data transmitted from the bar code reader means that the Element String denoting an expiration date and time has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **EXPIRY TIME**

- ✓ **Note:** This Element String can only specify dates in the range from 49 years in the past to 50 years in the future. Determination of the correct century is explained in Section 7.13.

3.8.1.4. Active Potency: AI (7004)

The Application Identifier (7004) indicates that the GS1 Application Identifier data field contains an active potency.

The active potency of certain healthcare products (e.g. certain biologics, such as haemophilia products) varies by batch, and this will vary, within agreed tolerances, from the nominal potency of the trade item. Both the nominal and active potency of the item are measured in International Units (IUs).

Figure 3.8.1.4 - 1

Format of the Element String	
Application Identifier	Active Potency
7 0 0 4	N ₁ — variable length —→ N ₄

The data transmitted from the bar code reader means that the Active Potency of a Trade Item has been captured. The Active Potency must be processed with the GTIN and batch or lot number of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **ACTIVE POTENCY**.

3.8.1.5. Approval Number of Processor with Three-Digit ISO Country Code: AI (703s)

The Application Identifier (703s) indicates that the GS1 Application Identifier data fields contain the ISO country code and approval number of the processor of a trade item. As many processors may be involved, each with an individual approval number, the fourth digit of the AI (s in the Figure below) indicates the sequence of the processors. For a typical meat supply chain, the following sequence would be used:

- 7030: slaughterhouse
- 7031: first deboning/cutting hall
- 7032 to 7037: second through seventh processing location (cutting hall)
- 7038: slaughterhouse
- 7039: slaughterhouse

The ISO country code contains the three-digit country number of the numerical international standard ISO 3166 that relates to the following approval number of processor.

The approval number of processor is an attribute to a Global Trade Item Number (GTIN). It designates the approval number of the company who did the processing.

Note: The approval number is usually assigned by a national or pluri-national authority to processors in the food supply chain. These authorities may use the Global Location Number (GLN) (see Section 2.4) for this purpose. The approval number (or GLN) remains with the item regardless of whether or not it changes ownership or function.

Figure 3.8.1.5 - 1

Format of the Element String		
Application Identifier	ISO Country Code	Approval Number of Processor
7 0 3 s	N ₁ N ₂ N ₃	X ₄ ——— variable length ———→ X ₃₀

The data transmitted from the bar code reader means that the Element String denoting the ISO country code and approval number of processor has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **PROCESSOR # s**

3.8.1.6. National Healthcare Reimbursement Number (NHRN): AIs (710), (711), and (712)

The Application Identifiers (710), (711) and (712) indicate that the GS1 Application Identifier data field contains a National Healthcare Reimbursement Number, from the NHRN Application Identifier series, associated to the Global Trade Item Number (GTIN) of the trade item. The Application Identifiers (710), (711) and (712) indicate a specific NHRN from within the assigned series.

Use of the NHRN Application Identifier, associated to the GTIN of the trade item, is needed for compliance with a national/regional regulatory or industry requirement where the GTIN will not meet the need.


GTIN is the GS1 identifier for pharmaceutical and medical device trade items. The Application Identifier for National Healthcare Reimbursement Number is provided to meet regulatory or industry requirements until they are amended to accept the GTIN as a compliant identifier.


Within this application are the rules and recommendations for the association of NHRNs to the Global Trade Item Number (GTIN) where regulatory requirements require an NHRN for product identification, registration or reimbursement purposes.


There are a number of known NHRNs but at this time not all are required to be encoded within the data carrier found on the trade item. Flexibility for additional assigned NHRN AIs has been provided if required.


The National Healthcare Reimbursement Number Application Identifier is an initial step in a migration path to the most efficient method to identify trade items. GS1 recommends that Healthcare stakeholders faced with national numbers:


- a) Use GTIN for all supply chain and reimbursement purposes (GTIN used in the data carrier and as the NHRN) as this is the most efficient and effective way for all stakeholders to identify trade items.
- b) Use GTIN, cross-referenced to an NHRN in an existing database, in the case of an existing system of NHRNs (i.e. GTIN used in the data carrier with the NHRN found via cross-reference).
- c) Use GTIN with an associated NHRN (GTIN and NHRN both used in the data carrier via the NHRN AI) as an intermediate solution for those who cannot use “a” or “b”. GS1 only recommends this as a migration path to noted options “a” or “b”.


 **Note:** There is a mandatory association of the National Healthcare Reimbursement Number Application Identifier with the GTIN.

 **Note:** The NHRN is usually assigned by a national authority to healthcare brand owners for specific trade items and shall only be used for compliance to regulatory requirements where the GTIN alone will not meet the requirements.

 **Note:** Additional individual NHRN AIs can only be assigned by GS1 and only in response to a work request being submitted into the GSMP system.

 **Note:** The GTIN and all associated NHRNs should be concatenated into a single data carrier (i.e. single GS1-128, GS1 DataMatrix).

 **Note:** Use of NHRN on the item is controlled by and subject to the rules and regulations of national/regional agencies. Those rules and/or regulations may supersede these recommendations.

 **Note:** More than one NHRN may need to be associated with a given GTIN.

The general format of an NHRN Application Identifier is

Figure 3.8.1.6 - 1

Format of the Element String	
Application Identifier	National Healthcare Reimbursement Number
n n n	X ₁ — variable length —> X ₂₀

- ✔ **Note:** When an NHRN AI is approved, the overall variable length (i.e. allowable number of characters) is specified by the national authority, with a twenty (20) character maximum as noted in the general format above if applicable.

The Application Identifiers used with this Element String, their specific format and associated regulatory body or assigning organization, are shown in Figure 3.8.1.6 - 2 below:

Figure 3.8.1.6 - 2

Application Identifier	National Healthcare Reimbursement Number	Organization
710	X ₁ variable length X ₂₀	Germany IFA
711	X ₁ variable length X ₂₀	France CIP
712	X ₁ variable length X ₂₀	Spain National Code
nnn*	X ₁ variable length X ₂₀	Country "A" NHRN Authority

- ✔ **Note:** Companies wishing to apply one of the listed NHRN AIs will need to associate that NHRN AI to the trade item's GTIN according to the NHRN AI rules and should contact their GS1 Member Organization for further considerations of use.
- ✔ ***Note:** An example to illustrate future additional NHRNs. If additional NHRN AIs are required, a request for a new NHRN AI shall be made through the GS1 GSMP.

The data transmitted from the bar code reader means that the Element String denoting a National Healthcare Reimbursement Number has been captured. This Element String is an attribute of a trade item and must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the human readable section of a bar code label, the Data Title in Figure 3.2-1 should be used.

3.9. GS1 Application Identifiers starting with digit 8

3.9.1. Roll Products - Width, Length, Core Diameter, Direction, Splices: AI (8001)

The Application Identifier (8001) indicates that the GS1 Application Identifier data fields contain the variable attributes of a roll product. Depending on the method of production, some roll products cannot be numbered according to standard criteria that have been determined in advance. They are, therefore, classified as variable items. For those products where the standard trade measures are not sufficient, the following guidelines should be used.

The identification of a roll product consists of the Global Trade Item Number (GTIN) and the variable attributes. The basic product (e.g., a certain type of paper) is included as data in the GTIN-14 ID

Number (see Section 2.1.6), and the variables contain information about the special features of the particular item that has been produced.

The variable values of a roll product, N1 to N14, consist of the following data:

- N1 to N4: slit width in millimetres (width of the roll)
- N5 to N9: actual length in metres
- N10 to N12: internal core diameter in millimetres
- N13: winding direction (face out 0, face in 1, undefined 9)
- N14: number of splices (0 to 8 = actual number, 9 = number unknown)

Figure 3.9.1 - 1

Format of the Element String				
Application Identifier	Variable Values of a Roll Product			
8 0 0 1	N ₁ N ₂ N ₃ N ₄	N ₅ N ₆ N ₇ N ₈ N ₉	N ₁₀ N ₁₁ N ₁₂	N ₁₃ N ₁₄

The data transmitted from the bar code reader means that the Element String denoting the variable attributes of the identification of a roll product trade item have been captured. This Element String must be processed together with the GTIN of the trade item to which it relates (see Section 3.3.3).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **DIMENSIONS**

3.9.2. Cellular Mobile Telephone Identifier: AI (8002)

The Application Identifier (8002) indicates that the GS1 Application Identifier data field contains the serial number of a cellular mobile telephone.

The Serial Number field is alphanumeric and may contain all characters contained in Figure 7.12 - 1. A national or pluri-national authority usually assigns the number. It uniquely identifies each mobile telephone within a given authority for special control purposes. It is not considered as an attribute of the identification of the telephone as a trade item.

Figure 3.9.2 - 1

Format of the Element String	
Application Identifier	Serial Number
8 0 0 2	X ₁ _____variable length _____ X ₂₀

The data transmitted from the bar code reader means that the Element String denoting an electronic serial identifier of a cellular mobile telephone has been captured. This Element String is normally processed as stand-alone information.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **CMT NO.**

3.9.3. Global Returnable Asset Identifier (GRAI): AI (8003)

The Application Identifier (8003) indicates that the GS1 Application Identifier data field contains the GRAI (Global Returnable Asset Identifier). The GRAI is used to identify returnable assets.

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GRAI – here the owner of the returnable asset (see Section 1.5). It makes the number unique worldwide. The zero in the leftmost position is added to generate 14 digits in the asset identification number field.

The structure and content of the Asset Type is at the discretion of owner of the GS1 Company Prefix to uniquely identify each type of asset.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

The optional serial number is assigned by the owner of the asset. It identifies an individual asset within a given Asset Type. The field is alphanumeric and may contain all characters contained in Figure 7.12 - 1.

Figure 3.9.3 - 1

Format of the Element String					
Application Identifier	Global Returnable Asset Identifier (GRAI)				
	GS1 Company Prefix		Asset Type	Check Digit	Serial Number (Optional)
8 0 0 3	0	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂		N ₁₃	X ₁ variable X ₁₆

The data transmitted from the bar code reader means that the Element String denoting the GRAI has been captured.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GRAI**

3.9.4. Global Individual Asset Identifier (GIAI): AI (8004)

The Application Identifier (8004) indicates that the GS1 Application Identifier data field contains a GIAI (Global Individual Asset Identifier). This Element String may be used for the unique identification of individual assets to provide a means to store relevant data.

Note: This Element String must never be used to identify the entity as a trade item or logistic unit. If an asset is transferred between parties, the GIAI cannot be used for ordering the asset. However, asset identification may be exchanged between parties for the purpose of traceability

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GIAI – here the owner of the individual asset (see Section 1.5). It makes the number unique worldwide.

The structure and content of the Individual Asset Reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each individual asset. It may contain all characters contained in Figure 7.12 - 1.

Figure 3.9.4 – 1

Format of the Element String	
Application Identifier	Global Individual Asset Identifier (GIAI)
	GS1 Company Prefix Individual Asset Reference
8 0 0 4	$N_1 \dots N_i$ $X_{i+1} \dots$ variable length $X_j (j \leq 30)$

The data transmitted from the bar code reader means that the Element String denoting a GIAI has been captured.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GIAI**

3.9.5. Price per Unit of Measure: AI (8005)

The Application Identifier (8005) indicates that the GS1 Application Identifier data field contains a price per unit of measure. This Element String is used to indicate the price per unit of measure of price marked goods on a Variable Measure Trade Item to discriminate price variants of the same item. It is considered as an attribute of the respective trade item and not as part of its identification.

Content and structure of the Price Per Unit of Measure field are left to the discretion of the trading partners.

Figure 3.9.5 – 1

Format of the Element String	
Application Identifier	Price Per Unit of Measure
8 0 0 5	$N_1 N_2 N_3 N_4 N_5 N_6$

The data transmitted from the bar code reader means that the Element String denoting the price per unit of measure has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates (see Section 3.3.3).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **PRICE PER UNIT**

3.9.6. Identification of the Components of a Trade Item: AI (8006)

The Application Identifier (8006) indicates that the GS1 Application Identifier data fields contain the identification of the trade item and the enumeration of its components.

The GTIN is the item number under which the whole item is traded. For the structures of the GTIN, see Section 4.

The relative number field shows the consecutive number of a particular component within the assembly. A component of a given trade item must always be identical for the respective trade item.

The Total Number of Components in the Assembly field shows the total number of components of the trade item.

Figure 3.9.6 - 1

Format of the Element String			
Application Identifier	Global Trade Item Number (GTIN)	Relative Number of the Component Within the Assembly	Total Number of Components in the Assembly
8 0 0 6	N ₁ N ₂ N ₃ N ₁₁ N ₁₃ N ₁₄	N ₁₅ N ₁₆	N ₁₇ N ₁₈

The data transmitted from the bar code reader means that the Element String denoting the identification of a component of a trade item has been captured. This Element String is normally processed as stand-alone information.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GCTIN**

3.9.7. International Bank Account Number (IBAN): AI (8007)

The Application Identifier (8007) indicates that the GS1 Application Identifier data field contains the international bank account identifier.

The international bank account number (IBAN), AI (8007), defined as ISO 13616, indicates to which account the amount of the respective payment slip is to be transferred. The invoicing party determines the applicable bank account number. The data field is alphanumeric and may contain all characters contained in Figure 7.12 - 1.

Figure 3.9.7 - 1

Format of the Element String	
Application Identifier	International Bank Account Number
8 0 0 7	X ——— variable length ———> X ₃₀

The data string transmitted by the bar code reader means that the Element String denoting an IBAN has been captured. This Element String must be processed together with the payment slip reference number, AI (8020), and the GLN of the invoicing party, AI (415).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **IBAN**

3.9.8. Date and Time of Production: AI (8008)

The Application Identifier (8008) indicates that the GS1 Application Identifier data fields contain a date and time of production (or assembly). The date and time of production is determined by the manufacturer. The date and time may refer to the trade item itself or to the items contained.

The structure is:

- Year: the tens and units of the year (e.g., 2000 = 00), which is mandatory
- Month: the number of the month (e.g., January = 01), which is mandatory
- Day: the number of the day of the relevant month (e.g., second day = 02), which is mandatory

- Hour: the number of the hour based on local time (e.g., 2 p.m. = 14), which is mandatory
 - Minutes: may be dropped if not required
 - Seconds: may be dropped if not required
- ✔ **Note:** This Element String can only specify dates ranging from 49 years in the past to 50 years in the future. Determination of the correct century is explained in Section 7.13.

Figure 3.9.8 - 1

Format of the Data Element						
Application Identifier	Date and Time of Production					
	YY	MM	DD	HH	MM	SS
8008	N ₁ N ₂	N ₃ N ₄	N ₅ N ₆	N ₇ N ₈	N ₉ N ₁₀	N ₁₁ N ₁₂

The data transmitted from the bar code reader means that the Element String denoting a date and time of production has been captured. As this Element String is an attribute of a trade item, it must be processed together with the GTIN of the trade item to which it relates.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **PROD TIME**

3.9.9. Global Service Relation Numbers (GSRN): AIs (8017, 8018)

The Application Identifiers (8017, 8018) indicate that the GS1 Application Identifier data field contains a GSRN (Global Service Relation Number). The GSRN is used to identify either the recipient or individual provider of services in the context of a service relationship. In order to provide identification for both roles in a service relationship, recipient and provider, two GSRN AIs are available. The resultant Element String provides a means for the service provider to store data relevant to services provided to the recipient and by the individual provider.

The GS1 Company Prefix is allocated by GS1 Member Organisations to the company that allocates the GSRN – here the organisation offering the service (see Section 1.5). It makes the number unique worldwide.

The structure and content of the Service Reference is at the discretion of owner of the GS1 Company Prefix to uniquely identify each service relation.

The Check Digit is explained in Section 7.10. Its verification, which must be carried out in the application software, ensures that the number is correctly composed.

The Global Service Relation Number – Provider (see Figure 3.9.9 - 1) identifies the relationship between an organisation offering services and the provider of services.

Figure 3.9.9 - 1

Format of the Element String		
Application Identifier	Global Service Relation Number (GSRN) - PROVIDER	
	GS1 Company Prefix 	Service Reference
8017	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃ N ₁₄ N ₁₅ N ₁₆ N ₁₇	N ₁₈

The data transmitted from the bar code reader means that the Element String denoting the Global Service Relation Number for the Provider has been captured.

When indicating this Element String in the human readable section of a bar code label, the following Data Title should be used (see also Section 3.2): **GSRN – PROVIDER**

The Global Service Relation Number – Recipient (see Figure 3.9.9 - 2) identifies the relationship between an organisation offering services and the recipient of services.

Figure 3.9.9 - 2

Format of the Element String		
Application Identifier	Global Service Relation Number (GSRN) - RECIPIENT	
	GS1 Company Prefix 	Service Reference
8018	N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂ N ₁₃ N ₁₄ N ₁₅ N ₁₆ N ₁₇	N ₁₈

The data transmitted from the bar code reader means that the Element String denoting Global Service Relation Number for the Recipient has been captured.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **GSRN - RECIPIENT**

3.9.10. Service Relation Instance Number (SRIN): AI (8019)

The Application Identifier (8019) indicates that the GS1 Application Identifier data field contains a Service Relation Instance Number (SRIN). The SRIN is used when the identification of a Subject of Care Global Service Relation Number for the Service Recipient (GSRN) needs to be further identified with a sequence indicator corresponding to each encounter during the episode of care. The resultant Element String provides a means for the service provider to store data relevant to specific instances of service provided to the recipient.

The structure and content of the Service Relation Instance Number is at the discretion of the owner of the GS1 Company Prefix to uniquely identify each service relation instance.

Figure 3.9.10 - 1

Format of the Element String	
Application Identifier	Service Relation Instance Number
8019	N ₁ — variable length —> N ₁₀

The data transmitted from the bar code reader means that the Element String denoting a Service Relation Instance Number has been captured.

When indicating this Element String in the human readable section of a bar code label, one of the following Data Title should be used as appropriate (see also Section 3.2): **SRIN**

3.9.11. Payment Slip Reference Number: AI (8020)

The Application Identifier (8020) indicates that the GS1 Application Identifier data field contains a payment slip reference number.

The payment slip reference number, assigned by the invoicing party, identifies a payment slip within a given Global Location Number (GLN) of an invoicing party. Together with the GLN of the invoicing party, the payment slip reference number uniquely identifies a payment slip. The data field is alphanumeric and may contain all characters contained in Figure 7.12 - 1.

Figure 3.9.11 - 1

Format of the Element String	
Application Identifier	Payment Slip Reference Number
8 0 2 0	X ₁ — variable length —> X ₂₅

The data string transmitted from the bar code reader means that the Element String denoting a payment slip reference number has been captured. This Element String must be processed together with the GLN of the invoicing party, AI (415).

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **REF NO.**

3.9.12. GS1-128 Coupon Extended Bar Code: AIs (8100 - 8102)

The Application Identifiers (8100) to (8102) indicate that the GS1 Application Identifier data fields contain data supplementary to a GS1 US coupon identification.

The filler digit 0 is used in AI (8102) to generate an even number of digits in the Element String.

The U.P.C. Prefix is the digit that is preceded by a zero and followed by a Company Number to form the U.P.C. Company Prefix. The Offer Code is assigned by the issuer and identifies a particular promotion.

The expiration date indicates the end of the redemption period of the coupon.

Figure 3.9.12 - 1

Formats of the Element Strings				
Application Identifier	Filler Digit	U.P.C. Prefix	Offer Code	Expiration Date (Month + Year)
8 1 0 0		N ₁	N ₂ N ₃ N ₄ N ₅ N ₆	
8 1 0 1		N ₁	N ₂ N ₃ N ₄ N ₅ N ₆	N ₇ N ₈ N ₉ N ₁₀
8 1 0 2	0	N ₂		

The data string transmitted from the bar code reader means that a GS1-128 Coupon Extended Code has been captured.

3.9.13. Coupon Code Identification for Use in North America (AI 8110)

The coupon bar code is constructed by starting with a coupon Application Identifier of 8110, followed by the required and optional data elements, until all desired data is encoded (or the limit of 70 digits is reached).

Figure 3.9.13 - 1

Format of the Element String	
Application Identifier	Formatted according to rules of GS1 Canada or GS1 US
8 1 1 0	X ₁ ——— variable length ———> X ₇₀

The data string transmitted from the bar code reader means that the Element String denoting a Coupon Code for Use in North America has been captured.

3.9.14. Extended Packaging URL: AI (8200)

The Application Identifier (8200) indicates that the GS1 Application Identifier data fields contain the identification of a brand owner authorized URL to be used in mandatory association with GTIN AI (01) encoded in one symbol.

Figure 3.9.14 - 1

Format of the Element String	
Application Identifier	Brand Owner authorized URL
8 2 0 0	X ₁ ——— variable length ———> X ₇₀

The data transmitted from the bar code reader means that the Element String denoting the Extended Packaging URL for a trade item has been captured. This Element String shall be processed as specified in Section 2.1.8 to obtain one URL address associated with the trade item identified by the GTIN.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **PRODUCT URL**

3.10. GS1 Application Identifiers starting with digit 9

3.10.1. Information Mutually Agreed Between Trading Partners: AI (90)


The Application Identifier (90) indicates that the GS1 Application Identifier data field contains any information mutually agreed between trading partners.

The data field shows the information agreed between the two trading partners. The field is alphanumeric and may contain all characters contained in Figure 7.12 - 1. It may also be used to incorporate data preceded by ASC MH10 Data Identifiers.


Figure 3.10.1 - 1

Format of the Element String	
Application Identifier	Data Field
9 0	X ₁ ————— variable length —————> X ₃₀

The data transmitted from the bar code reader means that the Element String denoting mutually agreed information has been captured. As this Element String may contain any information, processing is subject to prior agreement between trading partners.

 **Important:** The bar code carrying this Element String should be removed from any item that leaves the jurisdiction of the trading partners.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section 3.2): **INTERNAL**

 **Note:** The actual data title may be specified by the issuer of the data.

3.10.2. Company Internal Information: AIs (91 - 99)


The Application Identifier (A1 A2) assigned to company internal information is AI (91 to 99).

The GS1 Application Identifier data field may contain any company internal information. The field is alphanumeric and may show all characters contained in Figure 7.12 - 1.


Figure 3.10.2 - 1

Format of the Element String	
Application Identifier	Data Field
A ₁ A ₂	X ₁ ————— variable length —————> X ₃₀

The data transmitted from the bar code reader means that the Element String denoting company internal information has been captured. Processing of this Element String is to be organised by the using company.

 **Important:** This Element String should be removed from any item that leaves the jurisdiction of the company.

When indicating this Element String in the Non-HRI text section of a bar code label, the following Data Title should be used (see also Section [3.2](#)): **INTERNAL**

 **Note:** The actual data title may be specified by the issuer of the data.

3.11. Compatibility of EPCglobal Tag Data Standard and GS1 General Specifications

The GS1 Application Identifiers, defined in this section of the GS1 General Specifications, may be used in GS1 endorsed GS1 Bar Codes in line with the Application Standards outlined in Section 2. GS1 Application Identifiers may also be used in GS1 endorsed RFID tags as defined in the latest version of the EPC Tag Data Standards that can be found on: <http://www.gs1.org/gsm/kc/epcglobal>



4. Application Rules and Management Practices

- Introduction
- Rules for Keys
- SSCC Rules
- Allocating GS1 System Asset Identifiers
- GLN Rules
- GSRN Rules
- GDTI Rules
- GINC Rules
- GSIN Rules
- GCN Rules
- Data Relationships
- Human Readable Interpretation (HRI) Rules
- Multiple Bar Code Management Practices for Consumer Trade Items (cross-sector)

WHILST EVERY EFFORT HAS BEEN MADE TO ENSURE THAT THE GUIDELINES TO USE THE GS1 STANDARDS CONTAINED IN THE DOCUMENT ARE CORRECT, GS1 AND ANY OTHER PARTY INVOLVED IN THE CREATION OF THE DOCUMENT HEREBY STATE THAT THE DOCUMENT IS PROVIDED WITHOUT WARRANTY, EITHER EXPRESSED OR IMPLIED, REGARDING ANY MATTER, INCLUDING BUT NOT LIMITED TO THE OF ACCURACY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND HEREBY DISCLAIM ANY AND ALL LIABILITY, DIRECT OR INDIRECT, FOR ANY DAMAGES OR LOSS RELATING TO OR RESULTING FROM THE USE OF THE DOCUMENT. THE DOCUMENT MAY BE MODIFIED, SUBJECT TO DEVELOPMENTS IN TECHNOLOGY, CHANGES TO THE STANDARDS, OR NEW LEGAL REQUIREMENTS. SEVERAL PRODUCTS AND COMPANY NAMES MENTIONED HEREIN MAY BE TRADEMARKS AND/OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE COMPANIES. GS1 IS A REGISTERED TRADEMARK OF GS1 AISBL.

4.1. Introduction

The main purpose of Automatic Data Capture (ADC) is to replace manual entry of visually captured information. This implies that an ADC message has to provide all information required for a transaction without human intervention. GS1 System data may be used, for example, to record entities in computer files, to sort goods on conveyor belts, to check completeness of a consignment, to verify dates, and to record physical stock taking.

Element Strings may be applied directly on physical goods or printed in catalogues or documents. The scanning source and the type of transaction determine the required information in a given business application. Since all ADC data is being used in Electronic Data Processing (EDP) applications, strict validation of data to be processed is an absolute prerequisite.

For correct processing of scanned data, certain business applications may require the association of Element Strings representing a particular combination of identification data. The GS1 System enables users to achieve the needed level of data accuracy through the use of adequate Element Strings.

The logical set up of the data standard of the GS1 System enables system users to validate scanned data messages (see Section 7, AIDC Validation Rules).

Validation is affected on two levels. The first is validation of the data for conformity with system rules (e.g., to provide a message that contains all information to be processed logically without human intervention). The second level is validation of the data for conformity with the requirements of a particular business application.

Sections [4.12.1](#) and [4.12.2](#) show the rules for the first verification level (e.g., validate data to conform with the system logic). Section [4.12.1](#) defines the pairs of Element Strings that cannot appear on the same physical entity. Section [4.12.2](#) defines the Element Strings that mandate the appearance of another Element String on the same physical entity. All other combinations of Element Strings are possible at the first level of verification, although they may not make sense at the second, the application level.

4.2. Rules for Keys

The tables in the sub-section below refer to a sequential rule number for the keys rule and are linked to the appropriate wording. The columns are used, where appropriate, to indicate which rules apply to an industry. Section 2 will point to these tables for directions on which rules to apply to an application.

4.2.1. GTIN Rules

Rules	Section / Link	GTIN Rule #
Allocation General Rule	4.3.1.1	1
Allocation and Responsibility for Branded Items	4.3.1.2.1	2
Allocation and Responsibility Exceptions and Non-Branded Items	4.3.1.2.2	3
Management of Uniqueness	4.3.1.3.1	4
Pre-Defined Characteristics	4.3.1.3.2	5
Pre-Priced Merchandise	4.3.1.3.3	6
Promotional Variants	4.3.1.3.4	7
Trade Item Changes	4.3.1.3.5	8
Variants for Groupings	4.3.1.3.6	9
Lead Time in Re-Using a GTIN	4.3.1.4	10

Rules	Section / Link	GTIN Rule #
Data Alignment	4.3.1.5	11
GTIN Allocation Rules	www.gs1.org/gtinrules	12

4.2.2. SSCC Rules

Rules	Section	SSCC Rule #
Allocating Serial Shipping Container Codes	4.4.1	1

4.2.3. Assets Rules

Rules	Section	Asset Rule #
GS1 System Asset Identifiers	4.5.1.1	1
Uniqueness of Asset Identifiers	4.5.1.2	2
Best Practice	4.5.1.3	3
Change of Asset Ownership	4.5.2	4
Allocating Global Returnable Asset Identifiers (GRAIs): AI (8003)	4.5.1.4	5
Serial Number (Optional)	4.5.1.6	6
Allocating Global Individual Asset Identifiers (GIAIs): AI (8004)	4.5.1.7	7

4.2.4. GLN Rules

Rules	Section/Link	GLN Rule #
General Rule	4.6.1.1	1
Company Liquidation, Acquisition, and Mergers: Change of Ownership	4.6.1.2	2
Relocations	4.6.1.3	3
Physical Location, Ownership Remain Unchanged; Associated Data for a Particular GLN Change	4.6.1.4	4
GLN Allocation Rules	www.gs1.org/glnrules	5

4.2.5. GSRN Rules

Rules	Section/Link	GSRN Rule #
General Rule	4.7.1.1	1
Changes in a Service Relationship	4.7.1.2	2

Rules	Section/Link	GSRN Rule #
Recommendation for Allocating Global Service Relation Numbers	4.7.1.3	3
Information Associated with a Global Service Relation Number	4.7.1.4	4

4.3. GTIN Rules

4.3.1. Allocating the Numbers

4.3.1.1. Allocation General Rule

A Global Trade Item Number (GTIN) is used to identify any item (trade item or service) upon which there is a need to retrieve pre-defined information and that may be priced or ordered or invoiced at any point in any supply chain. A separate, unique GTIN is required whenever any of the pre-defined characteristics of an item are different in any way that is relevant to the trading process. As a guiding principle, if the customer is expected to distinguish a new trade item from an old trade item and purchase accordingly, a new GTIN should be assigned to the new trade item. This will ensure the product package and shelf edge label declarations should appear the same to the consumer. However, any law or regulation that contradicts these rules shall supersede these rules.

Specific rules that apply to prevalent industry practices have been endorsed by the Global Commerce Initiative Board, for the Fast Moving Consumer Goods (FMCG) industry. These rules covering many common business cases can be found at www.gs1.org/gtinrules. While all GS1 standards are voluntary, the rules are intended to drive normative practice within the FMCG sector.

Specific rules that apply to packaging and raw material trade items supplied to manufacturing companies can be found at <http://www.gs1.org/gtinrules/index.php/tid=29>.

4.3.1.2. Responsibility

4.3.1.2.1. Allocation and Responsibility for Branded Items

The brand owner, the organisation that owns the specifications of the trade item regardless of where and by whom it is manufactured, is normally responsible for the allocation of the Global Trade Item Number (GTIN). On joining a GS1 Member Organisation, the brand owner receives a GS1 Company Prefix, which is for the sole use of the company to which it is assigned.

The brand owner is the organisation that owns the trade item specifications and may be:

- The manufacturer or supplier: The company that manufactures the trade item or has it manufactured, in any country, and sells it under its own brand name
- The importer or wholesaler: The importer or wholesaler that has the trade item manufactured, in any country and sells it under its own brand name or the importer or wholesaler that changes the trade item (for example by modifying the packaging of the trade item)
- The retailer: The retailer that has the trade item manufactured, in any country, and sells it under its own brand

4.3.1.2.2. Allocation and Responsibility Exceptions and Non-Branded Items

There are some exceptions to the rules regarding responsibility described in

- Non-Branded Items: Items without a brand name and generic items (not private labels) are still assigned Global Trade Item Numbers (GTIN) by their manufacturer. As different

manufacturers and/or suppliers may supply items that appear identical to the buyer (this could be a consumer as well as a retailer or manufacturer), it is possible that items that are apparently the same have different GTINs. Companies that trade in these items need to organise their computer applications (e.g., replenishment programs) to cope with this eventuality. Examples of items that sometimes have no brand are apples, plasterboard, candles, and drinking glasses. Examples for trade items that sometimes have no brand and are not intended for retail include salt, fragrances, and food cans.

- **Customer Specific Items:** If a trade item is made specifically for one trade customer (buyer) and is orderable only by this customer, then the buyer assigns the GTIN. In this case the GTIN should be formed from the customer's GS1 Company Prefix (see Section 1.5). If the supplier (seller) sells a trade item to more than one buyer or intends to sell to more than one buyer, then the seller assigns the GTIN.
- **Other Exceptions:** If the brand owner does not assign a GTIN, the importer or another intermediary can assign an item a temporary GTIN. This would imply that the importer takes on the role of the brand owner and could, for example, register the product in a data catalogue. This temporary GTIN may be used until a GTIN is assigned in the normal way. Alternatively, a retail organisation can assign an internal number to an item that does not yet have a GTIN assigned to it only if the item is used within its own stores.

4.3.1.3. Guidelines for Allocating the Global Trade Item Number (GTIN)

4.3.1.3.1. Management of Uniqueness

Global Trade Item Numbers (GTIN) must be allocated uniquely. GTINs should not contain any intelligence or parsable strings. The embedding of internal codes is discouraged because it is often found that the rules for changing them differ from the rules for changing a GTIN.

For some product types (e.g., Healthcare items) it is common for national regulators to require the submission of a product filing from a party based within the jurisdiction of the regulator. Such arrangements have no direct impact on GTIN Allocation but need to be covered by the normal contractual arrangements (e.g., licensed distributor, subsidiary, reseller).

4.3.1.3.2. Pre-Defined Characteristics

Although this list is not exhaustive, the basic pre-defined characteristics of a trade item are:

- The product name, product brand, and product description
- The trade item type and variety
- The net quantity of trade item (weight, volume, or other dimension impacting trade)
- If the trade item is a grouping, the number of elementary items contained, and their subdivision in sub-packaging units, the nature of the grouping (e.g., carton, pallet, box-pallet, flat-pallet)


A modification to any of the basic elements that characterise a trade item will usually lead to a change in the Global Trade Item Number (GTIN).

- ✔ **Note:** Price is not a relevant criterion for changing a GTIN except when the price is printed directly on the trade item.
- ✔ **Note:** National, federal or local regulations may take precedence over this rule. For example, in some industries, such as healthcare, regulations or other requirements may dictate that any trade item changes require a new GTIN.

Note: For complex products, such as some Medical Devices, key consideration for GTIN Allocation is the commercialisation of the product (e.g., different for pricing or ordering or invoicing). If the product is ‘different’ a ‘different GTIN’ is required. The figure below is a scenario to represent the difficulties in determining when a GTIN change is necessary for complex medical devices, depending upon how the device is viewed (i.e., from a commercial and/or Form, Fit, Function perspective). Nominally the commercial aspects of an item determine a GTIN change, the objective is to recognise that other important factors reside which may not necessarily signify a commercialization shift, but would impact the GTIN assignment – particularly in the Healthcare industry. It is the brand owner’s responsibility to manage appropriately the configuration of any complex device and its appropriate GTIN(s) assignment. The example shows major hardware components managed by GTIN and Serial Number combinations, recognising that within this complex medical device there are other potential parameters where configuration change must be managed; GTIN change may be dictated based on the manufacturers change management process

It is the Brand Owner that decides upon the identification requirement.

Figure 4.3.1.3.2 - 1 Example of the complexity of a Medical Device product with regard to GTIN Allocation



* GUI: Graphical User Interface

Typically the gross dimensions of a trade item communicated via the item file that do not affect net trade item quantity or measure do not impact the GTIN assignment. However, as a general rule if any gross dimension (e.g., length, depth, weight) changes by more than 20 percent, a new GTIN is required. Changes below 20 percent may require a new GTIN at the discretion of the brand owner.

In all cases, a change to a GTIN for the trade item at a lower level of packaging will always lead to a change of any GTIN used for associated packaging at higher grouping levels.

4.3.1.3.3. Pre-Priced Merchandise

Pre-pricing is discouraged as a trade practice as it introduces complexity for trade item file maintenance throughout the supply chain. If, however, the price that the consumer will pay is marked on the item, the Global Trade Item Number (GTIN) should be changed when the priced marked on the item changes.

Note: National, federal or local regulations may take precedence over this guideline.

4.3.1.3.4. Promotional Variants

A promotion is a temporary change to a trade item, which modifies the presentation of the trade item. It usually coexists with the standard trade item.

- Promotional variants of trade items that affect the net weight or volume of the trade item must be allocated a separate, unique Global Trade Item Number (GTIN). Examples include an attached free additional item or 10 percent extra free.
- Promotional variants of trade items may impact the logistic weight or dimension of the trade item by more than 20 percent. In this case, the promotional variants must be allocated a separate, unique GTIN.
- Promotional variants of trade items where a price reduction is explicitly specified on the pack (flash packs) must be allocated a separate, unique GTIN unless local trade practices or price marking legislation dictate otherwise. An example would be a 10 cents off offer.
- Each seasonal promotion of a trade item should be allocated a separate, unique GTIN. An example would be chocolate that is over-wrapped for Easter.
- Other promotional variants should not be allocated a separate, unique GTIN. Examples include money off coupon, free gift inside (unless this causes an increase in gross weight by more than 20 percent), "send for" offer, competition offer, or samples sent directly to consumer bypassing the retail Point-of-Sale.

4.3.1.3.5. Trade Item Changes

Trade item changes are any change or improvement during the life of a trade item. The "new" trade item replaces the old one. Should the brand owner decide to create a variant (e.g., with different ingredients) in parallel with the standard trade item, then a separate, unique Global Trade Item Number (GTIN) has to be allocated.

- Minor trade item changes or improvements do not require the allocation of a different GTIN. Examples include label artwork redesign, minor trade item description changes that do not impact the supply chain, gross dimension change in any axis of less than 20 percent with content quantity or measure unchanged. This rule applies to retail consumer trade items (retail POS unit) and standard trade item groupings (orderable cases or pallets).

If a trade item's quantity or measure changes or if the consumer will be expected to distinguish between an old and new brand name or product description, then a new GTIN must be allocated.

4.3.1.3.6. Variants for Groupings

- Trade items that are a standard and stable grouping of smaller units identified by a Global Trade Item Number (GTIN) must be allocated a separate GTIN whenever there is a change to the GTIN of any of the units contained.
- For trade items containing units that are themselves promotional variants or minor trade item variants of trade items whose GTINs remain unchanged, the rule is the following:
 - If the trade item has to be distinguished for effective ordering, handling, and tracking, a separate GTIN must be allocated to the trade item. Examples include promotions that are limited to certain geographical areas or date specific promotions.
 - If the identification of minor trade item variants is only relevant to the manufacturer, they should distinguish these variants by using the Element String product variant (AI 20). Examples include minor package design changes and side loading as opposed to top loading cases.

4.3.1.4. Lead Time in Re-Using a GTIN

A GTIN allocated to a trade item that has become obsolete must not be re-used for another trade item until at least 48 months have elapsed after:

- the expiration date of the last original trade items produced with that number
- or-
- the last original trade items produced with that number have been supplied to the customer.

In the case of clothing the minimum retention period is reduced to 30 months.

Brand Owners should consider a longer period depending upon the type of goods and/or any regulatory framework. For example, steel beams may be stored for many years before entering the supply chain, and processes should be put in place to ensure that the GTIN is not reallocated for a significant period of time. Another example is found with very specific products within the healthcare sector, such as prescription drugs, implants, etc., where steps should be taken by the assigning company to ensure that the issued GTINs are not reallocated for a period well beyond the lifetime of the product or beyond the end of treatment.

In addition, when contemplating the re-use of a GTIN, consideration should be given to the use of data associated with the original GTIN by trading partners for statistical analysis or service records, which may continue long after the original trade item was last supplied.

If a GTIN has been assigned to an item, which was then never actually produced, the GTIN may be deleted from any catalogue immediately without first being marked as discontinued. In this exceptional case the GTIN may be re-used 12 months after deletion from the seller's catalogue.

4.3.1.5. Data Alignment

When a new Global Trade Item Number (GTIN) is assigned to a trade item, it is essential that the brand owner provide the detailed information to trading partners about the item's characteristics. This information should be provided at as soon as possible before the trade item is actually traded.

Expediting GTIN information to buyers reduces order exception handling and reduces the lead-time in getting goods to the selling floor.

4.3.1.5.1. Data Alignment Best Practice

A number of actions are vital to ensure that Global Trade Item Numbers (GTINs) are accurately communicated within the supply chain. These ensure that the data associated with any scanned bar code can be associated with accurate, up-to-date data. This is particularly essential for items scanned at the Point-of-Sale where the absence of accurate data may have legal implications.

The GTIN provides a supply chain solution for the identification of any item that is traded (priced, invoiced, or ordered). Overall supply chain costs are minimised by all partners in the supply chain adhering to identical allocation rules (see Section [4.3.1.6](#)).

The following best practices are proposed for all items. It has been developed by manufacturers, distributors, and retailers to help eliminate any confusion between product identification and product listing in the retailer's database in the supply chain.

GTIN allocation and the bar coding of the GTIN are technical processes with rules detailed in these *GS1 General Specifications*. Product listing is the act of adopting a new product in an assortment by a commercial organisation. Product listing is the result of commercial negotiations between purchaser and seller. For example, GTIN allocation should be independent from product listing.

For management reasons, or to ensure that correct information is communicated to the final consumer, changes to an item may require a new GTIN. A new GTIN does not automatically imply a new listing. For example, if a change requiring a new GTIN is made to a listed product, this should not automatically imply a new product listing is needed.

GTIN allocation and database listing are to be considered as two entirely autonomous decisions: GTIN allocation is not an object of negotiation.

The brand owner makes available to its client all information regarding the listed items, ideally with an EDI message or in an e-product catalogue, no later than at the time of item listing. In case of time limited promotions or a product evolution, this information will be communicated largely beforehand, thus allowing the retailer to validate this information and to circulate it internally.

4.3.1.5.1.1. Primary Refrigeration State

It is recommended that GTIN allocation consider the primary refrigeration state of the product. When a product is regularly marketed in both chilled and frozen states, then two GTINs should be allocated for the product, one for each refrigeration state. However, if a product is only primarily marketed in one refrigeration state or the other, then only one GTIN for the product is necessary. For seasonal products which could be sold as chilled or frozen, such as spiral-cut hams and whole turkeys, the possibility of product being in delivered in either refrigeration state even though there is only one GTIN for the product needs to be noted when the retailer authorizes the product.

The key to efficient movement through the supply chain is good communications between retailer and packer. If packers only have frozen product available for a retailer that normally buys only chilled, the packer needs to communicate with the retailer to ensure that this is acceptable. This communication is critical in cases where over-production has required product with a “chilled” GTIN to be frozen before releasing it into the supply chain. To summarize:

1. Assign the GTIN based on the primary state in which the product is marketed (e.g., Chilled or Frozen).
2. If product is normally marketed in both a Chilled and Frozen state, assign two GTINs to the product, one for each state.
3. Suppliers should communicate carefully with retailers regarding the refrigeration state of seasonal or feature products than can be marketed in a Chilled, Tempered, or Frozen state.

4.3.1.6. GTIN Allocation Definitions

The following terms may be useful when reviewing the GTIN Allocation Rules that are published on <http://www.gs1.org/gtinrules>:

- **Trade Item** – Any item (product or service) upon which there is a need to retrieve pre-defined information and that may be priced, ordered, or invoiced at any point in any supply chain.
- **Retail Consumer Trade Item** – The trade item intended to be sold to the end consumer at retail Point-of-Sale. They are identified with a unique GTIN-13, GTIN-12, or GTIN-8. (See the Section 2.).
- **Standard Trade Item Grouping** – A grouping of retail consumer trade items that is not intended for Point-of-Sale scanning. It is identified with a unique GTIN -14, GTIN -13, or GTIN -12.
- **Non-GTIN Pack** – A packaging level for trade items where there is no trading partner requirement for Global Trade Item Number (GTIN) identification. If a GTIN is required, then this item becomes a retail consumer trade item or standard trade item grouping.
- **Logistic Unit** – An item of any composition established for transport and/or storage that needs to be managed through the supply chain. It is identified with an SSCC (Serial Shipping Container Code).
- **Dynamic Assortment** – A standard trade item grouping that comprises a fixed count of a changing assortment of two or more different retail consumer trade items, each identified with a unique GTIN. All of the retail consumer trade items and their GTINs will have been communicated to the retailer before trading takes place. The retailer has accepted that the supplier may change the assortment without any prior notice. An example is a trade item grouping of ten toy cars that may contain any mix of possibly more than ten different toy cars that have been individually identified and notified to the retailer.

- **Pre-Defined Assortment** – A standard trade item grouping that comprises a fixed configuration of two or more different retail consumer items, each identified with a GTIN. Any change in the configuration of the assortment is considered a new trade item.
- ✔ **Note:** These rules are intended for global use. Exceptions may occur only when local regulatory or legal requirements mandate otherwise.

4.3.1.7. GTIN Allocation Rules for Upstream Suppliers

Specific rules that apply to packaging and raw material trade items supplied to manufacturing companies can be found on <http://www.gs1.org/gtinrules/index.php/tid=29>.

Upstream suppliers are those companies that typically supply or manufacture trade items that are supplied to other companies for further processing. Examples of these trade items include raw ingredient and packaging materials.

A Global Trade Item Number (GTIN) must be assigned to each pre-defined trade item and any unit of measure used in the price, order, or invoice process.

- ✔ **Note:** These rules are intended for global use. Exceptions may occur only when local regulatory or legal requirements mandate otherwise.

4.3.1.8. GTIN Allocation Considerations for Home Apparel and Home Fashion

The GSMP General Merchandise Work Team validated the existing Global Trade Item (GTIN) allocation rules and concluded that they are applicable to the apparel and home fashions product category. The content of this section extends the content in Section [4.3.1.8.1](#) to cover scenarios specific to apparel and home fashions and may be different in other sectors. This section is the result of the review of the Trade Item Identification and Communication Guidelines (VICS EDI) TIIC, May 2001, by the GSMP Work Team.

4.3.1.8.1. Pre-pack/Multi-pack/Set-pack

For a pre-pack or standard assortment of trade items, each different item within the pre-pack will be assigned a GTIN maintaining the one-to-one relationship between trade item/colour ID/size ID and GTIN. Each GTIN must be marked so as to enable scanning at the Point-of-Sale. A separate, unique GTIN is assigned to each orderable pre-pack. This GTIN is not intended to be scanned at the retail Point-of-Sale. Different pre-packs of trade items are assigned different GTINs when either the component item or quantity contents of the pre-packs are different.

A multi-pack is a group of trade items (the same or different) that are intended to be sold as a single consumer unit at the Point-of-Sale (e.g., a three-pack of men's white T-shirts or a 12-piece set of glassware). A multi-pack is not intended to be broken apart and sold as individual trade items. A multi-pack is assigned a GTIN that is different from the GTIN that may be assigned to the individual trade items. Generally components of a multi-pack are not marked with individual GTINs. Each different multi-pack of the same trade items (e.g., three-pack socks versus six-pack socks) must have a different GTIN assigned. Each different multi-pack GTIN must also have its own trade item/colour ID/size ID.

For a set-pack, each different trade item within the set-pack will be assigned a GTIN, maintaining the one-to-one relationship between trade item/colour ID/size ID and the GTIN. The individual trade item GTIN must be marked to enable retail Point-of-Sale scanning and may or may not be orderable separately outside the set-pack(s). A separate, unique GTIN is assigned to each set-pack. Different set-packs are assigned different GTINs when either the trade item or quantity contents are different.

The figure below provides a summary of the requirements.

Figure 4.3.1.8.1 – 1

	PACK			INDIVIDUAL ITEMS OF THE PACK		
	Orderable	Sell to	GTIN	Orderable	Sellable	GTIN
			by Retailer Marked Retailer Marked			by Consumer to Consumer
Pre-pack	Yes	No	Yes	Maybe	Yes	Yes
Multi-pack	Yes	Yes	Yes	No	No	No
Set-pack	Yes	Yes	Yes	Maybe	Yes	Yes

- ✔ **Note:** GTINs on individual trade items in a multi-pack are optional
- ✔ **Note:** GTINs in a set-pack are required because the individual pieces are available for sale to the consumer
- ✔ **Note:** Individual components of pre-packs and set-packs may be ordered separately based on individual partnership agreement

4.3.1.8.2. Gift with Purchase/Purchase with Purchase/Collateral Item

A gift with purchase is a trade item given to a consumer as part of a promotional event, contingent on the consumer making a purchase of another item or items. A gift with purchase is considered inventory and has no retail value.

A purchase with purchase is a trade item sold to a consumer at a special price as part of a promotional event, contingent on the consumer purchasing another item or items. A purchase with purchase is considered inventory and has a retail value. When assigning and tracking Global Trade Item Numbers (GTINs) for gift with purchase and purchase with purchase trade items, GTINs should be assigned to all gift with purchase and purchase with purchase items and be marked with a GTIN to enable Point-of-Sale scanning.

A collateral item is a trade item delivered from a manufacturer to the retail selling floor that is not considered inventory and has no retail value (e.g., a display case that needs to be identified but has no retail value). GTINs should be assigned to all collateral items.

4.3.1.9. GTIN Allocation Rules for Healthcare

Specific rules that apply to healthcare trade items can be found in the Healthcare GTIN Allocation Rules publication found at <http://www.gs1.org/1/gtinrules/index.php/p=static/t=healthcare>.

4.4. SSCC Rules

4.4.1. Allocating Serial Shipping Container Codes

4.4.1.1. General Rule

An individual Serial Shipping Container Code (SSCC) is a unique number, which remains the same for the life of the logistic unit to which it is assigned. When assigning an SSCC, the rule is that an individual SSCC number must not be reallocated within one year of the shipment date from the SSCC assignor to a trading partner. However, prevailing regulatory or industry organization specific requirements may extend this period.

4.4.1.2. Responsibility

The Serial Shipping Container Code (SSCC) provides functionality to support the management (tracking, tracing, storage, etc.) of logistic units through the supply chain. To ensure global uniqueness and traceability, the company creating the logistic unit or the brand owner of the logistic unit is responsible for the allocation of the SSCC.

4.5. Allocating GS1 System Asset Identifiers

4.5.1. General Rule

4.5.1.1. GS1 System Asset Identifiers

GS1 System asset identifiers can be used to identify any fixed assets of a company. It is left to the discretion of the issuer to determine whether the Global Returnable Asset Identifier (GRAI), AI (8003), or Global Individual Asset Identifier (GIAI), AI (8004), is more suitable for the application concerned.

4.5.1.2. Uniqueness of Asset Identifiers

Asset identifiers must not be used for any other purpose and must remain unique for a period well beyond the lifetime of the relevant records. If a company assigns asset identifiers to trade items supplied to its customers, the company must ensure that the asset identifiers are never re-used.

4.5.1.3. Best Practice

Best practices may dictate that the trade item manufacturer apply the asset identifier during the manufacturing process (see Section 2.3).

4.5.1.4. Allocating Global Returnable Asset Identifiers (GRAIs): AI (8003)

The structure of the Element String for a Global Returnable Asset Identifier (GRAI) can include two parts: the mandatory Identification of an Asset Type and an optional serial number, to distinguish individual assets within the same asset type (see Section 2).

Figure 4.5.1.4 – 1

Format of the Element String			
Application Identifier	Global Returnable Asset Identifier (GRAI)		
	GS1 Company Prefix →	Asset Type ←	Check Digit Serial Number (Optional)
8 0 0 3	0 N ₁ N ₂ N ₃ N ₄ N ₅ N ₆ N ₇ N ₈ N ₉ N ₁₀ N ₁₁ N ₁₂		N ₁₃ X ₁ variable X ₁₆

The exact method used to allocate the GRAI is left to the discretion of the issuing organisation. However, a unique number, the Asset Type, must be assigned for each type of asset being identified, and for ease of administration, the GS1 System recommends that numbers be allocated sequentially and not contain classifying elements.

When it is not possible to assign an Asset Type (e.g., for museum exhibits), or when the type of asset is not required by the application (e.g., when the item is only used for a single type of asset), then the Global Individual Asset Identifier (GIAI), AI (8004), should be used.

To encode the following Examples of Identification Numbers in a GS1-128 Bar code a zero in the leftmost position must be added to generate the defined length for the 14-digit asset identification number field.

4.5.1.5. Identical Assets Identification

A single Global Returnable Asset Identifier (GRAI) should be assigned to a series of identical assets.

Figure 4.5.1.5 – 1

Asset Type	GRAI
50 litre aluminium beer keg	1234567890005
10 litre aluminium beer keg	1234567890012
10 litre wooden beer keg	1234567890029

4.5.1.6. Serial Number (Optional)

The owner of the asset assigns the optional serial number. It denotes an individual asset within a given Asset Type. The field is alphanumeric and is used to distinguish individual assets with the same Asset Types.

Figure 4.5.1.6 – 1

Asset Type	GRAI (incl. the Serial Number)
50 litre aluminium beer keg	12345678900051234AX01
50 litre aluminium beer keg	12345678900051234AX02
50 litre aluminium beer keg	12345678900051234AX03

4.5.1.7. Allocating Global Individual Asset Identifiers (GIAs): AI (8004)

The Global Individual Asset Identifier (GIAI) is structured according to Figure 4.6.1.7 - 1.

Figure 4.5.1.7 - 1

Format of the Element String	
Application Identifier	Global Individual Asset Identifier (GIAI)
8 0 0 4	<div style="display: flex; justify-content: space-between;"> <div style="text-align: center;"> <p>GS1 Company Prefix</p> <p>—————→</p> <p>$N_1 \dots N_i$</p> </div> <div style="text-align: center;"> <p>Individual Asset Reference</p> <p>—————→</p> <p>$X_{i+1} \dots$ variable length $X_j (j \leq 30)$</p> </div> </div>

The exact method used to allocate the GIAI is left to the discretion of the issuing organisation. However, each GIAI must be unique for each individual asset being identified and, for ease of administration, the GS1 System recommends that GIAs be allocated sequentially and not contain classifying elements.

4.5.2. Change of Asset Ownership

Asset identification numbers are used in a diverse range of business applications ranging from tracking the movements of re-usable packaging trays to recording the life-cycle history of aircraft parts.

If a company sells an asset to another company then the asset identifier should ideally be replaced by another Global Individual Asset Identifier (GIAI) or Global Returnable Asset Identifier (GRAI) or be removed. It is permissible for the asset identifier to remain on the item when the ownership changes if the new owner takes responsibility for the GS1 Company Prefix associated with the asset identifier.

For further information regarding changes of ownership, please refer to Section 1.5.

4.5.3. Information Associated with Asset Identifiers

The attributes of the asset should be established on a computer file using the GS1 System asset identifier as the key to the information. Examples of the type of information held include the full name and address of the party who owns the asset, the value of the asset, the location of the asset, and the life-cycle history of the asset.

4.6. GLN Rules

4.6.1. Allocating Global Location Numbers

4.6.1.1. General Rule

Global Location Numbers (GLNs) can be used to identify any physical location or party that has meaning within a business scenario. The general rule is that a separate GLN is required to identify each different location (e.g., each store of a retail group is required to have a separate GLN to enable efficient delivery to the individual store).


The exact method used to allocate the GLN is at the discretion of the issuing organisation. In line with best practice, GS1 recommends that the GLN be assigned at source, usually by the party owning the location. When a new GLN is issued, it is recommended that:

- The GLN be associated with the master data for the identified location
- This master data be communicated to trading partners in a timely manner
- GLNs be allocated sequentially without classifying elements

Once assigned at the source, usually by the party owning the location, the GLN becomes a global reference that can be used by all. See Section [4.6.1.6](#), for guidance on trading with organisations that do not use GLNs.

The GLN allocated to an entity should be communicated from the owner of the location through the supply chain in advance of a transaction/delivery so that all systems can be prepared for interaction. GLNs are reference keys for retrieving the indicated information from databases.

From time to time, the details (associated data) related to a GLN might change. The following subsections are general cases or examples on the allocation of GLNs due to a change in the circumstances or business conditions in which the number was originally established. See Section [4.6.3](#) or GLN allocation rules and scenarios regarding when GLNs should remain the same or should be changed. These rules are based on business practices.

 **Note:** National, federal or local regulations may take precedence over this guideline. Examples include regulations affecting a company's registration, taxation, or fiscal obligations, as well as its industry requirements.

4.6.1.2. Company Liquidation, Acquisition, and Mergers: Change of Ownership

If a company sells a location to another party who may or may not be using Global Location Numbers (GLNs), the GLN for the address that is associated with the previous owner should be closed. If the new owner of the address wishes to identify the location with a GLN, a new number should be

assigned using the new owner's GS1 Company Prefix. In this scenario, the new owner should assign a new GLN within one year of purchase.

- If a company sells a location to another party, the GLN that was assigned should not be reassigned per the provisions of Section [4.6.1.7](#).
- If the purchase of the whole company by another has included assignment of the GS1 Company Prefix with the consent of the Member Organisation, then the existing GLNs already allocated can continue to be used.
- If a company is split as a result of the purchase, the new owner must assign new GLNs.

In addition, if two activities within a company merge and have separate GLNs before the merger, then transition to one of the existing GLNs should be made by updating records and retiring one of the GLNs.

4.6.1.3. Relocations

Relocations within the same building (e.g., a department moves from the second to the seventh floor of a building), or other changes in address that have little or no impact on such things as deliveries and payments, do not require assignment of a new GLN. The changed information may be updated and communicated to trading partners. However, whenever the point of access changes, a new GLN should be assigned.

When a given operation is closed in one location and replaced by a similar operation at a new location, a new GLN should be assigned.

4.6.1.4. Physical Location, Ownership Remain Unchanged; Associated Data for a Particular GLN Change

If an attribute associated with a Global Location Number (GLN) changes (e.g., a cross-docking station changes within a warehouse or a small enterprise starts electronic invoicing), the details associated with the GLN should be communicated to trading partners by the party responsible for the location. The GLN itself remains the same.

4.6.1.5. Grouping of Global Location Numbers

While GS1 user companies, for their internal purposes, may group Global Location Numbers (GLNs) into some logical grouping, there are currently no supply chain standards to do so. GLNs are assigned at the discretion of GS1 user companies to support their business applications. The principle of Non-Significance (see Section 1.) is critical to supply chain use, and it therefore follows that any additions or deletions from the group do not impact individual GLN assignment.

4.6.1.6. Trading Partners without Global Location Numbers

Trading partners without a Global Location Number who are responsible for a given location must request a GLN from their local GS1 Member Organisation. Assigning the GLN at source by the responsible trading partner ensures supply chain efficiency. A GLN shall not be sold, leased, or loaned to a separate party.

4.6.1.7. Reassignment of Global Location Numbers

A Global Location Number (GLN) that has been previously used or has become obsolete must not be reused for another location until at least 48 months have elapsed. A longer period may be needed in accordance with government requirements, such as invoicing and taxation, or requirements related to the nature of the location (e.g., a bonded warehouse). This period must allow time for all references of the old GLN to be removed from trading partners' files.

4.6.2. Information Associated with a Global Location Number

Master data for a location should be established on a computer file and the Global Location Number (GLN) may then be used to facilitate efficient communication of this information. There are a number of solution providers who provide services for the efficient communication of master data information associated with a GLN on a global or regional level.

An example of the type of information held includes the full name and address of the party, bank details and account number, sales department that deals with the party, and profile of a company.

Information associated with each GLN is held internally by trading partners or on central databases. If the location changes and the details are not changed, communications or deliveries will go to the address held on file. It is, therefore, essential for organisations to keep trading partners informed of any change of information associated with a GLN. See Section 4.6.3 for GLN allocation rules and scenarios where changes to a location or attributes relating to a GLN may require a new GLN.

Within the GS1 System, the GLN and the Global Trade Item Number (GTIN) are two distinct data identifiers. There is no conflict when a GTIN and a GLN have the same digits, as the data carrier (electronic data interchange, machine readable symbol, or radio frequency) will distinguish between the two identifiers. For example, when GLNs are used in Automatic Identification and Data Capture (AIDC) and EDI, the context (Application Identifiers and qualifiers) will prevent any misinterpretation.

4.6.3. GLN Allocation Rules

The GLN Allocation Rules (<http://www.gs1.org/glnrules>) was developed by the Global Location Number (GLN) Allocation Rules Work Group established under Global Standards Management Process (GSMP). The starting point for each of the scenarios listed is a correctly assigned GLN according to the general rules described in Section 4.6.1.

GLNs are assigned to physical and legal locations to provide a key to access master data in a business process (e.g., order, invoice, deliver). For each of these assigned GLNs, master data will be assigned to the GLN to support the business process. The scenarios <http://www.gs1.org/glnrules> illustrate a change in the business process or attribute data associated with a given GLN and indicate whether a new GLN should be assigned to signify the change or whether alternative business processes (e.g., change to the PARTIN (Party Information) message in business messaging or updating information in a Party Data Catalogue) can be used to communicate the GLN change.

GLNs are intended to support business processes and are used to identify entities and organisations. Individual businesses need to determine whether to use the same GLN for more than one business process (e.g., a small business may use a single GLN for order, delivery, and invoice, because each of these processes are undertaken in a single location, while a multinational organisation could choose to assign a distinct GLN to each location within its organisation).

The GLN Allocation Rules can be found at <http://www.gs1.org/glnrules>.



Note: These rules are intended for global use. Exceptions may occur only when local regulatory or legal requirements mandate otherwise.

4.7. GSRN Rules

4.7.1. Allocating Global Service Relation Numbers

4.7.1.1. General Rule

Global Service Relation Numbers (GSRNs) can be used to identify the service provider and/or service recipient in any service relationship. A separate, unique number can be issued, normally by the organization offering the service to identify the service provider and/or the service recipient, to identify

any given service relationship. Once assigned, the GSRN becomes a unique and universal reference that can be used by all parties involved in the service relationship.

A GSRN with either AI 8017 or AI 8018 are mutually exclusive, that is, a GSRN can only be assigned to a single role, recipient or provider, but not both.

4.7.1.2. Changes in a Service Relationship

From time to time the details related to a Global Service Relation Numbers (GSRN) may change. The following are general cases that may occur if the circumstances under which the GSRNs were originally set up change:

- If an organisation providing a service ceases trading (possibly because of liquidation), any GSRNs allocated by that organisation should be phased out. If the activity covered by the GSRN is transferred, the new organisation providing the service may continue to use existing GSRNs if it has taken over the GS1 Company Prefix of the original organisation providing the service; if not, the GSRN should be phased out and a new GSRN allocated using the new organisation's GS1 Company Prefix.
- If the range of services identified by a GSRN change, the organisation that provides the service should change the details associated with the GSRN on the related computer file record. The assignment of a new GSRN is not required in this case.
- A GSRN used to identify a particular service relationship that has terminated should not be reallocated for a period well beyond the lifetime of the relevant records.

4.7.1.3. Recommendation for Allocating Global Service Relation Numbers

The exact method used to allocate the Global Service Relation Number (GSRN) is left to the discretion of the issuing organisation. However, the GSRN must be unique for each individual service provider and for each individual service recipient and each must remain unique for a period well beyond the lifetime of the records relevant to the service relationship.

For ease of administration, GS1 recommends that GSRNs be allocated sequentially and not contain classifying elements.

4.7.1.4. Information Associated with a Global Service Relation Number

Global Service Relation Number (GSRN) may be used as standalone Element Strings, where all information required is established on a computer file using the individual GSRN as the key to access the information. The type of information stored is determined by the nature of the service relationship. Typical information includes the service recipient's or provider's full name, address, and details of the services received or rendered.

If the identification of a Global Service Relation Number for the Service Recipient (GSRN) needs to be further identified with a sequence indicator corresponding to specific encounters during a service relationship, a Service Relation Instance Number (SRIN), AI (8019) may be associated to the GSRN. As an example, in a healthcare setting this could be used to allow for differentiation of "Subject of Care" identification capture from an identification band, both before and after its replacement (i.e. due to a radiology examination, etc.).

4.8. GDTI Rules

4.8.1. Application Rules

4.8.1.1. Definition of a Document Requiring Internal Control

The term *document* is applied broadly to cover any paper(s) or digital file(s). The Global Document Type Identifier (GDTI) can be used to identify any type of document including but not limited to:

- commercial documents (e.g. invoice, purchase order)
- documents that infer a right (e.g., proof of ownership)
- documents that infer an obligation (e.g., notification or call for military service)
- identification documents (e.g. driver's license, passport)
- images

The issuer of the document is normally responsible for the identification of the document which may be physical or virtual: such as a database record. Such documents typically require storage of the appropriate information contained on the document.

Examples of documents that can be identified with the GDTI include, but are not limited to:

- Land registration papers
- Tax demands
- Proof of shipment/receipt forms
- Customs clearance forms
- Insurance policies
- Internal invoices
- National press documents
- Educational papers
- Transporting company documents
- Mail companies documents

4.8.1.2. Bar Code Symbology

The GS1-128 Bar Code is used for Documents that require control. The bar code in no way replaces the need for Human Readable information.

4.8.1.3. Bar Code Information

4.8.1.3.1. Symbol Requirements

To facilitate efficient scanning, all bar codes shall be printed at an X-dimension between 0.25 millimetre (0.00984 inch) and 0.495 millimetre (0.0195 inch) and be a minimum of 13 millimetres (0.5 inch) in height.

The information required for the internal control of documents should be carried by GS1-128 Bar Codes.

4.8.1.3.2. Global Document Type Identifier (GDTI)

The Application Identifier to indicate the Global Document Type Identifier is AI (253).

The Global Document Type Identifier (GDTI) is assigned by the document issuer. The GDTI is used as a key to access database information that is required for document control purposes (normally held by issuing organisation). The same Document Type is used for all document classes that are issued with an identical purpose. This can then be used to reference the characteristics of the document, such as:

- The issuer of the document
- The exact right or obligation the document imposes
- The document type (e.g., insurance policy, governmental paper)

A different Document Type shall be used whenever characteristics of the document are different.

By their nature, each document needs to be individually tailored for the intended recipient and, therefore, requires a unique reference number in addition to the Document Type. Any duplicates of a document should use the same number as the original. The serial component is optional and assigned by the document issuer and is unique in a series of documents issued under the same Document Type. Ideally the serial component should be sequentially allocated for each new document generated.

The serial component is used to communicate exact details pertinent to the individual document such as:

- The name and address of the recipient
- The cross-reference to individual details

4.9. GINC Rules

4.9.1. Allocating Global Identification Numbers for Consignment

4.9.1.1. General Rule

An individual Global Identification Number for Consignment is a unique number, which remains the same for the life of a grouping of logistics or transport units to which it is assigned. When assigning a GINC, the rule is that an individual GINC number must not be reallocated within one year of the shipment date from the freight forwarder assigning the GINC to a transport. However, prevailing regulatory or industry organisation specific requirements may extend this period.

4.10. GSIN Rules

4.10.1. Allocating Global Shipment Identification Numbers

4.10.1.1. General Rule

An individual Global Shipment Identification Number (GSIN) is a unique number, which remains the same for the life of the grouping of logistics or transport units to which it is assigned. When assigning a GSIN, the rule is that an individual GSIN number must not be reallocated within ten years of the shipment date from the seller or third party logistics provider (sender) of the GSIN to a trading partner buyer (recipient) to comply with the regulations of the World Customs Organisation (WCO). For goods that circulate within one country (domestic transport), the period of re-use is based on either governmental, industry or the discretion of the seller (sender) of the goods.

4.11. GCN Rules

4.11.1. Allocating Global Coupon Numbers

The exact method used to allocate the Global Coupon Number (GCN) is left to the discretion of the issuing organisation. However, the GCN must remain unique for a period well beyond the lifetime of the records relevant to the coupon.

For ease of administration, GS1 recommends that GCNs be allocated sequentially and not contain classifying elements

4.12. Data Relationships

The Element Strings that require specialised software and/or scanner set up are not covered by these rules. These are the Element Strings with GS1 Prefixes 0001 to 0007, 02, 04, 05, 20 to 29, 98, and 99; GTIN-8 Prefixes 0 and 2; two-digit and five-digit Add-On Symbols; and AIs (8100) to (8102).

In Figures 4.12.1 - 1 and 4.12.2 - 1, the Application Identifiers (AIs) are used to indicate the Element String. The AI (01) is used to indicate a Global Trade Item Number (GTIN); however, the Element Strings that encode GTINs are defined in Section 3. GTINs may be encoded in bar codes from the EAN/UPC Symbology family, ITF-14 Bar Codes, GS1 DataBar Symbology family, GS1 DataMatrix and GS1-128 Bar Codes using AI (01) or AI (8006) and GS1 QR Bar Codes using AI (01).

- Note:** If duplicate element strings (e.g., two serial numbers, two batch/lot numbers, two Extended Packaging URLs) must appear on the same physical entity they must always have the same value in each occurrence on that entity.
- Note:** It is possible to have multiple different National Healthcare Reimbursement Numbers (NHRNs), from different country or regional NHRN authorities, associated with the same GTIN on a given item. It is possible and permissible to change one of these NHRNs without a change to the other NHRNs or to the GTIN.
- Note:** It is not allowed to have multiple of the same NHRN AI with different data associated with the same GTIN on a given item.

4.12.1. Invalid Pairs of Element Strings

This section defines the pairs of Element Strings that cannot appear on the same physical entity.

Figure 4.12.1 – 1

Pair of Element Strings				Comment
AI	Designation	AI	Designation	
01	Identification of a trade item	01	Identification of a trade item	Duplicate Global Trade Item Numbers (GTINs) with different values
01	Identification of a trade item	02	Identification of logistic unit contents	AI (02) must not be used for the identification of trade items contained in a trade item.
01	Identification of a trade item	37	Count of units contained	The count of units contained would duplicate the master data of the GTIN. AI (37) may only be used with AI (02).
22*	Secondary data for the health industry	30	Count	Duplicate counts with different values

Pair of Element Strings				Comment
AI	Designation	AI	Designation	
22*	Secondary data for the health industry	10	Batch/lot number	Duplicate lot numbers with different values
22*	Secondary data for the health industry	17	Expiration date	Duplicate expiration date with different values
22*	Secondary data for the health industry	21	Serial number	Duplicate serial numbers with different values
242	Made-to-Order Variation	01 or 02 with N ₁ not equal to 9	Identification of a Variable Measure Trade Item	Made-to-Order Variation can only be used with a GTIN-14, Indicator digit 9. This represents a Custom Industrial Supply Item
243	Packaging Component Number	01	Mandatory association with GTIN	243
420	Ship to postal code, single postal authority	421	Ship to postal code with ISO country code	Only one ship to postal code may be applied on an item
422	Country of origin of a trade item	426	Country of full processing	Duplication of country of origin of a trade item (covered by country of full processing)
423	Country of initial processing	426	Country of full processing	Duplication of country of initial processing (covered by country of full processing)
424	Country of processing	426	Country of full processing	Duplication of country of processing (covered by country of full processing)
425	Country of disassembly	426	Country of full processing	Duplication of country of disassembly (covered by country of full processing)
390n	Amount payable – single monetary area	391n	Amount payable – with ISO currency code	Only one amount payable Element String may be applied on a payment slip
392n	Amount Payable for a Variable Measure Trade Item – Single Monetary Area	393n	Amount Payable for a Variable Measure Trade Item and ISO Currency Code	Only one amount payable Element String may be applied on a Variable Measure Trade Item.
710, 711, 712 (nnn)	National Healthcare Reimbursement Number	Any AI (01) allowable attributes	Any GTIN allowable attributes	When NHRN(s) are applied to the physical trade item with the mandatory association to the GTIN, any attribute AIs must only be processed with the GTIN and must not be processed with the NHRNs (AIs 710, 711, 712,.....) alone.
8006	Component identification	01	Identification of a trade item	Other GTINs cannot be used with AI (8006). The trade item is identified by a GTIN contained in the AI (8006).
8018	Global Service Relation Number for the Recipient	8017	Global Service Relation Number for the Provider	Only one Global Service Relation Number (recipient or provider) can be applied at one time for identification of an individual in a given service relationship

* GS1 has established 01 January 2013 as a sunset date for AI (22)

4.12.2. Mandatory Association of Element Strings

This section defines the Element Strings that mandate the appearance of another Element String on the same physical entity.

Figure 4.12.2 – 1

If Element String		Then Mandatory Associated Element String	Comment
AI	Designation		
01 with N ₁ = 0	Identification of a Variable Measure Trade Item Scanned at POS	30, 3nnn* or 3nnn**	Mandatory association with a variable count or a trade measure information scanned at POS identified with GTIN-12 or GTIN-13. Only GS1 DataBar Expanded Bar Codes can encode associated elements strings for use at POS. (See Note at bottom)
01 or 02 with N ₁ = 9	Identification of a Variable Measure Trade Item Not Scanned at POS	30, 3nnn* or 3nnn** or 8001	Mandatory association with variable measure information not scanned at POS identified with a GTIN-14 starting with Indicator digit 9 (See Note at bottom) Only GS1-128, ITF-14, and GS1 DataBar Expanded Bar Codes can encode a GTIN with N ₁ = 9.
02	Identification of logistic unit contents	00	Mandatory association with an SSCC (Serial Shipping Container Code)
02	Identification of logistic unit contents	37	Mandatory count of the contained trade items
10	Batch/lot number	01 or 02	Mandatory association with a Global Trade Item Number (GTIN) or with the identification of logistic unit contents
11, 13, 15, 17	Dates	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
12	Due date	8020 and 415	Mandatory association with the payment slip reference number and the Global Location Number (GLN) of the invoicing party
20	Product variant	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
21	Serial number	01	Mandatory association with a GTIN of a single trade item (a serial number cannot apply to a grouping of trade items). SGTIN is a common term for the mandatory association of AI (21) with GTIN AI (01)
22****	Secondary data health industry	01	Mandatory association with a GTIN.
240	Additional product identification	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
241	Customer part number	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
242	Made-to-Order Variation Number	01 or 02 with N ₁ = 9	Mandatory association with a GTIN-14 with Indicator Digit 9 represents a Custom Industrial Supply Item
243	Packaging Component Number	01	Mandatory association with GTIN

If Element String		Then Mandatory Associated Element String	Comment
250	Secondary serial number	01 and 21	Mandatory association with a GTIN (a secondary serial number cannot apply to a grouping of trade items) and the serial number of the trade item AI(21)
251	Reference to source entity	01	Mandatory association with GTIN of the trade item
254	Extension component of a GLN	414	Mandatory association with AI (414). Only GS1-128, GS1 DataBar Expanded symbologies, and EPC RFID tags are valid. This is used with GLN and not GTIN.
30	Variable count	01 or 02	Mandatory association with a GTIN for a variable measure trade item (e.g., GTIN-12 or GTIN-13 for trade items scanned at POS, GTIN-14s starting with Indicator digit 9 for trade items not scanned at POS) or the identification of variable measure content of a logistic unit
3nnn*	Trade measures that cannot be summed	01	Mandatory association with a GTIN for a variable measure trade item (e.g., GTIN-12 or GTIN-13 for trade items scanned at POS, GTIN-14s starting with Indicator digit 9 for trade items not scanned at POS)
3nnn**	Trade measures that can be summed	01 or 02	Mandatory association with a GTIN for a variable measure trade item (e.g., GTIN-12 or GTIN-13 for trade items scanned at POS, GTIN-14s starting with Indicator digit 9 for trade items not scanned at POS) or the identification of variable measure content of a logistic unit
3nnn***	Logistic measures	00 or 01	Mandatory association with an SSCC or a variable measure GTIN for trade item not scanned at POS (e.g., a GTIN-14 starting with the digit 9)
337n	Kilograms per square metre	01	Mandatory association with a GTIN
37	Count of units contained	02	Mandatory association with the identification of logistic unit contents
390n	Amount payable – single monetary area	8020 and 415	Mandatory association with the payment slip reference number and the GLN of the invoicing party
391n	Amount payable – with ISO currency code	8020 and 415	Mandatory association with the payment slip reference number and the GLN of the invoicing party
392n	Amount payable – when scanned at POS - single monetary unit	01	Mandatory association with a variable count or a trade measure scanned at POS when identified with a GTIN-12 or GTIN-13,
392n	Amount payable when not scanned at POS – single monetary unit	01	Mandatory association with a a variable measure information when identified GTIN-14,
393n	Amount payable – when scanned at POS –with ISO currency code	01	Mandatory association with a variable count or a variable measure when scanned at POS and identified with GTIN-12 or GTIN-13,

If Element String		Then Mandatory Associated Element String	Comment
393n	Amount payable when not scanned at POS – with ISO currency code	01	Mandatory association with a variable measure information when identified with a GTIN-14,
403	Routing code	00	Mandatory association with an SSCC
415	GLN of the invoicing party	8020	Mandatory association with payment slip reference number
422	Country of origin	01 or 02	Mandatory association with a GTIN
423	Country of initial processing	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
424	Country of processing	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
425	Country of disassembly	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
426	Country of full processing	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
427	Country Subdivision of Origin Code for a Trade Item	01 or 02 and 422	Mandatory association with a GTIN and the Country of Origin of the trade item
7001	NATO stock number	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
7002	UN/ECE meat carcasses and cuts classification	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
7003	Expiration Date and Time	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
7004	Active Potency	01 and 10	Mandatory association with the GTIN and Batch/Lot Number
703(s)	Approval number of processor	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
710	National Healthcare Reimbursement Number	01	Mandatory association with the GTIN of the trade item
711	National Healthcare Reimbursement Number	01	Mandatory association with the GTIN of the trade item
712	National Healthcare Reimbursement Number	01	Mandatory association with the GTIN of the trade item
8001	Variables of roll products	01	Mandatory association with a variable measure GTIN (e.g., an GTIN-14 starting with the digit 9)

If Element String		Then Mandatory Associated Element String	Comment
8005	Price per unit of measure	01 or 02 with N ₁ = 9	Mandatory association with a variable measure GTIN or the identification of variable measure content of a logistic unit
8007	International Bank Account Number	8020 and 415	Mandatory association with the payment slip reference number and the GLN of the invoicing party
8008	Date and time of production	01 or 02	Mandatory association with a GTIN or with the identification of logistic unit contents
8019	Service Relation Instance Number	8018	Mandatory association with a Global Service Relation Number (GSRN), AI 8018
8020	Payment slip reference number	415	Mandatory association with the GLN of the invoicing party
8200	Extended Packaging URL	01	Mandatory association with GTIN

- * Is (3nnn) where the first three digits are 312, 313, 324, 325, 326, 327, 328, and 329
- ** Is (3nnn) where the first three digits are 310, 311, 314, 315, 316, 320, 321, 322, 323, 350, 351, 352, 356, 357, 360, 361, 364, 365, and 366
- *** Is (3nnn) where the first three digits are 330, 331, 332, 333, 334, 335, 336, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 353, 354, 355, 362, 363, 367, 368, and 369
- **** GS1 has established 01 January 2013 as a sunset date for AI (22)

Note: Exception for Point-of-Sale. See Section 5.5.2.6, Table 1 Note regarding GTIN-14 at POS.


4.13. Human Readable Interpretation (HRI) Rules

Human Readable Interpretation rules are provided to standardize requirements for brand owners and users to facilitate common training for operators who encounter GS1 AIDC data carriers that fail to scan or read. There are two categories of rules:

- General Rules that apply independent of sector, product category, or region
- Sector Specific Rules which must be aligned with the General Rules

For the purposes of interpreting this standard, there are two types of text that appear on a label, package, or item; Human-Readable Interpretation (HRI) and Non-HRI Text.

- Human Readable Interpretation (HRI) is the information below or beside a barcode or tag which is encoded in the bar code or tag and represents the same characters as carried in the bar code or tag (See Section 8 Glossary for full definition).
- Non-HRI Text is all other text on package, label or item (See Section 8 Glossary for full definition).





- ✓ **Note:** The following rules are intended for global use. Exceptions may occur only when local regulatory or legal requirements mandate otherwise
- ✓ **Note:** At present, HRI rules are applicable to bar codes as rules for EPCglobal RFID tags are under development.

Human Readable Interpretation Rules

1. Whether a GS1 AIDC Data Carrier encodes a GS1 Identification Key, GS1 Key Attributes, or a combination of both, the HRI should be placed below the bar code and grouped together wherever physically possible while maintaining the HRI legibility and minimum bar code height (as specified in the appropriate Symbol Specification Table referenced by the GS1 AIDC Application Standard).
 - a. In cases where the HRI must be printed above, to the left, or to the right of the symbol due to packaging or space constraints, HRI shall always be printed adjacent to (obviously associated with) the GS1 AIDC data carrier while protecting quiet zones.
 - b. If the HRI for GS1 Identification Keys and GS1 Key Attributes is split (for example GS1 Key HRI is below the bar code and GS1 Key attributes HRI is above the bar code), the preference for GS1 Key HRI placement is always below the bar code.
 - c. When HRI is grouped together (for example, all HRI data is grouped below the bar code or all HRI data is grouped above the bar code), HRI shall always follow the encoding sequencing of the GS1 AIDC data carrier.
2. A single data element shall not be broken into two lines of HRI, for example the data for a serial number would appear on one line of HRI.
3. Parentheses shall surround AIs in HRI but are not encoded in the GS1 AIDC data carrier.
4. A clearly legible font shall be used (e.g., OCR-B as defined in ISO 1073-2) and the character set as defined in Section 7.12. Reasonable alternative type fonts and character sizes are acceptable provided the interpretation is clearly legible.
5. HRI shall be limited to element strings and will not include GS1 AIDC data carrier overhead such as FNC1 characters.
6. If the required bar code and associated HRI is marked directly on the part, then both satisfy the requirements for Healthcare Primary Package marking (see Section 2.1.2.3) if the bar code can be scanned and the HRI is legible through a panel in the primary packaging.
7. HRI shall appear except in rare circumstances for specific applications where there are extreme space constraints (e.g., direct part marking). If the GS1 AIDC data carrier cannot be read or scanned and the HRI does not appear on the label, package, or item, non-HRI text should be used as backup information.
8. If the bar code is printed in ladder orientation on the product, the HRI should remain clearly associated with the bar code and may appear below, to the left, or to the right of the symbol respecting quiet zones. See Figure 4.13 - 1 below.

Figure 4.13 1



 **Note:** There may be local variants for non-HRI text on the label (e.g., dates, prices) which are formatted based on local practice rather than the way the data is encoded in GS1 AIDC data carriers. In this case, the HRI associated with AIDC shall still be expressed as it is encoded in the GS1 AIDC data carrier encodation (per Application Identifier definition).

9. When AI (8200) appears on the label, the expression of the URL shall not appear in HRI. If it appears in Non-HRI text, the Non-HRI text shall be the full product URL consisting of the contents of AI(8200), followed by a slash (/) character, followed by the GTIN expressed as 14 numeric digits. For example, if the GTIN is 01234567890128 and the contents of AI (8200) is <http://example.com>, then the non-HRI text shall read <http://example.com/01234567890128>.

4.13.1. Healthcare Human Readable Interpretation Rules

The GS1 System requires printing of both the GS1 AIDC data carrier and the HRI that represents all the information encoded within that GS1 AIDC data carrier. However, printing of both the GS1 AIDC data carrier and the associated HRI may not be possible due to many factors such as the type of item being labelled or marked, intended use of the item, available space for marking, etc.


If the GS1 AIDC data carrier cannot be read or scanned, usually the HRI should be used as backup information. If the HRI is not printed then the Non-HRI Text could be used as a backup.

Whenever it is not possible to print both the GS1 AIDC data carrier and the HRI, Figure 4.12.1 – 1 should be used to determine the most appropriate course of action to be taken in deciding how HRI will be implemented. When it is not possible to print all of the HRI, preference for printing shall be given to the GS1 Key.

When considering the practical implementation and application of Human Readable Interpretation (HRI) text during the creation of the GS1 bar code, many factors must be taken into account to determine if and how HRI text is included with the symbol. These factors may include the type of product being labelled or marked, product use, available space for marking, alternate data availability, etc.

In deciding how HRI text will be implemented, Figure 4.12.1 – 1 should be used to determine the proper course of action.

Figure 4.13.1 – 1 Healthcare Human Readable Interpretation (HRI) Decision Tree



Active Potency (AI 7004) HRI Rule

Printing of the Active Potency on the item is controlled by regulation. Human readable interpretation of the Active Potency is not required on the trade item.

4.13.2. Manual Date Marking

Where regulations and/or trade partner agreements require applied date markings for stock rotation and manual identification, the ISO standard (8601) for date sequence should be used. The format should be YYYY-MM-DD preceded by the date type short form (See Figure 4.13.2-1 below for respective date types) based on ISO standard abbreviations (15223).

Figure 4.13.2-1

Date type	Short form
Production	PROD
Packaging	PACK
Best Before	BEST
Expiration	EXP

AIDC techniques are suggested over any manual process to ensure accurate and timely stock rotation. Every effort should be made to adopt an automated process to increase productivity and date management.

4.14. Multiple Bar Code Management Practices for Consumer Trade Items (cross-sector)

EAN/UPC symbols have been used for POS/POC and will continue to be used for existing applications however new symbologies have been introduced to support new application requirements. Until all parties can process GTIN using the new technologies, existing technology must be supported while new technology migration occurs. This standard provides a set of management practices intended to permit the use of existing and new technologies on one package. The management practices are designed to ensure brand owners will not carry two different inventories based on technologies.

In addition to supporting POS/POC and general distribution scanning applications, consumer trade item packages may now support additional business processes using bar codes. For example, support for B2C extended packaging and trade item production control. For this reason, a management practices has been introduced to separate, where possible, symbols for different functions and in the case of production control bar codes, another management practice is introduced to obstruct their supply chain scanning or make them obscure where possible.

The transition to use of additional data beyond GTIN in bar codes is a non-trivial step for the retail and healthcare industry. It means operators must learn to handle the new technologies and systems must be adapted to process them. The management practices were designed after considering the different types of scanner systems, testing over 170 symbols combinations, and the ways each interact with each other and the operator.

In Section 4.14.1, practices 1, 6, and 7 apply now and in the future. Section 4.14.2, practice 1 and Section 4.14.3, practice 1 and 2, once implemented, will eliminate the need for Section 4.14.1 practices 2-5 as they are present to support a migration period.

4.14.1. Multiple Bar Code Management Practices for Consumer Trade Items (All Sectors)

- 1. Current Standards:** All scanning systems shall deploy symbology identifiers (see Section 5.1.2) and when using GS1 Application Identifiers, process them according to GS1 Rules (see Section 7.9).

2. **GTIN Plus Attribute(s) Flag:** Where applications require additional data be captured in a multiple bar code symbol environment, modifications to systems should be made to automate this requirement to optimize efficiency.
3. **Adjacent Placement:** Wherever two symbols can be used for the same application (POS, POC) they should be placed adjacent to one another. Adjacent placement of symbols shall never infringe on symbol quiet zones. The orientation (stack or row of symbols) or sequence (which symbol is placed on the left, right, top, or bottom) and shall be determined by the brand owner. Where adjacent placement on one panel is not permitted based on space limitations, placement on adjacent panels should be attempted. This practice does not supersede any Section 6 Symbol Placement Rule (e.g., 8mm (0.3") free space between symbols and panel edge.)
4. **Non-Adjacent Placement:** Wherever two symbols are used for different applications (POS, B2C Extended Packaging (EP) Direct Mode), they should be placed non-adjacent to one another.
5. **Obscure Placement:** Wherever a symbol is used for product control purposes only, it should be made as obscure as possible or even obstructed on the consumer trade item package.
6. **Product URL Bar Code Indication:** For bar codes encoding AI (01) (8200) see Rule 12, Section 4.12.)
7. **GS1-128 Use as Secondary Symbol when EAN/UPC or ITF-14 is required**

In general distribution, where EAN/UPC and/or ITF-14 is used to encode GTIN and where GS1-128 is used to encode GTIN attributes, the GTIN should also be encoded in the GS1-128 encoding GTIN attributes but GTIN is not required based on previous standards based implementations.

Note: Where GS1 DataBar and GS1 DataMatrix are used, GTIN and GTIN attributes shall be concatenated to ensure accurate data association.

4.14.2. GS1 Multiple Bar Code Management Practice for General Retail

- **GTIN in GS1 DataBar Processing:** In order to facilitate migration away from a multiple bar code environment where one retailer requires EAN/UPC and another GS1 DataBar Expanded, at a minimum, all general retailers shall be able to process the AI (01) GTIN from GS1 DataBar Expanded.

4.14.3. GS1 Multiple Bar Code Management Practices for Healthcare

1. **GTIN in GS1 DataMatrix and GS1 DataBar Processing (retail healthcare):** In order to facilitate migration away from a multiple bar code environment where one retail pharmacy requires EAN/UPC and another retail pharmacy requires GS1 DataMatrix or GS1 DataBar Expanded, at a minimum, retail pharmacies shall have the capability to process the AI (01) GTIN from GS1 DataMatrix and GS1 DataBar in addition to the capability for EAN/UPC.
2. **GTIN in GS1 DataMatrix, GS1 DataBar, and GS1-128 Processing (non-retail healthcare):** In order to facilitate migration away from a multiple bar code environment where one healthcare provider requires EAN/UPC or ITF-14 and another healthcare provider requires GS1 DataMatrix, GS1 DataBar Expanded, or GS1-128, at a minimum, non-retail pharmacies shall have the capability to process AI (01) GTIN from GS1 DataMatrix, GS1 DataBar, and GS1-128 in addition to the capability for EAN/UPC and ITF-14.
3. **GS1-128 as Secondary Symbol:** In Point-of-Care applications, where EAN/UPC or ITF-14 is used to encode GTIN and where GS1-128 is used to encode GTIN attributes, GS1-128 should encode GTIN as it is best practice to encode the GTIN attributes and the GTIN in a single symbol whenever possible to ensure accurate data association.

4. **Scenario-based Management Practices:** Multiple bar code practices which apply to all sectors are found in Section 4.14.1 and take precedence over those specific only to healthcare. While industry best practice focuses on using only one bar code per package, a product package that serves multiple markets may have the need for application of multiple bar codes. When this occurrence is unavoidable, the management practices for use of multiple symbols found in Figure 4.14.3 - 1 apply for regulated healthcare trade items. 4.14.3 – 1. The Figure separates solutions based on combinations of scanner environments encountered for each scenario:
- Scanners Encountered Combination #1: Package scanned in Retail Pharmacies (Yes or No)
 - Scanners Encountered Combination #2: Package scanned in general distribution (Yes or No)

Figure 4.14.2 – 1 Multiple Bar Code Management Practices


Combinations of Scanners Encountered	Bar Code Data Scenario		Scanner Environment		Symbol Arrangement	Bar Code Options	Gen Spec	Proposal
	Symbol 1	Symbol 2	Retail Pharmacy or Non-Retail Pharmacy/ Bedside	Automated Conveyor	Vertical or Horizontal		Section	
#1	GTIN A	Only Attributes for GTIN A	Y	N	NA	GS1 DataMatrix GS1-128 GS1 DataBar * EAN/UPC plus GS1 DataMatrix, GS1 DataBar Expanded, GS1-128, or * EAN/UPC, GS1 DataBar, or GS1-128 plus ** Composite Component	2.1.2.3 2.1.2.4 4.14.1	See Note 1 below See Note 10 below For * see Note, 2 below For ** see Note 3 below
#2	GTIN A	Only Attributes for GTIN A	Y	Y	Horizontal	GS1 DataMatrix GS1-128 *EAN/UPC plus GS1 DataMatrix or GS1-128	2.1.2.6 4.14.1	See Note 1 below See Note 10 below For * see Note 2 below
#1	GTIN A	GTIN A + GTIN A Attributes	Y	N	Depends upon packaging limitations	GS1 DataMatrix GS1-128 GS1 DataBar * EAN/UPC plus GS1 DataMatrix, GS1 DataBar Expanded, GS1-128, or GS1 DataBar, or GS1-128 plus ** Composite Component or * EAN/UPC with ** Composite Component	2.1.2.3 2.1.2.4 4.14.1	See Note 1 below See Note 4 below See Note 10 below For * see Note 6 below For ** see Note 3 below
#2	GTIN A	GTIN A + GTIN A Attributes	Y	Y	Depends upon packaging limitations	GS1 DataMatrix GS1-128 *EAN/UPC plus GS1 DataMatrix or GS1-128	2.1.2.6 4.14.1	See Note 1 below See Note 2 below See Note 4 below For * see Note 6 below See Note 10 below




Combinations of Scanners Encountered	Bar Code Data Scenario		Scanner Environment		Symbol Arrangement	Bar Code Options		Gen Spec	Proposal
	Symbol 1	Symbol 2	Retail Pharmacy or Non-Retail Pharmacy/ Bedside	Automated Conveyor	Vertical or Horizontal			Section	
#1	GTIN A + Attribute Set 1	GTIN A + Attribute Set 1	Y	N	Duplicate symbols on bulky packages	GS1 DataMatrix GS1-128 GS1 DataBar Expanded EAN/UPC plus Composite Component	Duplicate of first symbol	2.1.2.3 2.1.2.4	See Note 1 below See Note 5 below See Note 7 below See Note 10 below
#2	GTIN A + Attribute Set 1	GTIN A + Attribute Set 1	Y	Y	Duplicate symbols on bulky packages	GS1 DataMatrix GS1-128 EAN/UPC plus Composite Component	Duplicate of first symbol	2.1.2.6	See Note 1 below See Note 5 below See Note 7 below See Note 10 below
#1	GTIN A + Attribute Set 1	GTIN A + Attribute Set 2	Y	N	Depends upon packaging limitations	GS1 DataMatrix GS1-128 GS1 DataBar Expanded EAN/UPC plus Composite Component	GS1 DataMatrix GS1-128 GS1 DataBar Expanded EAN/UPC plus Composite Component	2.1.2.3 2.1.2.4	See Note 1 below See Note 5 below See Note 8 below See Note 10 below
#2	GTIN A + Attribute Set 1	GTIN A + Attribute Set 2	Y	Y	Horizontal	GS1 DataMatrix GS1-128	GS1 DataMatrix GS1-128	2.1.2.6	See Note 1 below See Note 5 below See Note 8 below See Note 10 below
#1	GTIN with Serial Number	GIAI or GRAI	Not Permitted in Regulated Healthcare on Small Surgical Instruments where only one mark can be made based on the available marking surface and SGTIN is source-marked by brand owner on that surface See Note 10 below						
#1 or #2	GTIN A	GTIN B	Not Permitted						

Combinations of Scanners Encountered	Bar Code Data Scenario		Scanner Environment		Symbol Arrangement	Bar Code Options		Gen Spec	Proposal
	Symbol 1	Symbol 2	Retail Pharmacy or Non-Retail Pharmacy/ Bedside	Automated Conveyor	Vertical or Horizontal			Section	
#2	GTIN A	SSCC	Permitted on trade items which also serve as logistics units. Symbol placement per Section 6. (All clauses contained in sections 6.2,6.4, 6.6, 6.7 and 6.8) See Note 10 below						
#1	SSCC	AI (02) + AI (37)	Y	N	Vertical	GS1-128	GS1-128	2.2.1	See Note 9 below
#2	SSCC	AI (02) + AI (37)	Y	Y	Vertical	GS1-128	GS1-128	2.2.1	See Note 9 below
#1 and #2	GS1 Data carried by 1 or 2 symbols	Non-GS1 Data	Symbols encoding internal or proprietary data SHALL not be placed in a location where they could be scanned in the open supply chain (e.g. retail POS, by an automated conveyor line scanner per GS1 specifications) See Section 4.14.1 – Obscure Placement and Note 10 below						

- Note 1:** Concatenation of GTIN and GTIN attributes into one symbol is the preferred option for Regulated Healthcare Retail Consumer Trade Items to validate connectivity between GTIN and attributes. Separating GTIN attributes from the GTIN in the bar code should be avoided wherever possible as improper association is possible. The scenario takes into account the use of EAN/UPC which is widely used in retail pharmacies to capture GTIN but once a market is prepared to support a data carrier which can encode GTIN plus the GTIN attributes, this data carrier should replace EAN/UPC when GTIN attributes are required.
- Note 2:** Symbols which are not preferred for Regulated Healthcare Retail Consumer Trade Items because they do not allow for concatenation but remain permissible options.
- Note 3:** GS1 Composite Component does not stand alone as a complete symbol; it is necessary to associate the composite component with a linear symbol such as EAN/UPC, ITF-14, GS1-128 or GS1 DataBar. GS1 Composite Component therefore remains a legitimate option however but only in non-retail applications, GS1 DataMatrix is preferred for Regulated Healthcare Retail Consumer Trade Items based on its ability to encode all information in one symbol and do so efficiently in terms of print speed and panel size.
- Note 4:** It is recommended to use only one symbol that encodes the GTIN and attributes
- Note 5:** When two symbols are required to encode a large number of GTIN attributes, both symbols should be the same symbology and both encode GTIN.
- Note 6:** Symbols which are not preferred for Regulated Healthcare Retail Consumer Trade Items because they do not allow for concatenation but remain permissible options.
- Note 7:** Recommended for bulky or large trade items or pallets
- Note 8:** Wherever possible use of one symbol to encode GTIN plus all attributes is preferred to encoding attributes in two symbols

-  **Note 9:** AI (02) + AI (37) not recommended in regulated healthcare supply chain

-  **Note 10:** Since June 2007 GS1 has recommended all trading partners in the healthcare sector invest exclusively in imaging-based scanners. Now that GS1 DataMatrix has been approved within the standard, it is important to inform all trading partners of a process within GS1 to establish target deployment dates. Without these dates, brand owners do not have a way know when to deploy GS1 DataMatrix on their packaging and those needing to invest in scanning equipment may inadvertently purchase equipment that will not support the standards. To see GS1 Healthcare's Position Paper on GS1 DataMatrix adoption, visit GS1.org/GS1Healthcare.



5.

Data Carriers

- Introduction
- Linear Bar Codes - EAN/UPC Symbology Specifications
- Linear Bar Codes - ITF-14 Symbology Specifications
- Linear Bar Codes - GS1-128 Symbology Specifications
- Bar Code Production and Quality Assessment
- Linear Bar Codes – GS1 DataBar
- Two Dimensional Bar Codes – GS1 DataMatrix Symbology
- Composite Bar Codes
- Two Dimensional Bar Codes – GS1 QR Code Symbology
- Appendix: Rules for Encoding/Decoding Element Strings in GS1 Symbologies using GS1 Application Identifiers

WHILST EVERY EFFORT HAS BEEN MADE TO ENSURE THAT THE GUIDELINES TO USE THE GS1 STANDARDS CONTAINED IN THE DOCUMENT ARE CORRECT, GS1 AND ANY OTHER PARTY INVOLVED IN THE CREATION OF THE DOCUMENT HEREBY STATE THAT THE DOCUMENT IS PROVIDED WITHOUT WARRANTY, EITHER EXPRESSED OR IMPLIED, REGARDING ANY MATTER, INCLUDING BUT NOT LIMITED TO THE OF ACCURACY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND HEREBY DISCLAIM ANY AND ALL LIABILITY, DIRECT OR INDIRECT, FOR ANY DAMAGES OR LOSS RELATING TO OR RESULTING FROM THE USE OF THE DOCUMENT. THE DOCUMENT MAY BE MODIFIED, SUBJECT TO DEVELOPMENTS IN TECHNOLOGY, CHANGES TO THE STANDARDS, OR NEW LEGAL REQUIREMENTS. SEVERAL PRODUCTS AND COMPANY NAMES MENTIONED HEREIN MAY BE TRADEMARKS AND/OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE COMPANIES. GS1 IS A REGISTERED TRADEMARK OF GS1 AISBL.

5.1. Introduction

A data carrier is a means of representing data in machine readable form. Data carriers that are endorsed by GS1 are described in Sections [5.1](#), [5.2](#), [5.3](#), [5.4](#), [5.6](#), [5.7](#) and [5.7.3.7](#) and bar code production and quality assessment are covered in Section [5.5](#).

The GS1 System specifies the data carrier used to represent any given Element String. Section 2 covers rules indicating which data carrier should be used to represent which Element Strings in particular applications.

The GS1 System uses the following data carriers:


- The EAN/UPC Symbology family of bar codes (UPC-A, UPC-E, EAN-13, and EAN-8 Bar Codes and the two- and five-digit Add-On Symbols) can be read omnidirectionally. These symbols must be used for all items that are scanned at the Point-of-Sale and may be used on other trade items.

Figure 5.1 - 1 UPC-A and EAN-13 Bar Codes



- ITF-14 (Interleaved 2-of-5) Bar Codes carry ID numbers only on trade items that are not expected to pass through the Point-of-Sale. ITF-14 Symbols are better suited for direct printing onto corrugated fibreboard.

Figure 5.1 - 2 ITF-14 Bar Code



- The GS1-128 Bar Code is a subset of the Code 128 Bar Code Symbology. Its use is exclusively licensed to GS1. This extremely flexible symbology encodes Element Strings using Application Identifiers.

Figure 5.1 - 3 GS1-128 Bar Code



- GS1 DataBar is a family of linear symbologies used within the GS1 System. This family of linear symbologies in most cases implicitly encodes Application Identifier (01) and in the case of GS1 DataBar Expanded explicitly encodes Element Strings using Application Identifiers.

Figure 5.1 - 4 GS1 DataBar Omnidirectional Bar Code




(01)20012345678909

- Composite Component Symbols do not exist in isolation. The primary identification number is always encoded in the linear symbol and supplementary Application Identifier Element Strings are encoded in the two-dimensional (2D) component where they take up less space.

Figure 5.1 - 5 GS1 DataBar Stacked Omnidirectional Bar Code with a Composite Component

(17)050101(10)ABC123



(01)04012345678901

- Data Matrix ISO version ECC 200 is the only version that supports GS1 System data structures, including Function 1 Symbol Character. Implementation of GS1 DataMatrix shall be done per approved GS1 System application standards, such as those for Regulated Healthcare Retail Consumer Trade Items.

Figure 5.1 - 6 GS1 DataMatrix Bar Code

(21) ABCDEFG123456789



(01) 04012345678901

- GS1 QR Code, is a subset of ISO/IEC 18004 QR Code 2005. QR Code 2005 supports GS1 System data structures, including Function 1 Symbol Character. Implementation of GS1 QR Code shall be done per approved GS1 System application standards. QR Code is approved to obtain Extended Packaging information.

Figure 5.1 - 7 GS1 QR Code Bar Code



5.1.1. International Standards

A number of national and regional standardisation bodies have developed bar code technical standards. The International Organisation for Standardisation (ISO) has published standard bar code symbology specifications via a subcommittee of ISO/IEC JTC1 (International Organisation for Standardisation/International Electrotechnical Commission Joint Technical Committee 1).

GS1 is actively involved in developing these standards. The objective is for GS1 System standards to remain fully compatible with relevant published national, regional, and international symbology standards. The pertinent documents for Section 5 include the latest published version of:

- **Section 5.1:** ISO/IEC 15424: Information technology; automatic identification and data capture techniques; data carrier/symbology identifiers
- **Section 5.2:** ISO/IEC 15420: Information technology; automatic identification and data capture techniques; bar code symbology specifications; EAN/UPC
- **Section 5.3:** ISO/IEC 16390: Information technology; automatic identification and data capture techniques; bar code symbology specifications; ITF-14
- **Section 5.4:** ISO/IEC 15417: Information technology; automatic identification and data capture techniques; bar code symbology specifications; GS1-128 Symbology specifications
- **Section 5.5:** Bar Code Production and Quality Assessment
 - ISO/IEC 15415: Information technology; automatic identification and data capture techniques; bar code print quality test specification; two-dimensional symbols
 - ISO/IEC 15416: Information technology; automatic identification and data capture techniques; bar code print quality test specification; linear symbols
 - ISO/IEC 15419: Information technology; automatic identification and data capture techniques; bar code digital imaging and printing performance testing
 - ISO/IEC 15421: Information technology; automatic identification and data capture techniques; bar code master test specifications
 - ISO/IEC 15426-1: Information technology; automatic identification and data capture techniques; bar code verifier conformance specification - Part 1: Linear symbols
 - **ISO 1073-2** Alphanumeric character sets for optical recognition – Part 2: Character set OCR-B Shapes and dimensions of the printed image
 - **AIM DPM-1-2006** Direct Part Mark (DPM) Quality Guideline (contact AIM, Inc., 125 Warrendale-Bayne Rd. Suite 100, Warrendale, PA 15086 Tel: +1 724-934-4470, Fax: +1 724-934-4495, Web: www.aimglobal.org)
- **Section 5.6:** ISO/IEC 24724: Information technology; automatic identification and data capture techniques; Reduced Space Symbology (RSS) bar code symbology specification (formerly RSS; now GS1 DataBar)
- **Section 5.7:** ISO/IEC 16022: Information technology; automatic identification and data capture techniques; Data Matrix bar code symbology specification
- **Section 5.8:** ISO/IEC 24723: Information technology; automatic identification and data capture techniques; EAN.UCC Composite bar code symbology specification
- **Section 5.9:** ISO/IEC 18004: Information technology; automatic identification and data capture techniques; QR Code 2005 bar code symbology specification
- **All sections:** ISO/IEC 646: Information technology; ISO 7-bit coded character set for information interchange

5.1.2. Symbology Identifiers

The symbology identifier is not encoded in the bar code, but is generated by the decoder after decoding and is transmitted as a preamble to the data message.

All scanning equipment has the ability to recognise the symbology that has been scanned. Some scanners have the optional feature of being able to transmit a symbology identifier. The symbology identifier is a three-character data string comprising a flag character, code character, and a modifier character.

Character	Description
] 	The flag character (which has an ASCII value of 93). This denotes that the two characters following it are Symbol Identifier characters.
c	The code character. This denotes the type of symbology.
m	The modifier character. This indicates the mode in which the symbology is used.



Note: If used, the symbology identifier is transmitted as a prefix to the data message.

The symbology identifiers used in the GS1 System are shown in Figure 5.1.2 - 1.

Figure 5.1.2 - 1 ISO/IEC 15424 Symbology Identifiers used in the GS1 System

Symbology Identifier*	Symbology Format	Content
] E 0	EAN-13, UPC-A, or UPC-E	13 digits
] E 1	Two-digit Add-On Symbol	2 digits
] E 2	Five-digit Add-On Symbol	5 digits
] E 3	EAN-13, UPC-A, or UPC-E with Add-On Symbol**	15 or 18 digits
] E 4	EAN-8	8 digits
] I 1	ITF-14	14 digits
] C 1	GS1-128	Standard AI Element Strings
] e 0	GS1 DataBar	Standard AI Element Strings
] e 1	GS1 Composite	Data packet containing the data following an encoded symbol separator character.
] e 2	GS1 Composite	Data packet containing the data following an escape mechanism character.
] d 2	GS1 DataMatrix	Standard AI Element Strings
] Q3	GS1 QR Code	Use for Extended Packaging Direct Mode

Notes:

* Symbology identifiers are case sensitive.

** Bar codes with Add-On Symbols may be considered either as two separate symbols, each of which is transmitted separately with its own symbology identifier, or as a single data packet. The system designer shall select one of these methods, but the method using symbology identifier]E3 is preferable for data security.

5.2. Linear Bar Codes - EAN/UPC Symbology Specifications

5.2.1. Symbology Characteristics

Characteristics of bar codes in the EAN/UPC Symbology family include:

- Encodable character set: digits (0 through 9) in accordance with ISO/IEC 646: Refer to Figure 7.12 – 1 for more details.
- Symbology type: continuous
- Symbol character density: seven modules per symbol character
- Four elements per symbol character comprising two bars (dark bars) and two spaces (light bars), each of one, two, three, or four modules in width (auxiliary guard patterns have differing numbers of elements)
- Character self-checking
- Fixed data string length encodable: 8, 12, or 13 characters including Check Digit, depending on specific symbol type
- Omni-directionally decodable
- One mandatory Check Digit (described in Section 7.10)
- Non-data overhead not including the Check Digit or Quiet Zones:
 - 11 modules for EAN-13, EAN-8, and UPC-A Bar Codes (left Guard Bar Pattern/centre Guard Bar Pattern/right Guard Bar Pattern)
 - Nine modules for UPC-E Bar Codes (left Guard Bar Pattern/right Guard Bar Pattern)

5.2.1.1. Symbol Types

The bar codes in the EAN/UPC Symbology family are:

- EAN-13, UPC-A, and UPC-E Bar Codes, all of which may be accompanied by an Add-On Symbol
- EAN-8 Bar Code

The four symbol types are described in Sections [5.2.1.3.1](#), [5.2.1.3.2](#), [5.2.1.3.3](#), and [5.2.1.3.4](#), and the optional Add-On Symbols are described in Section [5.2.1.3.5](#).

5.2.1.2. Symbol Encodation

5.2.1.2.1. Symbol Character Encodation

Symbol characters shall encode digit values in seven module characters selected from different number sets known as A, B, and C as shown in Figure 5.2.1.2.1 - 1.

Figure 5.2.1.2.1 - 1 Number Sets A, B, and C

Digit Value	Set A Element Widths				Set B Element Widths				Set C Element Widths			
	S	B	S	B	S	B	S	B	B	S	B	S
0	3	2	1	1	1	1	2	3	3	2	1	1
1	2	2	2	1	1	2	2	2	2	2	2	1
2	2	1	2	2	2	2	1	2	2	1	2	2
3	1	4	1	1	1	1	4	1	1	4	1	1
4	1	1	3	2	2	3	1	1	1	1	3	2
5	1	2	3	1	1	3	2	1	1	2	3	1
6	1	1	1	4	4	1	1	1	1	1	1	4
7	1	3	1	2	2	1	3	1	1	3	1	2
8	1	2	1	3	3	1	2	1	1	2	1	3
9	3	1	1	2	2	1	1	3	3	1	1	2

Note: **S** denotes a space (light bar), **B** denotes a bar (dark bar), and the element widths are in modules.

Figure 5.2.4.1 - 1 graphically illustrates Figure 5.2.1.2.1 - 1. The sum of the bar (dark bar) modules in any symbol character determines its parity. Symbol characters in number set A are odd parity characters. Symbol characters in number sets B and C are even parity characters. Number set C characters are mirror images of number set B characters.

Symbol characters in number sets A and B always begin on the left with a space module and end on the right with a dark module. Symbol characters in number set C begin on the left with a dark module and end on the right with a light module.

A data character shall normally be represented by a symbol character. However, in certain specific instances defined in Sections [5.2.1.3.1](#), [5.2.1.3.4](#), and [5.2.1.3.5](#), the combination of number sets in a symbol may itself represent either data or a Check Digit value. This technique is referred to as variable parity encodation.

5.2.1.2.2. Auxiliary Pattern Encodation

Auxiliary patterns shall be composed as shown in Figure 5.2.1.2.2 - 1.

Figure 5.2.1.2.2 - 1 Auxiliary Patterns

Auxiliary Pattern	Number of Modules	Element Widths in Modules					
		S	B	S	B	S	B
Normal Guard Bar Pattern	3		1	1	1		
Centre Guard Bar Pattern	5	1	1	1	1	1	
Special Guard Bar Pattern	6	1	1	1	1	1	1
Add-On Guard Bar Pattern	4		1	1	2		
Add-On Delineator	2	1	1				

Note: **S** denotes a space (light) element and **B** denotes a bar (dark) element.

Section [5.2.3.2](#) graphically illustrates these patterns.

The normal Guard Bar Pattern corresponds to the start and stop patterns in other symbologies, and the special Guard Bar Pattern is used as a stop pattern in UPC-E Bar Codes.

5.2.1.3. Symbol Formats

5.2.1.3.1. EAN-13 Bar Codes

The EAN-13 Bar Code shall be made up as follows, reading from left to right:

- A left Quiet Zone
- A normal Guard Bar Pattern
- Six symbol characters from number sets A and B
- A centre Guard Bar Pattern
- Six symbol characters from number set C
- A normal Guard Bar Pattern
- A right Quiet Zone

The rightmost symbol character shall encode the Check Digit calculated in accordance with Section 7.10.

Since the EAN-13 Bar Code comprises only 12 symbol characters but encodes 13 digits of data (including the Check Digit), the value of the additional digit, which is the character in the leftmost position in the data string, shall be encoded by the variable parity mix of number sets A and B for the six symbol characters in the left half of the symbol. The numbering system for values of the leading digit is specified in Figure 5.2.1.3.1 - 1. Figure 5.2.1.3.1 - 2 is an example of an EAN-13 Bar Code.

Figure 5.2.1.3.1 – 1 Left Half of an EAN-13 Bar Code

Leading Digit, Implicitly Encoded	Number Sets Used for Numbering Left Half of an EAN-13 Bar Code					
	Symbol Character Position					
	1	2	3	4	5	6
0*	A	A	A	A	A	A
1	A	A	B	A	B	B
2	A	A	B	B	A	B
3	A	A	B	B	B	A
4	A	B	A	A	B	B
5	A	B	B	A	A	B
6	A	B	B	B	A	A
7	A	B	A	B	A	B
8	A	B	A	B	B	A
9	A	B	B	A	B	A



Note: The leading digit value “0” is reserved for symbols encoding GTIN-12 Element Strings.

Figure 5.2.1.3.1 – 2 EAN-13 Bar Code

5.2.1.3.2. EAN-8 Bar Codes

The EAN-8 Bar Code shall be made up as follows, reading from left to right:

- A left Quiet Zone
- A normal Guard Bar Pattern
- Four symbol characters from number set A
- A centre Guard Bar Pattern
- Four symbol characters from number set C
- A normal Guard Bar Pattern
- A right Quiet Zone

The rightmost symbol character shall encode the Check Digit calculated in accordance with Section 7.10. Figure 5.2.1.3.2 - 1 is an example of an EAN-8 Bar Code.

Figure 5.2.1.3.2 – 1 EAN-8 Bar Code

5.2.1.3.3. UPC-A Bar Codes

The UPC-A Bar Code shall be made up as follows, reading from left to right:

- A left Quiet Zone
- A normal Guard Bar Pattern
- Six symbol characters from number set A
- A centre Guard Bar Pattern
- Six symbol characters from number set C
- A normal Guard Bar Pattern
- A right Quiet Zone

The rightmost symbol character shall encode the Check Digit calculated in accordance with Section 7.10. A UPC-A Bar Code may be decoded as a 13-digit number by adding an implied leading zero to the GTIN-12. Figure 5.2.1.3.3 -1 is an example of a UPC-A Bar Code.

Figure 5.2.1.3.3 - 1 UPC-A Bar Code



5.2.1.3.4. UPC-E Bar Codes

The UPC-E Bar Code shall be made up as follows, reading from left to right:

- A left Quiet Zone
- A normal Guard Bar Pattern
- Six symbol characters from number sets A and B
- A special Guard Bar Pattern
- A right Quiet Zone

The UPC-E Bar Code may only be used to encode GTIN-12 Element Strings that commence with a zero and contain a sequence of four or five zeroes in defined positions, as shown in Figure 5.2.2.3.4 - 1. These zeros are removed from the data during encoding by the zero-suppression process described in Section 5.2.1.3.4.1. Figure 5.2.1.3.4 - 1 is an example of a UPC-E Bar Code.

Figure 5.2.1.3.4 - 1 UPC-E Bar Code (Encoding 001234000057 by Zero-Suppression)



5.2.1.3.4.1. Encodation of the UPC-E Bar Code

The following algorithm describes the encodation of a data string suitable for zero-suppression:

1. Let D1, D2, and D3 through D12 denote the GTIN-12 data characters (including Check Digit). D1 shall always be zero. D12 shall be the Check Digit calculated according to the algorithm in Section 7.10. Let X1 and X2 through X6 denote the six symbol characters in the final UPC-E Bar Code.

Convert D2 through D11 into a symbol character string by removing zeroes according to the following rules:

If	Then
<ul style="list-style-type: none"> ■ D11 equals 5, 6, 7, 8, or 9 ■ and D7 to D10 inclusive are all 0 ■ and D6 is not 0 	<ul style="list-style-type: none"> ■ D7 to D10 are not encoded. ■ Symbol character: X1 X2 X3 X4 X5 X6 ■ Data character: D2 D3 D4 D5 D6 D11

If	Then
<ul style="list-style-type: none"> ■ D6 to D10 inclusive are all 0 ■ and D5 is not 0 	<ul style="list-style-type: none"> ■ D6 to D10 are not encoded and X6 = 4. ■ Symbol character: X1 X2 X3 X4 X5 X6 ■ Data character: D2 D3 D4 D5 D11 4

If	Then
<ul style="list-style-type: none"> ■ D4 is 0, 1, or 2 ■ and D5 to D8 inclusive are all 0 	<ul style="list-style-type: none"> ■ D5 to D8 are not encoded. ■ Symbol character: X1 X2 X3 X4 X5 X6 ■ Data character: D2 D3 D9 D10 D11 D4

If	Then
<ul style="list-style-type: none"> ■ D4 is 3, 4, 5, 6, 7, 8, or 9 ■ and D5 to D9 inclusive are all 0 	<ul style="list-style-type: none"> ■ D5 to D9 are not encoded and X6 = 3. ■ Symbol character: X1 X2 X3 X4 X5 X6 ■ Data character: D2 D3 D4 D10 D11 3

Determine the number sets for the implicit encodation of D12 from Figure 5.2.1.3.4.1 - 1
 Encode symbol characters X1 to X6 using number sets A and B as determined in Step 3

Figure 5.2.1.3.4.1 - 1 Number Sets for Implicit Encodation of D12

Value of Check Digit D12	Number Sets Used for Numbering a UPC-E Bar Code					
	Symbol Character Position					
	1	2	3	4	5	6
0	B	B	B	A	A	A
1	B	B	A	B	A	A
2	B	B	A	A	B	A
3	B	B	A	A	A	B
4	B	A	B	B	A	A
5	B	A	A	B	B	A
6	B	A	A	A	B	B
7	B	A	B	A	B	A
8	B	A	B	A	A	B
9	B	A	A	B	A	B

Figure 5.2.1.3.4.1 - 2 Zero Supression Example 1

Example 1	Original Data	Zero-Suppressed	Rule
	0 1 2 3 4 5 0 0 0 0 5 8	1 2 3 4 5 5	2a
		B A B A A B	

Figure 5.2.1.3.4.1 - 3 Zero Supression Example 2

Example 2	Original Data	Zero-Suppressed	Rule
	0 4 5 6 7 0 0 0 0 8 0	4 5 6 7 8 4	2b
		B B B A A A	

Figure 5.2.1.3.4.1 - 4 Zero Suppression Example 3

Example 3	Original Data	Zero-Suppressed	Rule
	0 3 4 0 0 0 0 0 5 6 7 3	3 4 5 6 7 0	2c
		B B A A A B	

Figure 5.2.1.3.4.1 - 5 Zero Suppression Example 4

Example 4	Original Data	Zero-Suppressed	Rule
	0 9 8 4 0 0 0 0 0 7 5 1	9 8 4 7 5 3	2d
		B B A B A A	



Note: The number sets used to implicitly encode the Check Digit are shown in the zero-suppressed column.

5.2.1.3.4.2. Decoding a UPC-E Bar Code

Derivation of the 12-digit data string from the characters encoded in the UPC-E Bar Code SHALL be performed according to Figure 5.2.1.3.4.2 - 1.

Figure 5.2.1.3.4.2 - 1 Decoding a UPC-E Bar Code

Encoded UPC-E Bar Code Digits								Decoded Number											
	P1	P2	P3	P4	P5	P6		D1	D2	D3	D4	D5	D6	D7	D8	D9	D10	D11	D12
(0)	X1	X2	X3	X4	X5	0	(C)	(0)	X1	X2	0	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	X3	X4	X5	(C)
(0)	X1	X2	X3	X4	X5	1	(C)	(0)	X1	X2	1	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	X3	X4	X5	(C)
(0)	X1	X2	X3	X4	X5	2	(C)	(0)	X1	X2	2	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	X3	X4	X5	(C)
(0)	X1	X2	X3	X4	X5	3	(C)	(0)	X1	X2	X3	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	X4	X5	(C)
(0)	X1	X2	X3	X4	X5	4	(C)	(0)	X1	X2	X3	X4	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	X5	(C)
(0)	X1	X2	X3	X4	X5	5	(C)	(0)	X1	X2	X3	X4	X5	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	5	(C)
(0)	X1	X2	X3	X4	X5	6	(C)	(0)	X1	X2	X3	X4	X5	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	6	(C)
(0)	X1	X2	X3	X4	X5	7	(C)	(0)	X1	X2	X3	X4	X5	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	7	(C)
(0)	X1	X2	X3	X4	X5	8	(C)	(0)	X1	X2	X3	X4	X5	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	8	(C)
(0)	X1	X2	X3	X4	X5	9	(C)	(0)	X1	X2	X3	X4	X5	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	9	(C)

Notes:

- The symbol characters at positions P1 and P2 through P5 of the UPC-E Bar Code are represented by X1 and X2 through X5.
- Re-inserted zeroes are indicated by underlining.
- The leading digit for UPC-E Bar Codes, which is not encoded, is indicated by "0".
- The Check Digit implicitly encoded in UPC-E Bar Codes is indicated by "C".

5.2.1.3.5. Add-On Symbols

The Add-On Symbols were designed to encode information supplementary to that in the main bar code on periodicals, hardback, and paperback books. Because they provide reduced security, use of

Add-On Symbols shall be limited to applications where rules in the application specification governing data format and content provide appropriate safeguards.

5.2.1.3.5.1. Two-Digit Add-On Symbol

A two-digit Add-On Symbol may be used in specific applications to accompany an EAN-13, UPC-A, or UPC-E Bar Code. The two-digit Add-On Symbol is positioned following the right Quiet Zone of the main symbol and consists of the following:

- Add-On Guard Bar Pattern
- First digit of the additional number from number sets A or B
- Add-On delineator
- Second digit of the additional number from number sets A or B
- A right Quiet Zone

The Add-On Symbol has no right Guard Bar Pattern. It does not have an explicit Check Digit. Checking is done through the mix of the number sets (A or B) used for the two digits. The choice of number sets is linked to the value of the additional number as shown by Figure 5.2.1.3.5.1 - 1.

Figure 5.2.1.3.5.1 - 1 Number Sets for Two-Digit Add-On Symbols

Value of the digits carried by the Add-On Symbol	Left-Hand Digit	Right-Hand Digit
Multiple of 4 (00,04,08,..96)	A	A
Multiple of 4+1 (01,05,..97)	A	B
Multiple of 4+2 (02,06,..98)	B	A
Multiple of 4+3 (03,07,..99)	B	B

Figure 5.2.1.3.5.1 - 2 is an example of an EAN-13 Bar Code with a two-digit Add-On Symbol.

Figure 5.2.1.3.5.1 - 2 EAN-13 Bar Code with Two-Digit Add-On Symbol



5.2.1.3.5.2. Five-Digit Add-On Symbol

A five-digit Add-On Symbol may be used in specific applications to accompany an EAN-13, UPC-A, or UPC-E Bar Code. The five-digit Add-On Symbol is positioned following the right Quiet Zone of the main symbol and consists of the following:

1. Add-On Guard Bar Pattern
2. First digit of the Add-On number from number sets A or B
3. Add-On delineator
4. Second digit of the Add-On number from number sets A or B
5. Add-On delineator
6. Third digit of the Add-On number from number sets A or B

7. Add-On delineator
8. Fourth digit of the Add-On number from number sets A or B
9. Add-On delineator
10. Fifth digit of the Add-On number from number sets A or B
11. A right Quiet Zone

The Add-On Symbol has no right Guard Bar Pattern. It does not have an explicit Check Digit. Checking is done through the mix of the number sets (A or B) used for the five digits. A value V is determined by the following procedure:

1. Sum the digits in Positions one, three, and five
2. Multiply the result of step 1 by 3
3. Sum the remaining digits (Positions two and four)
4. Multiply the result of step 3 by 9
5. Sum the results of steps 2 and 4
6. The value of V is the unit's position (lowest-order digit) of the result of step

Example:

To calculate the value of V for an Add-On Symbol carrying the number 86104, follow these steps:

1. $8 + 1 + 4 = 13$
2. $13 \times 3 = 39$
3. $6 + 0 = 6$
4. $6 \times 9 = 54$
5. $39 + 54 = 93$
6. $V = 3$

The number sets can then be determined by using Figure 5.2.1.3.5.2 - 1.

Figure 5.2.1.3.5.2 - 1 Number Sets for Five-Digit Add-On Symbol

Value of V	Number Sets Used for Symbol Characters				
	1	2	3	4	5
0	B	B	A	A	A
1	B	A	B	A	A
2	B	A	A	B	A
3	B	A	A	A	B
4	A	B	B	A	A
5	A	A	B	B	A
6	A	A	A	B	B
7	A	B	A	B	A
8	A	B	A	A	B
9	A	A	B	A	B

Since $V = 3$ in Figure 5.2.1.3.5.2 - 1, the sequence of number sets used to encode the value 86104 is B A A A B.

Figure 5.2.1.3.5.2 - 2 shows an example of an EAN-13 Bar Code with a five-digit Add-On Symbol.

Figure 5.2.1.3.5.2 – 2 EAN-13 Bar Code with Five-Digit Add-On Symbol



5.2.1.4. Dimensions and Tolerances

5.2.1.4.1. Nominal Dimensions of Characters

Bar codes can be printed at various densities to accommodate a variety of printing and scanning processes. The significant dimensional parameter is **X**, the ideal width of a single module element. The X-dimension must be constant throughout a given symbol.

The dimensions of EAN-13, UPC-A, EAN-8 and UPC-E Bar Codes are referenced to a defined set of dimensions referred to as the nominal size symbol. Refer to Section 5.2.3.6 for dimensioned drawings of nominal size symbols.

The X-dimension at nominal size is 0.330 millimetre (0.0130 inch).

The width of each bar (dark bar) and space (light bar) is determined by multiplying the X-dimension by the module width of each bar (dark bar) and space (light bar) (1, 2, 3, or 4). There is an exception for characters 1, 2, 7, and 8. For these characters, the bars (dark bars) and spaces (light bars) are reduced or enlarged by one-thirteenth of a module to provide a uniform distribution of bar width tolerances and thus improve scanning reliability.

The reduction or enlargement in millimetres at nominal size of the bars (dark bars) and spaces (light bars) for the characters 1, 2, 7, and 8 in the number sets A, B, and C is shown in Figure 5.2.1.4.1 - 1.

Figure 5.2.1.4.1 - 1 Reduction/Enlargement for Characters 1, 2, 7, and 8

Character Value	Number Set A		Number Sets B and C	
	Bar (Dark Bar) mm	Space (Light Bar) mm	Bar (Dark Bar) mm	Space (Light Bar) mm
1	- 0.025	+0.025	+0.025	- 0.025
2	- 0.025	+0.025	+0.025	- 0.025
7	+0.025	- 0.025	- 0.025	+0.025
8	+0.025	- 0.025	- 0.025	+0.025



Note: The existing symbol generation equipment that uses a value of 0.030 millimetre for the reduction/enlargement factor at nominal size will continue to be used for the foreseeable future.

5.2.1.4.2. Symbol Height

For EAN-13, UPC-A, and UPC-E Bar Codes the height of the symbol at the nominal size is 22.85 millimetres (0.900 inch).

For EAN-8 Bar Codes the height of the symbol at the nominal size is 18.23 millimetres (0.718 inch).

The height of any two-digit or five-digit Add-On Symbol used must not extend outside the symbol height dimensions of the primary symbol.

In EAN-13, EAN-8, UPC-A, and UPC-E Bar Codes, the bars (dark bars) forming the left, centre, and right Guard Bar Patterns shall be extended downward by 5x (e.g., 1.65 millimetres (0.065 inch)). This shall also apply to the bars (dark bars) of the first and last symbol characters of the UPC-A Bar Code.

Note: The height of an EAN/UPC Bar Code no longer includes the Human Readable Interpretation and is the height of the bars only. The measurement of bar height does not include the extended height of either the guard patterns in EAN/UPC Bar Codes or the first and last symbol characters of a UPC-A Bar Code.

Symbol height is not modular.

5.2.1.4.3. X-Dimension (Magnification Factor)

In the past the term "magnification factor" was extensively used to specify the size of a bar code. This technique relied upon setting a nominal size (100 percent) that was directly related to a given X-dimension. Since January 2000, the more precise term "X-dimension" has been used to specify permissible symbol sizes (see Section 5.5).

The X-dimension of an Add-On Symbol shall be the same as the X-dimension of its associated main symbol.

5.2.1.4.4. Quiet Zone

The minimum Quiet Zone width required by the main bar code is 7x. However, other minimum Quiet Zone dimensions are specified for some symbol types due to the size and location of their Human Readable Interpretation. These dimensions are noted in Figure 5.2.1.4.4 - 1.

Figure 5.2.1.4.4 - 1 Quiet Zone Widths by Version

Symbol Version	Left Quiet Zone		Right Quiet Zone	
	Modules	mm*	Modules	mm
EAN-13	11	3.63	7	2.31
EAN-8	7	2.31	7	2.31
UPC-A	9	2.97	9	2.97
UPC-E	9	2.97	7	2.31
Add-Ons (EAN)	7-12	2.31-3.96	5	1.65
Add-Ons (U.P.C.)	9-12	2.97-3.96	5	1.65

* This is an example using an X-dimension of 0.330 millimetres.

Note: A useful device to help maintain the Quiet Zone in some production processes is to include a less than (<) and/or greater than (>) character in the Human Readable Interpretation field, with its apex aligned with the edge of the Quiet Zone. If this device is used, the character(s) shall be positioned in accordance with the appropriate drawings in Section 5.2.3.6.

5.2.1.4.5. Symbol Length

The symbol length in modules, including the minimum Quiet Zones, shall be as indicated in Figure 5.2.1.4.5 - 1.

Figure 5.2.1.4.5 - 1 Symbol Length in Modules

Symbol Type	Length
EAN-13	113
UPC-A	113
EAN-8	81

Symbol Type	Length
UPC-E	67
Two-digit Add-On	25
Five-digit Add-On	52
EAN-13 or UPC-A and two-digit Add-On	138
UPC-E and two-digit Add-On	92
EAN-13 or UPC-A and five-digit Add-On	165
UPC-E and five-digit Add-On	119

5.2.1.4.6. Positioning of the Add-On Symbol

The Add-On Symbol shall not encroach on the right Quiet Zone of the main symbol. The maximum separation shall be 12X.

The bottom edge of the bars (dark bars) in the Add-On Symbol shall be horizontally aligned with the bottom edge of the guard bars of the main symbol.

5.2.2. Reference Decode Algorithm


Decode algorithms are used by scanning equipment to convert the bar and space patterns of the bar code into data characters. As a matter of policy, GS1 makes no attempt to specify or standardise equipment beyond stating that it should be capable of reading symbols produced in accordance with the specifications laid out in this manual.

Bar code reader systems are designed to read imperfect symbols to the extent that practical algorithms permit. This section describes the reference decode algorithm used to determine decode and decodability in symbol verification in accordance with *ISO 15416*.

For each symbol character, let S equal the total measured width of the character. The value S is used to determine reference threshold (RT) values. Individual edge to similar edge measurements (e) are then compared to the reference threshold to determine E values. Character values are determined from E values.

Value e1 is defined as the measurement from the leading edge of a bar (dark bar) to the leading edge of the adjacent bar (dark bar). Value e2 is defined as the measurement from the trailing edge of a bar (dark bar) to the trailing edge of the adjacent bar (dark bar). For number sets A and B, the right edge of each of the two bars (dark bars) is considered to be leading, while for number set C, the left edge of each bar (dark bar) is considered to be leading. These relationships are illustrated in Figure 5.2.2 - 1.

Figure 5.2.2 - 1 Symbol Character Decode Measurements



Reference thresholds RT1, RT2, RT3, RT4, and RT5 are given by:

- $RT1 = (1.5/7)S$
- $RT2 = (2.5/7)S$
- $RT3 = (3.5/7)S$
- $RT4 = (4.5/7)S$
- $RT5 = (5.5/7)S$

Within each character, the measurements e_1 and e_2 are compared with the reference thresholds. The corresponding integer values E_1 and E_2 are considered to be equal to 2, 3, 4, or 5 as follows:

- If $RT1 \leq e_i < RT2$, $E_i = 2$
- If $RT2 \leq e_i < RT3$, $E_i = 3$
- If $RT3 \leq e_i < RT4$, $E_i = 4$
- If $RT4 \leq e_i < RT5$, $E_i = 5$

Otherwise the character is in error.

Figure 5.2.2 - 2, use the values of E_1 and E_2 as the primary determinant for the symbol character value.

Figure 5.2.2 - 2 Bar Code Decoding

Character	Number Set	Primary Determinant		Secondary Determinant $7(b_1 + b_2)/S$
		E1	E2	
0	A	2	3	
1	A	3	4	≤ 4
2	A	4	3	≤ 4
3	A	2	5	
4	A	5	4	
5	A	4	5	
6	A	5	2	
7	A	3	4	> 4
8	A	4	3	> 4
9	A	3	2	
0	B and C	5	3	
1	B and C	4	4	> 3
2	B and C	3	3	> 3
3	B and C	5	5	
4	B and C	2	4	
5	B and C	3	5	
6	B and C	2	2	
7	B and C	4	4	≤ 3
8	B and C	3	3	≤ 3
9	B and C	4	2	



Note: b_1 and b_2 are the widths of the two bar (dark bar) elements

The character is uniquely determined for all combinations of E1 and E2 except for the following four cases:

- E1 = 3 and E2 = 4 (characters 1 and 7 in number set A)
- E1 = 4 and E2 = 3 (characters 2 and 8 in number set A)
- E1 = 4 and E2 = 4 (characters 1 and 7 in number sets B and C)
- E1 = 3 and E2 = 3 (characters 2 and 8 in number sets B and C)

These cases require that the combined width of the two bars (dark bars) be tested as follows:

- For E1 = 3 and E2 = 4:
 - Character is 1 if $7 \times (b_1 + b_2) / S \leq 4$
 - Character is 7 if $7 \times (b_1 + b_2) / S > 4$
- For E1 = 4 and E2 = 3:
 - Character is 2 if $7 \times (b_1 + b_2) / S \leq 4$
 - Character is 8 if $7 \times (b_1 + b_2) / S > 4$
- For E1 = 4 and E2 = 4:

- Character is 1 if $7 \times (b1 + b2) / S > 3$
- Character is 7 if $7 \times (b1 + b2) / S \leq 3$
- For $E1 = 3$ and $E2 = 3$:
 - Character is 2 if $7 \times (b1 + b2) / S > 3$
 - Character is 8 if $7 \times (b1 + b2) / S \leq 3$

The requirements on $(b1 + b2)$ are shown in Figure 5.2.3 - 2.

The same procedures shall be used to decode the symbol characters in any Add-On Symbol.

Use Figure 5.2.3 - 3 to determine the appropriate S measurement for calculating the reference threshold values $RT1$ and $RT2$ applicable to the auxiliary patterns of the main symbol. For each symbol or half symbol, the measurements of the appropriate auxiliary pattern e_i values are then compared to the reference thresholds to establish the integer E_i values. The determined values of $E1$, $E2$, $E3$, and $E4$ shall match those of valid auxiliary patterns as shown in Figure 5.2.2 - 4. Otherwise the symbol is in error.

Figure 5.2.2 – 3 Auxiliary Pattern Measurements




Figure 5.2.2- 4 Main Symbol Auxiliary Pattern E Values

Auxiliary Guard Patterns	E1	E2	E3	E4
Normal Guard Bar Pattern	2			
Centre Guard Bar Pattern (left half)	2	2	2	
Centre Guard Bar Pattern (right half)		2	2	2
Special Guard Bar Pattern	2	2	2	2

5.2.3. Human Readable Interpretation

The human readable digits shall be printed underneath the main symbol and above the Add-On Symbol. A clearly legible font shall be used for these digits, and OCR-B as defined in ISO 1073-2: Alphanumeric character sets for optical recognition; Part 2: Character set OCR-B; Shapes and dimensions of the printed image, is recommended. This font is referenced only as a convenient standard typeface, and it is not intended that these characters be machine read or verified. Reasonable alternative type fonts and character sizes are acceptable provided the Human Readable Interpretation is clearly legible.

All the encoded digits for EAN-13, UPC-A, and EAN-8 Bar Codes, and the Add-On Symbols shall be shown in Human Readable Interpretation form. For UPC-E Bar Codes, the six digits directly encoded together with the leading zero and the implicitly encoded Check Digit shall be shown in Human Readable Interpretation form. Figures 5.2.1.3.1 - 2, 5.2.1.3.2 - 1, 5.2.1.3.3 - 1, 5.2.1.3.4 - 1, 5.2.1.3.5.1 - 2, and 5.2.1.3.5.2 - 2 illustrate each type of symbol and its Human Readable Interpretation.

The minimum space between the top of the digits and the bottom of the bars (dark bars) shall be 0.5X. Normally the minimum is one module, which is close enough to keep the Human Readable Interpretation associated with the symbol.

In the EAN-13, the leftmost digit, which is encoded by variable parity, is printed to the left of the start guard pattern in line with the other digits.

For UPC-A and UPC-E Bar Codes, the size of the first and last digits should be reduced to a maximum width equivalent to four modules. The height is reduced proportionally. The right-hand side of the first digit is positioned five module widths to the left of the leftmost guard bar. The left-hand side of the last digit is positioned five module widths to the right of the rightmost guard bar for UPC-A Bar Codes and three module widths for UPC-E Bar Codes. The bottom edge of the first and last digit shall be aligned with the bottom edge of the remaining full size digits.

The Human Readable Interpretation of the Add-On Symbol shall be above the symbol. The digits shall be the same height as those of the main symbol. The upper edges of the digits are aligned with the upper edges of the bars (dark bars) of the main symbol. The minimum space between the bottom of the digits and the top of the bars (dark bars) shall be 0.5X.

Some industries use specific variations of the recommended Human Readable Interpretation, such as inserted hyphens to segment the number field. An example of this is shown in Section [5.2.3.6](#)




5.2.3.1. Character Values in the EAN/UPC Symbology Family

Figure 5.2.3.1 - 1 Composition of EAN/UPC Symbol Characters

Value of Character	Number Set A (Odd)	Number Set B (Even)	Number Set C (Even)
0			
1			
2			
3			
4			
5			
6			
7			
8			
9			

5.2.3.2. Auxiliary Characters in the EAN/UPC Symbology Family

Figure 5.2.3.2 - 1 Composition of EAN/UPC Auxiliary Characters

Auxiliary Character	
Normal Guard Bar Pattern (right and left)	
Centre Guard Bar Pattern	
UPC-E Right Guard Bar Pattern	

5.2.3.3. Logical Structure of an EAN-13 and UPC-A Bar Code Excluding Quiet Zones

Figure 5.2.3.3 - 1 Logical Structure of an EAN-13 or UPC-A Bar Code

Logical Structure of an EAN-13 or UPC-A Bar Code (Excluding Quiet Zones)				
Left Guard Bar Pattern	Characters 12 Through 7 (Left Half)	Centre Guard Bar Pattern	Characters 6 Through 1 (Right Half)	Right Guard Bar Pattern
3 modules	42 modules (6x7)	5 modules	42 modules (6x7)	3 modules
Total number of modules = 95				

Figure 5.2.3.3 - 2 Combination of Number Sets Representing the Thirteenth Character of an EAN-13

Value of the Thirteenth Character	Character Position											
	Number Set Used for Representing Characters 12 Through 7						Number Set Used for Representing Characters 6 Through 1					
	12	11	10	9	8	7	6	5	4	3	2	1
0	A	A	A	A	A	A	ALWAYS USE NUMBER SET C					
1	A	A	B	A	B	B						
2	A	A	B	B	A	B						
3	A	A	B	B	B	A						
4	A	B	A	A	B	B						
5	A	B	B	A	A	B						
6	A	B	B	B	A	A						
7	A	B	A	B	A	B						
8	A	B	A	B	B	A						
9	A	B	B	A	B	A						

5.2.3.4. Logical Structure of an EAN-8 Bar Code Excluding Quiet Zones

Figure 5.2.3.4 - 1 Logical Structure of an EAN-8 Bar Code

Logical Structure of an EAN-8 Bar Code (Excluding Quiet Zones)				
Left Guard Bar Pattern	Characters 8 Through 5 (Left Half)	Centre Guard Bar Pattern	Characters 4 Through 1 (Right Half)	Right Guard Bar Pattern
3 modules	28 modules (4x7)	5 modules	28 modules (4x7)	3 modules
Total number of modules = 67				

Figure 5.2.3.4 - 2 Number Sets for EAN-8 Bar Code Characters

Character Position							
Number Set Used for Representing Characters 8 Through 5				Number Set Used for Representing Characters 4 Through 1			
8	7	6	5	4	3	2	1
ALWAYS USE NUMBER SET A				ALWAYS USE NUMBER SET C			

5.2.3.5. Logical Structure of a UPC-E Bar Code Excluding Quiet Zones

Figure 5.2.3.5 - 1 Logical Structure of a UPC-E Bar Code

Logical Structure of a UPC-E Bar Code (Excluding Quiet Zones)		
Normal Guard Bar Pattern	Six Symbol Characters (Note the Use of Variable Parity)	Special Guard Bar Pattern (UPC-E)
3 modules	42 modules (6x7)	6 modules
Total number of modules = 51		

Figure 5.2.3.5 - 2 Number Sets for UPC-E Bar Code Characters

Value of Prefix Digit	Value of Check Digit	Number Sets Used for Numbering a UPC-E Bar Code					
		1	2	3	4	5	6
0	0	B	B	B	A	A	A
0	1	B	B	A	B	A	A
0	2	B	B	A	A	B	A
0	3	B	B	A	A	A	B
0	4	B	A	B	B	A	A
0	5	B	A	A	B	B	A
0	6	B	A	A	A	B	B
0	7	B	A	B	A	B	A
0	8	B	A	B	A	A	B
0	9	B	A	A	B	A	B

5.2.3.6. Symbol Formats at Nominal Dimensions (Not to Scale)

All measurements in the following figures are in millimetres

Figure 5.2.3.6 - 1 EAN-13 Bar Code



Figure 5.2.3.6 - 2 UPC-A Bar Code



Figure 5.2.3.6 - 3 UPC-A Bar Code



Figure 5.2.3.6 - 4 EAN-8 Bar Code




Figure 5.2.3.6 - 5 UPC-E Bar Code



Figure 5.2.3.6 - 6 UPC-A Bar Code with Two-Digit Add-On Symbol



Figure 5.2.3.6 - 7 EAN-13 Bar Code with Five-Digit Add-On Symbol



5.2.3.7. Dimensions of Modules and Symbols at Different Levels of Magnification

Figure 5.2.3.7 - 1 Dimensions of EAN/UPC Symbols and their Modules at Different Levels of Magnification

Magnification Factor	Ideal Module Width [mm]	EAN-13/UPC-A Dimensions [mm]		EAN-8 Dimensions [mm]	
		Width	Height	Width	Height
0.80	0.264	29.83	18.28	21.38	14.58
0.85	0.281	31.70	19.42	22.72	15.50
0.90	0.297	33.56	20.57	24.06	16.41
0.95	0.313	35.43	21.71	25.39	17.32
1.00	0.330	37.29	22.85	26.73	18.23
1.05	0.346	39.15	23.99	28.07	19.14
1.10	0.363	41.02	25.14	29.40	20.05
1.15	0.379	42.88	26.28	30.74	20.96
1.20	0.396	44.75	27.42	32.08	21.88
1.25	0.412	46.61	28.56	33.41	22.79
1.30	0.429	48.48	29.71	34.75	23.70
1.35	0.445	50.34	30.85	36.09	24.61
1.40	0.462	52.21	31.99	37.42	25.52
1.45	0.478	54.07	33.13	38.76	26.43
1.50	0.495	55.94	34.28	40.10	27.35
1.55	0.511	57.80	35.42	41.43	28.26
1.60	0.528	59.66	36.56	42.77	29.17
1.65	0.544	61.53	37.70	44.10	30.08
1.70	0.561	63.39	36.85	45.44	30.99
1.75	0.577	65.26	39.99	46.78	31.90
1.80	0.594	67.12	41.13	48.11	32.81
1.85	0.610	68.99	42.27	49.45	33.73
1.90	0.627	70.85	43.42	50.79	34.64
1.95	0.643	72.72	44.56	52.12	35.55
2.00	0.660	74.58	45.70	53.46	36.46



Note: Refer to Section [5.5](#) for the minimum, nominal, and maximum X-dimensions, and symbol heights for bar codes.

5.3. Linear Bar Codes - ITF-14 Symbology Specifications

5.3.1. Symbology Characteristics

In the GS1 System, the characteristics of ITF-14 Symbols are:

- Encodable character set: digits 0 through 9, in accordance with ISO/IEC 646. Refer to Figure 7.12 – 1 for more details.
- Code type: continuous
- Elements per symbol character: five (two wide and three narrow) encoded as either five bars (dark bars) or five spaces (light bars)
- Self-checking symbol character
- Data string length encodable: fixed length at 14 digits
- Bidirectionally decodable
- One Check Digit is required (see Section 7.10)
- The symbol character density for ITF-14 is 16 to 18 modules per symbol character pair, depending on the wide-to-narrow ratio. The value is 16, based on the target ratio of 2.5 to 1.
- The non-data overhead is eight to nine modules, depending on the wide-to-narrow ratio. The value is 8.5, based on the target ratio of 2.5 to 1.

5.3.1.1. Symbol Structure

An ITF-14 Symbol includes:

- A left Quiet Zone
- A start pattern
- Seven pairs of symbol characters representing data
- A stop pattern
- A right Quiet Zone

5.3.1.2. Character Encodation

5.3.1.2.1. Data Character Encodation

Figure 5.3.1.2.1 - 1 defines the ITF-14 Symbol's character encodation. In the binary representation column, the character 1 represents a wide element and 0 represents a narrow element.

Figure 5.3.1.2.1 - 1 Binary Representation of Character Encodation

Data Character	Binary Representation				
0	0	0	1	1	0
1	1	0	0	0	1
2	0	1	0	0	1
3	1	1	0	0	0
4	0	0	1	0	1

Data Character	Binary Representation				
5	1	0	1	0	0
6	0	1	1	0	0
7	0	0	0	1	1
8	1	0	0	1	0
9	0	1	0	1	0

Figure 5.3.1.2.1 - 1 uses a modified binary coded decimal encoding scheme. The four leftmost bit positions for each character are assigned weights of 1, 2, 4, and 7, from left to right; the fifth position is used for an even parity bit. The sum of the positional weights of the 1 bits is equivalent to the data character value, except in the case of data character 0, where the weights 4 and 7 are applied. The parity bit ensures that there are always two 1 bits per character.


The algorithm shown in Figure 5.3.1.2.1 - 2 defines the rules for converting numeric data into the symbol characters of an ITF-14 Symbol (numeric data equals the Global Trade Item Number (GTIN) and, therefore, already contains the Check Digit).

Figure 5.3.1.2.1 - 2 Rules for Converting Numeric Data into Symbol Characters

Step in Algorithm	Example
1. Calculate Check Digit for 0367123456789	367
2. With ITF-14 Symbols, the data string, including the Check Digit, will always be a 14-digit number. The leftmost four digits of this number are 0367.	0367
3. Subdivide the numeric string into digit pairs. The leftmost four digits of the number are 0367.	0367 03 and 67
4. Encode the digit pairs as follows: <ul style="list-style-type: none"> ▪ Encode the leading digit of each pair into bar patterns, as shown in Figure 5.3.1.2.1 - 1 ▪ Encode the second digit of each pair into space patterns, as shown in Figure 5.3.1.2.1 - 1 	0 and 6 3 and 7
5. Form each symbol character pair by taking the bar (dark bar) and space (light bar) elements alternately from the patterns derived from the two steps in 4, commencing with the first bar (dark bar) of the pattern for the first digit, followed by the first space (light bar) of the pattern for the second digit.	

Figure 5.3.1.2.1 - 3 illustrates the sequence of bar (dark bar) and space (light bar) elements corresponding to the data character pairs 03 and 67.

Figure 5.3.1.2.1 - 3 ITF-14 Symbol Character Pairs Encoding 03 and 67



5.3.1.2.2. Start and Stop Patterns

The start pattern shall consist of four narrow elements in the sequence “bar (dark bar) - space (light bar) - bar (dark bar) - space (light bar).” The stop pattern shall consist of a “wide bar (dark bar) - narrow space (light bar) - narrow bar (dark bar)” sequence.

The start pattern shall be positioned at the normal left end of the symbol characters adjacent to the first bar (dark bar) of the most significant digit. The stop pattern shall be positioned at the normal right end of the symbol characters adjacent to the final space (light bar) of the least significant digit.

There is no assigned Human Readable Interpretation of the start and stop patterns, and they shall not be transmitted by the decoder.

Figure 5.3.1.2.2 - 1 illustrates the start and stop patterns and their relationship to the symbol characters.

Figure 5.3.1.2.2 - 1 Start and Stop Patterns





Figure 5.3.1.2.2 - 2 illustrates a complete bar code for the number 1234, showing the necessary Quiet Zones.

Figure 5.3.1.2.2 - 2 ITF-14 Symbol Inclusive of Quiet Zones



5.3.1.2.3. Check Digit

A Check Digit is required in the ITF-14 Symbology. Section 7.10 defines the Check Digit position and calculation.

5.3.1.3. Dimensions and Tolerances

ITF-14 Symbols shall use the following nominal dimensions:

- Width of narrow element (X): the X-dimension of ITF-14 Symbols is defined by the application specification based on the needs of the application. Refer to Section [5.5.2.6](#) for specifications by application area.
- The wide/narrow ratio (N): the range is 2.25:1 to 3.0:1 but the actual wide-to-narrow ratio is defined by the application specification based on the needs of the application. Refer to Section 5.5.2.6 for specifications by application area.
- The Quiet Zones to the right and left of the symbol are compulsory. The minimum width of each Quiet Zone is 10X.
- A minimum space of 1.02 millimetre (0.040 inch) between the bottom line of the Bearer Bar and the top of the human readable characters is required.

The length of an ITF-14 Symbol, including Quiet Zones, is calculated from the following expression:

$$W = (P(4N+6)+N+6)X+2Q$$

Where:

- **W** is the length in millimetres
- **P** is the number of character pairs
- **N** is the wide-to-narrow ratio
- **X** is the width of a narrow element in millimetres
- **Q** is the width of the Quiet Zone in millimetres

As an example, for an ITF-14 Symbol that has seven character pairs, a target wide-to-narrow ratio of 2.5:1, a target X width of 1.016 millimetres (0.0400 inch), and Quiet Zone widths of 10.16 millimetres (0.400 inch) the total symbol width is 142.75 millimetres (5.620 inches)

5.3.1.4. Reference Decode Algorithm

Bar code reading systems are designed to read imperfect symbols to the extent that practical algorithms permit. This section describes the reference decode algorithm used in the computation of the decodability value described in *ISO/IEC 15416*.

Decodability shall be determined as follows:

- Within each ITF-14 Symbol character (representing two digits), sort the bars (b_i) and spaces (s_i) such that:

$$\mathbf{b_1 < b_2 < b_3 < b_4 < b_5}$$

$$\mathbf{s_1 < s_2 < s_3 < s_4 < s_5}$$
- The determined X-dimension (Z) is given by:

$$\mathbf{Z = b_1 + b_2 + b_3 + s_1 + s_2 + s_3 / 6}$$
- Separation value (V_1) is:

$$\mathbf{V1 = (d/Z) - 0.5}$$

where d = the smaller of $(b_4 - b_3)$ or $(s_4 - s_3)$
- Uniformity value (V_2) is:

$$\mathbf{V2 = 1 - u/Z}$$

where u = the largest of:
 $b_5 - b_4$
 $b_3 - b_1$
 $s_5 - s_4$
 $s_3 - s_1$
- Narrowest element value (V_3) is:

$$\mathbf{V3 = [(n/Z) - 0.25] / 0.75}$$

where n = the smaller of s_1 or b_1
- For each symbol character, determine the decodability value V . V is the smallest of V_1 , V_2 , or V_3 .
- The scan profile decodability value is the smallest value of V measured in a Scan Reflectance Profile (SRP). The reference decode algorithm fails when V exhibits a negative value.
- The decodability grade for each profile is determined from the decodability value according to *ISO/IEC 15416*.

5.3.1.5. Bearer Bars


The purpose of a Bearer Bar is to equalise the pressure exerted by the printing plate over the entire surface of the symbol and to enhance reading reliability by helping to reduce the probability of misreads or short scans that may occur when a skewed scanning beam enters or exits the bar code through its top or bottom edge.

The Bearer Bar is mandatory unless it is not technically feasible to apply it (in which case reading reliability will be reduced).

For printing methods requiring printing plates, the nominal Bearer Bar has a constant thickness of 4.83 millimetres (0.190 inch) and must completely surround the symbol, including its Quiet Zones, and butt directly against the top and bottom of the bars (dark bars) of the symbol.

For printing methods that do not require printing plates, the Bearer Bar SHALL be a minimum of twice the width of a narrow bar (dark bar) and need only appear at the top and bottom of the symbol, butting directly against the top and bottom of the symbol bars (dark bars). The Bearer Bar may extend above and below the Quiet Zones. However, it is not mandatory to print the vertical sections of the Bearer Bar. See Figure 5.3.1.5 - 1.

Figure 5.3.1.5 - 1 ITF Symbols with Bearer Bars



5.3.1.6. Human Readable Interpretation

For Human-Readable Interpretation Rules see Section 4.12. For HRI Rules specific to Regulated Healthcare Retail Consumer Trade Items, see Section 4.12.1.

5.3.1.7. Additional Features (Informative)

5.3.1.7.1. Protection Against Short Scans

In ITF-14 Symbols, the bar (dark bar) patterns of the start and stop patterns may be found at the respective end and beginning of certain encoded symbol characters within the code. There is, therefore, no guarantee that a partial scan of the symbol will not produce a valid read for an embedded symbol having fewer characters.

In the GS1 System, short scans are very unlikely to happen, as the symbol must always contain 14 digits. However, a symbol containing more than 14 digits may cause a short scan of 14 digits. In this instance, the Check Digit offers security to detect this error.

These are the measures that SHALL be taken to minimise the risk of partial read.

5.3.1.7.2. Fixed Length Symbols

In any application standard, the number of characters encoded in an ITF-14 Symbol SHALL be fixed for that application and reading or data processing equipment should be programmed to only accept messages of that defined length. An ITF-14 Symbol must always carry a 14-digit number.

5.3.1.8. Guidelines for the Use of ITF-14 (Informative)

5.3.1.8.1. Autodiscrimination Compatibility

ITF-14 Symbols may be read by suitably programmed bar code readers that are designed to autodiscriminate the ITF Symbology from other symbologies. The ITF Symbology is fully distinguishable from and compatible with many symbologies including the ISO standard symbologies.

The decoder's valid set of symbologies should be limited to those needed by a given application to maximize reading security.

5.3.1.8.2. System Considerations

It is important that the various components making up a bar code installation system (e.g., printers, labels, readers) operate in concert. A failure in any component, or a mismatch between components, can compromise the performance of the overall system.

5.3.1.9. Symbology Identifier (Informative)

The symbology identifier allocated to the ITF-14 Symbol in ISO/IEC 15424, which is added as a preamble to the decoded data by a suitably programmed bar code reader, is: **]Im**

where:

-]** is ASCII character 93
- I** (upper case I) is the code character for the ITF-14 Symbology
- m** is a modifier character



Note: The symbology identifier **]1** is the only symbology identifier used by GS1 with the ITF-14 Symbol. This information shall not be encoded in the bar code, but shall be generated by the decoder after decoding and transmitting as a preamble to the data message. The value of “m” in the symbology identifier is equal to 1, which indicates the Check Digit has been validated and transmitted by the scanner

5.3.1.10. Test Specifications (Informative)

To verify whether a symbol meets the specifications of the GS1 System, it shall be tested using the specification defined in *ISO/IEC 15416*, which details the conditions under which measurements SHALL be made. The specification defines methods of determining an overall quality grade based on the attributes of the bar code and determining its conformity with the system. For ITF-14 Symbols, the reference decode algorithm shall be the algorithm specified in Section [5.3.1.4](#).

Full details on bar code production and quality assessment can be found in Section [5.5](#).

The verifier shall determine the average wide-to-narrow ratio (N) for each profile. The value **N** is computed character by character, then averaged over all characters in the symbol. The range indicated below is passing:


2.25 <N < 3.00

N is calculated for each symbol character (pair of data digits) according to the following rule:

$N_i = 1.5 * [(b_4 + b_5 + s_4 + s_5) / (b_1 + b_2 + b_3 + s_1 + s_2 + s_3)]$

The value N for the profile is then obtained by averaging the N_i for all characters in the symbol.

Figure 5.3.1.9 - 1 ITF-14 Symbol: Main Dimensions at X-Dimension 1.016 mm (0.0400 in.)



Note: This diagram is not intended to be used as a basis for measurement.

5.4. Linear Bar Codes - GS1-128 Symbology Specifications

The GS1-128 Bar Code has been carefully designed through joint co-operation between GS1 and AIM (Association for Automatic Identification and Mobility). Use of GS1-128 Bar Codes provides a high degree of security and distinguishes GS1 System Element Strings from extraneous non-standard bar codes.

The GS1-128 Symbology is a subset of the more general Code 128 Symbology. By agreement between AIM and GS1, use of the Function 1 Symbol Character (FNC1) in Code 128 Symbols in the first symbol character position following the Start Character has been reserved exclusively for the GS1 System.

Code 128 is fully described in *ISO/IEC 15417, Information Technology - Automatic Identification and Data Capture Techniques - Bar code Symbology Specification - Code 128*.

The information covered in Section 5.4 includes:

- Sections 5.4.1, 5.4.2, 5.4.3, 5.4.4, 5.4.5, and 5.4.6: GS1-128 Symbology subset (using *ISO/IEC 15417* for reference)
- Section 5.4.7: GS1 System application-defined parameters
- Appendix 5.9: GS1 System rules for encoding/decoding Element Strings in GS1 Symbologies using GS1 Application Identifiers

5.4.1. GS1-128 Symbology Characteristics

The characteristics of the GS1-128 Symbology are:

- Encodable character set:
 - The GS1 System requires that only the subset of ISO/IEC 646 International Reference Version defined in these GS1 General Specifications be used for Application Identifier (AI) Element Strings. Refer to Figure 7.12 – 1 for the allowed encodable character set.
 - Characters with ASCII values 128 to 255 may also be encoded in Code 128 Symbols. Characters with ASCII values 128 to 255 accessed by Function 4 Symbol Character (FNC4) are reserved for future use and are not used in GS1-128 Bar Codes.
 - Four non-data function characters. FNC2 and FNC4 are not used in GS1-128 Bar Codes.

- Four code set selection characters (including single character code set shift)
- Three Start Characters
- One Stop Character
- Continuous code type
- Six elements per symbol character comprising three bars (dark bars) and three spaces (light bars), each one, two, three, or four modules in width. The Stop Character is made up of seven elements comprising four bars (dark bars) and three spaces (light bars).
- Character self-checking
- Variable symbol length
- Bi-directionally decodable
- One mandatory Symbol Check Character (see Section [5.4.3.6](#)).
- Data character density is 11 modules per symbol character (5.5 modules per numeric character in code set C, 13 modules per Stop Character)
- Non-data overhead:
 - GS1-128 Bar Codes have a special double character start pattern consisting of the appropriate Start Character and immediately followed by a Function 1 Symbol Character Code (FNC1). The FNC1 adds to the symbol's non-data overhead. The total symbol overhead is 46 modules.
 - The FNC1 character may also be used as a Separator Character between Element Strings not contained in the pre-defined table shown in Figure A1-1 Section [5.10.1](#)
- GS1-128 Bar Code size characteristics:
 - The maximum physical length is 165.10 millimetres (6.500 inch) including Quiet Zones.
 - The maximum number of data characters in a single symbol is 48.
 - For a given length of data, the symbol size is variable between limits in X-dimension to accommodate the ranges in quality achievable by the various printing processes.

5.4.2. GS1-128 Bar Code Structure

The GS1-128 Bar Code is made up as follows, reading from left to right:


- Left Quiet Zone

A Start Character (A, B, or C)	The Double Character
The Function 1 Symbol Character (FNC1)	Start Pattern

- Data (including the Application Identifier represented in character set A, B, or C)
- A Symbol Check Character
- The Stop Character
- Right Quiet Zone

For Human-Readable Interpretation Rules see Section 4.12. For HRI Rules specific to Regulated Healthcare Retail Consumer Trade Items, see Section 4.12.1.

Figure 5.4.2 - 1 General Format of a GS1-128 Bar Code



5.4.3. GS1-128 Symbology Character Assignments

Figure 5.4.3.2 – 1 defines all the Code 128 character assignments. In the element width column, the numeric values represent the widths of the elements in modules or multiples of the X-dimension.

GS1-128 Bar Code character assignments are identical to Code 128 Symbol character assignments.

5.4.3.1. Symbol Character Structure

The sum of the bar modules in any symbol character is always even (even parity) and the sum of the space modules is, therefore, always odd. This parity feature enables character self-checking.

Figure 5.4.3.1 - 1 GS1-128 Bar Code Start Character A




Figure 5.4.3.1 - 2 illustrates the encoding of the symbol character value 35, which represents data character C in code sets A or B or the digits 35 in code set C.

Figure 5.4.3.1 - 2 Symbol Character Value 35





Figure 5.4.3.1 - 3 GS1-128 Bar Code Stop Character



5.4.3.2. Data Character Encodation

Code 128 has three character sets, which are shown in Figure 5.4.3.2 - 1 as code sets A, B, and C.

GS1-128 Symbology specifies a character subset of ISO/IEC 646 International Reference Version to ensure international compatibility. For more information see Figure 7.12 - 1.

The symbol character bar (dark bar) and space (light bar) patterns shown in Figure 5.4.3.2 - 1 represent the data characters listed under the columns for code set A, B, or C. The choice of code set depends on the Start Character, the use of code A, code B, or code C characters, or the shift character. If the symbol begins with Start Character A, then code set A is defined initially. Code set B and code set C are similarly defined by beginning the symbol with Start Character B or C, respectively. The code set can be redefined within the symbol by using code A, code B, and code C characters or the shift character (see Section 5.4.3 for the use of special characters).

The same data may be represented by different Code 128 Symbols through the use of different combinations of Start Character, code set, and shift characters. The individual applications do not specify code sets A, B, or C. Section 5.4.7.7 contains rules to minimise the length of the symbol for any given data.

Each symbol character is assigned a numeric value listed in Figure 5.4.3.2 - 1. This value is used in calculating the Symbol Check Character value. It may also be used to provide a conversion to and from ASCII values (see Section 5.4.7.7).

Figure 5.4.3.2 – 1 Code 128 Character Encodation

Symbol Character Value	Code Set A	ASCII Value for Code Set A	Code Set B	ASCII Value for Code Set B	Code Set C	Element Widths (Modules)						Element Pattern										
						B	S	B	S	B	S	1	2	3	4	5	6	7	8	9	10	11
0	space	32	space	32	00	2	1	2	2	2	2											
1	!	33	!	33	01	2	2	2	1	2	2											
2	"	34	"	34	02	2	2	2	2	2	1											
3	#	35	#	35	03	1	2	1	2	2	3											
4	\$	36	\$	36	04	1	2	1	3	2	2											
5	%	37	%	37	05	1	3	1	2	2	2											
6	&	38	&	38	06	1	2	2	2	1	3											
7	apostrophe	39	apostrophe	39	07	1	2	2	3	1	2											
8	(40	(40	08	1	3	2	2	1	2											

Symbol Character Value	Code Set A	ASCII Value for Code Set A	Code Set B	ASCII Value for Code Set B	Code Set C	Element Widths (Modules)						Element Pattern												
						B	S	B	S	B	S	1	2	3	4	5	6	7	8	9	10	11		
69	ENQ	05	e	101	69	1	1	2	2	1	4	■		■	■			■						
70	ACK	06	f	102	70	1	1	2	4	1	2	■		■	■						■			
71	BEL	07	g	103	71	1	2	2	1	1	4	■			■	■								
72	BS	08	h	104	72	1	2	2	4	1	1	■			■	■						■		
73	HT	09	i	105	73	1	4	2	1	1	2	■				■	■				■			
74	LF	10	j	106	74	1	4	2	2	1	1	■				■	■					■		
75	VT	11	k	107	75	2	4	1	2	1	1	■	■					■					■	
76	FF	12	l	108	76	2	2	1	1	1	4	■	■			■		■						
77	CR	13	m	109	77	4	1	3	1	1	1	■	■	■	■			■	■	■	■			■
78	SO	14	n	110	78	2	4	1	1	1	2	■	■					■			■			
79	SI	15	o	111	79	1	3	4	1	1	1	■				■	■	■	■	■			■	
80	DLE	16	p	112	80	1	1	1	2	4	2	■		■			■	■	■	■	■			
81	DC1	17	q	113	81	1	2	1	1	4	2	■			■	■			■	■	■			
82	DC2	18	r	114	82	1	2	1	2	4	1	■			■			■	■	■	■	■	■	■
83	DC3	19	s	115	83	1	1	4	2	1	2	■		■	■	■					■			
84	DC4	20	t	116	84	1	2	4	1	1	2	■			■	■					■			
85	NAK	21	u	117	85	1	2	4	2	1	1	■			■	■						■		
86	SYN	22	v	118	86	4	1	1	2	1	2	■	■	■	■			■				■		
87	ETB	23	w	119	87	4	2	1	1	1	2	■	■	■	■			■				■		
88	CAN	24	x	120	88	4	2	1	2	1	1	■	■	■	■			■				■		
89	EM	25	y	121	89	2	1	2	1	4	1	■	■			■	■	■	■	■	■			
90	SUB	26	z	122	90	2	1	4	1	2	1	■	■			■	■	■	■	■	■			
91	ESC	27	{	123	91	4	1	2	1	2	1	■	■	■	■			■	■	■	■	■		
92	FS	28		124	92	1	1	1	1	4	3	■		■		■	■	■	■	■	■			
93	GS	29	}	125	93	1	1	1	3	4	1	■		■			■	■	■	■	■	■		
94	RS	30	~	126	94	1	3	1	1	4	1	■				■	■	■	■	■	■			
95	US	31	DEL	127	95	1	1	4	1	1	3	■		■	■			■				■		
96	FNC3		FNC3		96	1	1	4	3	1	1	■		■	■	■						■		
97	FNC2		FNC2		97	4	1	1	1	1	3	■	■	■	■			■				■		
98	SHIFT		SHIFT		98	4	1	1	3	1	1	■	■	■	■			■				■		

5.4.3.4. Special Characters

The last seven characters of code sets A and B (character values 96 to 102) and the last three characters of code set C (character values 100 to 102) are special non-data characters that, though they have particular significance to the bar code reader, have no ASCII character equivalents.

5.4.3.4.1. Code Set and Shift Characters

Code set and shift characters shall be used to change from one code set to another within a symbol. The decoder shall not transmit them.

- Code set characters: Code A, B, or C characters change the symbol code set from the code set previously defined to the new code set, which is defined by the code character. This change applies to all characters following the code set character until either the end of the symbol, another code set character, or the shift character is encountered.
- Shift character: The shift character changes the code set from A to B or B to A for the single character following the shift character. Characters following the affected character shall revert to the code set A or B defined prior to the shift character.

5.4.3.4.2. Function Characters

Function Characters (FNC) provide special operations and application instructions to the bar code reading device.

- The Function 1 Symbol Character (FNC1) shall be subject to the special considerations defined in Section [5.4.3.6](#). An FNC1 in the first position following the Start Character of a Code-128 Symbol is at all times a reserved use, which identifies the GS1 System.
- The Function 2 Character (FNC2) (Message Append) is not used in the GS1 System. It instructs the bar code reader to temporarily store the data from the symbol containing the FNC2 and transmit it as a prefix to the data of the next symbol. This may be used to concatenate several symbols before transmission. This character may occur anywhere in the symbol. Where the sequence of data is significant, provision should be made to ensure reading of the symbols in the correct sequence.
- The Function 3 Character (FNC3) (Initialise) instructs the bar code reader to interpret the data from the symbol containing the FNC3 as instructions for initialisation or reprogramming of the bar code reader. The data from the symbol shall not be transmitted by the bar code reader. This character may occur anywhere in the symbol.
- The Function 4 Character (FNC4) is not used in the GS1 System. In Code 128 Symbols, FNC4 is used to represent an extended ASCII character set (byte values 128 to 255) as specified in ISO 8859-1: Information technology; 8-bit single-byte coded graphical character sets; Part 1: Latin alphabet No.1, or otherwise in an application specification. If a single FNC4 is used, the value 128 is added to the ASCII value of the following data character in the symbol. A shift character may follow the FNC4 if it is necessary to change the code set for the following data character. Subsequent data characters revert to the standard ASCII set. If two consecutive FNC4s are used, the value 128 is added to the ASCII value of the following data characters until two further consecutive FNC4s are encountered or the end of the symbol is reached. If, during this sequence of extended ASCII encodation, a single FNC4 is encountered, it is used to revert to standard ASCII encodation for the next data character only. Shift and code set characters shall have their normal effect during such a sequence. The default reference character set for extended ASCII values 128 to 255 is the corresponding half of ISO 8859-1, Latin alphabet 1, but application specifications may define or reference alternative sets corresponding to byte values 128 to 255.

5.4.3.5. Start and Stop Characters

- Start Characters A, B, and C define the corresponding code set to be used initially in the symbol.
- The Stop Character is common to all code sets.
- The decoder shall not transmit Start and Stop Characters.

5.4.3.6. Symbol Check Character

The Symbol Check Character shall be included as the last symbol character before the Stop Character. Section [5.4.7.6.1](#) defines the algorithm for its calculation. The Symbol Check Character shall not be represented in the Human Readable Interpretation nor shall it be transmitted by the decoder.

5.4.3.7. GS1-128 Symbology Start Pattern

The GS1-128 Symbology has special double character start patterns consisting of Start (A, B, or C) and FNC1. These special Start Characters differentiate GS1-128 Bar Codes from the more generalised Code 128 Symbols.

In other words, a Code 128 Symbol, which begins with one of the GS1-128 Symbology double character start patterns, is always a GS1-128 Bar Code; a Code 128 Symbol, which does not begin with this start pattern, is never a GS1-128 Bar Code.

A Function 1 Symbol Character (FNC1) may be the Symbol Check Character (in less than 1 percent of cases). It is also used as a Separator Character, when appropriate, if Application Identifiers (AIs) and their data fields are concatenated into a single bar code.

- Start A begins the GS1-128 Symbol data encodation according to character set A.
- Start B begins the GS1-128 Symbol data encodation according to character set B.

Start C begins the GS1-128 Symbol data encodation according to character set C. Start Character C should always be used when the data inclusive of the AI begins with four or more numeric characters.

5.4.3.8. Relationship of Symbol Character Value to ASCII Value (Informative)

In order to convert symbol character value (S) to ASCII decimal value or vice versa, the following relationships are applicable for code set A and code set B.

- Code set A
 - If:** $S \leq 63$
 - Then:** ASCII value = $S + 32$
 - If:** $64 \leq S \leq 95$
 - Then:** ASCII value = $S - 64$
- Code set B
 - If:** $S \leq 95$,
 - Then:** ASCII value = $S + 32$

The resulting values are shown in Figure 5.4.3.2 – 1.

- ✔ **Note:** As described in Section [5.4.3](#), the Function 4 Character (FNC4) is not used in the GS1 System. However, the presence of FNC4 in Code 128 Symbols has the effect of adding 128 to the ASCII value of the subsequent data character or characters derived from the rules given above.

5.4.4. Dimensional Requirements

GS1-128 Bar Codes shall conform to the dimensions in the subsections that follow.

5.4.4.1. Minimum Width of a Module (X-Dimension)

The minimum X-dimension is defined by the application specification and requirements (see Section 5.5), while considering the equipment available for symbol production and scanning. For GS1-128 Bar Codes, the absolute minimum X-dimension is 0.249 millimetre (0.0098 inch). The maximum X-dimension is 1.016 millimetres (0.0400 inch). Application specifications stipulate a target and range of the X-dimension.

The X-dimension shall be constant throughout a given symbol.

5.4.4.2. Quiet Zone

The minimum width of the Quiet Zone to the left and right of the GS1-128 Bar Code is 10x.

5.4.4.3. Maximum Symbol Length

The maximum length of any GS1-128 Bar Code must be within the following limits:

- The physical length, including Quiet Zones, cannot exceed 165.10 millimetres (6.500 inches).
- The maximum number of encoded data characters is 48, including the Application Identifier(s) and Function 1 Symbol Character (FNC1) when used as a Separator Character, but excluding the auxiliary characters and the Symbol Check Character.


5.4.5. Reference Decode Algorithm

Bar code reading systems are designed to read imperfect symbols to the extent that practical algorithms permit. This section describes the reference decode algorithm used in the computation of the decodability value described in *ISO/IEC 15416*.

The algorithm contains the following steps to decode each character:

- Calculate eight width measurements p , e_1 , e_2 , e_3 , e_4 , b_1 , b_2 , and b_3 (see Figure 5.4.5 - 1).

Figure 5.4.5 - 1 Decode Measurements



- Convert measurements e_1 , e_2 , e_3 , and e_4 to normalised values e_1 , e_2 , e_3 , and e_4 , which will represent the integral module width (e_i) of these measurements. The following method is used for the i -th value:
 - If $1,5p/11 \leq e_i < 2,5p/11$, then $E_i = 2$

- If $2,5p/11 \leq e_i < 3,5p/11$, then $E_i = 3$
- If $3,5p/11 \leq e_i < 4,5p/11$, then $E_i = 4$
- If $4,5p/11 \leq e_i < 5,5p/11$, then $E_i = 5$
- If $5,5p/11 \leq e_i < 6,5p/11$, then $E_i = 6$
- If $6,5p/11 \leq e_i < 7,5p/11$, then $E_i = 7$

Otherwise the character is in error.

- Look up the character in the decode table using the four values E1, E2, E3, and E4 as the key (see Figure 5.4.5 – 2).
- Retrieve the self-checking symbol character value V, which is stored in the table with the character. The value V is equal to the sum of the modules for the bars (dark bars) as defined for that character.
- Verify that:

$$(V-1, 75)p / 11 < (b1 + b2 + b3) < (V + 1, 75)p / 11$$

Otherwise the character is in error.

The calculation indirectly uses character parity to detect all decode errors caused by single non-systematic one-module edge errors.

Using these five steps, decode the first character. If it is a Start Character, continue decoding the symbol in the normal forward direction. If it is not a Start Character but decodes as a Stop Character, attempt to decode all subsequent characters in the reverse direction.

After all characters have been decoded, make sure there is a valid Start Character, a valid Stop Character, and that the Symbol Check Character is correct.

Translate the symbol characters into the appropriate data characters from code set A, B, or C according to the Start Character, code characters, and shift characters used in the symbol.

In addition, perform other secondary checks on Quiet Zones, beam acceleration, absolute timing, and dimensions that are appropriate considering the specific reading device and intended application environment.


Note: In this algorithm the symbol is decoded using edge to similar edge measurements (e) and an additional measurement of the sum of the three bar (dark bar) widths.

Figure 5.4.5 – 2 Edge Differences for Decoding Code 128 Symbols

Char. Value	E1	E2	E3	E4	V	Char. Value	E1	E2	E3	E4	V
00	3	3	4	4	6	54	4	2	2	3	6
01	4	4	3	3	6	55	4	2	4	5	6
02	4	4	4	4	6	56	6	4	2	3	6
03	3	3	3	4	4	57	4	3	3	2	6
04	3	3	4	5	4	58	4	3	5	4	6
05	4	4	3	4	4	59	6	5	3	2	6
06	3	4	4	3	4	60	4	5	5	2	8
07	3	4	5	4	4	61	4	3	5	5	4
08	4	5	4	3	4	62	7	4	2	2	6
09	4	3	3	3	4	63	2	2	3	4	4

Char. Value	E1	E2	E3	E4	V	Char. Value	E1	E2	E3	E4	V
10	4	3	4	4	4	64	2	2	5	6	4
11	5	4	3	3	4	65	3	3	2	3	4
12	2	3	4	5	6	66	3	3	5	6	4
13	3	4	3	4	6	67	5	5	2	3	4
14	3	4	4	5	6	68	5	5	3	4	4
15	2	4	5	4	6	69	2	3	4	3	4
16	3	5	4	3	6	70	2	3	6	5	4
17	3	5	5	4	6	71	3	4	3	2	4
18	4	5	5	3	6	72	3	4	6	5	4
19	4	3	2	4	6	73	5	6	3	2	4
20	4	3	3	5	6	74	5	6	4	3	4
21	3	4	5	3	6	75	6	5	3	3	4
22	4	5	4	2	6	76	4	3	2	2	4
23	4	3	3	4	8	77	5	4	4	2	8
24	4	2	3	4	6	78	6	5	2	2	4
25	5	3	2	3	6	79	4	7	5	2	6
26	5	3	3	4	6	80	2	2	3	6	6
27	4	3	4	3	6	81	3	3	2	5	6
28	5	4	3	2	6	82	3	3	3	6	6
29	5	4	4	3	6	83	2	5	6	3	6
30	3	3	3	3	6	84	3	6	5	2	6
31	3	3	5	5	6	85	3	6	6	3	6
32	5	5	3	3	6	86	5	2	3	3	6
33	2	2	4	5	4	87	6	3	2	2	6
34	4	4	2	3	4	88	6	3	3	3	6
35	4	4	4	5	4	89	3	3	3	5	8
36	2	3	5	4	4	90	3	5	5	3	8
37	4	5	3	2	4	91	5	3	3	3	8
38	4	5	5	4	4	92	2	2	2	5	6
39	3	2	4	4	4	93	2	2	4	7	6
40	5	4	2	2	4	94	4	4	2	5	6
41	5	4	4	4	4	95	2	5	5	2	6
42	2	3	3	4	6	96	2	5	7	4	6
43	2	3	5	6	6	97	5	2	2	2	6
44	4	5	3	4	6	98	5	2	4	4	6
45	2	4	4	3	6	99	2	4	4	5	8
46	2	4	6	5	6	100	2	5	5	4	8

Char. Value	E1	E2	E3	E4	V		Char. Value	E1	E2	E3	E4	V
47	4	6	4	3	6		101	4	2	2	5	8
48	4	4	4	3	8		102	5	2	2	4	8
49	3	2	4	6	6		103	3	2	5	5	4
50	5	4	2	4	6		104	3	2	3	3	4
51	3	4	4	2	6		105	3	2	3	5	6
52	3	4	6	4	6		Stop _A	5	6	4	2	6
53	3	4	4	4	8		Stop _B	3	2	2	4	6

 **Note:** Stop_A values are for decoding in a forward direction. Stop_B values apply to the first six elements of the Stop Character starting at the rightmost side when scanned in a reverse direction.

5.4.6. Symbol Quality

5.4.6.1. General

ISO/IEC 15416 defines a standardised methodology for measuring and grading bar codes. Code 128 Symbols shall be evaluated according to that standard. The reference decode algorithm defined in Section [5.3.1.4](#) shall be used for the assessment of the decode and decodability parameters under *ISO/IEC 15416*.

 **Note:** For GS1-128 Bar Code minimum quality levels, refer to Section [5.4.7](#).

5.4.6.2. Decodability

Decodability is a measure of how closely the decode algorithm measurement values approach those in a theoretically perfect symbol. Thus, decodability is a parameter that measures how closely the Scan Reflectance Profile is to approaching decode failure for a given printed symbol.

For the calculation of the decodability value V, the following provisions apply, which supplement those described in *ISO/IEC 15416* for edge to similar edge decodable symbologies:

Substitute V1 for VC in the formula $VC = K / (S / 2n)$

Where: **K** = the smallest difference between a measurement and a reference threshold

N = 11 (number of modules in a symbol character)

S = total width of the character

Calculate V2

$$1,75 - (ABS((Wb \times 11/S) - M))$$

$$V2 =$$

$$1,75$$

Where: **M** = number of dark modules in the character

S = total width of the character

Wb = sum of the bar (dark bar) widths in the character

ABS = mathematical term for taking the absolute of the calculation that follows it

VC is the lesser of V1 and V2.

The Stop Character includes an additional terminating bar (dark bar). For the purpose of measuring decodability, the Stop Character should be checked twice: first using the six leftmost elements and then using the six rightmost elements from right to left. Both sets of six elements are equivalent in width to a standard character.

5.4.6.3. Quiet Zone Measurement

The Quiet Zones to the right and left of the GS1-128 Bar Code are compulsory. Both Quiet Zones have a minimum width of 10x.

ISO/IEC 15416 allows for additional pass/fail criteria to be stipulated by a symbology specification. In the case of a GS1-128 Bar Code, a minimum Quiet Zone of 10Z is specified. Both left and right Quiet Zones on each Scan Reflectance Profile (SRP) under *ISO/IEC 15416* shall be measured and graded as follows:

Quiet Zone \geq 10Z: Grade 4 (A)

Quiet Zone < 10Z: Grade 0 (F)

Where Z = the average measured width of the narrow bars (dark bars) and spaces (light bars) (one module) in the symbol

5.4.6.4. Transmitted Data

Transmitted data from a decoded GS1-128 Bar Code shall comprise the byte values of the data characters. It is prefixed by the symbology identifier]C1, if used. The Start and Stop Characters, function characters, code set and shift characters, and Symbol Check Character shall not be included in the transmitted data.



Note: For GS1-128 Symbology implementation, see Section [5.4.7](#).

5.4.7. GS1-128 Symbology Application Parameters

5.4.7.1. Symbol Height

For GS1-128 Bar Codes used in general distribution, the minimum height of the bars (dark bars) in the symbol is 31.75 millimetres (1.250 inches). The actual symbol height used depends on the specific application requirements.

5.4.7.2. Symbol Length

The dimensions of the GS1-128 Bar Code depend on the number of characters encoded:

1 Start Character x 11 modules = 11

Function 1 Symbol Character (FNC1) x 11 modules = 11

1 Symbol Check Character x 11 modules = 11

1 Stop Character x 13 modules = 13

N symbol characters x 11 modules = 11N

(11N + 46) modules

Where N is the number of symbol characters, any auxiliary characters (shift and code characters) embedded in the data are included.

A module is equal to the X-dimension of the symbol.

Character set C allows two digits to be encoded in one symbol character. Thus, numeric data can be encoded with twice the density of other data when using character set C.

In addition, Quiet Zones to the right and left of the bar code are compulsory and both have widths of 10 modules.

Thus total symbol length, including Quiet Zones, is: **(11N + 66) modules = (11N + 66) x**

5.4.7.3. Maximum Symbol Length

Two parameters have to be taken into consideration for defining the maximum length of a GS1-128 Bar Code: the physical length, which depends on the number of characters encoded and the module width (or X-dimension) used, and the number of data characters encoded excluding the auxiliary characters.

The maximum length of any GS1-128 Bar Code must be within the following limits:

The physical length, including Quiet Zones, cannot exceed 165.10 millimetres (6.500 inches).

The maximum number of encoded data characters is 48, including the Application Identifier(s) and Function 1 Symbol Character (FNC1) when used as a Separator Character, but excluding the auxiliary characters and the Symbol Check Character.

5.4.7.4. Human Readable Interpretation

For Human-Readable Interpretation Rules see Section 4.12. For HRI Rules specific to Regulated Healthcare Retail Consumer Trade Items, see Section 4.12.1.

5.4.7.5. Transmitted Data (FNC1)

The following GS1-128 Symbology implementation specifications are in accordance with *ISO/IEC 15417 Appendix 2* for transmitted data:

- The Function 1 Symbol Character (FNC1) may validly occur as the Symbol Check Character.
- FNC1 in the third or subsequent character position is transmitted as the ASCII character 29 (GS).
- Symbols using FNC1 in the first data position should have symbology identifiers enabled.

When FNC1 is used in the first position it shall not be represented in the transmitted message, although its presence is indicated by the use of modifier value 1 in the symbology identifier.

5.4.7.6. Additional Features of Code 128 (Normative)

5.4.7.6.1. Symbol Check Character

The Code 128 Symbol Check Character shall be calculated according to the following rules.

1. Retrieve the symbol character value from Figure 5.4.3.2 - 1.
2. Each symbol character position is given a weight. The Start Character is weighted 1. Then, beginning on the left with the first symbol character following the Start Character, the weights are 1, 2, 3, and 4 to...n for all subsequent symbol characters up to, but not including, the Symbol Check Character itself; n denotes the number of symbol characters representing data or special information in the symbol, exclusive of the Start and Stop Characters and Symbol Check Character.



Note: Both the Start Character and the first symbol character following the Start Character (the Function 1 Symbol Character (FNC1) for all GS1-128 Bar Codes) are weighted by one.

3. Each symbol character value is multiplied by its weight.
4. The products of the calculations in step 3 are totalled.
5. The sum of the products is divided by 103.
6. The remainder derived from the calculation in step 5 is the symbol character value of the Symbol Check Character.

Figure 5.4.7.6.1 - 1 shows how to calculate the Symbol Check Character value for the batch number 2503X using the GS1-128 Bar Code.

Figure 5.4.7.6.1 - 1 Symbol Check Character Value Calculation Example

Start C FNC1 10* 25 03 Code B X [Symbol Check Character] Stop

Characters	Start C	FNC1	10	25	03	Code B	X
Character values (Step 1)	105	102	10	25	3	100	56
Weights (Step 2)	1	1	2	3	4	5	6
Products (Step 3)	105	102	20	75	12	500	336
Sum of products (Step 4)	1150						
Divide by 103 (Step 5)	1150 / 103 = 11						
Remainder = Symbol Check Character value	17						

* Application Identifier (10) is defined as batch or lot number.

The Symbol Check Character shall be positioned immediately following the final data or special character and before the Stop Character.

Note: The Symbol Check Character shall not be shown in the Human Readable Interpretation.

5.4.7.7. Use of Start, Code Set, and Shift Characters to Minimize Symbol Length (Informative)

The same data may be represented by different GS1-128 Bar Codes through the use of different combinations of Start, code set, and shift characters.

The following rules should normally be implemented in printer control software to minimise the number of symbol characters needed to represent a given data string (and, therefore, reduce the overall symbol length).

- Determine the Start Character:
 - D If the data consists of two digits, use Start Character **C**.
 - If the data begins with four or more numeric data characters, use Start Character **C**.
 - If an ASCII symbology element (e.g., NUL) occurs in the data before any lowercase character, use Start Character **A**.
 - Otherwise, use Start Character **B**.
- If **Start Character C** is used and the data begins with an odd number of numeric data characters, insert a code set **A** or code set **B** character before the last digit, following rules 1c and 1d to determine between code sets **A** and **B**.
- If four or more numeric data characters occur together when in code sets **A** or **B** and:
 - If there is an even number of numeric data characters, then insert a code set **C** character before the first numeric digit to change to code set **C**.

- If there is an odd number of numeric data characters, then insert a code set **C** character immediately after the first numeric digit to change to code set **C**.
 - When in code set **B** and an ASCII symbology element occurs in the data:
 - If following that character, a lowercase character occurs in the data before the occurrence of another symbology element, then insert a shift character before the symbology element.
 - Otherwise, insert a code set **A** character before the symbology element to change to code set **A**.
 - When in code set **A** and a lowercase character occurs in the data:
 - If following that character, a symbology element occurs in the data before the occurrence of another lowercase character, then insert a shift character before the lowercase character.
 - Otherwise, insert a code set **B** character before the lowercase character to change to code set **B**.
 - When in code set **C** and a non-numeric character occurs in the data, insert a code set **A** or code set **B** character before that character, and follow rules 1c and 1d to determine between code sets **A** and **B**.
- ✓ **Note:** In these rules, the term “lowercase” is used for convenience to mean any code set **B** character with Code 128 Symbol character values 64 to 95 (ASCII values 96 to 127) (e.g., all lowercase alphanumeric characters plus `{}`~DEL). The term “symbology element” means any code set **A** character with Code 128 Symbol character values 64 to 95 (ASCII values 00 to 31).
- ✓ **Note:** If the Function 1 Symbol Character (FNC1) occurs in the first position following the Start Character, or in an odd-numbered position in a numeric field, it should be treated as two digits for the purpose of determining the appropriate code set.

5.4.7.8. Guidelines for the Use of Code 128 (Informative)

5.4.7.8.1. Autodiscrimination Compatibility

Code 128 Symbols may be read by suitably programmed bar code readers that have been designed to autodiscriminate these symbols from other symbologies. Code 128 Symbology is fully distinguishable from and compatible with the following linear symbologies:

- ITF (Interleaved 2 of 5)
- Codabar
- Code 39
- Code 93
- EAN/UPC
- Telepen
- GS1 DataBar

5.5. Bar Code Production and Quality Assessment

5.5.1. Introduction

This section has been evolving to meet the changes to data carriers and their use within the GS1 System. Some of those changes are, for example, dimension requirements, the introduction of new

symbols (e.g., GS1 DataBar and Composite Component), and the shift from the use of analogue Film Masters to digital bar code files.

Consideration should be given to how these changes affect bar code production and the maintenance of quality in the production process.

5.5.2. GS1 System Symbol Specification Tables

Over the years, operational requirements of GS1 System users have influenced the dimensional specifications of GS1 System symbols, and these dimensional specifications have in turn influenced the development of scanning system optics and printing processes. The GS1 System Symbol Specification Tables (SSTs) relate to the application areas defined in Section 2. Each SST provides the following bar code specification detail:

- The bar code(s) specified by the GS1 System for each application area
- The minimum, target, and maximum X-dimension (narrow element width) for the symbol, based on the scanning environment
- The minimum and target bar code height, based on the scanning environment
- The Quiet Zone width and, for primary/secondary symbols, the minimum and maximum separation between the two symbols

✓ **Note:** These measurements are expressed as multiples of the X-dimension in the form nX .

- The minimum ISO quality specification

✓ **Note:** Expressed as **g.g/aa/www**, where **g.g** is the minimum overall symbol grade to one decimal place (on a 4.0 scale), **aa** is the effective measuring aperture in thousandths of an inch, and **www** is the wavelength of the light source in nanometres.

✓ **Note:** Please refer to Section 2 for any specific application standard (such as Section 2.1.2.4, Fixed Measure - Regulated Healthcare Retail Consumer Trade Items, and Section 2.1.5, Fixed Measure - Direct Part Marking) that may supplement or supersede these symbol specification tables for specific application areas.

Before determining the exact symbol specification required, additional factors, such as scanning environment, SHALL be considered. These are summarised in Section [5.5.2.1](#).

5.5.2.1. Role of the Symbol's Dimensional Specifications

The three major dimensional specifications are the symbol's nominal (target) X-dimension, the symbol's allowable X-dimension range, and the symbol's minimum bar height. These dimensional characteristics are always specified based on the operating environment. The X-dimension target and range determine the scanner's operating range (field of view). The bar code's height along with its X-dimension target and range help determine the ergonomic aspects of product handling when using a scanner. These dimensional specifications are critical components of the efficient use of all scanners.

5.5.2.2. Omnidirectional Scanning and the Term Magnification (X-Dimension)

The EAN/UPC Symbology was originally designed for omnidirectional scanners. Based on this type of scanner, the specifications include a fixed relationship between the symbol's nominal (target) width and height. The term "symbol magnification" has been used extensively to refer to this fixed relationship. For example, EAN-13 Symbols have a fixed relationship between the symbol target width and height (100 percent magnification) based on the symbol's bar height of 22.85 millimetres (0.900 inches) and a target X-dimension of 0.330 millimetre (.0130 inch). The term magnification has been

used to refer to a range of magnification percentages below and/or above a target value that are specified based on the omnidirectional scanning environment. The Symbol Specification Tables (SSTs) do not use magnification values and instead list the target, minimum, and maximum values for the symbol's X-dimension and height.

5.5.2.3. Laser versus Image Based Scanning

Most scanners based on laser technology can scan all linear symbologies in the GS1 System. New laser and linear array scanners are even capable of scanning GS1 DataBar and Composite Component Symbols. 2D Imaging technology, such as array scanners and vision systems, are capable of scanning all symbols in the GS1 System, including GS1 approved 2D symbols (GS1 DataMatrix and GS1 QR Code). Note that linear imagers, like laser scanners, cannot scan approved 2D symbols; only 2D or array imaging scanners can scan GS1 approved 2D symbols, as well as camera based or vision systems.

5.5.2.4. Printing Considerations

The functional and operative bands provide printers and labellers with the flexibility needed to produce quality symbols over a wide range of processes. Once a scanning operational environment is determined and the allowable specification range is known, the printer should be consulted for guidance on:

- The minimum recommended symbol size based on printing press or print characterisation tests
- Colour/substrate considerations (e.g., separate print station for symbol or double ink layer)
- The optimum orientation of the symbol on the printed web (the direction of movement of the media in relation to a printing plate on a printing press)
- Direct part marking, such as is done by dot peening on items, requires special considerations for material properties
- Laser or chemically etched parts with low contrast or light marked elements on a dark background (e.g., circuit boards and electronic components, medical instruments, surgical implants)
- High-speed ink jet printed parts and components where the marked dots cannot form a scannable linear symbol
- Very small items that require a symbology with a square aspect ratio and/or cannot be marked within the allocated packaging space by existing GS1 DataBar and Composite symbols

5.5.2.5. Packaging Considerations

Once a scanning operational environment is determined and the allowable symbol characteristics are known, the package designer should be consulted to:

- Ensure the symbol will not be obstructed by other graphics or package design parameters (e.g., folds, creases, corner wraps, flaps, laminates, embossed logos/patterns, text)
- Ensure that only the symbol intended for scanning will be scanned (e.g., obscure all symbols on the individual units within larger trade items so that the individual units' symbols do not scan instead of the larger unit's symbol)

Section 6 contains complete information on symbol placement criteria to meet quality and ergonomic needs.

5.5.2.6. Operative Scanning Environments for GS1 System Symbols

The application where the bar code will be used SHALL be determined prior to locating the correct Symbol Specification Table (SST) entry. Figure 5.5.2.6 - 1 provides a cross-reference for all system applications defined in Section 2. Use the “See SST(s) #” column to find the SST appropriate for the application area. Because most application areas provide a reference to two Symbol Specification Tables based on the operative scanning environment, a decision must be made between the two. See the decision tree in Figure 5.5.2.6.1 - 2 to determine the correct Symbol Specification Table.

Figure 5.5.2.6 - 1 Areas of GS1 System Application

Application Areas	See Section	See SST(s) #	Read Before Reviewing Symbol Specification Table
Fixed Measure Trade Items – Packages/Containers Scanned in General Retail at POS	2.1.2.1	1 or 3	EAN-13, UPC-A, EAN-8, UPC-E, GS1 DataBar Omnidirectional, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded and GS1 DataBar Expanded Stacked Symbols only
Fixed Measure Trade Items – Books and Serials	2.1.2.1.4 and 2.1.2.1.5	1 or 3	EAN/UPC Symbols only
Fixed Measure Trade Item - Loose Produce Trade Items Scanned at POS	2.1.2.2	1	GS1 DataBar Omnidirectional, GS1 DataBar Stacked Omnidirectional, EAN/UPC
Fixed Measure Trade Items – Packages/Containers NOT Scanned at POS	2.1.2.6	2 or 4	
Fixed Measure Trade Items – Trade Item Packed in Several Physical Units NOT Scanned at POS	2.1.3	2 or 4	GS1-128, GS1 DataBar Symbols
Fixed Measure Trade Items – Restricted Distribution	2.1.6	1 or 3	
Fixed Measure Trade Items – Regulated Healthcare Retail Consumer Trade Items	2.1.2.5	8 or 10	GS1-128, GS1 DataMatrix. GS1 DataBar, EAN/UPC, ITF-14, Composite Component
Fixed Measure Trade Items - Regulated Healthcare Non-Retail Consumer Trade Items	2.1.2.4 and 2.1.2.5	6 or 8	GS1-128, GS1 DataMatrix. GS1 DataBar, EAN/UPC, ITF-14, Composite Component
Variable Measure Fresh Food Trade Items Scanned at Point-of-Sale Using GTIN	2.1.7.2.1	1	GS1 DataBar Expanded, GS1 DataBar Expanded Stacked only
Variable Measure Trade Items Scanned at Point-of-Sale Using Restricted Circulation Numbers	2.1.7.2.2	1	EAN-13 and UPC-A Symbols only
Variable Measure Trade Items – Packages/Containers NOT Scanned in General Retail at POS	2.1.5	2 or 4	GS1-128, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked
POS Trade Item Attributes – Using Secondary EAN/UPC-2 or EAN/UPC-5 Add-On Symbols	2.1.2.1.5	1	Use the X-dimension specified for the primary EAN/UPC Symbol
Trade Item Attributes – Using Secondary Symbols	2.1.2	2 or 4	Use the X-dimension specified for the primary symbol

Application Areas	See Section	See SST(s) #	Read Before Reviewing Symbol Specification Table
Trade Item Extended Packaging (General Retail Trade Items)	2.1.8	1 Addendum	GS1 DataMatrix or GS1 QR Code .
Trade Item Extended Packaging (Regulated Healthcare Trade Items)	2.1.8	6, 8, or 10	GS1 DataMatrix
Logistics – Mandatory SSCC	2.2.1	5	GS1-128 Symbols only
Logistics – Logistic Unit Element Strings	2.2.1	5	GS1-128 Symbols only
Assets – Global Returnable Asset Identifier	2.3.1	9	GS1-128 Symbols only
Assets – Global Individual Asset Identifier	2.3.2	9	GS1-128 Symbols only
Locations (Global Location Numbers) or Postal Codes	2.4	9	GS1-128 Symbols only
Global Service Relation Numbers	2.5	11	GS1-128, GS1 DataMatrix Symbols
Coupons – Restricted Geographic Distribution Outside USA or Common Currency Area identification	2.6.3 and 2.6.4	1	EAN-13 Symbols only
Coupons – Restricted Geographic Distribution Inside USA	2.6.5, 2.6.6, 2.6.7	4	<i>See Guidelines for Supply Chain Identification</i> GS1 DataBar Expanded and GS1 DataBar Expanded Stacked
Refund Receipts – Restricted Geographic Distribution	2.6.8	1	EAN-13 Symbols only
Electronic Serial Identifier for Cellular Mobile Telephones	2.6.9	4	GS1-128 Symbols only
Company Internal Application Using EAN/UPC Symbols	2.1.6 and 2.1.7	1	EAN-13, UPC-A, and UPC-E Symbols only
Internal Application Using GS1-128 Symbols	2.6.14	2 or 4	GS1-128 Symbols only
Payment Slips	2.6.10	4	GS1-128 Symbols only
Customer Specific Articles	2.6.11	4	
Custom Trade Item	2.12	4	GS1-128 Symbols only
Direct Part Marking	2.1.5	7	GS1 DataMatrix




Note: GS1 DataBar has the capacity to carry GTIN-14, GTIN-14 is not intended for use at Point of Sale (POS) applications; therefore GS1 DataBar symbols for POS must not encode GTIN-14.

5.5.2.6.1. GS1 System Scanner Functional Operative Bands

Symbol selection and specifications for AIDC Application Standards are centralized in the Symbol Specification Tables. In establishing X-dimension specifications for Symbol Specification Tables, the Scanner Functional Operative Bands below are normative as they illustrate X-dimension ranges

deployed by industry based on GS1 standards. The twelve scanner functional bands that have evolved to meet user needs are illustrated in Figure 5.5.2.6.1 - 1.

Figure 5.5.2.6.1 - 1 GS1 Scanner Functional Operative Bands



Note: Figure not to scale and target size for each functional band can be found in the Symbol Specification Tables (see Section [5.5.2.7](#))


The Scanner Functional Bands

- The Omnidirectional Scanners for General Retail/POS band is primarily intended for General Retail Consumer Trade Items to provide orientation-free scanning in high-volume check-out lanes. Scanners are designed to read over-square symbols such as EAN/UPC and GS1 DataBar Retail POS Family. The approximate average distance between scanner and symbol is 100 millimetres (4 inches).
- The Linear Bar Codes for Imaging Scanners for Retail Pharmacies band is intended for regulated healthcare consumer trade items sold in a pharmacy or apothecary that is a separate retail store or a “controlled” area for distribution of healthcare trade items inside a larger retail operation. This band allows for the use of 2D symbols but this functional band shows the X-dimension ranges used for linear bar codes. Over the counter trade items that

are sold in retail pharmacy but also general retail are marked according to general retail scanning specifications.

- The Fixed Scanners in General Distribution band is primarily intended to facilitate automated scanning of trade items packaged for transport and logistic units using fixed mount scanners. In this environment it is essential to maintain symbol height and location to achieve acceptable scan rates.
- Linear bar codes for both Retail and General Distribution band covers trade items in specific packaging suitable for transport purposes in General Distribution Scanning, but that are also scanned as General Retail Consumer Trade Items. See the overlap area between EAN/UPC Retail and General Distribution (Retail/GD) in Figure 5.5.2.6.1 - 1.
- The Imaging Scanners for Non-Retail Regulated Healthcare trade items band is intended for non-retail regulated healthcare consumer trade items sold outside of the retail channel. For example these X-dimension bands should be used for products destined for hospitals or nursing homes that will never be scanned in a retail pharmacy.
- The Linear bar codes for hand scanning band is intended for non-retail trade items using a linear bar code.
- The Composite Component bar codes for hand scanning band is intended for non-retail trade items using Composite Component bar codes which are, in effect, a multi-row 2D linear bar code. In general, the rule is that Composite Components shall be printed at the same X-dimension as their linear host. GS1 DataMatrix Symbols shall be printed at X-dimensions that are 50 percent greater than corresponding linear symbols with Composite Components. Therefore, the bands for linear symbols and Composite Components are very similar in X-dimension and if the same scanner types are chosen, as in the case of Composite Symbols, the bands become one.
- The 2D Bar Codes for Automated Scanning by Imaging Scanners in General Distribution band has been added to show the X-dimension band used by those who support general distribution of regulated healthcare consumer trade items which may be marked with GS1 DataMatrix.
- 2D Bar Codes for Imaging Scanners for Retail Pharmacy band is intended for regulated healthcare consumer trade items sold in a pharmacy or apothecary that is a separate retail store or a “controlled” area for distribution of healthcare trade items inside a larger retail operation. This band allows for the use of linear symbols but this functional band shows the X-dimension ranges used for 2D bar codes. Over the counter trade items that are sold in retail pharmacy but also general retail are marked according to general retail scanning specifications.
- Today, there is no functional band for mobile devices as the variables of symbol selection, data, operative scanning environment, and allowable symbol specifications for size would require a detailed table solely for mobile devices. At this time, the assumption for mobile devices is that they will support all currently approved symbols, symbol data scenarios, and symbol size specifications however where testing and/or practical experience shows a constraint, this will be addressed in GS1 standards.

Figure 5.5.2.6.1 - 2 GS1 Symbology Operational Environment Decision Tree





Note: If an item is a General Retail Consumer Trade Item and Regulated Healthcare Retail Consumer Trade Item then the bar code marking for general retail is required at a minimum.

Figure 5.5.2.6.1 – 3: Summary of the Symbol Specification Tables per following Figure 5.5.2.6.1 - 2 GS1 Symbology Operational Environment Decision Tree

Symbol Spec. Tables	General Retail POS	Retail Pharmacy	* Non-Retail Pharmacy	Non-Retail Non-Healthcare	General Distribution	Direct Part Marking	Logistics Unit (SSCC)	GIAI, GRAI, GLN	GSRN
Table 1	Yes				No				
Table 2				Yes	Yes				
Table 3	Yes				Yes				
Table 4				Yes	No				
Table 5					Yes		Yes		
Table 6			Yes		No				
Table 7			Yes	Yes	No	Yes			
Table 8		Yes	Yes		Yes				
Table 9					No			Yes	
Table 10		Yes			No				
Table 11									Yes

* Table 6 should be used for products scanned at bedside.

5.5.2.7. GS1 System Symbol Specification Tables

In order to find the correct bar code specification, you must:

- Find the appropriate GS1 System application area using Figure 5.5.2.6 - 1.
- If the application area references two Symbol Specification Tables, use the decision tree in Figure 5.5.2.6.1 - 2 to determine which one to use.

Figure 5.5.2.7 - 1 provides a quick reference list of the symbol quality parameters depending on their type and their application.

Figure 5.5.2.7 - 1 Quick Reference on Symbol Quality

Symbology	Application or ID Code	ISO (ANSI) Symbol Grade	Aperture	Wavelength
EAN/UPC	GTIN-8	1.5 (C)	6 mils	670 nm +/-10
EAN/UPC	GTIN-12	1.5 (C)	6 mils	670 nm +/-10
EAN/UPC	GTIN-13	1.5 (C)	6 mils	670 nm +/-10
GS1-128	Coupon Extended Code	1.5 (C)	6 mils	670 nm +/-10
GS1-128	GTIN-12, GTIN-13, GTIN-14	1.5 (C)	10 mils	670 nm +/-10
GS1-128	SSCC	1.5 (C)	10 mils	670 nm +/-10
GS1-128	Small Shipping Packages	1.5 (C)	10 mils	670 nm +/-10
GS1 DataBar Expanded GS1 DataBar Expanded Stacked	Small Shipping Packages	1.5 (C)	10 mils	670 nm +/-10
ITF-14 (<0.635 mm (0.025 in.) X)	GTIN-12, GTIN-13, GTIN-14	1.5 (C)	10 mils	670 nm +/-10

Symbology	Application or ID Code	ISO (ANSI) Symbol Grade	Aperture	Wavelength
ITF-14 (≥0.635 mm (0.025 in.) X)	GTIN-12, GTIN-13, GTIN-14	0.5 (D)	20 mils	670 nm +/-10
GS1 DataBar and Composite	GTIN-8, GTIN-12, GTIN-13,GTIN-14 and other AIs	1.5 (C)	6 mils	670 nm +/-10
GS1 DataMatrix	Direct Part Marking, Regulated Healthcare Retail or Non-Retail Consumer Trade Items Extended Packaging	1.5 (C)	See Symbol Specification Tables 6, 7, 8 and 10 for values.	670 nm +/-10
GS1 QR Code	Extended Packaging limited use to AI (8200) in association with mandatory GTIN-8, GTIN-12, or GTIN-13	1.5 (C)	See Symbol Specification Table 1 Addendum for values.	670 nm +/-10



Note: An EAN/UPC-based symbol SHALL be verified using a 6 mils (0.006 inch) aperture, a 670 nanometres +/-10 nanometres wavelength of light, and requires a minimum symbol grade of 1.5 (overall symbol grade on a 4.0 scale) equivalent to a “C” under the ANSI X3.182 standard. In the Symbol Specification Tables that follow, as well as on a typical bar code purchase order, this is expressed as 1.5/06/670.

Figure 5.5.2.7 - 2 GS1 System Symbol Specification Table 1

Primary Symbol(s) Specified	X-Dimension mm (inches)			Tol.	** Minimum Symbol Height for Given X mm (inches)			Tol.	Quiet Zone		Minimum Quality Specification
	* Minimum	Target	Maximum		For Minimum X-dimension	For Target X-dimension	For Maximum X-dimension		Left	Right	
EAN-13	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	± 0.025 (0.001")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	3X	11X	7X	1.5/06/670
EAN-8	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		14.58 (0.574")	18.23 (0.718")	36.46 (1.435")		7X	7X	1.5/06/670
UPC-A	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		18.28 (0.720")	22.85 (0.900")	45.70 (1.800")		9X	9X	1.5/06/670
UPC-E	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		18.28 (0.720")	22.85 (0.900")	45.70 (1.800")		9X	7X	1.5/06/670
GS1 DataBar Omnidirectional ****	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		12.14 (0.478")	15.19 (0.598")	30.36 (1.195")		None	None	1.5/06/670
GS1 DataBar Stacked Omnidirectional *** ****	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		25.10 (0.988")	31.37 (1.235")	62.70 (2.469")		None	None	1.5/06/670
GS1 DataBar Expanded	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		8.99 (0.354")	11.23 (0.442")	22.44 (0.883")		None	None	1.5/06/670
GS1 DataBar Expanded Stacked *****	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.75 (0.738")	23.44 (0.923")	46.86 (1.845")	None	None	1.5/06/670		

Primary Symbol(s) Specified Plus Add-on 2 or 5	X-Dimension mm (inches)			Tol.	** Minimum Symbol Height for Given X mm (inches)			Tol.	Quiet Zone		Min. Quality Spec.		
	* Minimum	Target	Maximum		For Min. X-dimension	For Target X-dimension	For Max. X-dimension		Left	Right			
EAN-13 + 2	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	± 0.025 (0.001")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	3X	11X	7X	12X	5X	1.5/06/670
EAN-13 + 5	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		18.28 (0.720")	22.85 (0.900")	45.70 (1.800")		11X	7X	12X	5X	1.5/06/670
UPC-A + 2	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		18.28 (0.720")	22.85 (0.900")	45.70 (1.800")		9X	9X	12X	5X	1.5/06/670
UPC-A + 5	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		18.28 (0.720")	22.85 (0.900")	45.70 (1.800")		9X	9X	12X	5X	1.5/06/670
UPC-E + 2	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		18.28 (0.720")	22.85 (0.900")	45.70 (1.800")		9X	7X	12X	5X	1.5/06/670
UPC-E + 5	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")		18.28 (0.720")	22.85 (0.900")	45.70 (1.800")		9X	7X	12X	5X	1.5/06/670



Note: See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.

- * These bar codes may only be printed using an X-dimension below 0.264 millimetre (0.0104 inch) or 80 percent magnification under the following conditions:
- The allowance for X-dimensions between 0.249 millimetre (0.0098 inch) or 75 percent magnification and 0.264 millimetre (0.0104 inch) or 80 percent magnification is only applicable to on demand (e.g., thermal, laser) print processes. For all other printing processes, an X-dimension of 0.264 millimetre (0.0104 inch) is attainable and is the minimum allowable size.
 - When printing a minimum symbol with any method of printing, the area provided for printing the symbol and the required Quiet Zone should never be less than the area required for an X-dimension of 0.264 millimetre (0.0104 inch).
 - When printing a minimum symbol with any method of printing, the symbol height SHALL never be truncated below the minimum.
- ** The minimum symbol height dimensions listed for all symbologies including EAN/UPC Symbols do not include the Human Readable Interpretation. Because of the operative scanning environment for EAN/UPC Symbols, there is a direct relationship between the symbol's height and width. This means the minimum symbol height listed is tied to the minimum, target, and maximum X-dimension listed. There is no maximum for the height, but if the maximum X-dimension is used, the symbol height must be equal to or greater than those listed in the Minimum Symbol Height column. For GS1 DataBar Expanded Stacked symbols, the table reflects the minimum symbol height for symbols that are two rows in height.
- *** In addition to the factors above related to digital printing, one other exception is permitted; For loose produce being weighed at the Point-of-Sale (POS) using GS1 DataBar Stacked Omnidirectional minimum X-dimension of 0.203 millimetre (0.0080 inch) is permitted but may produce scanning performance reduction. However, for POS, this performance drop off is not noticeable when the product must be weighed at the Point-of-Sale. Even with a slower scanning performance to conduct the transaction, the weighing process takes longer than the scanning process. For that reason, a lower minimum X-dimension should never be used on products crossing Point of Sale which are not weighed as loose produce during the scan event.
- **** The current symbol specification for GS1 DataBar Omni-directional (minimum height 33X) and GS1 DataBar Stacked Omni-directional (minimum height 69X) indicate a square aspect ratio for the symbol segments. To enhance scanning performance, in an omni-directional scanning environment, an over square aspect ratio shall be used following the example of the EAN/UPC symbology specification and rigorous field test of the GS1 DataBar symbology (46X or 95X).
- ***** For North American Coupon Codes using GS1 DataBar Expanded Stacked in 2 row and 3 row configurations the X Dimension may be as low as 0.0080" (0.203mm) as long as a minimum overall bar height of 1.020" (25.91mm) is maintained. X-dimensions less than 0.0100" (.254mm) might not always be feasible for all GS1 DataBar Coupon bar codes due to variables, such as printing process, symbol orientation, and material. Due to the time sensitive nature of the coupon printing process, these variables should be considered during the design and bar code origination processes. Bar code verification should always be done from printing press proofs.

Figure 5.5.2.7 – 2.1 GS1 System Symbol Specification Table 1 Addendum for AI (8200)

In addition to the symbol used at general retail POS, an additional 2D symbol may be used to carry AI (8200). As AI (8200) has a mandatory association with GTIN, the GTIN within the symbol ensures compatibility with direct or indirect mode. GS1 DataMatrix is approved for all applications including regulated healthcare trade items covered by SSTs 6, 7, 8, and 10, but for general retail consumer trade items, either GS1 QR Code or GS1 DataMatrix are GS1 approved options. When using 2D symbols to carry AI (8200) on general retail trade items, the following specifications are required.

Symbol(s) Specified ****	X-Dimension mm (inches)			Minimum Symbol Height for Given X mm (inches)			Quiet Zone Surrounding Symbol	Minimum Quality Specification
	Minimum	Target	Maximum	For Minimum X-dimension	For Target X-dimension	For Maximum X-dimension		
GS1 DataMatrix (ECC 200) **	0.396 (0.0150")	0.495 (0.0195")	0.743 (0.0293")	Height is determined by X-Dimension for Data that is encoded			1X *	1.5/***/670
GS1 QR Code **	0.396 (0.0150")	0.495 (0.0195")	0.743 (0.0293")	Height is determined by X-Dimension for Data that is encoded			4X *	1.5/***/670

- * 2D Quiet Zones - Quiet Zones for GS1 DataMatrix are 1X on all four sides and 4X for GS1 QR Code.
- ** 2D X-dimension - Optical effects in the image capture process require that the GS1 DataMatrix and GS1 QR Code Symbols be printed at 1.5 times the equivalent printing density allowed for linear symbols.
- *** 2D Quality Measurement - The effective aperture for GS1 DataMatrix and GS1 QR Code quality measurements should be taken at 80% of the printing density.
- **** Where a linear symbol appears on the package, reverse and mirror-image representation of GS1 2D symbols shall not be permitted.

Figure 5.5.2.7 - 3 GS1 System Symbol Specification Table 2

Symbol(s) Specified		*X-Dimension mm (inches)			Tol.	** Minimum Symbol Height for Given X mm (inches)			Tol.	Quiet Zone		***Minimum Quality Specification
Minimum	Target	Maximum		For Minimum X-dimension		For Target X-dimension	For Maximum X-dimension	Left		Right		
EAN-13	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	± 0.025 (0.001")	34.28 (1.350")	45.70 (1.800")	45.70 (1.800")	3X	11X	7X	1.5/06/670	
EAN-8	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		27.35 (1.077")	36.46 (1.435")	36.46 (1.435")		7X	7X	1.5/06/670	
UPC-A	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		34.28 (1.350")	45.70 (1.800")	45.70 (1.800")		9X	9X	1.5/06/670	
UPC-E	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		34.28 (1.350")	45.70 (1.800")	45.70 (1.800")		9X	7X	1.5/06/670	
ITF-14	0.495 (0.0195")	0.495 (0.0195")	1.016 (0.0400")		31.75 (1.250")	31.75 (1.250")	31.75 (1.250")		10X	10X	1.5/10/670	
GS1-128	0.495 (0.0195")	0.495 (0.0195")	1.016 (0.0400")		31.75 (1.250")	31.75 (1.250")	31.75 (1.250")		10X	10X	1.5/10/670	
GS1 DataBar Omnidirectional	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		16.34 (0.644")	21.78 (0.858")	21.78 (0.858")		NA	NA	1.5/06/670	
GS1 DataBar Stacked Omnidirectional	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		34.16 (1.346")	45.54 (1.794")	45.54 (1.794")		NA	NA	1.5/06/670	
GS1 DataBar Expanded	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		16.83 (0.663")	22.44 (0.884")	22.44 (0.884")		NA	NA	1.5/06/670	
GS1 DataBar Expanded Stacked	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		35.15 (1.385")	46.86 (1.846")	46.86 (1.846")		NA	NA	1.5/06/670	
GS1 DataBar Stacked	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		6.44 (0.254")	8.58 (0.338")	8.58 (0.338")		NA	NA	1.5/06/670	
GS1 DataBar Limited	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		4.95 (0.195")	6.60 (0.260")	6.60 (0.260")		NA	NA	1.5/06/670	
GS1 DataBar Truncated	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		6.44 (0.254")	8.58 (0.338")	8.58 (0.338")		NA	NA	1.5/06/670	

Note: See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.

* UPC-E and EAN-8 Symbols are designed for use on small packages. Whenever space permits, UPC-A, EAN-13, ITF-14, or GS1-128 Symbols should be used in the General Distribution Scanning environment.

The minimum symbol height dimensions listed for all symbologies including EAN/UPC Symbols do not include the Human Readable Interpretation. Because of the operative scanning environment for EAN/UPC Symbols, there is a direct relationship between the symbol's height and width. This means the minimum symbol height is tied to the minimum, target, and maximum X-dimension listed.

ITF-14 Symbols with X-dimensions below 0.635 millimetre (0.0250 inch) should not be printed directly on corrugate with conventional (plate-based) processes. Packages and/or containers marked with ITF-14 Symbols with X-dimensions between 1.016 millimetres (0.0400 inch) and

1.219 millimetres (0.048 inch) are acceptable based on historical specifications, but a migration to the 1.016 millimetres (0.0400 inch) maximum X-dimension should be made on new artwork. The ITF-14 Symbol's bar width ratio target is 2.5:1, and the acceptable range is 2.25:1 to 3:1.

GS1-128 Symbols have a maximum symbol length of 165.10 millimetres (6.500 inch), which may impact the maximum achievable X-dimension. For example, a GS1-128 Symbol containing an SSCC has a maximum achievable X-dimension for 0.940 millimetre (0.0370 inch)

** The minimum symbol height for General Distribution Scanning is always 31.75 millimetres (1.250 inch). The minimum symbol height dimensions for ITF-14 and GS1-128 Symbols relate to the bar heights only (do not include Human Readable Interpretation text or ITF-14 Symbol Bearer Bars). There is no maximum for the height, but if the maximum X-dimension is used, the symbol height must be equal to or greater than those listed in the Minimum Symbol Height column.

*** For ITF-14 Symbols printed on labels with off-set, thermal, or laser print with an X-dimension 0.495 millimetre (0.0195 inch), the minimum quality specification is 1.5/10/670. For ITF-14 Symbols printed directly on corrugate or labels with an X-dimension greater than or equal to 0.635 millimetre (0.0250 inch), the minimum quality specification is 0.5/20/670.

Figure 5.5.2.7 - 4 GS1 System Symbol Specification Table 3

Symbol(s) Specified		*X-Dimension mm (inches)			Tol.	** Minimum Symbol Height for Given X			Tol.	Quiet Zone		Minimum Quality Specification
		Minimum	Target	Maximum		For Minimum X- dimension	For Target X- dimens ion	For Maximum X- dimension		Left	Right	
EAN-13	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	± 0.025 (0.001")	34.28 (1.350")	45.70 (1.800")	45.70 (1.800")	3X	11X	7X	1.5/06/670	
EAN-8	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		27.35 (1.077")	36.46 (1.435")	36.46 (1.435")		7X	7X	1.5/06/670	
UPC-A	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		34.28 (1.350")	45.70 (1.800")	45.70 (1.800")		9X	9X	1.5/06/670	
UPC-E	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		34.28 (1.350")	45.70 (1.800")	45.70 (1.800")		9X	7X	1.5/06/670	
GS1 DataBar Omnidire ctional ***	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		22.77 (0.897")	30.36 (1.196")	30.36 (1.196")		None	None	1.5/06/670	
GS1 DataBar Stacked Omnidire ctional ***	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		47.03 (1.853")	62.70 (2.470")	62.70 (2.470")		None	None	1.5/06/670	
GS1 DataBar Expand ed	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		16.83 (0.663")	22.44 (0.884")	22.44 (0.884")		None	None	1.5/06/670	
GS1 DataBar Expand ed Stacked	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")		35.15 (1.385")	46.86 (1.846")	46.86 (1.846")		None	None	1.5/06/670	

Note: See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.

* UPC-E and EAN-8 Symbols are designed for use on small packages. Whenever space permits, UPC-A and EAN-13 Symbols should be used.

** The minimum symbol height dimensions listed for all symbologies including EAN/UPC Symbols do not include the Human Readable Interpretation. Because of the operative scanning environment for EAN/UPC Symbols, there is a direct relationship between the symbol's height and width. This means the minimum symbol height listed is tied to the minimum, target, and maximum X-dimension listed.

There is no maximum for the height, but if the maximum X-dimension is used, the symbol height must be equal to or greater than those listed in the Minimum Symbol Height column.

*** The current symbol specification for GS1 DataBar Omni-directional (minimum height 33X) and GS1 DataBar Stacked Omni-directional (minimum height 69X) indicate a square aspect ratio for the symbol segments. To enhance scanning performance, in an omni-directional scanning environment, an over square aspect ratio shall be used following the example of the EAN/UPC symbology specification and rigorous field test of the GS1 DataBar symbology (46X or 95X).

Figure 5.5.2.7 - 5 GS1 System Symbol Specification Table 4

Symbol(s) Specified	*X-Dimension mm (inches)			** Minimum Symbol Height for Given X mm (inches)			Quiet Zone		Minimum Quality Specification
	Minimum	Target	Maximum	For Minimum X-dimension	For Target X-dimension	For Maximum X-dimension	Left	Right	
EAN-13	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	11X	7X	1.5/06/670
EAN-8	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	14.58 (0.574")	18.23 (0.718")	36.46 (1.435")	7X	7X	1.5/06/670
UPC-A	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	9X	9X	1.5/06/670
UPC-E	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	9X	7X	1.5/06/670
GS1 DataBar Omnidirectional	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	8.71 (0.343")	10.90 (0.429")	21.78 (0.858")	NA	NA	1.5/06/670
GS1 DataBar Stacked Omnidirectional	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.24 (0.718")	27.78 (0.897")	45.54 (1.794")	NA	NA	1.5/06/670
GS1 DataBar Expanded	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	8.99 (0.354")	11.23 (0.442")	22.44 (0.883")	NA	NA	1.5/06/670
GS1 DataBar Expanded Stacked	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.75 (0.738")	23.44 (0.923")	46.86 (1.845")	NA	NA	1.5/06/670
GS1 DataBar Stacked	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	3.43 (0.135")	4.29 (0.169")	8.58 (0.338")	N/A	N/A	1.5/06/670
GS1 DataBar Limited	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	2.64 (0.104")	3.30 (0.130")	6.60 (0.260")	N/A	N/A	1.5/06/670
GS1 DataBar Truncated	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	3.43 (0.135")	4.29 (0.169")	8.58 (0.338")	N/A	N/A	1.5/06/670
ITF-14	0.250 (0.00984")	0.495 (0.0195")	0.495 (0.0195")	12.70 (0.500")	12.70 (0.500")	12.70 (0.500")	10X	10X	1.5/10/670
GS1- 128	0.250 (0.00984")	0.495 (0.0195")	0.495 (0.0195")	12.70 (0.500")	12.70 (0.500")	12.70 (0.500")	10X	10X	1.5/10/670



Note: See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.

* ITF-14 Symbols with X-dimensions below 0.635 millimetre (0.0250 inch) should not be printed directly on corrugate with conventional (plate based) processes. Packages and/or containers marked with ITF-14 Symbols with X-dimensions between 1.016 millimetres (0.0400 inch) and 1.219 millimetres (0.0480 inch) are acceptable based on historical specifications, but a migration to the 1.016 millimetre (0.0400 inch) maximum X-dimension should be made on new artwork. The ITF-14 Symbol's bar width ratio target is 2.5:1, and the acceptable range is 2.25:1 to 3:1.

Section [5.5.3.4](#) gives full details on when bar codes can be printed at less than the minimum X-dimension. In general, bar codes may only be printed using an X-dimension below 0.264 millimetre (0.0104 inch) or 80 percent magnification under the following conditions:

- The allowance for X-dimensions between 0.249 millimetre (0.0098 inch) or 75 percent magnification and 0.264 millimetre (0.0104 inch) or 80 percent magnification is only applicable to on demand (e.g., thermal, laser) print processes. For all other printing processes, an X-dimension of 0.264 millimetre (0.0104 inch) is attainable and is the minimum allowable size.

- When printing a minimum symbol with any method of printing, the area provided for printing the symbol and the required Quiet Zone should never be less than the area required for an X-dimension of 0.264 millimetre (0.0104 inch).
- When printing a minimum symbol with any method of printing, the symbol height SHALL never be truncated.

** The minimum symbol height dimensions listed for all symbologies including EAN/UPC Symbols do not include the Human Readable Interpretation (or Bearer Bars for ITF-14 Symbols).

Because of the operative scanning environment for EAN/UPC Symbols, there is a direct relationship between the symbol's height and width. This means the minimum symbol height listed is tied to the minimum, target, and maximum X-dimension listed.

The minimum bar height for ITF-14 and GS1-128 Symbols in this operative scanning environment is 12.70 millimetres (0.500 inch), but if the package is physically too small to accommodate this rule, further truncation is permitted. In no case shall the bar height be less than 5.08 millimetres (0.200 inch).

There is no maximum for the symbol height, but if the maximum X-dimension is used, the symbol height must be equal to or greater than those listed in the Minimum Symbol Height column.

Whereas, linear symbol heights are set at a fixed dimension, Composite Components are printed at the same density as the linear portion of the Composite Symbology, and the bar code height varies depending on the amount of data, the printing density, and which linear symbol is used in conjunction with the Composite Component. Note that Composite Components have to be printed with a linear symbol such as GS1 DataBar, GS1-128, UPC-A, or EAN-13. ITF-14 cannot be used with Composite Components.

Figure 5.5.2.7 – 6 GS1 System Symbol Specification Table 5

Symbol(s) Specified	*X-Dimension mm (inches)			** Minimum Symbol Height for Given X mm (inches)			Quiet Zone		Minimum Quality Specification
	Minimum	Target	Maximum	For Minimum X-dimension	For Target X-dimension	For Maximum X-dimension	Left	Right	
GS1-128	0.495 (0.0195")	0.495 (0.0195")	0.940 (0.0370")	31.75 (1.250")	31.75 (1.250")	31.75 (1.250")	10X	10X	1.5/10/670

Note: See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.

* If the item is too small to accommodate the minimum X-dimension, the minimum X-dimension is 0.250 millimetre (0.0098 inch).

** The minimum symbol height indicated is for bar height only and does not include the Human Readable Interpretation. If the item is too small to accommodate the minimum, the minimum bar height is the greater of 15 percent of the symbol width including Quiet Zones or 12.70 millimetres (0.500 inch). If the package is physically too small to accommodate this rule, further truncation is permitted, but in no case shall the bar height be less than 5.08 millimetres (0.200 inch).

There is no maximum for the height, but if the maximum X-dimension is used, the symbol height must be equal to or greater than those listed in the Minimum Symbol Height column.

Figure 5.5.2.7 - 7 GS1 System Symbol Specification Table 6 – Regulated Healthcare Non-Retail Consumer Trade Items Not Scanned in General Distribution

Symbol(s) Specified	X-Dimension mm (inches)			Minimum Symbol Height for Given X mm (inches)			Quiet Zone		Minimum Quality Specification
	Minimum	Target	Maximum	For Minimum X-dimension	For Target X-dimension	For Maximum X-dimension	Left	Right	
GS1- 128	0.170 (0.0067")	0.495 (0.0195")	0.495 (0.0195")	12.70 (0.500")	12.70 (0.500")	12.70 (0.500")	10X	10X	1.5/10/670
GS1 DataMatrix (ECC 200) **	0.255 (0.0100")	0.380 (0.0150")	0.495 (0.0195")	Height is determined by X-Dimension for Data that is encoded			1X *	1X *	1.5/***/670
GS1 DataBar Omnidirectional	0.170 (0.0067")	0.200 (0.0080")	0.660 (0.0260")	5.61 (0.221")	6.60 (0.260")	21.78 (0.858")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Truncated	0.170 (0.0067")	0.200 (0.0080")	0.660 (0.0260")	2.21 (0.087")	2.60 (0.102")	8.58 (0.338")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Stacked	0.170 (0.0067")	0.200 (0.0080")	0.660 (0.0260")	2.21 (0.087")	2.60 (0.102")	8.58 (0.338")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Stacked Omnidirectional	0.170 (0.0067")	0.200 (0.0080")	0.660 (0.0260")	11.73 (0.462")	13.80 (0.543")	45.54 (1.794")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Limited	0.170 (0.0067")	0.200 (0.0080")	0.660 (0.0260")	1.70 (0.067")	2.00 (0.079")	6.60 (0.260")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Expanded	0.170 (0.0067")	0.200 (0.0080")	0.660 (0.0260")	5.78 (0.228")	6.80 (0.268")	22.44 (0.884")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Expanded Stacked	0.170 (0.0067")	0.200 (0.0080")	0.660 (0.0260")	12.07 (0.475")	14.20 (0.559")	46.86 (1.846")	Not Applicable	Not Applicable	1.5/06/670
EAN-13	0.170 (0.0067")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	11X	7X	1.5/06/670
EAN-8	0.170 (0.0067")	0.330 (0.0130")	0.660 (0.0260")	14.58 (0.574")	18.23 (0.718")	36.46 (1.435")	7X	7X	1.5/06/670
UPC-A	0.170 (0.0067")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	9X	9X	1.5/06/670
UPC-E	0.170 (0.0067")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	9X	7X	1.5/06/670
ITF-14	0.170 (0.0067")	0.495 (0.0195")	0.495 (0.0195")	12.70 (0.500")	12.70 (0.500")	12.70 (0.500")	10X	10X	1.5/10/670
CC-A	All CCs need to be printed at the same printing densities as their linear components, therefore consult the appropriate row and column for the linear symbol to be used.			Height is determined by X-Dimension for data that is encoded			1X	1X	1.5/06/670
CC-B							1X	1X	
CC-C							2X	2X	



Note: See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.



Note: This table contains several symbol options. All are permitted to promote backward compatibility, but Section 2 Application Standards define which symbols are the preferred options for the future.

* 2D Quiet Zones - Quiet Zones for GS1 DataMatrix are 1X on all four sides.

** 2D X-dimension - Optical effects in the image capture process require that the GS1 DataMatrix symbol be printed at 1.5 times the equivalent printing density allowed for linear or Composite Symbols.

*** 2D Quality Measurement - The effective aperture for GS1 DataMatrix quality measurements should be taken at 80% of the printing density. An aperture of 8 is used for Regulated Healthcare Non-Retail Consumer Trade Items in this application.

Figure 5.5.2.7 - 8 GS1 System Symbol Specification Table 7 - Direct Part Marking

Symbol(s) Specified	X-Dimension mm (inches) Note 1 Note 6			Minimum Symbol Height for Given X mm (inches)			Quiet Zone	Minimum Quality Specification	
	Minimum	Target	Maximum	For Minimum X- dimension	For Target X- dimension	For Maximum X- dimension			
GS1 DataMatrix	0.255 (0.0100")	0.300 (0.0118")	0.615 (0.0242")	Height is determined by X-Dimension for data that is encoded			1X on all four sides	1.5/06/670 Note 5	For Direct Marking of items other than Small Medical/Surgical Instruments
GS1 DataMatrix Ink Based Direct Part Marking	0.255 (0.0100")	0.300 (0.0118")	0.615 (0.0242")	Height is determined by X-Dimension for data that is encoded			1X on all four sides	1.5/08/670 Note 5	For Small Medical / Surgical Instrument Direct Marking
GS1 DataMatrix Direct Part Marking - A Note 2	0.100 (0.0039")	0.200 (0.0079")	0.300 (0.0118")	Height is determined by X-Dimension for data that is encoded			1X on all four sides	1.5/03/ Note 3 Note 4 Note 5	For Small Medical / Surgical Instrument Direct Marking
GS1 DataMatrix Direct Part Marking - B Note 2	0.200 (0.0079")	0.300 (0.0118")	0.495 (0.0195")	Height is determined by X-Dimension for data that is encoded			1X on all four sides	1.5/06/ Note 3 Note 4 Note 5	For Small Medical / Surgical Instrument Direct Marking



Note 1: Optical effects in the image capture process require that label based GS1 DataMatrix symbols be printed at approximately 1.5 times the equivalent printing density allowed for linear symbols in the same application.



Note 2: There are two basic types of non ink based Direct Part Marks, those with “connected modules” in the “L” shaped finder pattern (GS1 DataMatrix Direct Part Marking – A) created by DPM marking technologies such as laser or chemical etching and those with “non connected modules” in the “L” shaped finder pattern (GS1 DataMatrix Direct Part Marking – B) created by DPM marking technologies such as dot peen. Due to the marking technologies and characteristics of reading they each have varied ranges of X-Dimensions and different quality criteria recommended and may require different reading equipment.

GS1 DataMatrix – A is suggested for marking of small medical / surgical instruments. The Minimum X-Dimension of 0.100mm is based upon the specific need for permanence in direct marking of small medical instruments which have limited marking area available on the instrument with a target useable area of 2.5mm x 2.5mm and a data content of GTIN (AI 01) plus Serial Number (AI 21).



Note 3: The wavelength for Direct Part Marked GS1 DataMatrix is based upon the practical scanning environment and thus must in the grade be matched to the scanner / imagers being used. See ISO/IEC 15415 and AIM DPM-1-2006.



Note 4: The angle is an additional parameter defining the angle of incidence (relative to the plane of the symbol) of the illumination for Direct Part Marking verification. It shall be included in

the overall symbol grade when the angle of incidence is other than 45 degrees. Its absence indicates that the angle of incidence is 45 degrees. See ISO/IEC 15415 and AIM DPM-1-2006.



Note 5: The effective aperture for GS1 DataMatrix quality measurements should be taken at 80 percent of the minimum X-dimension allowed for the application. For Direct Part Marking - A this would equate to an aperture of 3; for Direct Park Marking – B this would equate to an aperture of 6 and for general healthcare label printing, an aperture of 8. See ISO/IEC 15415 and AIM DPM-1-2006.



Note 6: The largest X-dimension in a given range that will allow a symbol with the needed data content to fit within the available marking area should be used to maximize marking and reading performance (depth of field, tolerance to curvature, etc.).



Note: In small instrument marking, mixed marking technologies used within the same scanning environment should be avoided to ensure highest reading performance. Laser etching is recommended for small instrument marking.

Figure 5.5.2.7- 9 GS1 System Symbol Specification Table 8 - Trade Items Scanned in Retail Pharmacy and General Distribution or Non-Retail Pharmacy and General Distribution

Symbol(s) Specified	X-dimension mm (inches)			Minimum Symbol Height for Given X mm (inches)			Quiet Zone		Minimum Quality Specification
	Minimum	Target	Maximum	For Minimum X-dimension	For Target X-dimension	For Maximum X-dimension	Left	Right	
GS1- 128	0.495 (0.0195")	0.495 (0.0195")	1.016 (0.0400")	31.75 (1.250")	31.75 (1.250")	31.75 (1.250")	10X	10X	1.5/10/670
GS1 DataMatrix (ECC 200)	0.750 (0.0300")	0.750 (0.0300")	1.520 (0.0600")	Height is determined by X-Dimension for Data that is encoded			1X	1X	1.5*/670
EAN-13	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	34.28 (1.350")	45.70 (1.800")	45.70 (1.800")	11X	7X	1.5/06/670
EAN-8	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	27.35 (1.077")	36.46 (1.435")	36.46 (1.435")	7X	7X	1.5/06/670
UPC-A	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	34.28 (1.350")	45.70 (1.800")	45.70 (1.800")	9X	9X	1.5/06/670
UPC-E	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	34.28 (1.350")	45.70 (1.800")	45.70 (1.800")	9X	7X	1.5/06/670
ITF-14	0.495 (0.0195")	0.495 (0.0195")	1.016 (0.0400")	31.75 (1.250")	31.75 (1.250")	31.75 (1.250")	10X	10X	1.5/10/670
GS1 DataBar Omnidirectional	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	16.34 (0.644")	21.78 (0.858")	21.78 (0.858")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Truncated	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	6.44 (0.254")	8.58 (0.338")	8.58 (0.338")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Stacked	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	6.44 (0.254")	8.58 (0.338")	8.58 (0.338")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Stacked Omnidirectional	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	34.16 (1.346")	45.54 (1.794")	45.54 (1.794")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Limited	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	4.95 (0.195")	6.60 (0.260")	6.60 (0.260")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Expanded	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	16.83 (0.663")	22.44 (0.884")	22.44 (0.884")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Expanded Stacked	0.495 (0.0195")	0.660 (0.0260")	0.660 (0.0260")	35.15 (1.385")	46.86 (1.846")	46.86 (1.846")	Not Applicable	Not Applicable	1.5/06/670



Note: See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.

- Note:** This table contains several symbol options. All are permitted to promote backward compatibility, but Section 2 Application Standards define which symbols are the preferred options for the future.

- Note:** See the asterisked notes on 2D Quiet Zone, 2D X-dimension, 2D Quality Measurement (for * above) that follow Figure 5.5.2.7 – 7 "GS1 System Symbol Specification Table 6 -- Regulated Healthcare Non-Retail Consumer Trade Items Not Scanned in General Distribution"

- Note:** Since June 2007 GS1 has recommended all trading partners in the healthcare sector invest exclusively in imaging-based scanners. Now that GS1 DataMatrix has been approved within the standard, it is important to inform all trading partners of a process within GS1 to establish target deployment dates. Without these dates, brand owners do not have a way know when to deploy GS1 DataMatrix on their packaging and those needing to invest in scanning equipment may inadvertently purchase equipment that will not support the standards. To see GS1 Healthcare's Position Paper on GS1 DataMatrix adoption, visit GS1.org/GS1Healthcare.

Figure 5.5.2.7 - 10 GS1 System Symbol Specification Table 9 – GS1 Keys Other than GTIN

Symbol(s) Specified	X-Dimensions mm(inches)			Minimum Symbol Height for Given X mm(inches)			Quiet Zone		Minimum Quality Specification
	Minimum	Target	Maximum	For Minimum X-Dimension	For Target X-Dimension	For Maximum X-Dimension	Left	Right	
GS1- 128	0.250 (0.0098")	0.250 (0.0098")	0.495 (0.0195")	12.70 (0.500")	12.70 (0.500")	12.70 (0.500")	10X	10X	1.5/10/670
GS1 DataMatrix (ECC 200)	0.380 (0.0150")	0.380 (0.0150")	0.495 (0.0195")	Height is determined by X-Dimension for Data that is encoded			1X	1X	1.5*/670

- Note:** See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.

- Note:** This table contains several symbol options. All are permitted to promote backward compatibility, but Section 2 Application Standards define which symbols are the preferred options for the future.

- Note:** See the asterisked notes on 2D Quiet Zone, 2D X-dimension, 2D Quality Measurement (for * above) that follow Figure 5.5.2.7 – 7 "GS1 System Symbol Specification Table 6 -- Regulated Healthcare Non-Retail Consumer Trade Items Not Scanned in General Distribution"

Figure 5.5.2.7 - 11 GS1 System Symbol Specification Table 10 – Regulated Healthcare Retail Consumer Trade Items Not Scanned in General Distribution

Symbol(s) Specified	X-Dimension mm (inches)			Minimum Symbol Height for Given X mm (inches)			Quiet Zone		Minimum Quality Specification
	Minimum	Target	Maximum	For Minimum X-dimension	For Target X-dimension	For Maximum X-dimension	Left	Right	
GS1- 128	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	12.70 (0.500")	12.70 (0.500")	12.70 (0.500")	10X	10X	1.5/10/670
GS1 DataMatrix (ECC 200)	0.396 (0.0156")	0.495 (0.0195")	0.990 (0.0390")	Height is determined by X-Dimension for Data that is encoded			1X	1X	1.5*/670
GS1 DataBar Omnidirectional	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	8.71 (0.343")	10.89 (0.429")	21.78 (0.858)	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Truncated	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	3.43 (0.135")	4.29 (0.169")	8.58 (0.338")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Stacked	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	3.43 (0.135")	4.29 (0.169")	8.58 (0.338")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Stacked Omnidirectional	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.22 (0.718")	27.77 (0.897")	45.54 (1.794")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Limited	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	2.64 (0.104")	3.30 (0.130")	6.60 (0.260")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Expanded	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	8.98 (0.354")	11.22 (0.442")	22.44 (0.883")	Not Applicable	Not Applicable	1.5/06/670
GS1 DataBar Expanded Stacked	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.74 (0.738")	23.43 (0.923")	46.86 (1.846")	Not Applicable	Not Applicable	1.5/06/670
EAN-13	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	11X	7X	1.5/06/670
EAN-8	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	14.58 (0.574")	18.23 (0.718")	36.46 (1.435")	7X	7X	1.5/06/670
UPC-A	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	9X	9X	1.5/06/670
UPC-E	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	9X	7X	1.5/06/670
ITF-14	0.264 (0.0104")	0.330 (0.0130")	0.660 (0.0260")	18.28 (0.720")	22.85 (0.900")	45.70 (1.800")	10X	10X	1.5/10/670

- ✔ **Note:** See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.
- ✔ **Note:** See the asterisked notes on 2D Quiet Zone, 2D X-dimension, 2D Quality Measurement (for * above) that follow Figure 5.5.2.7 – 7 “GS1 System Symbol Specification Table 6 -- Regulated Healthcare Non-Retail Consumer Trade Items Not Scanned in General Distribution”
- ✔ **Note:** Since June 2007 GS1 has recommended all trading partners in the healthcare sector invest exclusively in imaging-based scanners. Now that GS1 DataMatrix has been approved within the standard, it is important to inform all trading partners of a process within GS1 to establish target deployment dates. Without these dates, brand owners do not have a way know when to deploy GS1 DataMatrix on their packaging and those needing to invest in scanning equipment may inadvertently purchase equipment that will not support the standards. To see GS1 Healthcare’s Position Paper on GS1 DataMatrix adoption, visit GS1.org/GS1Healthcare.

Figure 5.5.2.7 - 12 GS1 System Symbol Specification Table 11 – GS1 GSRNs

Symbol(s) Specified	X-Dimensions mm(inches)			Minimum Symbol Height for Given X mm(inches)			Quiet Zone		Minimum Quality Specification
	Minimum	Target	Maximum	For Minimum X-Dimension	For Target X-Dimension	For Maximum X-Dimension	Left	Right	
GS1- 128	0.170 (0.0067")	0.250 (0.0098")	0.495 (0.0195")	12.70 (0.500")	12.70 (0.500")	12.70 (0.500")	10X	10X	1.5/10/670
GS1 DataMatrix (ECC 200)	0.255 (0.0100")	0.380 (0.0150")	0.495 (0.0195")	Height is determined by X-Dimension for Data that is encoded			1X	1X	1.5*/670

- ✔ **Note:** See Section [5.5.2.6](#) to ensure the correct Symbol Specification Table is used.
- ✔ **Note:** This table contains several symbol options. All are permitted to promote backward compatibility, but Section 2 Application Standards define which symbols are the preferred options for the future.
- ✔ **Note:** See the asterisked notes on 2D Quiet Zone, 2D X-dimension, 2D Quality Measurement (for * above) that follow Figure 5.5.2.7 – 7 “GS1 System Symbol Specification Table 6 -- Regulated Healthcare Non-Retail Consumer Trade Items Not Scanned in General Distribution”

5.5.3. Bar Code Production

The following subsections will:

- Provide background on major bar code printing methods and materials
- Provide general printing and packaging background for major application groups

The various definitions and specialist terms used throughout this section are found in *ISO/IEC 15419*, Information Technology, Automatic Identification and Data Capture Techniques, Bar Code Digital Imaging and Printing Performance Testing, *ISO/IEC 15416*, Information technology, Automatic Identification and Data Capture Technologies, Bar Code Print Quality Test Specification – Linear Symbols and *ISO/IEC 15415*, Information technology, Automatic Identification and Data capture Techniques, Bar Code Print Quality Test Specification, Two-dimensional Symbols.

5.5.3.1. Digital Imaging

5.5.3.1.1. General Requirements

General requirements consisting of the following topics are found in Section 4 of *ISO/IEC 15419*.

- Data input
- Quiet Zones
- Classification of imaging device categories, from informative reference Annex E of *ISO/IEC 15419*
- Programmer’s examples, from informative reference Annex F of *ISO/IEC 15419*
- Programmer’s example for general-purpose printers
- Programmer’s example for indirect bar code imaging devices
- Programmer’s example for symbols distorted for plate roll circumference
- Direct bar code imaging devices

- Dedicated bar code printers
- Adjustment of target element dimensions
- Record of design elements
- General purpose printers
- Adjusted bar width compensation (BWC) (including the General Purpose Printer Dot/Pixel Comparison figure)
- Record of design attributes
- Indirect bar code imaging devices
- Adjustments for planned distortion (disproportioning)
- Adjustments for special EAN/UPC Symbol characters
- Test requirements
 - System configuration
 - Test procedure
- Conformance
- Test report, including sample test layout, from normative reference Annex A of *ISO/IEC 15419*
- Certification
- Software specification, including classification of software categories, from informative reference Annex D of *ISO/IEC 15419* and functions of bar code production software from informative reference Annex G of *ISO/IEC 15419*
- Maintenance and supplies, from informative reference Annex C of *ISO/IEC 15419*

5.5.3.1.2. Dedicated Bar Code Printers


Section 5 of *ISO/IEC 15419* contains information on dedicated bar code printers and includes the following topics:

- Data input requirements
- Test requirements
- Selection of equipment for testing
- Test conditions; environment, equipment configuration
- Test procedure
- Conformance
- Test report
- Certification and labelling
- Equipment specification

5.5.3.1.3. EAN/UPC On-Demand Printed Symbols at Minimum Size

It is more difficult for the user to create high quality bar codes with general-purpose printers than it is with direct thermal transfer label printers. There are two reasons for this difficulty. First, the printed dot size for general-purpose printers is appreciably larger than the pixel dimension, as shown in Figure 5.5.3.1.3 - 1. This causes the bars (dark bars) to be printed wider and the spaces (light bars) to be narrower than nominal, unless the software driving the printer corrects for this distortion. Second, the software that constructs the bar code may itself introduce dimensional errors.

Figure 5.5.3.1.3 - 1 Example of Digital Printing



The most common printing densities used by on-demand, bar code printers are 200 and 300 dpi. However, due to the constraints of the dot pitch, these printers cannot print a minimum X-dimension of 0.264 mm (0.0104 inch) or 80 percent magnification symbol correctly. The closest to 80 percent that these printers can print is 75.7 percent or 76.9 percent depending on the exact dot geometry (see Figure 5.5.3.1.3 - 2).

Even though a minimum X-dimension of 0.264 mm (0.0104) inch or 80 percent magnification) is the minimum value specified, users of on-demand printers have used magnifications between 75 percent and 80 percent in Point-of-Sale (POS) scanning environments for years. They have done so with no significant reduction in scan rate, as compared to symbols printed precisely at 80 percent. Because larger in-specification symbols are always easier to scan, 80 percent symbols and larger are preferred. However, when an on-demand printer is required, the 75 to 80 percent symbols are an acceptable alternative given the following qualifications for printing:

- The allowance for symbols from the EAN/UPC Symbology family of magnifications from 75 to 80 percent is only applicable to on-demand (e.g., thermal, laser) print processes. For all other printing processes, 80 percent is attainable and is the minimum allowable size.
- When printing a minimum symbol with any method of printing, the area provided for printing the symbol, including the required Quiet Zones, should never be less than the area required for an 80 percent symbol. This area is derived from the total width of an 80 percent symbol times its height.
- When printing a minimum symbol with any method of printing, the symbol height SHALL never be truncated below minimum bar height as stated in the Symbol Specification Tables.
- The minimum print quality grade is the same for all symbols in the EAN/UPC Symbology family: 1.5/06/670.

Figure 5.5.3.1.3 - 2 Achievable X-Dimensions for Thermal Printed EAN/UPC Symbols

Reference DPI	Actual DPI	Dots Per Millimetre	Actual Dot Width (Centre Point to Centre Point)		Dots Per Module Width	Module Width (X-Dimension)		*Corrected Magnification
			Inch	mm		Inch	mm	
200	203.2	8	0.004921	0.12500	2	0.0098	0.250	**75.76%
200	203.2	8	0.004921	0.12500	3	0.0148	0.375	113.64%
200	203.2	8	0.004921	0.12500	4	0.0197	0.500	151.52%
200	203.2	8	0.004921	0.12500	5	0.2461	0.625	189.39%
300	304.8	12	0.003281	0.08333	3	0.0098	0.250	**75.76%
300	304.8	12	0.003281	0.08333	4	0.0131	0.333	100.01%

300	304.8	12	0.003281	0.08333	5	0.0164	0.417	126.26%
300	304.8	12	0.003281	0.08333	6	0.0197	0.500	151.52%
300	304.8	12	0.003281	0.08333	7	0.0230	0.583	176.77%
400	406.4	16	0.002461	0.06250	4	0.0098	0.250	**75.76%
400	406.4	16	0.002461	0.06250	5	0.0123	0.312	94.70%
400	406.4	16	0.002461	0.06250	6	0.0148	0.375	113.64%
400	406.4	16	0.002461	0.06250	7	0.0172	0.437	132.58%
400	406.4	16	0.002461	0.06250	8	0.0197	0.500	151.52%
400	406.4	16	0.002461	0.06250	9	0.0221	0.563	170.45%
400	406.4	16	0.002461	0.06250	10	0.0246	0.625	189.39%
600	609.6	24	0.001640	0.04167	6	0.0098	0.250	**75.76%
600	609.6	24	0.001640	0.04167	7	0.0115	0.292	88.38%
600	609.6	24	0.001640	0.04167	8	0.0131	0.333	101.01%
600	609.6	24	0.001640	0.04167	9	0.0148	0.375	113.64%
600	609.6	24	0.001640	0.04167	10	0.0164	0.417	126.26%
600	609.6	24	0.001640	0.04167	11	0.0180	0.458	138.89%
600	609.6	24	0.001640	0.04167	12	0.0197	0.500	151.52%
600	609.6	24	0.001640	0.04167	13	0.0213	0.542	164.14%
600	609.6	24	0.001640	0.04167	14	0.0230	0.583	176.77%
600	609.6	24	0.001640	0.04167	15	0.0246	0.625	189.39%

* The nominal EAN/UPC Symbol is based on a module width (X-dimension) of either 0.0130 inch or 0.330 millimetre. In North America, long-standing GS1 US specifications set the nominal module size (X-dimension) at 0.0130 inch or 0.330 millimetres. The ISO/IEC specification for EAN/UPC Symbols set the nominal module size (X-dimension) at 0.330 millimetre. The international metric nominal is 0.0606 percent smaller than the original inch-based nominal. The data in the right-most column labelled "Corrected Magnification" are based on a nominal module width (X-dimension) of 0.330 millimetre.

** See Figure 5.5.2.7 – 2 for when a Magnification of less than 80% is acceptable

5.5.3.2. Film Master Production


5.5.3.2.1. Introduction

For symbols in the EAN/UPC Symbology family, the biggest usage of verification has always been in conjunction with printing and production of packaging and labels by means of the conventional or "wet ink" printing processes, such as offset lithography, flexography, and photogravure. These printing processes use a Film Master as the initial artwork of the symbol, although some form of electronic origination of the symbol is increasingly replacing this high-precision article.

The first point at which one might use verification is the printability test stage prior to actual production of "real-life" symbols, where a printing run of a test symbol is carried out under normal conditions and measured in order to characterise the printing process for a particular press and printing substrate. It is necessary to assess how much bar gain (or loss) has occurred and over what range of variation, to decide how much bar width adjustment (BWA) is required. BWA can be in the form of bar width reduction (BWR), where there is bar gain, or the less common bar width increase (BWI). The required

BWA is associated with the X-dimension used. These details are required in order to specify the Film Master correctly, or as input parameters for the bar code origination software.

Figure 5.5.3.2.1 - 1 Example of Bar Width Adjustment



Verifying the Film Master on receipt confirms that the correct BWA has been applied and that it is otherwise as specified. Note that a special type of verifier using traditional measurement and capable of more precise measurement is necessary at this point, since Film Master requirements are specified in terms of element widths and are subject to tolerances of only plus or minus five microns for EAN/UPC Symbols. In addition, the verifier needs to be capable of measuring the intensity of light transmitted through, rather than that reflected by, the film material. Also, Film Masters may be either photographic positives or negatives, and in the latter case, the light and dark characteristics of the background and bars are reversed. In the absence of such a verifier, reliance may be placed on the verification report normally provided by the Film Master supplier with the master.

If a proof of the print job is produced, the bar code should be verified as part of the approval process. Note, however, that since proofing presses are not the same as production printing presses, there may be a slight difference in the quality of the proof and the production job.

While the presses are being made ready, a check of bar widths on the first few printed sheets can help to ensure that the press is correctly set to produce near-ideal bar widths. Once the presses have started to roll, periodic sampling should be carried out, at intervals based on experience or dictated by the company's quality control procedures, to monitor both bar widths and other aspects of symbol quality (in particular Symbol Contrast), since these are the attributes most easily adjusted during the run.

Finally, a further sample should be verified following completion of the print job. The Scan Reflectance Profile (SRP) analysis SHALL be used as the basis for decision making, to ensure that the job has achieved at least the minimum quality grade specified by the customer or based on the application.

The following items are recommended to appear on or with a Film Master:

- X-dimension (magnification factor)
- Selected bar (line) width reduction
- Product identification, including company name
- A test square (outside the symbol area) for emulsion studies (this should be incorporated in the film, not affixed on a separate label)
- Printing process for which the Film Master is intended
- Identification of the Film Master supplier
- Date of Film Master manufacture

5.5.3.2.2. Terms and Definitions

Definitions for the following terms are found in *ISO/IEC 15421*, Section 4:

- Achieved bar width difference
- Bar edge
- Bar edge conformance
- Bar edge contour
- Bar edge gradient
- Bar width adjustment (BWA)
- Bar width increase (BWI)
- Bar width reduction (BWR)
- Bar width tolerance
- Base density
- Negative image
- Nominal bar width (EAN/UPC Family)
- Optical density profile
- Polarity
- Positive image
- Specified bar width
- Target element width

5.5.3.2.3. Physical Requirements

Physical requirements consisting of the following topics are found in Section 6 of *ISO/IEC 15421* Information Technology, Automatic Identification and Data Capture Techniques, Bar Code Master Test Specifications:

- Material
 - Dimensional stability
 - Archival properties
- Physical requirements controlled by the manufacturing process
 - Target bar width
 - Bar width adjustment (BWA)
- Tolerances
 - Tolerance A – all symbologies
 - Tolerance B – two-width symbologies
 - Tolerance C – (n,k) symbologies
 - Tolerance D – all symbologies
- Bar edge characteristics
 - Bar edge conformance
 - Bar edge gradient
- Defects

- Quiet Zones
- Corner marks
- Optical densities (including table “Reference Density Values,” and, from informative reference Annex A of *ISO/IEC 15421* Optical Density Profiles, the following figures: Minimum and Maximum Values of Optical Density, Measurement of Slope, Threshold Point for Bar Edge Determination, Measurements for Ratio-Based Symbologies, Measurements for (n,k) Symbologies, and Symbol Character Pitch Measurement)
 - Minimum density (D_{\min})
 - Maximum density (D_{\max})
- Orientation
- Polarity
- Encodation
- Human Readable Interpretation
- Test Methods
 - Bar and space width measurement
 - Conditions for dimensional measurements
 - Calculation of the achieved BWA
 - Test report and traceability

5.5.3.3. Quality Assessment

5.5.3.3.1. Verification

Verification is the technical process by which a bar code is measured to determine its conformance with the specification for that symbol. Verification is not intended to be used alone as a method for downstream rejection. For example, GS1’s advice is to use the *ISO/IEC 15416* methodology as a tool to improve overall scanning performance. An ISO-based verifier is of enormous assistance in diagnosing the problem and providing a standard means of reporting among printing companies and their trading partners.

It is also important to note the difference between a scanner and a verifier. A verifier is a measuring tool by which one can make certain determinations concerning the ability of the symbol to do its job, namely, to carry and deliver data on demand. Because traditional verification measurement is typically made in a single scan across the symbol, it is uncertain whether this "snapshot" is truly representative of the symbol's characteristics throughout the symbol.

When interpreting the results from verification it is also important to remember that:

- Most verifiers do not measure symbol height.
- Without additional software linking the decoded data to a database, the quality and accuracy of the data content of a symbol cannot be confirmed.
- The verifier cannot confirm that the symbol dimensions are those intended and are as indicated in Symbol Specification Tables (SSTs). For example, many of the simpler verifiers cannot measure in dimensional terms (X-dimension), though they can be remarkably accurate in measuring the relationships of element widths to each other. The amount that bar widths differ from nominal width on average in a symbol is called the average bar error. This number is expressed as a fraction of X-dimension. A positive value indicates average bar growth and a negative value indicates bar shrinkage.

- The verifier does not check that the Human Readable Interpretation matches the bar code data (and it is necessary to check that the two correspond, particularly where the bar code generating software does not include Human Readable Interpretation data).
- Because only a sample of the symbols produced are actually verified, the quality of all the symbols in a production batch cannot be guaranteed beyond the statistical confidence limits associated with the sampling rate used.
- Even a perfect symbol at the time of production can be damaged or otherwise affected in its passage through the supply chain (e.g., scratched, frozen, dampened).
- Operator error can cause inconsistent results. Operators should be properly trained and visual checks should be made to confirm verifier results (e.g., where the bar code is expected to get a good result and fails the verifier test, recheck the operation of using the verifier).
- The correct bar code has been printed for the scanning environment of the item (e.g., an ITF-14 Symbol shall not be used on an item intended for retail Point-of-Sale).

5.5.3.3.1.1. Traditional Verification

Traditional verification methods were introduced in the early to mid-1970s and were based on the measurement of two symbol parameters: print contrast signal (PCS) and the bar width deviation. If the bar (or space) widths were within a defined (but somewhat arbitrary) tolerance, and if PCS was above a defined minimum value, the symbol was regarded as being "in spec."

Initially, none of these measurements were automated, and human factors affected the accuracy and consistency of measurements. Also, checking that the symbol was correctly encoded was a laborious task. However, within a few years, instruments were developed that performed these measurements automatically. These were the first true verifiers that enabled the printer to take steps to produce the symbols as nearly perfectly as this process allowed.

Traditional verification does not necessarily give results that correlate very closely with the actual scanning performance of the symbols. One reason is that the assessment of the symbol gives only a single threshold for acceptability: "Pass" or "Fail." In addition if the assessment is based on a single scan across the symbol, which might be through an exceptionally good or bad section of the symbol, it cannot be guaranteed to be truly representative of its condition.

Measurements of bar gain or loss are less meaningful in the case of certain symbologies, like the EAN/UPC Symbology and the GS1 128 Bar Code, where decoding relies primarily on edge-to-similar-edge distances, which are relatively immune to even substantial amounts of consistent gain or loss across the symbol. These distances are measured from the leading edge of one bar to the leading edge of the next (or from one trailing edge to the next), which tends to move in the same direction if there is bar gain or loss. A more subtle factor is that the method is not standardised, either as to where the dark and light reflectance (or density) measurements are made for the calculation of PCS, or as to how the exact position of an element edge is defined, so that some models of verifier could assess a given symbol as "Pass" whereas others could "Fail" it – a source of potential and, indeed, actual disagreements among suppliers and customers.

5.5.3.3.1.2. ISO Verification

During the 1980s, two factors led to attempts to improve the traditional verification technique. One was the disparity between traditional verification results and the real life performance of symbols, and the other was the increasing number of product rejections by customers based on differing verification results between the supplier's instrument and his customer's.

A wide-ranging programme by a group of experts from bar code and user industries working on all types of scanning systems determined the factors that most directly affect symbol-scanning performance and resulted in the analysis of the Scan Reflectance Profile (SRP). This methodology was originally known as ANSI verification because it was first described in the United States' standard ANSI X3.182, published in 1990 under the title *Bar Code Print Quality Guidelines*. The method was then defined in a European standard (*EN 1635*), published in 1995, and an international standard

(*ISO/IEC 15416*), published in 2000. *ISO/IEC 15416* is the definitive international specification of the ISO bar code verification methodology, and the numeric grading system is used.

The method, as described in the *ISO/IEC 15416* standard, is technically fully compatible with the ANSI X3.182 and *EN 1635* method, so verifiers based on these standards are not obsolete. Additionally, *ISO/IEC 15415* standard achieves comparable results to the linear bar code symbol quality standard *ISO/IEC 15416*, with the modifications in terms of parameters and methodologies that are applicable to two dimensional symbols.

In simple terms, an ISO verifier looks at the symbol in exactly the same way a scanner sees it. The ISO verifier reports its assessment of the symbol quality not as a single "Pass" or "Fail" decision, but as one of a range of four passing grades (from 4 to 1, in order of decreasing quality) or one failing grade (0). This enables an application to set the most appropriate minimum grade for acceptability. It may be noted that the ANSI standard uses the alphabetic scale A to D for passing grades and F for failing symbols, but the grade thresholds are identical.

The relationship between symbol grades measured in this way and the way the symbols behaved when they were scanned was so close that users rapidly came to accept the SRP assessment method for verifying symbols received from their trading partners. Users knew that as long as a symbol achieved grade 1.5 or better it would give them acceptable performance when they had to scan it to capture the encoded data.



Note: The GS1 System requires that the Quiet Zone be a measured parameter for EAN/UPC Symbology, GS1-128 Symbols, and ITF-14 Symbols per the values expressed in *ISO/IEC 15416*, Section 5. For GS1 DataMatrix it is equal to one x-dimension expressed in *ISO/IEC 16022* Section 7 and for GS1 QR Code it is equal to the four x-dimension expressed in *ISO/IEC 18004* Section 5.

5.5.3.3.1.3. Types of Verifiers

There are many types of verifiers and almost as many ways of classifying them, but for practical purposes, it is convenient to group them into two classes related to where they are used and the extent to which all their possible functions are required. This grouping corresponds reasonably closely to the Class A and Class B classification respectively (as used in the European pre-standard ENV 12647).

The first group (broadly equivalent to the Class A category) contains the full-function type of verifier, which is mainly found in a quality control laboratory. It performs a full range of measuring functions and provides comprehensive analytical reports on the symbol, enabling the cause of problems to be diagnosed. Its use requires a good degree of knowledge of the technology, and the operator must, therefore, be specially trained. Its measurement accuracy may be substantially higher than the average; its cost almost certainly is, and the time taken to perform the necessary scans and output the results may be relatively long; however, in the expected conditions for which such an instrument is purchased, this is not likely to be a problem. This type of verifier may have motorised optical heads to improve the evenness of movement and achieve the multiple scanning requirements, and to enable accurate dimensional measurements. In addition, this verifier may have interchangeable measuring apertures and light sources to enable measurement of symbols with a wide range of X-dimensions and to meet the illumination needs of differing application standards. Some of these instruments are used in conjunction with a personal computer with special verification software for the symbol analysis and display/printing of results, while others are integrated stand-alone units.

The second group (corresponding to the Class B category) contains all the simpler, easy-to-use devices intended for use in the pressroom or on the receiving dock by relatively less trained operators. At their simplest, these devices are used to rapidly check that symbols are of the desired grade or better and, particularly in the pressroom, to obtain an indication of bar gain or loss and of contrast to help the press operator fine-tune his machine. Typically they have a single light source and measuring aperture, though by using plug-in wands or mice, a degree of interchange functionality may be achieved. Some instruments use laser beam illumination, which facilitates multiple scans of the

symbol, though the effective measuring aperture may not be circular in shape, and its size may not be precisely known. They also may be more limited in their reflectance measurements.

A group of specialised verifiers is designed for mounting on printing equipment. They monitor the bar codes produced by the equipment and provide continuous analysis of key parameters, notably element widths, to enable the operator to control the printing process very quickly. Some are designed for high-speed presses and others for on-demand printers. Some are even able to automatically feed back control instructions to improve symbol quality and reprint defective labels.

A particular verifier may be hard to fit neatly into either class, as it may resemble the simpler class of unit in its physical construction, but its functions and the amount of information that it can give on the symbol may correspond more closely to those of the laboratory unit. Partly for this reason and partly because the Class A and Class B reporting requirements did not necessarily correspond precisely to what a verifier manufacturer might wish to offer for commercial reasons, the international standard *ISO/IEC 15426* (composed of *ISO/IEC 15426-1* for linear symbols and *ISO/IEC 15426-2* for two dimensional symbols), which replaces *ENV 12647*, has eliminated the classification scheme in favour of a minimum set of reporting requirements for all verifiers, to which manufacturers are at liberty to add in accordance with their view of the market needs.

5.5.3.3.2. Measurement Methodology

The symbol must be verified in its final configuration wherever possible (e.g., including over-laminate, package material, contents), but if this is not feasible, the following procedure is recommended to allow for the effects of show-through.

Place the symbol to be verified on a flat surface. If the substrate is not opaque (allows light through), perform the verification procedure with the symbol on a dark surface, and then repeat it on a light surface. Take the poorer set of results, unless it is known what type of material is likely to back the symbol in practice, in which case attempt to match it.

5.5.3.3.3. Symbol Grading

Symbol Grading for linear symbols consisting of the following topics is found in Section 6 of *ISO/IEC 15416*:

- Scan Reflectance Profile (SRP) grading (further explained in normative reference Annex B of *ISO/IEC 15416*)
- Decode
- Reflectance parameter grading (including the Reflectance Parameter Grading figure)
- Decodability (including the Decodability Grades figure; also covered in normative reference Annex A of *ISO/IEC 15416*)
- Expression of symbol grade
- Symbol grading process flowchart is available from normative reference Annex C of *ISO/IEC 15416*
- Guidance on the verification report template is available in Section 5.5.3.5 Bar Code Verification Template.

Symbol Grading for two dimensional symbols consisting of the following topics can be found in section 5 of *ISO/IEC 15415*:

- Expression of quality grades
- Overall Symbol Grade
- Reporting of the Symbol Grade
- Symbology-specific parameters and values for symbol grading (further explained in normative reference Annex A of *ISO/IEC 15415*)

- Symbology grading flowchart for two-dimensional matrix symbols (further explained in informative reference Annex B of *ISO/IEC 15415*)
- Guidance on selection of grading parameters in application specification available from informative reference Annex D of *ISO/IEC 15415*

5.5.3.3.4. Substrate Characteristics

Substrate characteristics consisting of the following topics are found in the informative reference Annex D of *ISO/IEC 15416* and informative reference Annex E of *ISO/IEC 15415*

- Substrate opacity
- Gloss
- Over-laminate
- Static reflectance measurements
- Prediction of Symbol Contrast
- Prediction of minimum edge contrast ($E_{c_{min}}$) and modulation (MOD)
- Acceptability of measured and derived values

5.5.3.3.5. Interpretation of the Scan Reflectance Profile and Profile Grades

Interpretation of the Scan Reflectance Profile (SRP) and profile grades consisting of the following topics is found in the informative reference Annex E of *ISO/IEC 15416* and informative reference Annex C of *ISO/IEC 15415*:

- Significance of SRPs
- Interpretation of results
- Matching grades to applications
- Alphabetic grading

5.5.3.3.6. Comparison with Traditional Methodologies

Comparison with traditional methodologies consisting of the following topics is found in the informative reference Annex I of *ISO/IEC 15416*:

- Traditional methodologies
- Correlation of print contrast signal with Symbol Contrast measurements
- Guidance on grading for applications also specifying print contrast signal (PCS)

5.5.3.3.7. Process Control Requirements

Process control requirement methodologies consisting of the following topics are found in the informative reference Annex J of *ISO/IEC 15416*:

- Process control for repetitive printing
- Number of scans
- Bar width deviation
- Two-width symbologies
- (n,k) symbologies
- Average bar gain/loss

Average bar error is not graded directly, but is used to calculate what fraction of a defined bar tolerance is consumed by the printing process. This traditional bar tolerance calculation differs by symbology and, in the case of the EAN/UPC Symbology, it also differs by the X-dimension at which the symbol is printed. Generally a smaller X-dimension yields a smaller tolerance.

5.5.3.3.8. Compliance Statement

Verifiers that are suitable for use with the recommendations contained in these *GS1 General Specifications* will often be supplied with a statement that associates the instrument with the following calibration standards:

“Applied Image certified EAN/UPC Symbology calibration standards are manufactured to specifications set by Applied Image and the collaboration of GS1 using ISO/IEC 15416 and/or ISO/IEC 15415 methodologies and are calibrated using standards traceable to the National Institute of Standards and Technology.”

5.5.3.3.9. Calibrated Conformance Standard Test Cards

The verifier operator may use a variety of tools and procedures to periodically ensure maintenance of the verifier's calibration. For example, the operator may follow the manufacturer's recommended procedure for set-up, programming (if necessary), normal operational calibration, and use of the verifier prior to performing any tests. Indeed such procedures are considered essential to ensure the consistency of verification results over time.

Some verifier manufacturers may require the operator to utilise a calibration patch designed for use in maintaining instrument calibration. A common form of patch is often referred to as a "reflectance patch," which may be provided with the instrument. It is very important that the manufacturer's instructions are followed carefully and conscientiously to properly calibrate the instrument. An indication of "calibration complete" normally signals successful recalibration of the device.

Other manufacturers may require periodic factory calibration of their verifier to maintain proper calibration.

With the increasing use of verifiers as communication tools, all verifiers must be periodically checked for their calibration conformance to a traceable standard (within accuracy and repeatability limits stated by the manufacturer). For this reason, Calibrated Conformance Standard Test Cards are available for the verifier user.

Calibrated Conformance Standard Test Cards have been designed for verifiers with 6, 8, 10, and 20 mils apertures, and the following are currently available from your GS1 Member Organisation:

- EAN/UPC Calibrated Conformance Standard Test Card
- ITF Calibrated Conformance Standard Test Card
- GS1-128 Calibrated Conformance Standard Test Card
- GS1 DataBar Calibrated Conformance Standard Test Card
- GS1 DataMatrix Calibrated Conformance Standard Test Card

Use of these test cards provide a number of benefits including:

- Validates verifiers for UPC-A, EAN-13, ITF, GS1-128, GS1 DataMatrix and GS1 DataBar symbols. Covers all GS1 symbologies except Composite Component and GS1 QR Code
- Training tool for operators of verifiers
- Validates that the verifier is working within its specified tolerances for the symbology selected

Each test card is designed to test particular characteristics of *ISO/IEC 15416* and *ISO/IEC 15415* - based verification equipment. The standards are manufactured on special materials and are made

traceable to the National Institute of Standards and Technology (NIST). This traceability is facilitated through a custom designed piece of hardware (nicknamed “the Judge”) and has been engineered to measure the various attributes outlined in *ISO/IEC 15416*. The Judge has also been made traceable to NIST in Washington, D.C.

The idea behind the standard is to regularly test the verification equipment to ensure it is operating within ISO tolerance levels as published by the verifier manufacturer. This is especially important in heavy use applications where various operators may be involved or where a new user is learning to properly verify. The operator should routinely scan each of the symbols on the test card to determine if the verifier device provides the values listed. These specifications stipulate an aperture and 670 nanometres +/-10 nanometres wavelength be used, and the exact scanning method should be determined by following all of the verifier manufacturer recommendations. This may require some practice to obtain the right touch, but it will inform the operator when the correct method has been used.

If the verifier reports values that agree with the values listed on the test card (within the verifier manufacturer’s stated accuracy and repeatability limits), then the operator can assume the verifier is calibrated. If, after repeated attempts, the device does not provide the value as printed on the standard (within the verifier manufacturer’s stated accuracy and repeatability limits), then the device or the operator’s scanning technique must be considered suspect. In this event, the operator should refer to his or her operator’s manual as to the proper remedies specified by the verifier manufacturer.

Test cards are sensitive and should be handled with care. If the symbols show dirty areas, one can safely clean these by using a soft cotton pad and photographic grade film cleaner. If visible scratches develop on a symbol, that area of the symbol SHALL not be used. If sufficient visible scratches develop so that a clean scan path is not available, then the test card is no longer useable and SHALL be replaced.

The test card serves as a device for, or means of, confirming that an ISO-based verifier has been properly calibrated and that users are obtaining results within the accuracy limits stated by the manufacturer of their instruments.

It is possible that a defective verifier, use of a damaged or incorrect reflectance patch, or, in some cases, a careless user performing the calibration to the patch might provide a false indication of successful calibration. The proper use of the Calibrated Conformance Standard Test Cards is the only way multiple trading partners can be assured of reliable quality measurements for the printed GS1 endorsed symbol.

As a general rule, any ISO-based verifier (NIST or non-NIST traceable) should be periodically tested using a Calibrated Conformance Standard Test Card. This procedure will confirm both the accuracy of the instrument and the skill of the user.

5.5.3.3.10. Special Considerations for Verification of GS1 System Symbologies

5.5.3.3.10.1. General

Since ISO verification does not measure dimensions, it is part of the additional visual checking that has to be carried out to ensure that, for example, the symbol height meets the application requirements.

With better digital imaging software, element dimensions can only be adjusted automatically to the nearest integer number of pixels in the output device, be it imagesetter or printer, enabling element width ratios to be maintained with allowance duly made, for example, for bar gain/loss and adjustment of element widths for digits 1, 2, 7, and 8 in EAN/UPC Symbols. This means that symbol sizes may not match those input as target dimensions, but will vary in discrete steps within the permitted range, which will result in a more accurate symbol overall.



Note: For a list of international standards pertaining to GS1 System Symbologies, see Section 5.1.1

5.5.3.3.10.2. EAN/UPC Symbology

The main characteristic of the EAN/UPC Symbology that affects verification is the different treatment of the three sets of symbol characters for digits 1, 2, 7, and 8 from the remaining digits (0, 3, 4, 5, 6, and 9). The reference decode algorithm uses the combined width of both bars in these characters to discriminate between a 1 and a 7, and between a 2 and an 8, which are ambiguously decodable since they share the same set of edge-to-similar-edge modular dimensions. The addition to or subtraction from the element widths of 1/13 module is intended to increase the differences between the sums of the bar widths for each pair of ambiguous characters. The decodability parameter for these characters takes account of bar gain and loss whereas it does not for the remaining symbol characters. Consequently, a symbol not containing any of these four symbol characters may suffer substantial bar gain or loss without degrading its decodability, whereas a symbol that does contain one or more of them is likely to have a lower decodability grade, with the same amount of bar gain or loss. However, the laws of probability suggest that only some 6.9 percent of symbols would not be affected by this, so it is wise to be cautious and assume that bar gain or loss is a possible cause of a poor decodability grade for EAN/UPC Symbols. It is also wise (for process control purposes) not to assume that the decodability grade correlates with bar width deviation, but it is far safer and easier to rely on the traditional measurement of bar width deviation for adjusting the production process.

The measuring aperture for EAN/UPC Symbols, irrespective of X-dimension, is 6 mils (which is equivalent to 0.15 millimetre (0.006 inch)). This is not one of the four ISO-recommended standard default aperture sizes, which are 3, 5, 10, and 20 millimetres, but is usually available from verifier manufacturers. This diameter was based on measurement of symbols with various apertures and much test scanning in order to determine which aperture gave results correlating best with scanning performance.


Additional EAN/UPC Symbol Grading Criteria

ISO/IEC 15416 Bar code print quality test specification — Linear symbols allows for additional pass/fail criteria to be stipulated by a symbology specification. For the EAN/UPC Symbology, the minimum quiet zone dimensions are given in [5.2.1.4.4](#). Any individual scan profile which does not meet these requirements allowing for the following tolerances shall receive a grade of "0".

Figure 5.5.3.3.10.2 - 1 Minimum Width of Measured Quiet Zones

Symbol Version	Left Quiet Zone	Right Quiet Zone
EAN-13	10X	6.2X
EAN-8	8X	6.2X
UPC-A	8X	8X
UPC-E	8X	6.2X
Add-Ons (EAN)	EAN 13/8 right QZ	4.2X
Add-Ons (U.P.C.)	UPC A/E right QZ	4.2X

Symbols that fall below range defined in [5.2.3.7-1](#) Magnification factors shall receive a grade of 0 (see [5.5.3.4.3](#) for exception).

 **Note:** The choice of minimum quiet zone dimension was based on the historical U.P.C. Quality Guideline. Since EAN-13 and EAN-8 were not included, minimum quiet zone dimension similarly derived were chosen for those symbols.

5.5.3.3.10.3. GS1-128 Symbology

The important aspects to verify for a GS1-128 Symbol are its print quality, which is assessed in the standard way, and its formatting, which may need to be visually checked from the information output by the verifier. The Code 128 Symbology is an edge-to-similar-edge decodable symbology, but its reference decode algorithm also requires a check of the sum of the widths of the three bars in each character as part of its parity checking process. Consequently, its decodability is affected by bar gain or loss.

Measuring apertures for GS1-128 Symbols varies according to the application. For all applications except the GS1-128 Coupon Extended Code, an aperture of 10 mils is specified, giving a minimum acceptable grade of 1.5/10/670. The GS1 Common Currency Coupon Code requires an aperture of 6 mils and a minimum grade of 1.5/06/670.

Data contained in GS1-128 Symbols must be formatted according to these specifications for the use of Application Identifiers (AIs). Specific features to check are:

- Presence of Function 1 Symbol Character (FNC1) as a flag for the GS1 System subset of the Code 128 Symbol, in the first position after the Start Character
- Use of FNC1 as a field separator following non-predefined length AIs
- Sequencing of AIs, with pre-defined length AIs preceding non pre-defined length ones
- Length of data fields with fixed length AIs
- Correct formatting of data in all AI fields
- Absence of encoded parentheses around AIs

The extent to which a verifier can do this automatically will vary greatly among devices, even those that have GS1-128 Symbols as a specific symbology option.

5.5.3.3.10.4. ITF-14 Symbology

ITF-14 Bar Codes are, unlike the others used in the GS1 System, two-width (narrow/wide) symbols that cannot be decoded by the edge-to-similar-edge technique, but all element widths must be measured. They are, therefore, more subject to the problems caused by bar gain or loss.

The standard ISO verification technique is fully applicable to these symbols. However, in the GS1 System application, additional checks must be made to ensure that the X-dimension (magnification factor) is within the permitted range.

Measuring apertures for the ITF-14 Symbol SHALL be 10 mils for symbols with an X-dimension less than 0.635 millimetre (0.0250 in) and SHALL be 20 mils for symbols with an X-dimension equal to or greater than 0.635 millimetre (0.0250 in).

The minimum acceptable grade for symbols printed with the higher range of X-dimension (above 0.635 millimetre or 0.0250 in) SHALL be 0.5/20/670. This is because the brown corrugated substrates on which such symbols are often printed typically have a reflectance value below 40 percent, and sometimes below 30 percent, and cannot, therefore, ever achieve a Symbol Contrast better than 40 percent (the lower threshold for a grade 2 Symbol Contrast) no matter how dense the ink or how well the other attributes of the symbol are graded. As a result, the Scan Reflectance Profile (SRP) grade will most often be dictated by Symbol Contrast, so it cannot be higher than 1 for symbols on these materials, giving a maximum achievable overall symbol grade of 1.0.

Such symbols may also be affected by the inherent interference in the background reflectance caused by the substrate's composition, which may well lead to reduced defect grades and possibly low edge contrast and modulation values. It is, therefore, desirable to ensure that symbols printed on these corrugated materials are of as high a quality as possible in respect of the other parameters.

5.5.3.3.10.5 GS1 DataMatrix

Determining symbol quality for items marked with GS1 DataMatrix (both traditionally printed and Direct Part Marked - DPM) involves a specialized approach due to the physical nature of the marking

and the optical systems used to read those marks. The minimum symbol quality grade for GS1 DataMatrix Symbols shall be specified by the application specification. The measurement of the quality parameters for DPM symbols shall be made by a verifier conforming to ISO/IEC 15415 and when direct marked augmented with AIM DPM-1-2006 which defines DPM quality specific alternative illumination conditions, terms, parameters, modifications to the measurement and grading of certain parameters and the reporting of the grading results. According to these standards an overall grade is shown in the form:

Grade/Aperture/Light/Angle

Where:

- **"Grade"** is the overall symbol grade as defined in *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code print quality test specification - Two-dimensional symbols (e.g., the arithmetic mean to one decimal place of the Scan Reflectance Profile or scan grades) *with the additional information found in the AIM DPM Quality Guideline for direct marked parts*. For GS1 DataMatrix, the grade number may be followed by an asterisk, *, which indicates that the surroundings of the symbol contain extremes of reflectance that may interfere with reading. For most applications, this should be specified as causing the symbol to fail.
 - **"Aperture"** is the diameter in thousandths of an inch (to the nearest thousandth) of the synthetic aperture defined in *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code symbol print quality test specification - Two-dimensional symbols.
 - **"Light"** defines the illumination: A numeric value indicates the peak light wavelength in nanometers (for narrow band illumination); the alphabetic character W indicates that the symbol has been measured with broadband illumination ("white light"), the spectral response characteristics of which must imperatively be defined or have their source specification clearly referenced.
 - **"Angle"** is an additional parameter defining the angle of incidence (relative to the plane of the symbol) of the illumination. It shall be included in the reporting of the overall symbol grade when the angle of incidence is other than 45 degrees. Its absence indicates that the angle of incidence is 45 degrees.
- ✓ **Note:** This international standard provides for 30 degrees and 90 degrees illumination in addition to the default 45 degrees.

The aperture is normally specified as being 80 percent of the minimum X-dimension allowed for the application. The printing method must produce the GS1 DataMatrix "L" pattern with gaps between the dots less than 25 percent of the specified aperture. If symbols with greater than the minimum X dimension are allowed by the application, the same absolute maximum gap dimension must be maintained.

5.5.3.3.10.6 GS1 QR Code

Determining symbol quality for items marked with GS1 QR Code symbols involves a specialized approach due to the physical nature of the marking and the optical systems used to read those marks. The minimum symbol quality grade for GS1 QR Code Symbols shall be specified by the application specification. The overall grade is shown in the form minimum grade/aperture/measuring wavelength.

Grade/Aperture/Light/Angle

Where:

- **"Grade"** is the overall symbol grade as defined in *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code print quality test specification - Two-dimensional symbols (e.g., the arithmetic mean to one decimal place of the Scan

Reflectance Profile or scan grades). For GS1 QR Code, the grade number may be followed by an asterisk, *, which indicates that the surroundings of the symbol contain extremes of reflectance that may interfere with reading. For most applications, this should be specified as causing the symbol to fail.

- **"Aperture"** is the diameter in thousandths of an inch (to the nearest thousandth) of the synthetic aperture defined in *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code symbol print quality test specification - Two-dimensional symbols.
- **"Light"** defines the illumination: A numeric value indicates the peak light wavelength in nanometers (for narrow band illumination); the alphabetic character W indicates that the symbol has been measured with broadband illumination ("white light"), the spectral response characteristics of which must imperatively be defined or have their source specification clearly referenced.
- **"Angle"** is an additional parameter defining the angle of incidence (relative to the plane of the symbol) of the illumination. It shall be included in the reporting of the overall symbol grade when the angle of incidence is other than 45 degrees. Its absence indicates that the angle of incidence is 45 degrees.

The aperture is normally specified as being 80 percent of the minimum X-dimension allowed for the application

5.5.3.3.11. Possible Causes of Less-Than-Perfect Verification Grades

5.5.3.3.11.1. Reflectance Parameters

Symbol Contrast is governed by the reflectance of the substrate and ink. A symbol printed in black ink on a white paper will almost certainly achieve the top grade 4 for Symbol Contrast, as white papers typically have reflectance in excess of 75 percent, and black ink will usually have about 3 to 8 percent reflectance. Coloured backgrounds or coloured inks will affect the result. Highly glossy materials may also appear to have a lower background reflectance than expected. The worst case may be when printing on a corrugated brown fibre-board material, which may have a reflectance in a range between 27 and 40 percent, so even with a very dense, low reflectance ink it can never achieve better than the minimum passing grade 1 for Symbol Contrast (grade 1 includes Symbol Contrast values from 20 to 39 percent).

The causes of low Symbol Contrast and the solutions are:

- Background too dark: Use lighter or less glossy material, or change background colour (if printed) to one with higher reflectance
- Bars too light: Change bar colour for one with lower reflectance, and increase ink weight or print head temperature (thermal printing) (Watch for consequential increase in bar widths)
- Show-through of contents: Use more opaque material for package, or print opaque white underlay prior to printing symbol
- Show-through of imprint: Use more opaque labels

Minimum reflectance, or R_{min} , must always be equal to or less than half the highest reflectance value, R_{max} . In practice, this means that the reflectance of at least one bar must meet this criterion. For example, if R_{max} is 70 percent, at least one bar must have a reflectance of 35 percent or less. A symbol that fails on this parameter will almost certainly have a low Symbol Contrast grade also.

The cause of and solution for R_{min} being too high include:

- Bars too light: Change bar colour to one with lower reflectance, and increase ink weight or print head temperature (thermal printing) (Watch for consequential increase in bar widths)

Minimum Edge Contrast (EC_{min}) will always be lower than Symbol Contrast, but will only be a problem in itself if it approaches or drops below 15 percent (the pass/fail threshold). However, low edge contrast (EC) values, acceptable under this criterion, may still cause low modulation (MOD) grades.

The causes of a low value of EC_{min} and the possible remedies are:

- Local variations in background reflectance (e.g., fragments of darker material in a recycled material): Use a more consistent substrate or one with higher reflectance
- Local variations in inking of the bars: Adjust press settings to ensure even inking
- Show-through of contents: Use more opaque material for package, or print opaque white underlay prior to printing symbol
- Elements adjoining the edge in question are excessively narrow relative to the measuring aperture used: Increase X-dimension; ensure correct measuring aperture is used; ensure correct bar width adjustment (BWA) applied to Film Master/original symbol; print bars marginally narrower than spaces of same modular dimension

Modulation, being calculated as the percentage of Symbol Contrast represented by the EC_{min}, will be reduced for the same reasons as when EC_{min} is low in the symbol. A scanner will tend to see spaces as narrower than bars and also to see narrow elements as less distinct than wider ones. Consequently, if there is significant bar loss, modulation will be reduced. Measuring with an aperture that is too large for the X-dimension will also reduce modulation.

The causes of a low value of modulation (often listed as “MOD” on verification reports) and the possible remedies are:

- Local variations in background reflectance (e.g., fragments of darker material in a recycled material): Use a more consistent substrate or one with higher reflectance
- Local variations in inking of the bars: Adjust press settings to ensure even or darker inking
- Show-through of contents: Use more opaque material for package, or print opaque white underlay prior to printing symbol
- Element(s) adjoining the edge in question appear excessively narrow relative to the measuring aperture used: Increase X-dimension; ensure correct measuring aperture is used; apply correct BWA when originating symbol; print bars marginally narrower than spaces of same modular dimension

5.5.3.3.12. Other Parameters

Decode is graded on a pass/fail basis by applying the reference decode algorithm to the edge positions and element widths determined for the symbol. A failure to decode may be evidence of the symbol being incorrectly encoded, which may include an incorrect Check Digit. It also may indicate either that the bars and spaces initially identified by the global threshold are too many or too few for a valid symbol or that one or more edge positions are ambiguous.

The possible causes of decode failure and possible remedies are:

- Symbol incorrectly encoded: Re-originate symbol; over-label with correctly encoded symbol
- Check Digit incorrectly calculated: Correct software error in origination system; re-originate symbol; over-label with correctly calculated symbol
- Gross element width errors due to excessive bar gain or loss, or to defects: Apply correct bar width adjustment (BWA) when originating symbol; adjust press or printer settings
- Too many elements detected due to defects: Correct cause of defects; adjust press (relief printing processes) to reduce halving; replace print head (thermal/ink-jet printing)
- Too few elements detected (failure to cross global threshold): Refer to solutions for edge contrast (EC)

In the ISO standard, a decode failure occurs because an incorrect number of elements has been perceived to be present, either because the profile of one or more elements has failed to cross the global threshold or because a gross defect has caused one element to be seen as three or more, corresponding to the separately graded Edge Determination failure in the ANSI standard, which may also be reported by some verifiers following the ANSI methodology.


Figure 5.4.3.3.12 – 1 shows a symbol in which the narrow spaces have been partly filled in, reducing their contrast below the global threshold and causing an edge determination or decode failure. This could also be interpreted as an extreme example of modulation (MOD).

Figure 5.5.3.3.12 - 1 Symbol with Edge Determination Problem



Figure 5.5.3.3.12 - 2 illustrates a Scan Reflectance Profile (SRP) showing narrow space profiles failing to reach the global threshold, giving an (ISO) decode failure or (ANSI) edge determination failure.

Figure 5.5.3.3.12 - 2 Scan Reflectance Profile with Narrow Space Profiles



Decodability grades are influenced by bar gain or loss in most symbologies and by distortion of the symbol. Distortion can occur with relief printing processes, such as flexography, when the printing plate is stretched around the press cylinder with the bars parallel to the cylinder axis (e.g., at right angles to the print direction). A common reason for distortion with digitally-originated images is that they have been rescaled in graphics software, resulting in uneven addition or removal of pixels to or from the element widths. Print processes that tend to produce irregular bar edges, such as ink-jet and photogravure, will also be likely to give lower decodability grades.

The causes of a low value of decodability and the possible remedies are:

- Bar gain/loss (systematic): Apply correct bar width adjustment (BWA) when originating symbol; adjust press settings
- Element width gain/loss (non-systematic): Correct missing pixels (burnt-out print head elements, blocked ink-jet nozzles); rectify cause of defects


- Distortion of symbol (uneven stretching of flexographic plate; non-linear disproportioning in plate-making process): Print symbol with height of bars parallel to direction of printing; do not disproportion bar code image in plate-making
- Rescaling of digitally-originated images: Ensure symbol is created in correct size; ensure software matches module widths to integer number of pixels after all adjustments
- Irregular element edges (ink-jet, photogravure, screen process printing): Change print technology; increase X-dimension/magnification factor; re-orient symbol relative to cylinder engraving angle/screen mesh

The symbol in Figure 5.5.3.3.12 - 3 is taken from the GS1 Calibrated Conformance Standard Test Card and has an engineered low decodability grade of 50 percent. As may be determined from the accompanying Scan Reflectance Profile (SRP), just to the left of halfway across the symbol, the width of a two-module bar has been increased in the sixth digit (and since the character is a 1, its decodability is affected by bar width). Although the original symbol has a very consistent image density, the profile also shows the effect of modulation (MOD), most noticeably on the narrow spaces.

Figure 5.5.3.3.12 - 3 Calibration Symbol with Engineered Low Decodability Grade



Figure 5.5.3.3.12 – 4 Scan Reflectance Profile of Symbol with Low Decodability Character



Defects, which show as irregularities in the Scan Reflectance Profile, may be caused by spots of extraneous ink in Quiet Zones or in the spaces. Small voids (white areas) in the bars are also highlighted as defects. In symbols printed on recycled or some other materials, local variations in reflectance of the background will also show as defects. The significance of a defect is in direct relation to the depth of the irregularity it causes in the Scan Reflectance Profile.

Common causes and the most likely solutions include:

- Defective print head elements (thermal printing or ink-jet printing), which will tend to produce an unprinted line running through the symbol in the direction of printing: Clean or replace print head
- Satellite (ink droplets in the white are surrounding the printed bars): Clean head; change ink formulation

- Haloining (e.g., a double line impression where there should only be a single line impression): Adjust impression pressure and/or ink viscosity
- Incorrect matching of thermal transfer ribbons and substrate (poor adhesion of ink to surface): Use correct ribbon for substrate; use smoother substrate
- Measuring aperture too small: Use verifier with correct aperture

The use of a smaller or larger measuring aperture than specified for the symbol will produce misleading defect grades, and this is perhaps the strongest argument for ensuring that the right aperture size is used. Too small an aperture will exaggerate the apparent size of a defect; too large an aperture will tend to smooth it out.

Quiet Zones are a frequent source of scanning problems. Although the ISO standard does not directly require measurement of the Quiet Zones, it requires any additional requirements specified by the application specification to be graded on a pass/fail basis. The *GS1 General Specifications* establishes Quiet Zone requirements for all symbols used in the GS1 System, and a Quiet Zone less than the minimum width will, therefore, cause the profile grade to fail.

Possible causes of Quiet Zone failure and the remedies are:

- Printed box surrounding symbol or other interfering print: Enlarge box; ensure symbol registration to other print allows adequate margins; use Quiet Zone Indicators if possible
- Symbol too close to label edge: Adjust label feed; reposition symbol farther from edge; use larger label size or smaller symbol

5.5.3.4. Print Process Characterisation Techniques

5.5.3.4.1. Introduction

This section specifies when EAN/UPC Symbols can be printed at less than the current minimum specification of 0.264 millimetres or 0.0104 inch X-dimension (80 percent magnification).

5.5.3.4.2. Background

Many printer users have asked if the magnifications in the 75 to 80 percent range for EAN/UPC Symbols printed by thermal and laser on-demand printers are acceptable for use. The most common printing densities used by on-demand, bar code printers are 200 and 300 dpi. However, due to the constraints of the dot pitch, these printers cannot print an 80 percent symbol correctly. The nearest to 80 percent that these printers can print is 75.7 or 76.9 percent depending on the exact dot geometry.

Even though 80 percent magnification is the minimum value specified in the EAN/UPC Symbol specification, users of on-demand printers have used magnifications between 75 and 80 percent in Point-of-Sale scanning environments for years. They have done so with no significant reduction in scan rate, as compared to symbols printed precisely at 80 percent. Because larger in-specification EAN/UPC Symbols are always easier to scan, 80 percent symbols and larger are preferred. However, when an on-demand printer is required, the 75 to 80 percent EAN/UPC Symbols are an acceptable alternative given the conditions in Section [5.5.3.4.3](#).

5.5.3.4.3. New Qualifications for Printing


The allowance for EAN/UPC Symbol magnifications from 75 to 80 percent is only applicable to "on demand" (e.g., thermal or laser) print processes. For all other printing processes, 80 percent is attainable and is the minimum allowable size.

When printing a minimum symbol with any method of printing, the area provided for printing the symbol and the required Quiet Zone should never be less than the area required for an 80 percent symbol. This area is derived from the total width of an 80 percent symbol times its height as shown in the dimensions in Figure 5.5.3.4.3 - 1.

When printing a minimum symbol with any method of printing, the symbol height should never be truncated below the 80 percent value (20.7 millimetres or 0.816 inch).

The minimum print quality grade should be the same for all EAN/UPC Symbols; at least an ISO/ANSI grade of 1.5 (or C). It is advisable to print EAN/UPC Symbols that are at least a 2.5 (B) grade at the time of printing regardless of size.

Figure 5.5.3.4.3 - 1 EAN/UPC Symbol Shown with Minimum Height and Overall Width Dimensions for Magnifications of 75 Percent to 80 Percent



Note: As you move from 80 to 75 percent magnification, the Quiet Zone increases from 0.094 inch (2.38 millimetres) to 0.124 inch (3.16 millimetres) in order to keep the overall width constant at 1.175 inches (29.85 millimetres).

5.5.3.4.4. Summary

When printing with on-demand printers (e.g., thermal or laser) the resulting element widths for EAN/UPC Symbols SHALL never be less than 75 percent magnification. If the symbol printed with element widths is less than 80 percent, then the overall symbol shall have both larger Quiet Zones and taller bars such that the resulting area is not less than that of 80 percent magnification symbols. The symbol print quality must still meet the EAN/UPC Symbol requirements of 1.5/06/670.

5.5.3.5. GS1 Bar Code Verification Template

5.5.3.5.1. Introduction

These GS1 Bar Code Verification Templates were developed in co-operation with retailers, manufacturers, logistic providers and equipment providers to ensure a common reporting approach on a global level. They help ensure consistency regardless of where and by whom the symbols are tested thus removing the costly and inefficient requirements for multiple testing of identical symbols and reducing the cost of compliant equipment.

These templates do not introduce any requirements in and of themselves. The sole aim is to provide a common reporting format to measure compliance with the numbering and bar coding standards of GS1 laid down elsewhere in these GS1 General Specifications.

5.5.3.5.2. Background

GS1 has developed these verification templates on the basis of ISO/IEC 15416 Information technology – Automatic identification and data capture techniques, Bar Code Print Quality Test Specifications for Linear Symbols and ISO/IEC 15415 Information technology – Automatic identification and data capture techniques – Bar code print quality test specification – Two dimensional symbols. This not only allows for assessing the quality of printed bar codes but also checks against other key aspects of GS1 System (symbol location, fit-for purposes, data integrity, etc).

A GS1 initiated Verifier Conformance Testing Project was conducted because of concerns expressed that different verifiers or verification services were unable to perform consistently. The perception was

that different verifiers gave substantially different results when measuring the same symbol. A precisely defined test programme was performed under the auspices of GS1 and concluded that:

- All verifiers tested (each one ISO compliant) demonstrated the capability of consistent performance.
- Operators of verifiers require proper training and instruments require regular calibration in accordance with manufacturer recommendations.
- Most verifiers tested were capable of conforming to GS1 requirements

It is therefore important to stress the need for professional verification services and that bar code print quality should be integral part of an overall quality programme. Section [5.5.2.7](#) provides a quick reference list of symbol quality specifications depending on the symbol type, the application, or the identification number the symbol is carrying.

All GS1 user companies should perform quality control of bar code production and most GS1 Member Organisations offer a verification service. These report templates may be used by any organisation or company as part of a quality programme while respecting the Copyright of the GS1 logo (or any heading or text that imply actual GS1 endorsement (subject to local licensing agreements such as accreditation programmes, which may allow exceptions)).

The templates below highlighting critical issues relating to verification and provides a common template for reporting on the most common areas of application. They are not a guarantee of scan performance.

5.5.3.5.3. GS1 Bar Code Verification Template for Linear Symbols

<NAME>	Issue Date	<Date of Issue>
<Line one address>		
<Line two address>		
<Town>		
<Postcode>		
Product Description:	<Brand and Name of Product>	
Type of bar code:	<Symbol Type>	
Data encoded:	< Data Encoded>	
Print Method:	<Print Method>	
Number of bar codes on product:	<Number of Symbols>	

Please Note: These assessments are based on meeting the minimum GS1 standards.
To ensure efficient scanning, the bar code should exceed the minimum.

Testing Summary of the Linear Symbol

<i>GS1 General Specifications for Linear Symbols tested environments:</i>
Approved / Not Approved/ Not Assessed for Retail, Point of Sale Scanning
Approved / Not Approved/ Not Assessed for General Distribution and Logistics scanning



Approved / Not Approved/Not Assessed for Other Scanning Applications
 (Specify) _____

Complies with GS1 Symbol Location Recommendations	In/Out Spec (& comment on business critical issue)
ISO Symbol Grade	ISO <x.x>/06/660 (0.0 – 4.0) PASS/FAIL

Business Critical Comments

Technical Analysis of the Linear Symbol

GS1 Parameters	Comment Reference	Assessed	Within Standard Range	Required
Symbol Structure ¹			✓	(dependent on symbol encoded)
X-dimension (magnification)		0.330	✓	0.264mm-0.660mm
Bar Code Height		26mm	✓	26.04mm
Quiet Zone (Left)			✓	3.63mm
Quiet Zone (Right)			✓	2.31mm
Human Readable			✓	One-to-one match with bar code data
Bar Code Width			✓	<165mm
Validity of GS1 Company Prefix			✓	
Data Structure			✓	(dependent on structure encoded)

ISO Parameters	Comment Reference	Grade ISO/ANSI	Within Standard Range	Required
Overall ISO Grade ²		3.8/06/660	✓	>1.5
Decode		4.0	✓	>1.5
Symbol Contrast		3.8	✓	>1.5
Minimum Reflectance		4.0	✓	>1.5
Edge Contrast		4.0	✓	>1.5
Modulation		4.0	✓	>1.5
Defects		4.0	✓	>1.5
Decodability		4.0	✓	>1.5



Note 1 Includes Check Digits, ITF-14 wide-to-narrow ratio, etc.

Note 2 0.5 acceptable for ITF-14 with X-dimension > 0.635mm

Additional Tests	ISO Symbol Grade (0.0 – 4.0) PASS/FAIL	General Comment
GS1-128 Application Identifiers encoded – See comments		Pass/Fail/Not assessed
(example) Multiple GS1-128 symbols - Row 2		
(example) Multiple GS1-128 symbols - Row 3		
Educational Comments ¹		

Notes (informative localised)

It is the responsibility of the brand owner to ensure the correct use of the GS1 Company Prefix and the correct allocation of the data content.

Rejection of products should not necessarily be based only on an out of specification results

Bar Code verifiers are measuring devices and are tools that can be used for assisting in quality control. The results are not absolute in that they do not necessarily prove or disprove that the bar code will scan.

This report may not be amended after issue. In the event of a dispute over contents the version held at [TESTING AGENCY] will be deemed to be the correct and original version of this report.

Important Note (normative localised)

This Verification Report may contain privileged and confidential information intended only for the use of the addressee named above. If you are not the intended recipient of this report you are hereby notified that any use, dissemination, distribution or reproduction of this message is prohibited. If you received this message in error please notify [TESTING AGENCY].

Disclaimer (legal localised)

This report does not constitute evidence for the purpose of any litigation, and [TESTING AGENCY] will not enter into any discussion, or respond to any correspondence in relation to litigation.

Every possible effort has been made to ensure that the information and specifications in the Bar Code Verification Reports are correct, however, [TESTING AGENCY] expressly disclaims liability for any errors.

5.5.3.5.4. GS1 Bar Code Verification Template for Two Dimensional Symbols

<NAME> Issue Date<Date of Issue>
 <Line one address>
 <Line two address>
 <Town>
 <Postcode>
Product Description: <Brand and Name of Product>
Type of bar code: <Symbol Type>
Data encoded: < Data Encoded>
Print Method: <Print Method>
Number of bar codes on product: <Number of Symbols>

Please Note: These assessments are based on meeting the minimum GS1 standards.
 To ensure efficient scanning, the bar code should exceed the minimum.

Testing Summary of the Two Dimensional Symbol

GS1 General Specifications for Two Dimensional Symbols, environments tested:

¹ Educational comments are based on the technical analysis of the symbol. In this comment box the operator comments on what the problem is and how to make the symbol better by explaining the parameter’s meanings.



PASS or FAIL or Not assessed Healthcare Items (Healthcare Retail Consumer Item or Healthcare Non-Retail Consumer Item or Healthcare Trade Item)
PASS or FAIL or Not assessed Direct Part Marking
PASS or FAIL or Not assessed Extended Packaging

Complies to GS1 Symbol Location Recommendations	In/Out Spec (& comment on business critical issue)
ISO Symbol Grade	ISO <x.x>/06/660 (0.0 – 4.0) PASS/FAIL

Business Critical Comments

Technical Analysis of the Two Dimensional Symbol

GS1 Parameters	Comment Reference	Values	Within Standard Range?	Required
Symbol Structure			✓	Dependent on symbol encoded
Matrix Size		NN X NN	✓	
X Dimension/Cell Size		in mm / inc	✓	
Data Structure			✓	Dependent on structure encoded
Validity of GS1 Company Prefix			✓	
Human Readable			✓	

ISO/IEC Parameters	Comment Reference	ISO Grade A to F	Within Standard Range?	Required
Overall ISO Grade			✓	
Decode		PASS /FAIL	✓	
Cell Contrast/Symbol Contrast		A-F	✓	
Cell Modulation/Modulation		A-F	✓	
Axial Nonuniformity		A-F	✓	
Grid Nonuniformity		A-F	✓	
Unused Error Correction (UEC)		A-F	✓	
Print Growth (Horizontal) Informative Only		0%-100%	Non-Graded	
Print Growth (Vertical) Informative Only		0%-100%	Non-Graded	
Fixed Pattern Damage		A-F	✓	

Clock Track and Solid Area Regularity*		A-F	✓	
Quiet Zones (QZL1, QZL2)*		A-F	✓	
L1 and L2*		A-F	✓	
Format Information**				
Version Information**				

Educational Comments ²

Notes (informative localised)

It is the responsibility of the brand owner to ensure the correct use of the GS1 Company Prefix and the correct allocation of the data content.

Rejection of products should not necessarily be based only on an out of specification results

Bar Code verifiers are measuring devices and are tools that can be used for assisting in quality control. The results are not absolute in that they do not necessarily prove or disprove that the bar code will scan.

This report may not be amended after issue. In the event of a dispute over contents the version held at [TESTING AGENCY] will be deemed to be the correct and original version of this report.

* GS1 DataMatrix Only, see ISO/IEC 15415

** GS1 QR Code Only, see ISO/IEC 15415,

all others are both for GS1 DataMatrix and GS1 QR Code

Important Note (normative localised)

This Verification Report may contain privileged and confidential information intended only for the use of the addressee named above. If you are not the intended recipient of this report you are hereby notified that any use, dissemination, distribution or reproduction of this message is prohibited. If you received this message in error please notify [TESTING AGENCY].

Disclaimer (legal localised)

This report does not constitute evidence for the purpose of any litigation, and [TESTING AGENCY] will not enter into any discussion, or respond to any correspondence in relation to litigation.

Every possible effort has been made to ensure that the information and specifications in the Bar Code Verification Reports are correct, however, [TESTING AGENCY] expressly disclaims liability for any errors.

5.6. Linear Bar Codes – GS1 DataBar

5.6.1. GS1 DataBar

5.6.1.1. Introduction

GS1 DataBar is a family of linear symbologies used within the GS1 System. There are three types of GS1 DataBar symbols, two of which have a number of variations optimised for different application requirements.

The first type has four variations (GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked and GS1 DataBar Stacked Omnidirectional) and encodes AI (01) in a linear symbol. The second type comprises only one variation namely GS1 DataBar Limited which encodes AI (01) in a linear symbol for use on small items that will not be scanned in an omnidirectional scanning environment. The third type has two variations; a single row variation (GS1 DataBar Expanded) and a multi-row stacked variation (GS1 DataBar Expanded Stacked) Both variations encode GS1 System primary item identification plus supplementary AI Element Strings, such as weight and “best before” date, in a linear symbol that can be scanned omnidirectionally by suitably programmed slot scanners.

GS1 DataBar Stacked is a variation of the first type of GS1 DataBar Symbology that is stacked in two rows and used when the normal symbol would be too wide for the application. It comes in two variations: a truncated variation used for small item marking applications and a taller variation that is

² Educational comments are based on the technical analysis of the symbol. In this comment box the operator comments on what the problem is and how to make the symbol better by explaining the parameter’s meanings.

designed to be read by omnidirectional scanners. GS1 DataBar Expanded can also be printed in multiple rows as a stacked symbol.

Any member of the GS1 DataBar family can be printed as a stand-alone linear symbol or as a component of a composite symbol with an accompanying two-dimensional (2D) Composite Component printed above the GS1 DataBar linear component.

The GS1 DataBar family is fully described in ISO/IEC 24724 (formerly RSS; now GS1 DataBar).

5.6.1.1.1. Symbology Characteristics

The GS1 DataBar family consists of the following variations:

- GS1 DataBar Omnidirectional
- GS1 DataBar Truncated
- GS1 DataBar Stacked
- GS1 DataBar Stacked Omnidirectional
- GS1 DataBar Limited
- GS1 DataBar Expanded
- GS1 DataBar Expanded Stacked

The characteristics of the GS1 DataBar family are:

- Encodable character set:
 - GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional and GS1 DataBar Limited: Digits 0 through 9 (with the restriction of GS1 DataBar Limited to 0 or 1 in the first digit) in accordance with ISO/IEC 646. Refer to Figure 7.12 – 1 for more details.
 - GS1 DataBar Expanded variations: The GS1 System requires that only the subset of ISO/IEC 646 International Reference Version defined in these GS1 General Specifications be used for Application Identifier (AI) Element Strings. Refer to Figure 7.12 – 1 for the allowed encodable character set.
- Symbol character structure: Different (n,k) symbol characters are used for each member of the family, where each symbol character is n modules in width and is composed of k bars and k spaces
- Code type: Continuous, linear bar code symbology
- Maximum numeric data capacity (including implied Application Identifiers (AIs) where appropriate, but not including any encoded FNC1 characters):
 - All GS1 DataBar symbols except the expanded versions: AI (01) plus a 14-digit numeric item identification
 - GS1 DataBar Expanded variations: 74 numeric or 41 alphabetic characters
- Error detection:
 - GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked and GS1 DataBar Stacked Omnidirectional: mod 79 checksum
 - GS1 DataBar Limited: mod 89 checksum
 - GS1 DataBar Expanded variations: mod 211 checksum
- Character self-checking
- Bidirectionally decodable
- Quiet Zones: None required

5.6.1.1.2. Additional Features

Additional GS1 DataBar features include:


- Data compaction: Each member of the GS1 DataBar family has data compaction methods optimised for the data strings that it will encode. GS1 DataBar Expanded variations are also optimised for specific sequences of Application Identifiers (AIs) that are commonly used.
- Component linkage: All GS1 DataBar symbols include a linkage flag. If the linkage flag is 0, then the GS1 DataBar symbol stands alone. If the linkage flag is 1, then a 2D Composite Component and its separator pattern are printed above the GS1 DataBar symbol with the separator pattern aligned and contiguous to the GS1 DataBar symbol.
- Edge to similar edge decoding: All GS1 DataBar family symbol characters, finder patterns, and Symbol Check Characters can be decoded using edge-to-edge measurements.
- Large symbol characters: Unlike EAN/UPC Symbols, a GS1 DataBar Symbol's symbol characters do not directly correspond to the encoded data character. The symbol's symbol characters encode thousands of possible combinations to increase the encoding efficiency. They are then combined mathematically to form the encoded data string.
- GS1-128 Symbol emulation: Readers set to the GS1-128 Symbol emulation mode transmit the data encoded within a GS1 DataBar symbol as if the data were encoded in one or more GS1-128 Symbols.

5.6.1.2. The First Group of GS1 DataBar Symbols

The first group of GS1 DataBar symbols encodes the Element String AI (01). It has four variations: GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, and GS1 DataBar Stacked Omnidirectional. All four variations encode data in an identical manner.

Figure 5.6.1.2 - 1 shows the structure of this group of GS1 DataBar symbols. These four different symbols, as explained below, contain four symbol characters and two finder patterns. The symbols are capable of being scanned in four separate segments, each consisting of a symbol character and an adjacent finder pattern. The two finder patterns together encode a modulo 79 check value for data security.

Figure 5.6.1.2 - 1 First Group of GS1 DataBar Symbols Structure



The left and right Guard Bar Patterns consist of a narrow space and narrow bar. These variations do not require a Quiet Zone.

5.6.1.2.1. GS1 DataBar Omnidirectional

The GS1 DataBar Omnidirectional Bar Code is designed to be read by an omnidirectional scanner, such as a retail slot scanner. Its dimensions are 96X wide, starting with a 1X space and ending with a 1X bar, by 33X high (where X is the width of a module). 33X is the minimum height of the symbol but the actual height of the symbol used depends on the specific application requirements. For example, a GS1 DataBar Omnidirectional Symbol with an X-dimension of 0.254 millimetre (0.0100 inch) would be 24.38 millimetre (0.960 inch) wide and 8.38 millimetre (0.330 inch) high.

Figure 5.6.1.2.1 - 1 GS1 DataBar Omnidirectional Bar Code



(01)20012345678909

5.6.1.2.2. GS1 DataBar Truncated

The GS1 DataBar Truncated Bar Code is a reduced height variation of the GS1 DataBar Omnidirectional Bar Code that is designed for small items that will not need to be read by omnidirectional scanners. Its dimensions are 96X wide by 13X high (where X is the width of a module). For example, a GS1 DataBar Truncated Symbol with an X-dimension of 0.254 millimetre (0.0100 inch) would be 24.38 millimetres (0.960 inch) wide by 3.30 millimetres (0.130 inch) high.

Figure 5.6.1.2.2 - 1 GS1 DataBar Truncated Bar Code



(01)00012345678905

5.6.1.2.3. GS1 DataBar Stacked

The GS1 DataBar Stacked Bar Code is a reduced height two-row variation of the GS1 DataBar Omnidirectional Bar Code that is designed for small items that will not need to be read by omnidirectional scanners. Its dimensions are 50X wide by 13X high (where X is the width of a module). For example, a GS1 DataBar Stacked Symbol with an X-dimension of 0.254 millimetre (0.0100 inch) would be 12.70 millimetres (0.500 inch) wide by 3.30 millimetres (0.130 inch) high. Its structure includes a 1X high separator pattern between the two rows.

Figure 5.6.1.2.3 - 1 GS1 DataBar Stacked Bar Code



(01)00012345678905

5.6.1.2.4. GS1 DataBar Stacked Omnidirectional

The GS1 DataBar Stacked Omnidirectional Bar Code is a full height, two-row variation of the GS1 DataBar Omnidirectional Bar Code that is designed to be read by an omnidirectional scanner, such as a retail slot scanner. Its dimensions are 50X wide by 69X high (where X is the width of a module). 69X is the minimum height of the symbol but the actual height of the symbol used depends on the specific application requirements. For example, a GS1 DataBar Stacked Omnidirectional Symbol with an X-dimension of 0.254 millimetre (0.0100 inch) would be 12.70 millimetres (0.500 inch) wide by 17.53 millimetres (0.690 inch) high. The height of 69X includes a 3X high separator pattern between two rows of 33X each.

Figure 5.6.1.2.4 - 1 GS1 DataBar Stacked Omnidirectional Bar Code



(01)00034567890125

5.6.1.3. The Second Group of GS1 DataBar Symbols: GS1 DataBar Limited

The GS1 DataBar Limited Bar Code is the second group of GS1 DataBar symbols. It encodes the Element String AI (01). This Element String is based on the GTIN-12, GTIN-13, or GTIN-14 Data Structures. However, when using the GTIN-14 Data Structure, only the indicator value 1 is allowed. When encoding GTIN-14 Data Structures with an Indicator value greater than 1, one of the first group of GS1 DataBar symbols must be used: see section [5.6.1.2](#).


The GS1 DataBar Limited Bar Code is designed for small items that will not need to be read by omnidirectional Point-of-Sale (POS) scanners. Its dimensions are 79X wide, starting with a 1X space and ending with a 5X space, by 10X high (where X is the width of a module). For example, a GS1 DataBar Limited Bar Code with an X-dimension of 0.254 millimetre (0.0100 inch) would be 20.07millimetres (0.790 inches) wide by 2.54 millimetres (0.100 inch) high.

Figure 5.6.1.3 - 1 GS1 DataBar Limited Bar Code



Figure 5.6.1.3 - 2 shows the structure of the GS1 DataBar Limited Bar Code. A GS1 DataBar Limited Symbol contains two data characters and a Symbol Check Character. The Symbol Check Character encodes a modulo 89 check value for data security.

Figure 5.6.1.3 - 2 GS1 DataBar Limited Bar Code Structure



(a) GS1 DataBar Limited symbol representing (01)00312345678906

(b) the same symbol on a dark background. Notice the trailing space in the right guard pattern


The total symbol contains 47 elements comprising 79 modules. The minimum height shall be 10X. No quiet zones are required, however while each light module on both ends of the Limited symbol may look like a quiet zone, each differs from a quiet zone in that the reference decode algorithm must check for these guard bar patterns in order to avoid misreading a UPC-A symbol as a GS1 DataBar Limited symbol. The leading and trailing space elements may blend into the background of the symbol if that background is the same color as the spaces in the symbol.

5.6.1.4. The Third Group of GS1 DataBar Symbols: GS1 DataBar Expanded Variations

GS1 DataBar Expanded variations are the third group of GS1 DataBar symbols and are a variable length linear symbology capable of encoding up to 74 numeric or 41 alphabetic characters of AI Element String data. The two variations, GS1 DataBar Expanded and GS1 DataBar Expanded Stacked are designed to encode primary and supplementary data on items for Point-of-Sale (POS) and other applications. They have the same capabilities as a GS1-128 Symbol except that they are also designed to be scanned by omnidirectional slot scanners. They are designed for variable weight products, perishable products, traceable retail products, and coupons.

Figure 5.6.1.4 - 1 shows the structure of a six-segment GS1 DataBar Expanded Symbol. GS1 DataBar Expanded Symbols contain a Symbol Check Character, 3 to 21 symbol characters and 2 to 11 finder patterns, depending on the symbol length. GS1 DataBar Expanded is capable of being scanned in separate segments, each segment consisting of a symbol character or Symbol Check Character and the adjacent finder pattern. The Symbol Check Character encodes a modulo 211 check value for data security.

Figure 5.6.1.4 - 1 GS1 DataBar Expanded Structure



The left and right Guard Bar Patterns consist of a narrow bar and narrow space. GS1 DataBar Expanded variations do not require a Quiet Zone.

5.6.1.4.1. GS1 DataBar Expanded

The GS1 DataBar Expanded Bar Code has a variable width (from 4 to 22 symbol characters, or a minimum of 102X wide and a maximum of 534X wide) and is 34X high (where X is the width of a module). The symbol starts with a 1X space and ends with either a 1X bar or space. For example, the GS1 DataBar Expanded Symbol shown in Figure 5.6.1.4.1 - 1 with an X-dimension of 0.254 millimetre (0.0100 inch) would be 38.35 millimetres (1.51 inches) wide by 8.64 millimetres (0.340 inch) high.

Figure 5.6.1.4.1 - 1 GS1 DataBar Expanded Bar Code



5.6.1.4.2. GS1 DataBar Expanded Stacked

The GS1 DataBar Expanded Stacked Bar Code is a multi-row stacked variation of GS1 DataBar Expanded. It can be printed in widths of 2 to 20 segments and can have from 2 to 11 rows. Its structure includes a 3X high separator pattern between rows. It is designed to be read by an omnidirectional scanner such as a retail slot scanner. The GS1 DataBar Expanded Stacked Symbol shown in Figure 5.6.1.4.2 - 1 with an X-dimension of 0.254 millimetre (0.0100 inch) would be 25.91 millimetres (1.020 inches) wide by 18.03 millimetres (0.710 inch) high.

The white space at the end of the second row of the symbol shown in Figure 5.6.1.4.2 - 1 is not part of the symbol and can be used for other purposes, such as text.

Figure 5.6.1.4.2 - 1: GS1 DataBar Expanded Stacked Bar Code



GS1 DataBar Expanded Stacked is used when the symbol area or print mechanism is not wide enough to accommodate the full single-row GS1 DataBar Expanded Symbol. It is designed for variable weight products, perishable products, traceable retail products, and coupons.

5.6.1.4.3. Compressed Element String Sequences

While GS1 DataBar Expanded Symbols can encode any sequence of Application Identifier (AI) data up to the maximum capacity of the symbol, certain sequences of AI Element Strings have been selected for special compression in GS1 DataBar Expanded variations. If the application requires the use of the AI Element Strings in one of these sequences and they are used in the predefined sequence, a smaller symbol will result.

The selected sequences are two types: fixed length, where the sequence of selected AI Element Strings is the only data encoded, and open-ended, where the sequence occurs at the start of the symbol's data, and other AI Element Strings may be added following the sequence. If the data to be encoded in an GS1 DataBar Expanded Symbol starts with a sequence defined as fixed length but is followed by additional AI Element Strings, all the data will be encoded normally without special compression.

5.6.1.4.3.1. Fixed-Length Sequences

This section contains information on Fixed-Length Sequences.

5.6.1.4.3.1.1. (01) and Weight with Limited Range

This sequence consists of the two Application Identifier (AI) Element Strings AI (01), followed by AI (3103), AI (3202), or AI (3203) for weight. The AI (01) Element String must start with an Indicator value of 9 for variable measure. Using AI (3103) (weight in grams), the special compression can only be applied up to a maximum weight of 32.767 kilograms. Using AI (3202) (weight in 0.01 pounds) the special compression can only be applied up to a maximum weight of 99.99 pounds. Using AI (3203) (weight in 0.001 pounds) the special compression can only be applied up to a maximum weight of 22.767 pounds. If the weight is in excess of these values, the sequence defined in [Section 5.6.1.4.3.1](#) still enables special compression to be performed.

5.6.1.4.3.1.2. AI (01): Weight and Optional Date

This sequence consists of the two or three Application Identifier (AI) Element Strings AI (01), AI (310n), or (320n) for weight (n ranging from 0 to 9) and optionally AI (11), AI (13), AI (15), or AI (17) for date. The AI (01) Element String must start with an Indicator value of 9 for variable measure. If the date is not needed, this sequence still gives additional compression when the weight is outside the ranges required by the AI (01) and weight with limited range sequence above.

5.6.1.4.3.2. Open-Ended Sequences

This section contains information on Open-Ended Sequences.

5.6.1.4.3.2.1. AI (01) and Price

This sequence consists of the two Application Identifier (AI) Element Strings, AI (01), followed by AI (392x) for price or AI (393x) for price with ISO currency code (where x is in the range of 0 to 3). The AI (01) Element String must start with an Indicator value of 9 for variable measure. For example, this sequence is used for an AI (01) Element String, price and weight, because the fixed-length sequence AI (01) and weight does not give additional compression if the AI Element String for price is added to the end since the length of the sequence is fixed.

5.6.1.4.3.2.2. AI (01)

Any sequence that starts with Application Identifier (AI) (01) will have special compression applied to the AI (01). So when the data includes AI (01), it SHALL be the first Element String encoded.

5.6.1.4.4 Maximum Width and Height of GS1 DataBar Expanded Versions (Informative)

Advice for maximum symbol size to optimize scanner performance

5.6.1.4.4.1 Maximum Symbol Width (flat surface)

For GS1 DataBar Expanded and GS1 DataBar Expanded Stacked Symbols scanned with an omnidirectional slot scanner, the following maximum symbol length is recommended: 158.75 mm (6.250 inch).

For GS1 DataBar Expanded and GS1 DataBar Expanded Stacked Symbols scanned with a presentation scanner, the following maximum symbol length is recommended: 158.75 mm (6.250 inch).

For GS1 DataBar Expanded and GS1 DataBar Expanded Stacked Symbols scanned with a hand held scanner, the following maximum symbol length is recommended as;

- Hand Held Linear (Laser) Scanner: 158.75 mm (6.250 inch)
- Hand Held Linear (CCD type) Scanner: 101.60 mm (4.000 inch)
- Hand Held Imager (2D) Scanner: 158.75 mm (6.250 inch)

GS1 DataBar Expanded - Symbol Length vs. Symbol Characters

Figure 5.6.1.4.4 – 1 GS1 DataBar Symbol Length Specification (flat surface) Table 1

X [Inch]	0.0080		0.010		0.0130		0.0260		0.0390	
X [mm]		0.203		0.254		0.330		0.660		0.991
Characters										
4	0.816	20.73	1.020	25.91	1.326	33.68	2.652	67.36	3.978	101.04
5	1.072	27.23	1.340	34.04	1.742	44.25	3.484	88.49	5.226	132.74
6	1.208	30.68	1.510	38.35	1.963	49.86	3.926	99.72	5.889	149.58
7	1.464	37.19	1.830	46.48	2.379	60.43	4.758	120.85	7.137	181.28
8	1.600	40.64	2.000	50.80	2.600	66.04	5.200	132.08	7.800	198.12
9	1.856	47.14	2.320	58.93	3.016	76.61	6.032	153.21	9.048	229.82
10	1.992	50.60	2.490	63.25	3.237	82.22	6.474	164.44	9.711	246.66
11	2.248	57.10	2.810	71.37	3.653	92.79	7.306	185.57	10.959	278.36
12	2.384	60.55	2.980	75.69	3.874	98.40	7.748	196.80	11.622	295.20
13	2.640	67.06	3.300	83.82	4.290	108.97	8.580	217.93	12.870	326.90

14	2.776	70.51	3.470	88.14	4.511	114.58	9.022	229.16	13.533	343.74
15	3.032	77.01	3.790	96.27	4.927	125.15	9.854	250.29	14.781	375.44
16	3.168	80.47	3.960	100.58	5.148	130.76	10.296	261.52	15.444	392.28
17	3.424	86.97	4.280	108.71	5.564	141.33	11.128	282.65	16.692	423.98
18	3.560	90.42	4.450	113.03	5.785	146.94	11.570	293.88	17.355	440.82
19	3.816	96.93	4.770	121.16	6.201	157.51	12.402	315.01	18.603	472.52
20	3.952	100.38	4.940	125.48	6.422	163.12	12.844	326.24	19.266	489.36
21	4.208	106.88	5.260	133.60	6.838	173.69	13.676	347.37	20.514	521.06
22	4.344	110.34	5.430	137.92	7.059	179.30	14.118	358.60	21.177	537.90

Best Performance
Not Recommended

5.6.1.4.4.2 Maximum Symbol Width (curved surface)

For GS1 DataBar Expanded Variation Symbols with a maximum subtended angle of 60° (see Figure 6.2.3.2-2 Relationship between symbol and curvature), Table 2 provides the length of a GS1 DataBar Expanded Variation symbol as a function of the X-dimension chosen. Tests show that GS1 DataBar Expanded Variations have decreased performance at the maximum angle and it is recommended that, when possible, these symbols be made such that a smaller angle is subtended.

5.6.1.4.4.3 Maximum Height GS1 DataBar Expanded Stacked

For GS1 DataBar Expanded Stacked Symbols, Table 3 provides the height of the symbol as a function of the number of rows and X-dimension chosen. Advice is provided, as a result of tests conducted, that indicate (shading of table cells) scanning performance as a function of the number of rows and X-dimension. It should be noted that the testing showed, independent of X-dimension, significant reduction in scanner performance, for symbols containing more than 7 rows.

Diameter (inch)	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.50	3.00
L max (inch)	0.131	0.262	0.393	0.524	0.654	0.785	0.916	1.047	1.309	1.571
Diameter (mm)	6.35	12.70	19.05	25.40	31.75	38.10	44.45	50.80	63.50	76.20
L max (mm)	3.32	6.65	9.97	13.30	16.62	19.95	23.27	26.60	33.25	39.90
Diameter (inch)	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
L max (inch)	1.833	2.094	2.356	2.618	2.880	3.142	3.456	3.665	3.927	4.189
Diameter (mm)	88.90	101.60	114.30	127.00	139.70	152.40	167.64	177.80	190.50	203.20
L max (mm)	46.55	53.20	59.85	66.50	73.15	79.80	87.78	93.10	99.75	106.40
Diameter (inch)	8.50	9.00	9.50	10.00	20.00	30.00	40.00	50.00	60.00	
L max (inch)	4.451	4.712	4.974	5.236	10.472	15.708	20.944	26.180	31.42	
Diameter (mm)	215.90	228.60	241.30	254.00	508.00	762.00	1016.00	1270.00	1524.00	
L max (mm)	113.05	119.69	126.34	132.99	265.99	398.98	531.98	664.97	797.96	
Diameter (inch)	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.50	3.00
L max (inch)	0.131	0.262	0.393	0.524	0.654	0.785	0.916	1.047	1.309	1.571
Diameter (mm)	6.35	12.70	19.05	25.40	31.75	38.10	44.45	50.80	63.50	76.20
L max (mm)	3.32	6.65	9.97	13.30	16.62	19.95	23.27	26.60	33.25	39.90
Diameter (inch)	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00
L max (inch)	1.833	2.094	2.356	2.618	2.880	3.142	3.456	3.665	3.927	4.189
Diameter (mm)	88.90	101.60	114.30	127.00	139.70	152.40	167.64	177.80	190.50	203.20
L max (mm)	46.55	53.20	59.85	66.50	73.15	79.80	87.78	93.10	99.75	106.40
Diameter (inch)	8.50	9.00	9.50	10.00	20.00	30.00	40.00	50.00	60.00	
L max (inch)	4.451	4.712	4.974	5.236	10.472	15.708	20.944	26.180	31.42	
Diameter (mm)	215.90	228.60	241.30	254.00	508.00	762.00	1016.00	1270.00	1524.00	
L max (mm)	113.05	119.69	126.34	132.99	265.99	398.98	531.98	664.97	797.96	

Figure 5.6.1.4.4 – 3 GS1 DataBar Expanded Stacked Height Specification (Informative) Table 3

Height of GS1 DataBar Expanded Stacked by row [Metric Units]										
X [mm]		0.203	0.254	0.330	0.381	0.508	0.660	0.762	0.889	0.991
Row	Height (modules)									
2	71	14.41	18.03	23.43	27.05	36.07	46.86	54.10	63.12	70.36
3	108	21.92	27.43	35.64	41.15	54.86	71.28	82.30	96.01	107.03
4	145	29.44	36.83	47.85	55.25	73.66	95.70	110.49	128.91	143.70
5	182	36.95	46.23	60.06	69.34	92.46	120.12	138.68	161.80	180.36
6	219	44.46	55.63	72.27	83.44	111.25	144.54	166.88	194.69	217.03
7	256	51.97	65.02	84.48	97.54	130.05	168.96	195.07	227.58	253.70
8	293	59.48	74.42	96.69	111.63	148.84	193.38	223.27	260.48	290.36
9	330	66.99	83.82	108.90	125.73	167.64	217.80	251.46	293.37	327.03
10	367	74.50	93.22	121.11	139.83	186.44	242.22	279.65	326.26	363.70
11	404	82.01	102.62	133.32	153.92	205.23	266.64	307.85	359.16	400.36

Figure 5.6.1.4.4 – 2 GS1 DataBar Symbol Length Specification (curved surface) Table 2
Height of GS1 DataBar Expanded Stacked by row [Imperial Units]

X [inch]		0.0080	0.0100	0.0130	0.0150	0.0200	0.0260	0.0300	0.0350	0.0390
Row	Height (modules)									
2	71	0.568	0.710	0.923	1.065	1.420	1.846	2.130	2.485	2.769
3	108	0.864	1.080	1.404	1.620	2.160	2.808	3.240	3.780	4.212
4	145	1.160	1.450	1.885	2.175	2.900	3.770	4.350	5.075	5.655
5	182	1.456	1.820	2.366	2.730	3.640	4.732	5.460	6.370	7.098
6	219	1.752	2.190	2.847	3.285	4.380	5.694	6.570	7.665	8.541
7	256	2.048	2.560	3.328	3.840	5.120	6.656	7.680	8.960	9.984
8	293	2.344	2.930	3.809	4.395	5.860	7.618	8.790	10.255	11.427
9	330	2.640	3.300	4.290	4.950	6.600	8.580	9.900	11.550	12.870
10	367	2.936	3.670	4.771	5.505	7.340	9.542	11.010	12.845	14.313
11	404	3.232	4.040	5.252	6.060	8.080	10.504	12.120	14.140	15.756

Best Performance
Reduced Performance
Not Recommended

5.6.1.5. Human Readable Interpretation in GS1 DataBar Symbols

For Human-Readable Interpretation Rules see Section 4.12. For HRI Rules specific to Regulated Healthcare Retail Consumer Trade Items, see Section 4.12.1.

As a Non-HRI text option, the data title (see Section 3.2) may be associated with the data instead of using the AI numbers.

Figure 5.6.1.5 - 1 shows the weight and price identified with Non-HRI text.

Figure 5.6.1.5 - 1 The Human Readable Interpretation and Non-HRI Text



5.6.1.6. Data Transmission and Symbology Identifier Prefixes

5.6.1.6.1. Default Transmission Mode

The GS1 System requires the use of symbology identifiers. GS1 DataBar family symbols are normally transmitted using symbology identifier prefix “je0” (see Section 5.1.2). For example, an GS1 DataBar Symbol encoding AI (01) Element String 10012345678902 produces the transmitted data string “je00110012345678902.” Data transmission follows the Rules for Encoding/Decoding Element Strings in GS1 symbologies using GS1 Application Identifiers (see Appendix [5.9](#))

If a 2D Composite Component accompanies a GS1 DataBar family linear symbol, the AI Element String data from the 2D Composite Component immediately follows the linear component’s data. However, readers have an option to transmit only the linear component data and ignore the 2D Composite Component.

5.6.1.6.2. GS1-128 Symbol Emulation Mode

Readers also have an option for GS1-128 Symbol emulation mode. This mode emulates the GS1-128 Symbology for data transmission. This mode is used for applications programmed for GS1-128 but not yet programmed to recognise the symbology identifier prefix “je0.” The symbology identifier for GS1-128 emulation mode is “jC1.” GS1 DataBar Expanded Symbols that exceed 48 data characters are transmitted as two messages so as not to exceed the maximum GS1-128 Symbol message length. Each of the two messages has a symbology identifier prefix of “jC1” and does not exceed 48 data characters. The two messages are split at a boundary between two Element Strings. This mode is inferior to the normal transmission mode as message integrity may be lost when a message is split.

5.6.1.7. Width of a Module (X-dimension)

The range of the X-dimension will be defined by the application specification, having due regard to the availability of equipment for the production and reading of symbols and complying with the general requirements of the application. Symbol Specifications are subject to change at the application standards level and are governed by the Scanner Operational Environment Decision Tree in Section 5.5.2.6.1-2.

The X-dimension shall be constant throughout a given symbol.

5.6.1.8. Height of Symbol

The height of a symbol is a multiple of the X-dimension defined by the type of GS1 DataBar Symbology given in Sections [5.6.1.2.1](#), [5.6.1.2.2](#), [5.6.1.2.3](#), [5.6.1.2.4](#), 5.6.1.3, [5.6.1.4.1](#), and [5.6.1.4.2](#). Symbol Specifications are subject to change at the application standards level and are governed by the Scanner Operational Environment Decision Tree in Section 5.5.2.6.1-2.

5.6.1.9. Print Quality Grade

The International Standard *ISO/IEC 15416* methodology is used for measuring and grading the GS1 DataBar family of symbols. The *ISO/IEC 15416* print quality specification is functionally identical to the older ANSI and CEN print quality specifications. The print quality grade is measured by verifiers that comply with the standard. The grade includes a grade level, measuring aperture, and the wavelength of light used for the measurement.

Symbol Specifications are subject to change at the application standards level and are governed by the Scanner Operational Environment Decision Tree in Section 5.5.2.6.1-2., For most applications, the minimum quality grade for GS1 DataBar Symbols is:

1.5 / 6 / 670


Where

- 1.5 is the overall symbol quality grade.
- 6 is the measuring aperture reference number (corresponding to an 0.15 millimetre or 0.006 inch diameter aperture).
- 670 is the peak response wavelength in nanometres.

In addition to the minimum print quality grade, all elements in the row separator patterns should be visually distinguishable.

5.6.1.10. Advice for Selecting the Symbology

Any use of GS1 DataBar should comply with GS1 System global application guidelines. GS1 DataBar is not meant to replace other GS1 System Symbologies. Existing applications that are satisfactorily utilising EAN/UPC Symbols, ITF-14 Symbols, or GS1-128 Symbols should continue to use them.

 **Note:** Scanning systems that need to read GS1 DataBar Symbols must be appropriately programmed.

If GS1 DataBar is used on items that will be read by omnidirectional slot scanners, then GS1 DataBar Omnidirectional, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded or GS1 DataBar Expanded Stacked should be used. If only an AI (01) is to be encoded, then GS1 DataBar Omnidirectional or GS1 DataBar Stacked Omnidirectional should be used. The selection of one or the other depends on the aspect ratio of the area available for the symbol.

If supplementary Application Identifier (AI) Element Strings are required or the primary identification has an AI other than AI (01), then GS1 DataBar Expanded or GS1 DataBar Expanded Stacked must be used. The selection of one or the other depends on the width of the print head or the area available for the symbol.

When using GS1 DataBar Expanded or GS1 DataBar Expanded Stacked Symbols to encode the Global Trade Item Number (GTIN), any required additional data should be included within the same symbol.

If GS1 DataBar is used on small items that do not need omnidirectional scanning capability, then GS1 DataBar Stacked, GS1 DataBar Limited, or GS1 DataBar Truncated should be used. GS1 DataBar Limited cannot be used to encode a GTIN-14 Data Structure with an Indicator value greater than 1. Otherwise GS1 DataBar Truncated or GS1 DataBar Stacked must be used. GS1 DataBar Stacked is the smallest symbol; however, as the heights of both rows are very low, it is harder to scan and cannot be used with wand scanners. If space is available, GS1 DataBar Limited can be used for number structures that it can encode. Otherwise GS1 DataBar Truncated should be used for GTIN-14 Data Structures with an Indicator value greater than 1.

If the symbol is a GS1 DataBar Composite Symbol, then using a wider GS1 DataBar Symbol such as GS1 DataBar Truncated instead of GS1 DataBar Limited may be preferable because the wider companion 2D Composite Component may result in a GS1 DataBar Composite Symbol of lower overall height even though the GS1 DataBar component itself is slightly taller.

If the data capacity in a two-column or three-column CC-B 2D Composite Component is inadequate to encode the required 2D component's data message, then the linear component can be changed to increase the number of columns of the companion CC-B component. This will increase the maximum data capacity of the CC-B component as shown in Figure 5.6.1.10 - 1.

Figure 5.6.1.10 – 1 Data Capacity of CC-B

Number of CC-B Columns	Used with	Maximum Numeric Characters	Maximum Alpha Characters
2	GS1 DataBar Stacked GS1 DataBar Stacked Omnidirectional	95	55

Number of CC-B Columns	Used with	Maximum Numeric Characters	Maximum Alpha Characters
3	GS1 DataBar Limited	219	127
4	GS1 DataBar Omnidirectional GS1 DataBar Expanded GS1 DataBar Expanded Stacked	338	196

5.7. Two Dimensional Bar Codes – GS1 DataMatrix Symbology

5.7.1. Introduction

This section of the *GS1 General Specifications* addresses some of the technical aspects of the two-dimensional bar code symbology called GS1 DataMatrix. GS1 DataMatrix is a standalone, two-dimensional matrix symbology that is made up of square modules arranged within a perimeter finder pattern. Unlike a Composite Component symbol (see Section [5.8.1](#)), GS1 DataMatrix does not require a linear symbol. GS1 DataMatrix has been used in the public domain since 1994.

This section provides only a brief technical description and overview of the GS1 DataMatrix symbology. A more detailed technical specification can be found in the International Standard *ISO/IEC 16022*. The GS1 System has adopted GS1 DataMatrix partly because, like GS1 QR Code, GS1 DataMatrix can encode GS1 System data structures and offers other technical advantages. Its compact design and the existence of various production methods that accommodate placing the symbology onto various substrates offer certain advantages over other symbologies currently in the GS1 System.

Data Matrix ISO version ECC 200 is the only version that supports GS1 System data structures, including Function 1 Symbol Character. The ECC 200 version of Data Matrix uses Reed-Solomon error correction, and this feature helps correct for partially damaged symbols. In the remainder of this section, the ECC 200 version of Data Matrix is assumed when the symbology is described as GS1 DataMatrix. This version of Data Matrix is similar in stability to ISO versions of current GS1 System symbologies.


Implementation of GS1 DataMatrix shall be done per approved GS1 System application guidelines. This section will not describe the specific applications. The user needs to refer to specific application standards and guidelines in other sections of these *GS1 General Specifications* as they are approved for use. However, some of the production processes that are used to produce GS1 DataMatrix Symbols are as follows:

- Direct part marking, such as is done by dot peening on items, such as automotive, aircraft metal parts, medical instruments, and surgical implants
- Laser or chemically etched parts with low contrast or light marked elements on a dark background (e.g., circuit boards and electronic components, medical instruments, surgical implants)
- High-speed ink jet printed parts and components where the marked dots cannot form a scannable linear symbol.
- Very small items that require a symbology with a square aspect ratio and/or cannot be marked within the allocated packaging space by existing GS1 DataBar and Composite Symbols
- Use with B2C Extended Packaging applications

GS1 DataMatrix Symbols are read by two-dimensional imaging scanners or vision systems. Most other scanners that are not two-dimensional imagers cannot read GS1 DataMatrix. GS1 DataMatrix Symbols are restricted for use with new niche applications that will involve imaging scanners throughout the supply chain.

5.7.2. GS1 DataMatrix Features and Symbol Basics

Figure 5.7.2 - 1 GS1 DataMatrix Symbol



- Figure 5.7.2 – 1 represents a GS1 DataMatrix Symbol with 20 rows and 20 columns (including the perimeter finder pattern but not including Quiet Zones).
- GS1 DataMatrix solid “L” shaped finder or alignment pattern is one module wide.
- GS1 DataMatrix Quiet Zone is one module wide on all four sides. As with other bar code Quiet Zones, do not print in this area.
- ECC 200 symbols can always be recognized from older versions of Data Matrix because the corner opposite the middle of the finder pattern is a zero module or white in normal print.
- For square GS1 DataMatrix symbols, only an even number of rows and columns exist. Depending on data requirements, symbols can range from 10 row by 10 columns (10 x10) to 144x144 (including finder pattern but not the Quiet Zone).
- For normal printing, a module is one X by one X in dimension. Representation of data: A dark module is a binary one and a light module is a binary zero (or a light module is a binary one and a dark module is a binary zero for a symbol with reflectance reversal).
- ECC 200 (ECC = Error Checking and Correction) that uses Reed-Solomon error correction. Figure 5.7.3.2 – 1 ECC 200 Square Symbol Attributes, shows the fixed amounts of error correction associated for each allowable Data Matrix Symbol size.
- FNC1 for GS1 System compatibility shall be encoded at the beginning of the data string and should be used as a group separator. When a FNC1 is used as a group separator, it shall be represented in the transmitted message by the ASCII character <GS> (ASCII value 29).
- Encodable character set:
 - The GS1 System requires that only the subset of *ISO/IEC 646* International Reference Version defined in these *GS1 General Specifications* be used for Application Identifier (AI) Element Strings. Refer to Figure 7.12 – 1 for the allowed encodable character set.
- Data characters per symbol (for the maximum symbol size):
 - Alphanumeric data: up to 2335 characters
 - Eight-bit byte data: 1556 characters
 - Numeric data: 3116 digits
- Large, square ECC symbols (at least 32 X32) will include alignment patterns to separate the data regions.
- Code type: matrix (Composite Component is a stacked type)
- Orientation independence: Yes (requires a two-dimensional imaging scanner)
- Summary of additional features inherent or optional in GS1 DataMatrix:
 - Reflectance reversal: (Inherent) Symbols can be read when marked so that the image is either dark on light or light on dark.

- Rectangular symbols: Six symbol formats are specified in a rectangular form.
- Extended Channel Interpretation (ECI) capability allows GS1 DataMatrix to encode data from other alphabets.

5.7.3. GS1 DataMatrix Symbology

The technical description of GS1 DataMatrix contained within this section provides additional information based on ISO technical specification 16022, and it is provided as a further aid in the development of specific applications. GS1 DataMatrix Symbols shown in the following subsections have been magnified to show detail.

5.7.3.1. Square and Rectangular Formats

GS1 DataMatrix may be printed in a square or rectangular format. The square format is usually used as it has a larger range of sizes and is the only format available for symbols encoding a large amount of data. The largest rectangular symbol can encode 98 digits, while the largest square symbol can encode 3,116 digits. An enlarged rectangular symbol and an equivalent square symbol are shown in Figure 5.7.3.1 - 1.

Figure 5.7.3.1 - 1 Rectangular and Square GS1 DataMatrix Symbols

(Specific applications are not used in the data encodation. Both symbols contain the same data)



5.7.3.2. GS1 DataMatrix Symbol Sizes

GS1 DataMatrix Symbology has multiple sizes to match various data content (see Figure 5.7.3.2 - 1). GS1 DataMatrix Symbols have 24 sizes of the square format ranging from 10 by 10 modules up to 144 by 144 modules, not including the 1-X surrounding Quiet Zone. The rectangular format has 6 sizes from 8 by 18 modules up to 16 by 48 modules, not including the 1-X surrounding Quiet Zone. GS1 DataMatrix sizes of 52 by 52 or larger have 2 to 10 interleaved blocks of Reed-Solomon error correction codewords.

The term “codeword” is used often to describe attributes concerning the encodation of data into GS1 DataMatrix Symbols. *ISO 16022* defines codeword as “A symbol character value. An intermediate level of coding between source data and the graphical encodation in the symbol.” Codewords are typically eight bits of data. FNC1, two numerics, and one alpha all take up one codeword each.

Figure 5.7.3.2 - 1 ECC 200 Square Symbol Attributes***

Symbol Size*		Data Region		Mapping	Total		Reed-Solomon		Inter-	Data Capacity			Error	Max. Correctable
Row	Col	Size	No.	Matrix Size	Codewords		Block		leaved	Num. Cap.	Alphanum. Cap.	Byte Cap.	Correction Overhead %	Codeword Error/Erasure
10	10	8x8	1	8x8	3	5	3	5	1	6	3	1	62.5	2/0
12	12	10x10	1	10x10	5	7	5	7	1	10	6	3	58.3	3/0
14	14	12x12	1	12x12	8	10	8	10	1	16	10	6	55.6	5/7
16	16	14x14	1	14x14	12	12	12	12	1	24	16	10	50	6/9

Symbol Size*		Data Region		Mapping	Total		Reed-Solomon		Inter-	Data Capacity			Error	Max. Correctable
				Matrix	Codewords		Block		leaved	Num.	Alphanum.	Byte	Correction	Codeword
Row	Col	Size	No.	Size	Data	Error	Data	Error	Blocks	Cap.	Cap.	Cap.	Overhead %	Error/Erasure
18	18	16x16	1	16x16	18	14	18	14	1	36	25	16	43.8	7/11
20	20	18x18	1	18x18	22	18	22	18	1	44	31	20	45	9/15
22	22	20x20	1	20x20	30	20	30	20	1	60	43	28	40	10/17
24	24	22x22	1	22x22	36	24	36	24	1	72	52	34	40	12/21
26	26	24x24	1	24x24	44	28	44	28	1	88	64	42	38.9	14/25
32	32	14x14	4	28x28	62	36	62	36	1	124	91	60	36.7	18/33
36	36	16x16	4	32x32	86	42	86	42	1	172	127	84	32.8	21/39
40	40	18x18	4	36x36	114	48	114	48	1	228	169	112	29.6	24/45
44	44	20x20	4	40x40	144	56	144	56	1	288	214	142	28	28/53
48	48	22x22	4	44x44	174	68	174	68	1	348	259	172	28.1	34/65
52	52	24x24	4	48x48	204	84	102	42	2	408	304	202	29.2	42/78
64	64	14x14	16	56x56	280	112	140	56	2	560	418	277	28.6	56/106
72	72	16x16	16	64x64	368	144	92	36	4	736	550	365	28.1	72/132
80	80	18x18	16	72x72	456	192	114	48	4	912	682	453	29.6	96/180
88	88	20x20	16	80x80	576	224	144	56	4	1152	862	573	28	112/212
96	96	22x22	16	88x88	696	272	174	68	4	1392	1042	693	28.1	136/260
104	104	24x24	16	96x96	816	336	136	56	6	1632	1222	813	29.2	168/318
120	120	18x18	36	108x108	1050	408	175	68	6	2100	1573	1047	28	204/390
132	132	20x20	36	120x120	1304	496	163	62	8	2608	1954	1301	27.6	248/472
144	144	22x22	36	132x132	1558	620	156	62	8**	3116	2335	1556	28.5	310/590
							155	62	2**					

Figure 5.7.3.2 - 2 ECC 200 Rectangular Symbol Attributes***

Symbol Size*		Data Region		Mapping	Total		Reed-Solomon		Inter-	Data Capacity			Error	Max. Correctable
				Matrix	Codewords		Block		leaved	Num.	Alphanum.	Byte	Correction	Codeword
Row	Col	Size	No.	Size	Block s	Cap.	Cap.	Cap.	Blocks	Cap.	Cap.	Cap.	Overhead %	Error/Erasure
8	18	6x16	1	6x16	5	7	5	7	1	10	6	3	58.3	3/+
8	32	6x14	2	6x28	10	11	10	11	1	20	13	8	52.4	5/+
12	26	10x24	1	10x24	16	14	16	14	1	32	22	14	46.7	7/11
12	36	10x16	2	10x32	22	18	22	18	1	44	31	20	45.0	9/15
16	36	14x16	2	14x32	32	24	32	24	1	64	46	30	42.9	12/21
16	48	14x22	2	14x44	49	28	49	28	1	98	72	47	36.4	14/25

Notes:

- * Symbol size does not include Quiet Zones.
- ** In the largest symbol (144x144), the first eight Reed-Solomon blocks shall be 218 codewords long encoding 156 data codewords. The last two blocks shall encode 217 codewords (155 data codewords). All the blocks have 62 error correction codewords.
- *** Equivalent to Table 7 in the international standard ISO-16022, second edition, 2006-09-15.
The square format is divided into 4 to 36 data regions for symbols sized 32 by 32 modules and larger. The rectangular format symbols may also be divided into two data regions. Each data region is separated from the other regions by alignment patterns that consist of an alternating pattern of ones and zeroes and a solid line of ones (a dark line when there is no reflectance reversal). Figure 5.7.3.2 - 3 shows a four-segment square symbol on the left and a two-segment rectangular symbol on the right, each with hypothetical data shown to create the effect.

Figure 5.7.3.2 - 3 Segmented GS1 DataMatrix Symbols: Square and Rectangular Formats

(Sizes of these GS1 DataMatrix Symbols are larger than what would be used in a typical application so that typical alignment patterns can be easily seen.)



5.7.3.3. Data Transmission and Symbology Identifier Prefixes

The GS1 System requires the use of symbology identifiers. GS1 DataMatrix uses the symbology identifier of "jd2" (see Figure 5.7.3.3 - 1) for GS1 System compliant symbols that have a leading FNC1 character. This indicates that Application Identifier (AI) data is encoded equivalent to the symbology identifier "JC1" for GS1-128 Symbols and "je0" for GS1 DataBar and Composite Symbols. For more information on symbology identifiers, see the International standard *ISO/IEC 15424* Information technology — Automatic identification and data capture techniques — Data Carrier Identifiers.

For example, a GS1 DataMatrix Symbol encoding AI (01) Element String 10012345678902 produces the transmitted data string "jd20110012345678902." Data transmission follows the same principles that apply to the concatenation of AI Element Strings in any GS1 BarCode that encodes Application Identifiers (see Section 7.9).

Figure 5.7.3.3 - 1 Symbology Identifier for Data Matrix ECC 200

	Message Content	Separator
jd2	Standard AI Element Strings	None

5.7.3.4. Width and Height of a Module (X)

The range of the X-dimensions will be defined by the application specification, having due regard to the availability of equipment for the production and reading of symbols and complying with the general requirements of the application.

The X-dimension shall be constant throughout a given symbol. The X-dimension applies to both the width and height of the modules.

5.7.3.5. Symbol Quality Grade

The International Standard *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code symbol print quality test specification - Two-dimensional symbols methodology shall be used for measuring and grading GS1 DataMatrix. The print quality grade is measured by verifiers that comply with the standard. The grade includes a grade level, measuring aperture, the wavelength of light used for the measurement, and the illumination angle relative to the symbol.

A symbol grade is only meaningful if it is reported in conjunction with the illumination and aperture used. It is shown in the format grade/aperture/light/angle, where:

- "grade" is the overall symbol grade as defined in *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code symbol print quality test specification - Two-dimensional symbols (e.g., the arithmetic mean to one decimal place of the Scan Reflectance Profile or scan grades). For GS1 DataMatrix, the grade number may be followed by an asterisk (*) which indicates that the surroundings of the symbol contain extremes of reflectance that may interfere with reading. For most applications, this should be specified as causing the symbol to fail.
- "aperture" is the diameter in thousandths of an inch (to the nearest thousandth) of the synthetic aperture defined in *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code symbol print quality test specification - Two-dimensional symbols.
- "light" defines the illumination: A numeric value indicates the peak light wavelength in nanometres (for narrow band illumination); the alphabetic character W indicates that the symbol has been measured with broadband illumination (white light) the spectral response characteristics of which must imperatively be defined or have their source specification clearly referenced.
- "angle" is an additional parameter defining the angle of incidence (relative to the plane of the symbol) of the illumination. It shall be included in the reporting of the overall symbol grade when the angle of incidence is other than 45 degrees. Its absence indicates that the angle of incidence is 45 degrees.



Note: This international standard provides for 30 degrees and 90 degrees illumination in addition to the default 45 degrees.

The aperture is normally specified as being 80% of the minimum X-dimension allowed for the application. The printing method must produce the GS1 DataMatrix "L" pattern with gaps between the dots less than 25% of the specified aperture. If symbols with greater than the minimum X dimension are allowed by the application, the same absolute maximum gap dimension must be maintained.

Examples:

- 2.8/05/660 would indicate that the average of the grades of the Scan Reflectance Profiles, or of the scan grades, was 2.8 when these were obtained with the use of a 0.125 millimetre aperture (ref. no. 05) and a 660 nanometre light source, incident at 45 degrees.
- 2.8/10/W/30 would indicate the grade of a symbol intended to be read in broadband light, measured with light incident at 30 degrees and using a 0.250 millimetre aperture (ref. no. 10), but would need to be accompanied either by a reference to the application specification defining the reference spectral characteristics used for measurement or a definition of the spectral characteristics themselves.
- 2.8/10/670* would indicate the grade of a symbol measured using a 0.250 millimetre aperture (ref. no. 10), and a 670 nanometre light source, and indicates the presence of a potentially interfering extreme reflectance value in the surroundings of the symbol.

Recommended symbol grades for GS1 DataMatrix are identified in individual applications in Section [5.5](#).

5.7.3.6. Advice for Selecting the Symbology

Any use of GS1 DataMatrix should comply with GS1 System global application guidelines and be restricted to those applications defined by the GS1 System for GS1 DataMatrix. GS1 DataMatrix will not replace other GS1 System Symbologies. Existing applications that are satisfactorily utilising EAN/UPC Symbols, ITF-14 Symbols, GS1-128 Symbols, GS1 DataBar Symbols, or Composite Symbols should continue to use them.

When using GS1 DataMatrix Symbols to encode the Global Trade Item Number (GTIN), any required additional data should be included within the same symbol.



Note: Scanning systems that need to read GS1 DataMatrix Symbols must be 2D imaging scanners and be appropriately programmed to read the GS1 System version of Data Matrix or ECC 200.

5.7.3.7. Human Readable Interpretation of GS1 DataMatrix Symbols

For Human-Readable Interpretation Rules see Section 4.12. For HRI Rules specific to Regulated Healthcare Retail Consumer Trade Items, see Section 4.12.1.

For GS1 DataMatrix Symbols encoding large amounts of data, it may not be practical to display all the data in Human Readable Interpretation form. Even if there is space to show it in this form, it may not be practical to key enter that much data. In these instances, some of the data may be omitted from the Human Readable Interpretation. However, primary identification data (GS1 System keys), such as the GTIN, must always be shown. Application specifications may provide additional guidance on Human Readable Interpretation.

5.8. Composite Bar Codes

5.8.1. Composite Symbology Introduction

The Composite Symbology integrates both a GS1 System linear symbol and a 2D Composite Component as a single symbology. There are three types of Composite Symbols A, B and C, each with different encoding rules. The encoder model is designed to automatically select the appropriate type and optimise.

The linear component encodes the item's primary identification. The adjacent 2D Composite Component encodes supplementary data, such as a batch number and expiration date. The Composite Symbol always includes a linear component so that the primary identification is readable by all scanning technologies. The Composite Symbol always includes a multi-row 2D Composite Component that can be read with linear- and area-CCD scanners, and with linear and rastering laser scanners.

The Composite Symbology is described in the Association for Automatic Identification and Mobility AIM ITS 99-002 - International Symbology Specification - Composite Symbology.

5.8.1.1. Composite Symbology Characteristics

The characteristics of the Composite Symbology are:

- Encodable character set:
 - Both linear and 2D components encode a subset of ISO/IEC 646. Refer to Figure 7.12 – 1 for the allowed encodable character set.

- The function character FNC1 and a Symbol Separator character. .
- Symbol character structure: Various (n,k) symbol characters are used in accordance with the underlying symbology of the selected linear and 2D Composite Components of the symbol.
- Code type:
 - Linear component: continuous, linear bar code symbology
 - 2D Composite Component: continuous, multi-row bar code symbology
- Maximum numeric data capacity:
 - Linear component:
 - GS1-128 Symbol: up to 48 digits
 - EAN/UPC Symbol: 8, 12, or 13 digits
 - GS1 DataBar Expanded Symbol: up to 74 digits
 - Other GS1 DataBar Symbols: 16 digits
 - 2D Composite Component:
 - CC-A: up to 56 digits
 - CC-B: up to 338 digits
 - CC-C: up to 2,361 digit
- Error detection and correction:
 - Linear component: a modulo check value for error detection
 - 2D Composite Component: a fixed or variable number of Reed-Solomon error correction codewords, depending upon the specific 2D Composite Component
- Character self-checking
- Bi-directionally decodable

5.8.1.2. Additional Features

The following is a summary of additional Composite Symbology features:

- Data compaction: The 2D Composite Components utilise a bit-oriented compaction mode designed to encode data efficiently using Application Identifiers (AIs).
- Component linkage: The 2D Composite Component of each Composite Symbol contains a linkage flag, which indicates to the reader that no data shall be transmitted unless the associated linear component is also scanned and decoded. All linear components except EAN/UPC Symbols also contain an explicit linkage flag.
- GS1-128 Symbol emulation: Readers set to the GS1-128 Symbol emulation mode transmit the data encoded within the Composite Symbol as if the data were encoded in one or more GS1-128 Symbols.
- A symbol Separator Character: A flag character to support future applications that instructs the reader to terminate transmission of the message at that point and to transmit the remaining data as a separate message
- 2D Composite Component escape mechanism: A mechanism to support future GS1 System applications that require characters beyond the ISO/IEC 646 character subset defined for Application Identifier (AI) Element String data (see Figure 7.12 – 1).

5.8.2. Symbol Structure

Each Composite Symbol consists of a linear component and a multi-row 2D Composite Component. The 2D Composite Component is printed above the linear component. The two components are separated by a separator pattern. Up to 3X of light space is permitted between the separator pattern

and 2D Composite Component to facilitate printing the two components separately; however, if the two components are printed at one time, the nominal alignment is followed as shown in Figure 5.8.2 - 1.

Figure 5.8.2 - 1 GS1 DataBar Limited Composite Symbol with CC-A



(01)13112345678906(17)010615(10)A123456

In Figure 5.8.2 - 1, the AI (01) Global Trade Item Number (GTIN) is encoded in the GS1 DataBar Limited linear component. The AI (17) expiration date and the AI (10) lot number are encoded in the CC-A 2D Composite Component.

The linear component is one of the following:

- A member of the EAN/UPC Symbology (EAN-13, EAN-8, UPC-A, or UPC-E)
- A member of the GS1 DataBar family
- A GS1-128 Symbol

The choice of linear component determines the name of the Composite Symbol, such as an EAN-13 Composite Symbol, or a GS1-128 Composite Symbol.

The 2D Composite Component (abbreviated as CC) is chosen based on the selected linear component and on the amount of supplementary data to be encoded. The three 2D Composite Components, listed in order of increasing maximum data capacity, are:

- CC-A: a variant of MicroPDF417
- CC-B: a MicroPDF417 symbol with new encoding rules
- CC-C: a PDF417 symbol with new encoding rules

Figure 5.8.2 - 2 GS1-128 Composite Symbol with CC-C



(01)03812345678908(10)ABCD123456(410)3898765432108

In Figure 5.8.2 - 2, the AI (01) GTIN is encoded in the GS1-128 Symbol linear component. The AI (10) lot number and the AI (410) ship-to location are encoded in the CC-C 2D Composite Component.

Based upon the width of the linear component, a choice of “best-fit” 2D Composite Component is specified. Figure 5.8.2 - 3 lists all of the permissible combinations.

Figure 5.8.2 - 3 Permissible Combinations of Linear and 2D Composite Components

Linear Component	CC-A/CC-B	CC-C
UPC-A and EAN-13	Yes (4-columns)	No
EAN-8	Yes (3-columns)	No
UPC-E	Yes (2-columns)	No
GS1-128	Yes (4-columns)	Yes (variable width)
GS1 DataBar Omnidirectional and GS1 DataBar Truncated	Yes (4-columns)	No
GS1 DataBar Stacked and GS1 DataBar Stacked Omnidirectional	Yes (2-columns)	No

Linear Component	CC-A/CC-B	CC-C
GS1 DataBar Limited	Yes (3-columns)	No
GS1 DataBar Expanded and GS1 DataBar Expanded Stacked	Yes (4-columns)	No

5.8.2.1. CC-A Structure

CC-A is a variant of MicroPDF417 with a unique combination of row address patterns (RAP). It is the smallest of the 2D Composite Components and can encode up to 56 digits. It has from 3 to 12 rows and 2 to 4 columns.

Each row is a minimum of 2X high (where X is the width of a module, narrow bar, or space). A 1X high minimum separator pattern is positioned between the linear component and 2D Composite Component. (A different separator pattern, 6X high, is used in Composite Symbols with EAN/UPC linear components).

Each column contains one $n,k = 17,4$ data or error correction character (codeword) per row (n is the number of modules, and k is the number of bars and also the number of spaces). So the width of a codeword is 17X.

In addition to the codeword columns, CC-A has two or three $n,k = 10,3$ RAP columns that encode the row numbers (each 10X wide). The rightmost RAP column is terminated on the right by a 1X bar, so it is 11X instead of 10X wide.

Each row also requires a 1X Quiet Zone at each end. There is no Quiet Zone required above CC-A. The separator pattern is printed directly above the linear component and no Quiet Zone is required below the CC-A.

The two-column and three-column CC-A versions have two RAP columns, and the four-column CC-A version has three RAP columns, as shown in Figure 5.8.2.1 -1.

Figure 5.8.2.1 - 1 CC-A Column Structures

Two-Column CC-A Structure

Quiet Zone	RAP Column	Codeword Column	Codeword Column	RAP Column	Quiet Zone
------------	------------	-----------------	-----------------	------------	------------

Three-Column CC-A Structure

Quiet Zone	Codeword Column	RAP Column	Codeword Column	Codeword Column	RAP Column	Quiet Zone
------------	-----------------	------------	-----------------	-----------------	------------	------------

Four-Column CC-A Structure

Quiet Zone	RAP Column	Codeword Column	Codeword Column	RAP Column	Codeword Column	Codeword Column	RAP Column	Quiet Zone
------------	------------	-----------------	-----------------	------------	-----------------	-----------------	------------	------------

Figure 5.8.2.1 - 2 lists all possible column and row combinations for CC-A. It also shows the capacity and size of the 2D Composite Components. For example, a two-column, five-row CC-A would be 57X wide (including 1X for the extra right-most guard bar) by 10X high (not including the separator pattern). With an X-dimension of 0.254 millimetre (0.0100 inch), it would be 14.48 millimetres (0.57 inch) wide by 2.54 millimetre (0.100 inch) high.

Figure 5.8.2.1 - 2 CC-A Row and Column Sizes

Number of Data Columns (c)	Number of Rows (r)	Total CWs in Data Region	Number of EC CWs (k)	Percent of CWs for EC	Number of CWs for Data	Max Alpha Chars	Max Digits	Component Width, in X (see Note 1)	Component Height, in X (see Note 2)
2	5	10	4	40.00%	6	8	16	57	10
2	6	12	4	33.33%	8	12	22	57	12
2	7	14	5	35.71%	9	13	24	57	14
2	8	16	5	31.25%	11	17	30	57	16
2	9	18	6	33.33%	12	18	33	57	18
2	10	20	6	30.00%	14	22	39	57	20
2	12	24	7	29.17%	17	26	47	57	24
3	4	12	4	33.33%	8	12	22	74	8
3	5	15	5	33.33%	10	15	27	74	10
3	6	18	6	33.33%	12	18	33	74	12
3	7	21	7	33.33%	14	22	39	74	14
3	8	24	7	29.17%	17	26	47	74	16
4	3	12	4	33.33%	8	12	22	101	6
4	4	16	5	31.25%	11	17	30	101	8
4	5	20	6	30.00%	14	22	39	101	10
4	6	24	7	29.17%	17	26	47	101	12
4	7	28	8	28.57%	20	31	56	101	14

CW = Codeword; EC = Error Correction



Note: Includes a 1X Quiet Zone on each side



Note: Assumes row height = 2X; does not include separator pattern

5.8.2.2. CC-B Structure

CC-B is a MicroPDF417 symbol uniquely identified by the codeword 920 as the first codeword in the symbol. Encoding systems normally automatically select CC-B when the data to be encoded exceeds the capacity of CC-A. CC-B can encode up to 338 digits. It has from 10 to 44 rows and 2 to 4 columns.

Each row is a minimum of 2X high (where X is the width of a module, narrow bar or space). A 1X high minimum separator pattern is positioned between the linear component and 2D Composite Component. (A different separator pattern, 6X high, is used in Composite Symbols with EAN/UPC linear components).

Each column contains one n,k = 17,4 data or error correction character (codeword) per row (where n is the number of modules, and k is the number of bars and also the number of spaces). So the width of a codeword is 17X.

In addition to the codeword columns, CC-B has two or three n,k = 10,3 row address pattern (RAP) columns that encode the row numbers (each 10X wide). The rightmost RAP column is terminated on the right by a 1X bar, so it is 11X instead of 10X wide.

Each row also requires a 1X Quiet Zone on each end. There is no Quiet Zone required above CC-B. The separator pattern is printed directly above the linear component, and no Quiet Zone is required below the CC-B.

The two-column CC-B version has two RAP columns and the three- and four-column CC-B versions have three RAP columns, as shown in Figure 5.8.2.2 - 1.

Figure 5.8.2.2 – 1 CC-B Column Structures

Two-Column CC-B Structure

Quiet Zone	RAP Column	Codeword Column	Codeword Column	RAP Column	Quiet Zone
------------	------------	-----------------	-----------------	------------	------------

Three-Column CC-B Structure

Quiet Zone	RAP Column	Codeword Column	RAP Column	Codeword Column	Codeword Column	RAP Column	Quiet Zone
------------	------------	-----------------	------------	-----------------	-----------------	------------	------------

Four-Column CC-B Structure

Quiet Zone	RAP Column	Codeword Column	Codeword Column	RAP Column	Codeword Column	Codeword Column	RAP Column	Quiet Zone
------------	------------	-----------------	-----------------	------------	-----------------	-----------------	------------	------------

CC-B differs from CC-A in the three-column structure in that CC-B has a third RAP column on the left end that is missing in CC-A.

Figure 5.8.2.2 - 2 lists all the possible column and row combinations for CC-B. It also shows the capacity and size of the 2D Composite Components. For example a four-column, 10-row CC-B would be 101X wide by 20X high (not including the separator pattern). With an X-dimension of 0.254 millimetre (0.0100 inch), it would be 25.65 millimetres (1.010 inches) wide by 5.08 millimetres (0.200 inch) high.

Figure 5.8.2.2 - 2 CC-B Row and Column Sizes

Number of Data Columns (c)	Number of Rows (r)	Total CWs in Data Region	Number of EC CWs (k)	Percent of CWs for EC	Number of non-EC CWs	Number of CWs for Data (Note 1)	Max Alpha chars	Max Digits	CC-B Width, in X (see Note 2)	CC-B Height, in X (see Note 3)
2	17	34	10	29	24	22	34	59	57	34
2	20	40	11	28	29	27	42	73	57	40
2	23	46	13	28	33	31	48	84	57	46
2	26	52	15	29	37	35	55	96	57	52
3	15	45	21	47	24	22	34	59	84	30
3	20	60	26	43	34	32	50	86	84	40
3	26	78	32	41	46	44	68	118	84	52
3	32	96	38	40	58	56	88	153	84	64
3	38	114	44	39	70	68	107	185	84	76

Number of Data Columns (c)	Number of Rows (r)	Total CWs in Data Region	Number of EC CWs (k)	Percent of CWs for EC	Number of non-EC CWs	Number of CWs for Data (Note 1)	Max Alpha chars	Max Digits	CC-B Width, in X (see Note 2)	CC-B Height, in X (see Note 3)
3	44	132	50	38	82	80	127	219	84	88
4	10	40	16	40	24	22	34	59	101	20
4	12	48	18	38	30	28	43	75	101	24
4	15	60	21	35	39	37	58	100	101	30
4	20	80	26	33	54	52	82	141	101	40
4	26	104	32	31	72	70	111	192	101	52
4	32	128	38	30	90	88	139	240	101	64
4	38	152	44	29	108	106	168	290	101	76
4	44	176	50	28	126	124	196	338	101	88

CW = Codeword; EC = Error correction

- ✔ **Note:** Excludes EC codewords and 2 codewords to define CC-B encodation
- ✔ **Note:** Including 1X Quiet Zones on either side
- ✔ **Note:** Assumes Y = 2X; does not include separator pattern

5.8.2.3. CC-C Structure

CC-C is a PDF417 symbol uniquely identified by the codeword 920 as the first codeword in the symbol following the symbol length descriptor. CC-C is only used as a 2D Composite Component within a GS1-128 Composite Symbol. It has the greatest data capacity of the Composite Symbols, encoding up to 2,361 digits. It has from 3 to 30 rows and 1 to 30 data/EC codeword columns.

Each row is a minimum of 3X high (where X is the width of a module, narrow bar, or space). A 1X high minimum separator pattern is positioned between the linear component and 2D Composite Component.

Each column contains one n,k = 17,4 data or error correction character (codeword) per row (where n is the number of modules, and k is the number of bars and also the number of spaces). So the width of a data/EC codeword is 17X.

In addition to the codeword columns, CC-C has two 17,4 row indicator columns, a 17X wide start pattern, and a 18X wide stop pattern as illustrated in Figure 5.8.2.3 - 1.

Each row also requires a 2X Quiet Zone on each end. There is no Quiet Zone required above CC-C. The separator pattern is printed directly above the linear component, and no Quiet Zone is required below the CC-C.

Figure 5.8.2.3 - 1 CC-C Row Structure

Quiet Zone	Start Pattern	Left Row Indicator Column	1 to 30 Data/EC Codeword Columns	Right Row Indicator Column	Stop Pattern	Quiet Zone
------------	---------------	---------------------------	----------------------------------	----------------------------	--------------	------------

CC-C is normally printed with the number of columns that will result in a width nearly matching the width of the GS1-128 Symbol linear component. However, as an option, the user may specify a wider CC-C to be printed. This reduces the height of the 2D Composite Component. A lower Composite Symbol may be needed to fit in a height-restricted application. A wider CC-C may also be required if the amount of data does not fit in the default width CC-C.

5.8.2.4. Special Compressed Element String Sequences

While 2D Composite Components can encode any sequence of Application Identifier (AI) Element Strings up to the maximum capacity of the component, certain sequences of AI Element Strings have been selected for special compression in 2D Composite Component Symbols. If the application requires the use of the AI Element Strings in one of these sequences, and they are used in the predefined sequence, a smaller symbol will result.

For special compression to be performed, the AI Element String sequence must occur at the start of the 2D Composite Component's data. Other AI Element Strings may be added following the sequence.

The AI Element Strings selected for special compression are:


- Production date and lot number: AI (11) production date followed by AI (10) lot number
- Expiration date and lot number: AI (17) expiration date followed by AI (10) lot number
- AI (90): AI (90) followed by the Element String data starting with an alphabetic character and a digit; AI (90) may be used to encode data identifier data; the AI (90) followed by data in the data identifier format has special compression applied only if it is the start of the first Element String.

5.8.3. Human Readable Interpretation of Composite Symbols

For Human-Readable Interpretation Rules see Section 4.12. For HRI Rules specific to Regulated Healthcare Retail Consumer Trade Items, see Section 4.12.1.

As an option, the data title (see Section 3.2) may be associated with the data instead of using AIs. Figure 5.8.3 - 1 shows the expiration date and lot number identified with text. This can be compared with Figure 5.8.2 - 1, where the same data is shown using the all-AI format.

Figure 5.8.3 - 1 The Human Readable Interpretation and Non-HRI text



For Composite Symbols encoding a large amount of data, it may not be practical to display all the data in Human Readable Interpretation form or, even if there is space to show it in this form, it may not be practical to key enter that much data. In these instances, some of the data may be omitted from the Human Readable Interpretation. However, primary identification data such as the Global Trade Item Number (GTIN) and SSCC must always be shown. Application specifications provide guidance on Human Readable Interpretation.

5.8.4. Data Transmission and Symbology Identifier Prefixes

5.8.4.1. Default Transmission Mode

The GS1 System requires the use of symbology identifiers. Composite Symbols are normally transmitted using symbology identifier prefix “je0,” with the data from the 2D Composite Component directly appended to that of the linear component. For example, a Composite Symbol encoding (01)10012345678902(10)ABC123 produces the data string “je0011001234567890210ABC123” (note that the symbology identifier prefix “je0” is different from the symbology identifier prefix “JE0,” which has an uppercase “E” and is used for standard EAN/UPC Symbols). However, readers have an option to transmit only the linear component data and ignore the 2D Composite Component.

Data transmission follows the same principles that apply to the concatenation of Application Identifier (AI) Element Strings from GS1-128 Symbols. If the linear component data ends with a variable length AI Element String, an ASCII 29 character (GS) is inserted between it and the first character of the data from the 2D Composite Component.

5.8.4.2. GS1-128 Symbol Transmission Mode

Readers also have an option for GS1-128 Symbol emulation mode. This mode emulates the GS1-128 Symbology for data transmission. It can be used for applications programmed for GS1-128 Symbols but not yet programmed to recognise the symbology identifier prefix “je0.” The symbology identifier for GS1-128 Symbol emulation mode is “jC1.” Composite Symbols that exceed 48 data characters are transmitted as two or more messages so as not to exceed the maximum GS1-128 Symbol message length. Each of the messages has a symbology identifier prefix of “jC1” and does not exceed 48 data characters. The messages are split at boundaries between Element Strings. This mode is inferior to the normal transmission mode as message integrity may be lost when a message is split into multiple messages.



Note: When GS1-128 emulation option is enabled in the reader, each data packet (except the data from an EAN/UPC component) shall be prefixed with a symbology identifier of “jC1”. When transmitting data from GS1 Composite Symbols, two separate transmissions from the reader are required. The data from the EAN/UPC component is prefixed with a symbology identifier in accordance with Symbology Identifier “E”. Modifier character values 1 and 2 shall not be used when transmitting data from GS1 DataBar Symbols.

5.8.4.3. Symbol Separator Character

The 2D Composite Component can encode symbol Separator Characters as defined in the decoder. This character instructs the reader to terminate the current Composite Symbol’s data message and transmit the data following the symbol separator as a separate message. This new message will have the symbology identifier prefix of “je1.” This feature will be used for future GS1 System applications such as encoding the mixed contents of a logistical container.

5.8.4.4. 2D Composite Component Escape Mechanism

The CC-B and CC-C also can encode 2D Composite Component escape mechanism codewords. These instruct the reader to terminate the current Composite Symbol’s data message and transmit the data following the escape mechanism codeword as a separate message. This new message has the symbology identifier prefix of “je2” for standard data message. The codewords following the escape mechanism codeword are encoded and decoded using the standard PDF417 encoding defined in *ISO/IEC 15438 – Information technology; automatic identification and data capture techniques - Symbology specification - PDF417*. This feature is used for future GS1 System applications that require characters beyond the ISO/IEC 646 character subset defined for Application Identifier (AI) Element String data (see Figure 7.12 – 1).

- ✓ **Note:** The protocol for “je2” corresponds to the protocol defined for PDF417 using Symbology Identifier “[L2”.

5.8.5. Width of a Module (X)

The X-dimension of the 2D Composite Component must be the same as that of the associated linear component. Refer to the linear component’s X-dimension requirements.

5.8.6. Print Quality

The print quality assessment methodology defined in the International Standard *ISO/IEC 15416* is used for measuring and grading the linear components. The ISO print quality specification is functionally identical to the older ANSI and CEN print quality specifications. The print quality grade is measured by verifiers that apply the standard. The print quality grade reported includes a grade level, measuring aperture, and the wavelength of light used for the measurement.

AIM ITS 99-002 – International Symbology Specification - MicroPDF417 and ISO/IEC 15438 specify the methods for determining the print quality grade of the 2D Composite Components CC-A/B and CC-C respectively. An additional grading parameter unused error correction (UEC) is defined in these specifications.

The minimum quality grade for Composite Symbols is:

1.5 / 6 / 670

- Where-

- 1.5 is the overall symbol quality grade.
- 6 is the measuring aperture reference number (corresponding to an 0.15 millimetre or 0.006 inch diameter aperture).
- 670 is the peak response wavelength in nanometres. In addition to the print quality grade, all elements in the separator patterns should be visually distinguishable.

Both the linear component and the 2D Composite Component must independently achieve the minimum print quality grade.

- ✓ **Note:** An international standard methodology for quality grading two-dimensional symbologies is under development and may eventually supersede the method defined in the above specifications.

5.8.7. Advice for Selecting a Symbology

Any use of the 2D Composite Component SHALL comply with GS1 System global application standards and multiple bar code management practices (see Section 4.13). The linear component of a Composite Symbol should be selected according to the application rules defined in these *GS1 General Specifications*, but where a choice of linear components is available for the application, consideration should also be given to the 2D Composite Component options available. A wider linear component will result in a shorter 2D Composite Component and, particularly for CC-B, a higher capacity symbol.

For CC-A and CC-B, the selection of the linear component automatically determines the number of columns of the 2D Composite Component. The selection of CC-A or CC-B is automatically determined by the amount of data to be encoded. CC-A is always used unless the data exceeds its capacity.

When the linear component is a GS1-128 Symbol, the user may specify CC-A/B or CC-C. CC-A/B will produce a smaller 2D Composite Component. However, CC-C can increase in width to match the width of the GS1-128 Symbol or be selected to be even wider. This may produce a Composite Symbol of lower height. CC-C also has a larger data capacity, so it is suitable for applications such as logistics.

5.8.8. Sample Composite Symbols

Figure 5.8.8 - 1 EAN-13 Symbol with a Four-Column CC-A Component



Figure 5.8.8 - 2 UPC-A Symbol with a Four-Column CC-B Component



Figure 5.8.8 - 3 EAN-8 Symbol with a Three-Column CC-A



Figure 5.8.8 - 4 UPC-E Symbol with a Two-Column CC-A



Figure 5.8.8 - 5 GS1 DataBar Omnidirectional Symbol with a Four-Column CC-A



Figure 5.8.8 - 6 GS1 DataBar Stacked Symbol with a Two-Column CC-A



Figure 5.8.8 - 7 GS1 DataBar Limited Symbol with a Three-Column CC-B



✔ **Note:** The three-column CC-B is wider than the three-column CC-A shown in Figure 5.8.2 - 1.

Figure 5.8.8 - 8 GS1 DataBar Expanded Symbol with a Four-Column CC-A



(01)93712345678904(3103)001234

(91)1A2B3C4D5E

Figure 5.8.8 - 9 GS1-128 Symbol with a Four-Column CC-A



(01)03212345678906

(21)A1B2C3D4E5F6G7H8

5.9. Two Dimensional Bar Codes – GS1 QR Code Symbology

5.9.1. Introduction

This section of the *GS1 General Specifications* addresses some of the technical aspects of the two-dimensional bar code symbology called GS1 QR Code. GS1 QR Code is a standalone, two-dimensional matrix symbology that is made up of square modules arranged in an overall square pattern, including a unique finder pattern located at three corners of the symbol. Unlike a Composite Component symbol (see Section [5.8.1](#)), GS1 QR Code does not require a linear symbol. QR Code and QR Code 2005 have been used in the public domain since 1998 and 2005 respectively.

This section provides only a brief technical description and overview of the GS1 QR Code symbology. A more detailed technical specification can be found in the International Standard *ISO/IEC 18004 QR Code 2005 bar code symbology specification*. The GS1 System has adopted GS1 QR Code partly because, like GS1 DataMatrix, GS1 QR Code can encode GS1 System data structures and offers other technical advantages. Its compact design and the existence of various production methods that accommodate placing the symbology onto various substrates offer certain advantages over other symbologies currently in the GS1 System.

QR Code 2005 is the only member of the QR Code family that supports GS1 System data structures, including Function 1 Symbol Character. ISO/IEC QR Code 2005 also contains specifications for Micro QR Code, but this symbology is not supported for the GS1 System. QR Code 2005 uses Reed-Solomon error correction (four selectable levels of error correction are specified), and this feature helps correct for partially damaged symbols. In the remainder of this section, the ISO/IEC QR Code 2005 is assumed when the symbology is described as GS1 QR Code. QR Code 2005 is similar in stability to ISO versions of current GS1 System symbologies.

Implementation of GS1 QR Code shall be done per approved GS1 System application standards. This section will not describe the specific applications. The user needs to refer to specific application standards in other sections of these *GS1 General Specifications* as they are approved for use.

GS1 QR Code Symbols are read by two-dimensional imaging scanners or vision systems. Most other scanners that are not two-dimensional imagers cannot read GS1 QR Code. GS1 QR Code Symbols are restricted for use with new niche applications that will involve imaging scanners within mobile devices.

5.9.2. GS1 QR Code Features and Symbol Basics

GS1 QR Code is a subset of ISO/IEC QR Code 2005 that is a matrix symbology with the following characteristics:

Formats:

- QR Code, with full range of capabilities and maximum data capacity
- Not supported for the GS1 System: Micro QR Code, with reduced overhead, some restrictions on capabilities and reduced data capacity

Encodable character set:

- numeric data (digits 0 - 9);
- alphanumeric data (digits 0 - 9; upper case letters A -Z; nine other characters: space, \$ % * + - . / :);
- byte data (default: ISO/IEC 8859-1; or other sets as otherwise defined In byte mode, data is encoded at 8 bits per character. In closed-system national or application-specific implementations of QR Code 2005, an alternative 8-bit character set, for example as defined in an appropriate part of ISO/IEC 8859, may be specified for byte mode. When an alternative character set is specified, however, the parties intending to read the QR Code 2005 symbols require to be notified of the applicable character set in the application specification or by bilateral agreement.
- Not supported for the GS1 System: Kanji characters (Kanji characters in QR Code 2005 can be compacted into 13 bits.

Representation of data:

A dark module is nominally a binary one and a light module is nominally a binary zero. However, reflectance reversal is provided as an option.

Symbol size (not including Quiet Zone):

GS1 QR Code symbols: 21 × 21 modules to 177 × 177 modules (Versions 1 to 40, increasing in steps of four modules per side)

Data characters per symbol

- maximum QR Code symbol size, Version 40-L:
- numeric data: 7 089 characters
- alphanumeric data: 4 296 characters
- Byte data: 2 953 characters
- Kanji data: 1 817 characters (Not supported for the GS1 System)

Selectable error correction:

Four levels of Reed-Solomon error correction (referred to as L, M, Q and H in increasing order of capacity) allowing recovery of:

- L 7% of the symbol codewords
- M 15% of the symbol codewords
- Q 25% of the symbol codewords
- H 30% of the symbol codewords

Orientation independence:

both rotation and reflection

Figure 5.9.3-1 illustrates a QR Code 2005 symbol in normal colour and with reflectance reversal in both normal and mirror image orientations.

5.9.3. Summary of additional features

The use of the following additional features is optional in QR Code 2005; some of these features are not supported for GS1 System use.


Reflectance reversal

Symbols are intended to be read when marked so that the image is either dark on light or light on dark (Figure 5.9.3-1). The specifications in this document are based on dark images on a light background, therefore in the case of symbols produced with reflectance reversal references to dark or light modules should be taken as references to light or dark modules respectively. See note below Figure 5.5.2.7 – 2.1 for more information.

Mirror imaging

The arrangement of modules defined in this International Standard represents the "normal" orientation of the symbol. It is, however, possible to achieve a valid decode of a symbol in which the arrangement of the modules has been laterally transposed. When viewed with the finder patterns at the top left, top right and bottom left corners of the symbol, the effect of mirror imaging is to interchange the row and column positions of the modules. See note below Figure 5.5.2.7 – 2.1 for more information.


Figure 5.9.3-1 — Examples of QR Code 2005 symbols




normal orientation and normal reflectance arrangement;



normal orientation and reversed reflectances



mirror image orientation and normal reflectance arrangement



mirror image orientation and reversed reflectances

Not supported for the GS1 System: Structured append

This allows files of data to be represented logically and continuously in up to 16 QR Code 2005 symbols. These may be scanned in any sequence to enable the original data to be correctly reconstructed. Structured Append is not available with Micro QR Code symbols.

Not supported for the GS1 System: Extended Channel Interpretations

This mechanism enables data using character sets other than the default encodable set (e.g. Arabic, Cyrillic, Greek) and other data interpretations (e.g. compacted data using defined compression schemes) or other industry-specific requirements to be encoded

5.9.4. GS1 QR Code Symbology

The technical description of GS1 QR Code contained within this section provides additional information based on ISO/IEC technical standard 18004 and it is provided as a further aid in the development of specific applications.

5.9.4.1. GS1 QR Code Square Format

GS1 QR Code is printed in a square format. The square format has a large range of sizes. The largest symbol (177 X 177 modules, Error Correction Level = L) can encode up to 7089 digits or 4296 alphanumeric characters technically, however permissible data is specified by the application standards.

5.9.4.2. GS1 QR Code Symbol Sizes

GS1 QR Code Symbology has multiple sizes to match various data content (see Figure 5.9.4.2 - 1). GS1 QR Code Symbols have 40 sizes in a square format ranging from 21 by 21 modules up to 177 by 177 modules, not including the 4-X surrounding Quiet Zone.

The term “codeword” is used often to describe attributes concerning the encodation of data into GS1 QR Code. A codeword is defined as: “A symbol character value. An intermediate level of coding between source data and the graphical encodation in the symbol.” Codewords are typically eight bits of data.

Figure 5.9.4.2 - 1 GS1 QR Code Symbol Size and Data Capacity

Version	Modules/ side	Data capacity [codewords]	Version	Modules/ side	Data capacity [codewords]
1	21	26	21	101	1 156
2	25	44	22	105	1 258
3	29	70	23	109	1 364
4	33	100	24	113	1 474
5	37	134	25	117	1 588
6	41	172	26	121	1 706
7	45	196	27	125	1 828
8	49	242	28	129	1 921
9	53	292	29	133	2 051
10	57	346	30	137	2 185
11	61	404	31	141	2 323
12	65	466	32	145	2 465
13	69	532	33	149	2 611
14	73	581	34	153	2 761

15	77	655		35	157	2 876
16	81	733		36	161	3 034
17	85	815		37	165	3 196
18	89	901		38	169	3 362
19	93	991		39	173	3 532
20	97	1 085		40	177	3 706

Note:

* Symbol size does not include surrounding 4-X Quiet Zones.

Figure 5.9.4.2 - 2 GS1 QR Code Symbol Attributes for the first ten versions of the symbol

Version	Error correction level	Number of data codewords	Data capacity			
			Numeric	Alphanu- meric	Byte	Kanji
1	L	19	41	25	17	10
	M	16	34	20	14	8
	Q	13	27	16	11	7
	H	9	17	10	7	4
2	L	34	77	47	32	20
	M	28	63	38	26	16
	Q	22	48	29	20	12
	H	16	34	20	14	8
3	L	55	127	77	53	32
	M	44	101	61	42	26
	Q	34	77	47	32	20
	H	26	58	35	24	15
4	L	80	187	114	78	48
	M	64	149	90	62	38
	Q	48	111	67	46	28
	H	36	82	50	34	21
5	L	108	255	154	106	65
	M	86	202	122	84	52
	Q	62	144	87	60	37
	H	46	106	64	44	27
6	L	136	322	195	134	82
	M	108	255	154	106	65
	Q	76	178	108	74	45
	H	60	139	84	58	36
7	L	156	370	224	154	95
	M	124	293	178	122	75
	Q	88	207	125	86	53
	H	66	154	93	64	39
8	L	194	461	279	192	118
	M	154	365	221	152	93
	Q	110	259	157	108	66
	H	86	202	122	84	52
9	L	232	552	335	230	141
	M	182	432	262	180	111

Version	Error correction level	Number of data codewords	Data capacity			
			Numeric	Alphanumeric	Byte	Kanji
	Q	132	312	189	130	80
	H	100	235	143	98	60
10	L	274	652	395	271	167
	M	216	513	311	213	131
	Q	154	364	221	151	93
	H	122	288	174	119	74

5.9.4.3. Data Transmission and Symbology Identifier Prefixes

The GS1 System requires the use of symbology identifiers. GS1 QR Code uses the symbology identifier of "JQ3" (see Figure 5.9.4.3 - 1) for GS1 System compliant symbols that have a leading FNC1 character. This indicates that Application Identifier (AI) data is encoded equivalent to the symbology identifier "JC1" for GS1-128 Symbols, Jd2 for GS1 DataMatrix Symbols and "Je0" for GS1 DataBar and Composite Symbols. For more information on symbology identifiers, see the International standard *ISO/IEC 15424* Information technology — Automatic identification and data capture techniques — Data Carrier Identifiers.

For example, a GS1 QR Code Symbol encoding AI (01) Element String 10012345678902 produces the transmitted data string "JQ30110012345678902." Data transmission follows the same principles that apply to the concatenation of AI Element Strings in any GS1 BarCode that encodes Application Identifiers (see Section 7.9).

Figure 5.9.4.3 - 1 Symbology Identifier for GS1 QR Code

	Message Content	Separator
JQ3	Standard AI Element Strings	None

5.9.4.4. Width and Height of a Module (X)

The range of the X-dimensions will be defined by the application specification, having due regard to the availability of equipment for the production and reading of symbols and complying with the general requirements of the application.

The X-dimension shall be constant throughout a given symbol. The X-dimension should apply to both the width and height of the modules.

5.9.4.5. Symbol Quality Grade

The International Standard *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code symbol print quality test specification - Two-dimensional symbols methodology shall be used for measuring and grading GS1 QR Code Symbols. The print quality grade is measured by verifiers that comply with the standard. The grade includes a grade level, measuring aperture, the wavelength of light used for the measurement, and the illumination angle relative to the symbol.

A symbol grade is only meaningful if it is reported in conjunction with the illumination and aperture used. It should be shown in the format grade/aperture/light/angle, where:

- "grade" is the overall symbol grade as defined in *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code symbol print quality test specification - Two-dimensional symbols (e.g., the arithmetic mean to one decimal place of

the Scan Reflectance Profile or scan grades). For GS1 QR Code, the grade number may be followed by an asterisk (*) which indicates that the surroundings of the symbol contain extremes of reflectance that may interfere with reading. For most applications, this should be specified as causing the symbol to fail.

- "aperture" is the diameter in thousandths of an inch (to the nearest thousandth) of the synthetic aperture defined in *ISO/IEC 15415* Information technology - Automatic identification and data capture techniques - Bar code symbol print quality test specification - Two-dimensional symbols.
- "light" defines the illumination: A numeric value indicates the peak light wavelength in nanometres (for narrow band illumination); the alphabetic character W indicates that the symbol has been measured with broadband illumination (white light) the spectral response characteristics of which must imperatively be defined or have their source specification clearly referenced.
- "angle" is an additional parameter defining the angle of incidence (relative to the plane of the symbol) of the illumination. It shall be included in the reporting of the overall symbol grade when the angle of incidence is other than 45 degrees. Its absence indicates that the angle of incidence is 45 degrees.

The aperture is normally specified as being 80% of the minimum X-dimension allowed for the application.

Examples:

- 2.8/05/660 would indicate that the average of the grades of the Scan Reflectance Profiles, or of the scan grades, was 2.8 when these were obtained with the use of a 0.125 millimetre aperture (ref. no. 05) and a 660 nanometre light source, incident at 45 degrees.
- 2.8/10/W/30 would indicate the grade of a symbol intended to be read in broadband light, measured with light incident at 30 degrees and using a 0.250 millimetre aperture (ref. no. 10), but would need to be accompanied either by a reference to the application specification defining the reference spectral characteristics used for measurement or a definition of the spectral characteristics themselves.
- 2.8/10/670* would indicate the grade of a symbol measured using a 0.250 millimetre aperture (ref. no. 10), and a 670 nanometre light source, and indicates the presence of a potentially interfering extreme reflectance value in the surroundings of the symbol.

Recommended symbol grades for GS1 QR Code are identified in individual applications in Section [5.5](#).

5.9.4.6. Advice for Selecting the Symbology

Any use of GS1 QR Code should comply with GS1 System global application standards and be restricted to those applications defined by the GS1 System for GS1 QR Code. GS1 QR Code will not replace other GS1 System Symbologies. Existing applications that are satisfactorily utilising EAN/UPC Symbols, ITF-14 Symbols, GS1-128 Symbols, GS1 DataBar Symbols, GS1 DataMatrix or GS1 Composite Symbols should continue to use them.

- ✔ **Note:** Scanning systems that need to read GS1 QR Code Symbols must be 2D imaging scanners and be appropriately programmed to read the GS1 System versions of ISO/IEC 18004 QR Code 2005.

5.9.4.7. Human Readable Interpretation of GS1 QR Code Symbols


For Human-Readable Interpretation Rules see Section 4.12.

5.10. Appendix: Rules for Encoding/Decoding Element Strings in GS1 Symbologies using GS1 Application Identifiers

5.10.1. The Basic Structure of GS1 Bar Codes using GS1 Application Identifiers and Concatenation

All GS1 bar code symbologies that use GS1 Application Identifiers have a particular symbol characters to indicate that the data is encoded according to the GS1 Application Identifier rules. For example the GS1-128 Symbology uses the Function 1 Symbol Character (FNC1) in the position following the Start Character. This double start pattern is reserved for GS1 System applications worldwide. This makes it possible to distinguish GS1-128 Bar Codes from extraneous non-GS1 bar codes.

Figure A1 - 1 Example GS1-128 Bar Code Structure



All GS1 bar code symbologies that use GS1 Application Identifiers allow several Element Strings to be encoded in one bar code, a process called concatenation. Concatenation is advantageous because it means that the symbology elements are only needed once, and the space required for the symbol is smaller than when separate bar codes are used to encode each Element String. It also improves scanning accuracy, allowing for single scanning rather than multiple scanning. The various Element Strings are transmitted from the bar code reader as a single full string.

The various Element Strings, which are transmitted from concatenated bar codes, have to be analysed and processed. To simplify this procedure and reduce the symbol size, the lengths of some Element Strings are pre-defined (see Figure A1 -2). Element Strings that are not contained in Figure A1 - 2 and that do not appear at the end of the symbol (encoded immediately before the Symbol Check Character) must be delimited to separate them from the Element String that follows. The delimiter shall be a Function 1 Symbol Character in GS1-128 Symbology, GS1 DataBar Expanded Versions and GS1 Composite Symbology and should be a Function 1 Symbol Character in GS1 DataMatrix Symbology and GS1 QR Code Symbology.

Figure A1 - 2 contains all Application Identifiers that have a predefined length and, therefore, do not require a Function 1 Symbol Character (FNC1) separator.

Figure A1 - 2 Element Strings with Pre-Defined Length Using Application Identifiers

First Two Digits of the Application Identifier	Number of Characters (Application Identifier and Data Field)	First Two Digits of the Application Identifier	Number of Characters (Application Identifier and Data Field)
00	20	17	8
01	16	(18)	8
02	16	(19)	8
(03)	16	20	4
(04)	18	31	10
11	8	32	10
12	8	33	10
13	8	34	10
(14)	8	35	10
15	8	36	10
(16)	8	41	16

Note: Figure A1 - 2 is limited to the listed numbers and will remain unchanged. Those numbers in parentheses are not yet assigned. Application Identifiers starting with two digits that are not included in Figure A1 - 2 have a variable length even if the definition of the Application Identifier specifies a fixed length data field.

5.10.2. Concatenation

5.10.2.1. Pre-Defined Length Element Strings

Concatenated Element Strings constructed from Application Identifiers with a pre-defined length do not require a Separator Character. Each Element String is immediately followed by either the next Application Identifier or the Symbol Check Character and Stop Character.

For example, concatenation of net weight (4.00 kilograms) with the associated Global Trade Item Number (GTIN) 95012345678903 does not require the use of a Separator Character.

- (01) has a pre-defined Element String length of 16 digits.
- (31) has a pre-defined Element String length of 10 digits.

Figure A.1.1 – 1 Data Encoded in two GS1-128 symbols



Figure A.1.1 – 2 Data Encoded in one Concatenated GS1-128 symbol



5.10.2.2. Variable Length Data Strings

Concatenating Element Strings of variable length, including all Application Identifiers that do not start with two characters contained in Figure A1 - 2, involves the use of a Separator Character. The Separator Character used is the Function 1 Symbol Character (FNC1). It is placed immediately after the last symbol character of a variable length data string and is followed by the Application Identifier of the next Element String. If the Element String is the last to be encoded, it is followed by the Symbol Check and Stop Characters and not the FNC1 Separator Character.

For example, concatenation of price per unit of measure (365 currency units) and batch number (123456) requires the use of a Separator Character immediately after the price per unit of measure.

Figure A1.2 – 1 Data Encoded in two GS1-128 symbols



Figure A1.2 - 2 Data Encoded in one Concatenated GS1-128 symbol



Note: The FNC1 is not shown in Human Readable Interpretation.

5.10.2.3. Other considerations when using Concatenation

Concatenation is an effective means for presenting multiple Element Strings in a single bar code and is used to conserve label space and optimise scanning operations when permitted by the application standard (e.g., concatenation should be used with the GS1-128 bar code containing the SSCC on cartons or outer-cases).

When concatenating a mixture of pre-defined and other Element Strings, the pre-defined Element Strings should appear before the variable length Element Strings.

The FNC1 Separator Character appears in the decoded data string as <GS> (ASCII character 29, 7-bit character set ISO/IEC 646). A FNC1 is not required at the end of the last Element String represented in a GS1 Symbologies using GS1 Application Identifiers. The processing routine allows for a FNC1 entered by error after an Element String contained in Figure A1 - 2.

Figure A1.3 - 1 Example of GS1 DataBar Expanded Stacked Bar Code that uses concatenation



Concatenation may not be desirable in all circumstances (e.g., GS1 Logistic Labels are often constructed using multiple rows of bar code), in such cases the bar code containing the additional attribute data encoded using GS1 Application Identifiers should be printed in close proximity to the bar code containing the GS1 Identification Key.

Figure A1.3 - 2 Example of mixed GS1 Symbologies (GTIN encoded in UPC-E, Best Before Date in Composite)





6. Symbol Placement Guidelines

- Introduction
- General Placement Principles
- General Placement Guidelines for Point-of-Sale
- Placement Guidelines for Specific Package Types
- Symbol Placement for Clothing and Fashion Accessories
- Plastic Packaged Products Label Location Guidelines
- GS1 Logistics Label Design
- Placement Labels Used in General Distribution
- Symbol Placement for Regulated Healthcare Trade Items

WHILST EVERY EFFORT HAS BEEN MADE TO ENSURE THAT THE GUIDELINES TO USE THE GS1 STANDARDS CONTAINED IN THE DOCUMENT ARE CORRECT, GS1 AND ANY OTHER PARTY INVOLVED IN THE CREATION OF THE DOCUMENT HEREBY STATE THAT THE DOCUMENT IS PROVIDED WITHOUT WARRANTY, EITHER EXPRESSED OR IMPLIED, REGARDING ANY MATTER, INCLUDING BUT NOT LIMITED TO THE OF ACCURACY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND HEREBY DISCLAIM ANY AND ALL LIABILITY, DIRECT OR INDIRECT, FOR ANY DAMAGES OR LOSS RELATING TO OR RESULTING FROM THE USE OF THE DOCUMENT. THE DOCUMENT MAY BE MODIFIED, SUBJECT TO DEVELOPMENTS IN TECHNOLOGY, CHANGES TO THE STANDARDS, OR NEW LEGAL REQUIREMENTS. SEVERAL PRODUCTS AND COMPANY NAMES MENTIONED HEREIN MAY BE TRADEMARKS AND/OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE COMPANIES. GS1 IS A REGISTERED TRADEMARK OF GS1 AISBL.


6.1. Introduction

This section includes guidelines for the placement of bar codes on packages and containers. It gives the general principles that apply, mandatory rules, and recommendations for symbol placement on specific packaging and container types.

Consistency of symbol placement is critical to successful scanning. With manual scanning, variation of symbol placement makes it difficult for the scanning operator to predict where the symbol is located, and this reduces efficiency. With automated scanning, the symbol must be positioned so that it will pass through the field of vision of a fixed scanner as it travels past. Respecting the guidance in this section will result in the consistency and predictability required.

The guidelines in this global specification replace previous local recommendations; however, manufacturers should not scrap packaging that has been printed according to previous guidelines. When packaging is redesigned, the global specifications in this document SHALL be observed.

If government regulatory guidelines are inconsistent with those in this manual, the government guidelines should always take precedence.

 **Note:** Bar codes in this guideline that are used as examples are For Position Only and are not intended to denote correct symbol type, size, colour, or quality.

6.2. General Placement Principles

The following general principles for bar code placement SHALL be considered for any package type, whether it is scanned at the Point-of-Sale or elsewhere in the supply chain. Trade items intended to be scanned at a Point-of-Sale must be marked with an EAN-13, UPC-A, EAN-8, UPC-E, GS1 DataBar Omnidirectional, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded or GS1 DataBar Expanded Stacked Bar code. The bar codes that are scanned elsewhere are the EAN-13, UPC-A, ITF-14, and GS1-128 Bar codes

EAN-8 and UPC-E Bar codes are intended for use on very small trade items sold at the Point-of-Sale.

6.2.1. Number of Symbols

Bar codes representing different Global Trade Item Numbers (GTINs) must never be visible on any one item. Although a minimum of one symbol is required, two symbols representing the same GTIN are recommended on trade items for scanning in warehousing or General Distribution Scanning environments (see Section [6.8](#)). Two or more symbols representing the same GTIN are recommended on large, heavy, or bulky items for Point-of-Sale (see Section [6.4.9](#)) and are permissible on random wraps intended for Point-of-Sale (see Section [6.3.3.7](#)). Two symbols, EAN/UPC encoding GTIN and another encoding GTIN plus attributes may be required during migration periods to new data carriers (see Section 4.13).


6.2.2. Scanning Environment

Before considering the package type, determine whether the item will be scanned in a Point-of-Sale or a General Distribution Scanning environment. If the item is scanned at a Point-of-Sale only, the bar code placement guidelines in Sections [6.3](#), [6.4](#), and [6.5](#), and [6.6](#) apply. However, if the item is scanned in both a Point-of-Sale and General Distribution Scanning environment or in a General Distribution Scanning environment only, the requirements (see Section [6.8](#)) take precedence.

6.2.3. Orientation

Bar code orientation is determined primarily by the print process and any curvature of the item. If the printing process and curvature allow, the preferred placement is picket fence orientation, in which the bars of the bar code are perpendicular to the surface on which the package stands in its normal display position. For Human-Readable Interpretation Rules see Section 4.12. Empirical data has demonstrated that it makes no difference to the scanning process one way or the other. Rules for positioning bar codes on curved surfaces are given in Section [6.2.3.2](#).

Figure 6.2.3 – 1




6.2.3.1. Printing Direction

Bar code orientation is often determined by the printing process. Some printing processes give much higher quality results if the bars of the symbol run in the direction of the print, also known as the web direction. The printing company should always be consulted.

6.2.3.2. Trade Items with Curved Surfaces


When a bar code is printed onto a curved surface it is sometimes possible for the extremes of the symbol to disappear around the curve, so that both ends cannot be visible to the scanner at the same time. This is more likely to occur the bigger the symbol and the tighter the curve of the packaging. In these situations, bars must be printed using certain combinations of the X-dimension and diameter of the curved surface (e.g., in ladder orientation on a can, in picket fence orientation on a cylindrical packet of biscuits). This helps ensure that the curve results in an apparent loss of height of the bars rather than the more serious apparent loss of complete bars.

Figure 6.2.3.2 - 1 Bar code placement on curved surfaces



The angle between the tangent to the centre of the curved symbol and the tangent to the extremity of the curved symbol (outer edge of the guard bars for symbols in the EAN/UPC Symbology) must be less than 30 degrees. If this angle is more than 30 degrees, the symbol must be oriented such that the bars are perpendicular to the generating lines of the surface of the item.


Figure 6.2.3.2 – 2 Relationship between symbol and curvature




Figures 6.2.3.2 - 3 and 6.2.3.2 - 4 show the relationship between acceptable X-dimensions (narrow element width) for units of different diameters and the minimum diameters for different X-dimensions for bar codes printed in the picket fence orientation. Please refer to Section 5.5 for the minimum, target, and maximum X-dimension for the symbol, based on the scanning environment.

Figure 6.2.3.2 – 3

Diameter of Container		Maximum Value of X-Dimension			
		EAN-13 or UPC-A Bar code		EAN-8 Bar code	
mm	Inches	mm	Inches	Mm	Inches
30 or below	1.18 or below	*	*	*	*
35	1.38	*	*	<i>(0.274)</i>	<i>(0.0108)</i>
40	1.57	*	*	<i>(0.314)</i>	<i>(0.0124)</i>
45	1.77	*	*	0.353	0.0139
50	1.97	<i>(0.274)</i>	<i>(0.0108)</i>	0.389	0.0153
55	2.16	<i>(0.304)</i>	<i>(0.0120)</i>	0.429	0.0169
60	2.36	0.330	0.0130	0.469	0.0185
65	2.56	0.356	0.0140	0.508	0.0200
70	2.75	0.386	0.0152	0.549	0.0216
75	2.95	0.413	0.0163	0.587	0.0232
80	3.25	0.446	0.0174	0.627	0.0247
85	3.35	0.469	0.0185	0.660	0.0260
90	3.54	0.495	0.0195	0.660	0.0260
95	3.74	0.525	0.0207	0.660	0.0260
100	3.94	0.551	0.0217	0.660	0.0260
105	4.13	0.578	0.0228	N/A	N/A
110	4.33	0.607	0.0239	N/A	N/A
115	4.53	0.634	0.0250	N/A	N/A
120 or above	4.72	0.660	0.0260	N/A	N/A

- 
Note: An asterisk (*) indicates that the package diameter is too small to permit a picket fence orientation bar code, and the symbol must be rotated 90 degrees to a ladder orientation (see Section 5.5) The bar code is printed perpendicular to the generating lines of the surface of the container.

- 
Note: *Italics* indicate X-dimensions that are permissible, but are not recommended on curved surfaces.


- 
Note: EAN-8 Bar codes reserved for very small items (See Section 2.1.).

Figure 6.2.3.2 – 4 Relationship between the X-Dimension and diameter

X-Dimension		Minimum Diameter of Container					
		EAN-13 or UPC-A Bar code		EAN-8 Bar code		UPC-E Bar code	
mm	inches	mm	inches	mm	Inches	Mm	inches
0.264	0.0104	48	1.33	34	1.89	26	1.01
0.300	0.0118	55	1.51	38	2.14	29	1.51
0.350	0.0138	64	1.76	45	2.50	34	1.53
0.400	0.0157	73	2.02	51	2.86	39	1.54
0.450	0.0177	82	2.27	58	3.21	44	1.73
0.500	0.0197	91	2.52	64	3.57	49	1.92
0.550	0.0217	100	2.77	70	3.93	54	2.11
0.600	0.0236	109	3.02	77	4.29	59	2.31
0.650	0.0256	118	3.27	83	4.64	63	2.50
0.660	0.0260	120	3.35	85	4.72	64	2.54

6.2.3.3. Avoiding Scanning Obstacles

Anything that will obscure or damage a bar code will reduce scanning performance and SHALL be avoided. For example:

- Never position the bar code on the item in an area with inadequate space. Do not let the other graphics encroach on the space for the bar code.
- Never place bar codes, including Quiet Zones, on perforations, die-cuts, seams, ridges, edges, tight curves, folds, flaps, overlaps, and rough textures.
- Never put staples through a bar code or its Quiet Zones.
- Never fold a symbol around a corner.
- Never place a symbol under a package flap.
- Bar codes used for production control purposes should be obstructed wherever possible before entering general distribution (see Section 4.13.)

6.3. General Placement Guidelines for Point-of-Sale

This section outlines the guidelines for bar code placement on trade items that will be scanned at the Point-of-Sale. For detailed information on specific package types, see Sections [6.4](#), [6.5](#), and [6.6](#). Section [6.8](#) outlines guidelines for bar code placement on trade items that will be scanned in warehousing or General Distribution Scanning environments.

6.3.1. Number of Symbols

At least one bar code is needed on a trade item intended for the Point-of-Sale. Exceptions include large, heavy, or bulky items (see Section [6.4.9](#)) and random or unregistered wrapping (see Sections [6.3.3.7](#)) where two or more symbols with the same Global Trade Item Number (GTIN) may be required.

Trade items SHALL never have two or more bar codes encoding different Global Trade Item Numbers (GTINs). At the Point-of-Sale, this is particularly relevant with multipacks, such as over-wrapped items, sleeved items, and banded items, where the individual inner units carry a different GTIN from that on the outer wrapper or container. The bar codes on the inner products must be totally obscured so that

they cannot be read by the Point-of-Sale system. (see Section [6.3.3.7](#) for over-wrap special considerations.)

6.3.2. Identifying the Back of the Trade Item

The front of the trade item is the primary trading/advertising area, which typically displays the product name and the company's logo. The back of the trade item is directly opposite the front and is the preferred placement area for the bar code on most trade items.

6.3.3. Symbol Placement

Information in this section is provided to guide symbol placement when developing packaging for new products and should be adopted when changing the graphics of existing products.

6.3.3.1. Preferred Placement

Preferred bar code placement is on the lower right quadrant of the back, respecting the proper Quiet Zone areas around the bar code and the edge rule (see the Edge Rule in Section [6.3.3.3](#) and special considerations in Section [6.3.3.7](#)).

6.3.3.2. Undesirable Alternative

The undesirable alternative placement for a bar code is the lower right quadrant of a side of the container other than the back.

6.3.3.3. Edge Rule

When possible, the bar code must not be closer than 8 mm (0.3 in.) or farther than 100 mm (4 inch) from the nearest edge of the package/container. Previous guidelines suggested a distance of 5 millimetres (0.2 inch) as a minimum. Practical experience has shown this to be inadequate. For example, cashiers often grab the edges of bags and other trade items with their thumbs. Avoid placing the bar code too close to the edge. Such placement reduces efficiency at the Point-of-Sale.

6.3.3.4. Avoid Truncated Symbols

Truncation of a bar code is the reduction of the height of a bar code relative to its length. Truncation is not recommended because it destroys the ability of a symbol to be scanned omnidirectionally at the Point-of-Sale. A truncated symbol can only be scanned when the trade item is oriented in particular directions across the scanning beam. Truncation, therefore, reduces checkout efficiency. The more the height of the symbol is reduced, the more critical becomes the alignment of the symbol across the scanning beam. Truncation SHALL be avoided unless absolutely necessary (e.g., when printing on a tightly curved surface), and then the maximum height possible SHALL be printed. See Section [6.2.3.2](#) for rules on the relationship between the diameter of the item and the X-dimension.

6.3.3.5. Bottom Marking

Bottom marking of the trade item with the bar code continues to be acceptable, except for large, heavy, or bulky trade items. However, back (side) marking is preferred.

6.3.3.6. Exceptions to the General Placement Guidelines

Some trade items require special considerations for bar code placement.

- Bags

When bag contents settle, the bag edges can bulge to the extent that bar codes located on the lower right quadrant may not be flat enough to permit successful scanning. For this reason, bar codes on bags should be placed in the centre of the back about one third up from the bottom and as far from the edge as possible while respecting the edge rule. (See Section [6.4.1](#) for more details on bags.)

- Blister packs or unpackaged items

Trade items that cause scanners to read beyond the flat plane include blister packs and unpackaged items (e.g., deep bowls). For these items, the distance between the scanner window and the bar code on the container or item must be considered. The bar code must not be closer than 8 millimetres (0.3 inch) or farther than 100 millimetres (4 inches) from any edge of the package/container. (See Sections [6.4.2](#) and [6.4.16](#) for more details on blister packs and unpackaged items.)

- Large, heavy, or bulky items

Any package/container weighing more than 13 kilograms (28 pounds) or having two dimensions greater than 450 millimetres (18 inches) (width/height, width/depth, or height/depth) is considered a large, heavy, or bulky item. Large, heavy, or bulky items tend to be hard to handle. 'Large, heavy, or bulky items may require two or more symbols with the same Global Trade Item Number (GTIN) ideally one on top and one on the bottom of the opposite quadrant' (See Section [6.4.9](#) for more details on large, heavy, or bulky items.)

- Thin items or containers

Thin items or containers are packages/containers with a dimension less than 25 millimetres (1 inch) (height, width, or depth). Examples of thin items or containers are packages of pizza, powdered drink mixes, and writing pads. Any placement of the symbol on the edge hinders effective scanning because the symbol is obscured from the cashier and is likely to be truncated. (Refer to Section [6.4.12](#) for more details on thin items or containers.)

6.3.3.7. Special Packaging Considerations for Bar Code Placement

Some packaging methods require special considerations for bar code placement.


Over-wrap

Trade items sold in multiples are mechanically gathered and covered with clear over-wrap material that will carry print. Typical over-wrapped items are small cereal boxes and chocolate bars. Package over-wrap can create two distinct problems:

- Obscuring the bar codes on individual units inside the multipack is necessary so they are not confused with the outer multipack bar code, which must be different.
- Over-wrapping with such materials as cellophane causes diffraction or reflection of the light beam of the scanner and can reduce contrast, which causes scanning inefficiencies.

To determine proper bar code placement for over-wrapped packaging, follow the guidelines specific to the applicable package type/shape. (See Section [6.4](#) for details on symbol placement for specific package types.)

Figure 6.3.3.7 - 1 Bar code placement on over-wrapped item



Random (Unregistered) Wrap


Some wrappers, like those used on sandpaper or margarine, have a repeating design and are neither cut nor placed on the product such that a particular part of the design always appears in the same location. This is referred to as random or unregistered wrapping. As the wrapper is not registered, it is unlikely that the symbol will appear on one face of the package when the wrapper is placed on the product.

The presence of more than one bar code on a package can have a detrimental effect on scanning productivity and, more importantly, can lead to a double read. For this reason, the use of registered packaging is preferred. If random wrap must be used, the minimum requirement is to print the symbol with sufficient frequency so that a full symbol will appear on one package face.

Double reads are more likely when the gaps between the symbols are larger. Repeating symbols should never be more than 150 millimetres (6 inches) apart.

Consideration should also be given to elongating the bars of the symbol to ensure a full symbol on one face, instead of repeating the symbol.

Figure 6.3.3.7 - 2 Bar code placement on random-wrapped item




Shrink film/vacuum-formed packages

The bar code on an item packaged in shrink film or that is vacuum-formed SHALL be located on a flat surface and in an area free of creases, wrinkles, or other types of distortions. Refer to Figure 6.3.3.7 – 3, which shows bar code placement on hot dogs. Since the curvature of the hot dogs was greater than the diameter shown within the Section 6.2.3.2 figures, a ladder orientation symbol was used.

To determine proper bar code placement for shrink film/vacuum-formed packaging, follow the guidelines specific to the applicable package type/shape. (Refer to Section 6.4 for details on symbol placement for specific package types/shapes.)

Figure 6.3.3.7 – 3 Bar code placement on shrink film/vacuum-formed item



Spot labels

Bar codes printed on spot labels that are applied to the trade item are acceptable alternatives that incorporate symbols into existing packaging graphics or for use on items without packages, such as some pots, pans, tableware, and glassware. The most suitable type of spot label is one that cannot be removed from the item without destroying the symbol. Labels that are applied directly to the product should use an adhesive that is strong enough to adhere to the label for an extended shelf life, but which also allows the label to be removed without the use of solvents or abrasives.

To determine proper bar code placement on items bearing spot bar code labels, follow the guidelines specific to the applicable package type/shape. (Refer to Section 6.4 for details on symbol placement for specific package types.)

Figure 6.3.3.7 - 4 Bar code placement with a spot label





Figure 6.3.3.7 - 5 Tableware items using bar code spot labels



6.3.3.8. Operational Considerations of Bar Code Placement

Speed, efficiency, and effectiveness in scanning operations are the ultimate goals of proper bar code placement. To ensure that scanning performance will not be compromised, consider the following matters before deciding on final bar code placement:

- Consistent symbol location
 - Compare your package/container to packaging for like products to ensure equivalent symbol placement. The ease with which bar codes are located by a cashier from product to product essentially relies on consistent symbol placement.
- Scan simulation (hand motion effectiveness)
 - Pass the bar code across the scanner with your hand to test the initial bar code placement. This test is intended to confirm that the bar code placement does not necessitate unnatural hand motions while you are scanning the symbol.

6.3.3.9. Security Tag Placement

When a visible security tag is used, the preferred placement is within a 75 millimetres (3 inches) diameter of the bar code placement. Consistent security tag placement makes it easier for the operator to predict security tag location and, thus, improves scanning efficiency.

6.4. Placement Guidelines for Specific Package Types

The following bar code placement guidelines apply to specific package types. Section [6.5](#) contains diagrams illustrating symbol placement for clothing and fashion accessories. Figure 6.4 - 1, Package Type Reference, describes the main packaging categories and products. This figure can be used to determine correct bar code placement by product or packaging. For example, according to the figure below, a package of flower seeds in a 50 millimetres (2 inches) by 75 millimetres (3 inches) envelope is classified as a thin item or container. The example given of this type of package is powdered soft drink mix. According to the first column of the Package Type Reference, the correct bar code placement for this package type is determined by looking at Section [6.4.12](#).

Figure 6.4 - 1 Package type reference


Section	Package Type	Package Characteristics	Product Examples
6.4.1	Bags	Sealed cylindrical or rounded-corner wrapped units	Potato chips, flour, sugar, bird seed
6.4.2	Blister packs	Flat card backing a formed clear plastic bubble placed over product	Toys, hardware parts
6.4.3	Bottles and jars	Small or large-mouth vessels sealed with removable lids	Barbecue sauce, fruit jelly
6.4.4	Boxes	Folded, sealed, heavy paper or corrugated cardboard cartons	Crackers, cereal, detergent
6.4.5	Cans and cylinders	Cylindrical-shaped units sealed at each end	Soups, drinks, cheese, biscuits
6.4.6	Carded items	Items mounted or sealed on flat cards	Hammers, parcels of candy, kitchen utensils
6.4.7	Egg cartons	Irregular hexahedrons of plastic or moulded pulp with hinged lids	Eggs
6.4.8	Jugs	Glass or plastic vessel with built-in handle(s) and removable lid(s)	Household cleaners, cooking oil
6.4.9	Large, heavy, bulky items	Items having physical dimension of 450 mm (18 in.) or more in any two dimensions and/or weight in excess of 13 kg (28 lbs.)	Pet food, unassembled furniture, sledge hammers
6.4.10	Multipacks	Multiple items mechanically bound to create one package	Soft drink cans
6.4.11	Publishing items	Printed paper media that is bound, stapled, or folded	Books, magazines, newspapers, tabloids
6.4.12	Thin items or containers	Items or containers with one dimension less than 25 mm (1 in.)	Boxes of pizza, CD jewel boxes, powdered soft drink mix packages, writing pads
6.4.13	Trays	Flat, formed receptacles holding product covered with over-wrap	Prepared meats, pastries, snacks, pies, pie crusts
6.4.14	Tubes	Firmly packed cylinders sealed at both ends, or sealed at one end with a cap or valve on the other end	Toothpaste, sausage, caulk
6.4.15	Tubs	Deep vessels with removable lids	Margarine, butter, ice cream, whipped cream
6.4.16	Unpackaged	Trade items that have no packaging, are often of an unusual shape, and are hard to label and scan	Frying pans, mixing bowls, cooking pots, giftware
6.4.17	Sets	Trade items that can be sold individually or as part of a boxed set.	Table and giftware
6.4.18	Sporting goods	Unpackaged items of specific size and shape.	Racquets, skis, skateboards

6.4.1. Bags

Although this category is referred to as “bags,” these packages/containers are often called sacks or pouches. This category includes paper or plastic containers that are:

- Fold-sealed on both ends (e.g., flour, sugar)
 - Fold-sealed on one end and pinched sealed at the other end (e.g., potato chips)
 - Pinch-sealed at both ends (e.g., cough drops)
 - Fold-sealed on one end and gathered at the other end (e.g., bread)
- ✔ **Note:** Some bags are sealed at both ends and carded for display, such as bags of sweets. These types of items are not considered bags but fall into the carded items category. (See Section [6.4.6](#) for details on carded items.)
- Package characteristics: Sealed cylindrical or rounded-corner wrapped units
 - Unique considerations: Bags have a tendency to have contents that shift and bulge. Consequently, bar code placement must be on an area of the bag that is most likely to remain flat.
 - Bar code placement: Identify the front of the package/container. (See Section [6.3.2](#) for instructions on how to identify the package front.)
 - Preferred placement: On the lower right quadrant of the back and away from the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: On the lower right quadrant of the front, and away from the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.1 - 1 Symbol placement on bags




6.4.2. Blister Packs

Blister packs are pre-formed clear plastic bubbles, or blisters, containing a product and backed or topped with card stock.

- Package characteristics: flat card, backing a formed clear plastic bubble placed over the product

- Unique considerations: to ensure quality scanning, the bar code must be clear of the blister edges. Avoid placing the symbol under the blister pack or placing the symbol over any perforations on the back of the package.
- Bar code placement: identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: on the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: on the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.2 - 1 Symbol placement on blister packs



6.4.3. Bottles and Jars


Bottles and jars normally carry spot labels applied to confined areas of the package, not covering the entire surface or wrapping around the entire perimeter.

- Package characteristics: Small or large-mouth containers sealed with removable lids
- Unique considerations: Application of the bar code to the neck of a bottle is not allowed. Symbol placement on the neck of the bottle necessitates additional handling at the Point-of-Sale, and space limitations on this area of the bottle usually result in symbol truncation.

When a bar code is printed onto a curved surface it is sometimes possible for the extremes of the symbol to disappear around the curve. See Section [6.2.3.2](#) for rules on the relationship between the diameter of the item and the X-dimension.

- Bar code placement: Identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: On the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: On the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.3 - 1 Symbol placement on bottles and jars




6.4.4. Boxes

This package type includes cuboid or cylindrical card or plastic cartons, as well as rectangular sleeves (used for products such as light bulbs). These packages might contain anything from crackers or cereal to detergent.

- Package characteristics: Folded, sealed, heavy paper or corrugated cardboard cartons
- Unique considerations: There are no unique considerations that apply to this package type.
- Bar code placement: Identify the front of the package/container. (Refer to Section 6.3.2, Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: On the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: On the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section 6.3.3.3.

Figure 6.4.4 - 1 Symbol placement on boxes




6.4.5. Cans and Cylinders

This category includes cylindrical shaped containers (usually made of plastic or metal) that are sealed at each end. Some containers have removable lids or openings. Common examples are canned fruit and vegetables, paints, and adhesives.

- Package characteristics: Cylindrical-shaped units sealed at each end
- Unique considerations: Obstacles, such as beading, seams, and/or ridges on the package/container SHALL be avoided, because they will reduce scanning performance. When a bar code is printed onto a curved surface it is sometimes possible for the extremes of the symbol to disappear around the curve. See Section [6.2.3.2](#) for rules on the relationship between the diameter of the item and the X-dimension.
- Bar code placement: Identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: On the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: On the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.5 - 1 Symbol placement on cans and cylinders




6.4.6. Carded Items

Small, loose, or non-packaged items that are difficult to label are placed on cards that are marked with a bar code. Examples include hammers, toys, and kitchen utensils.

- Package characteristics: Items mounted or sealed on flat cards
- Unique considerations: When placing bar codes on carded items, it is important to take into consideration the proximity of the bar code to the product. Be sure to allow adequate space for the symbol, avoiding any obstructions that might be caused by placing the symbol too close to the product. In addition, do not place the symbol over any perforations or other obstructions on the package.
- Bar code placement: Identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: On the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: On the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.6 - 1 Symbol placement on carded items




6.4.7. Egg Cartons

Moulded pulp, foam, or plastic egg cartons come in sizes according to the number of eggs contained.

- Package characteristics: Irregular shaped hexahedrons of plastic or moulded pulp with a hinged lid
- Unique considerations: The recommended symbol placement is on the side of the lid portion of the egg carton that opens and closes to cover the eggs. The uneven surface of the moulded bottom of an egg carton prevents bar code placement in this area.
- Bar code placement: To determine bar code placement on an egg carton, first identify the top of the carton by locating the primary trading/advertising area, which is marked with the product name and the company's logo. The bottom of the egg carton is the moulded area directly opposite the top in which the eggs sit. The sides are divided horizontally by a hinged lid. The front of the carton is the long side containing the opening/closing mechanism. The back of the carton is directly opposite the front, on the long side with the hinge.
 - Preferred placement: Near the edge, on the right half of the back, above the hinge on the lid, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: On the lower right quadrant of the top, on the lid adjacent to the opening/closing mechanism, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.7 - 1 Symbol Placement on Egg Cartons



6.4.8. Jugs


Jugs are glass or plastic containers with a built-in handle(s) that aids in pouring of contents. Jugs normally carry spot labels applied to defined areas of the package, not covering the entire surface of the trade item or wrapping around the entire perimeter of the item.

- Package characteristics: Glass or plastic vessels with built-in handles and removable lids
- Unique considerations: Application of the symbol to the neck of the jug is not allowed. Placement of the symbol on the neck of the jug necessitates additional handling at the Point-of-Sale, and space limitations on the neck usually result in symbol truncation.

When a bar code is printed onto a curved surface it is sometimes possible for the extremes of the symbol to disappear around the curve. See Section [6.2.3.2](#) for the rules on the relationship between the diameter of the item and the X-dimension.

- Bar code placement: Identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: On the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: On the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.8 – 1 Symbol placement on jugs




6.4.9. Large, Heavy, or Bulky Items

- Package characteristics: Items considered large, heavy, or bulky have a physical dimension of 450 millimetres (18 inches) or more in any two dimensions (width/height, width/depth, or height/depth), and/or weigh in excess of 13 kilograms (28 pounds).
- Unique considerations:
 - Number of symbols: Large, heavy, or bulky items may require two or more symbols with the same Global Trade Item Number (GTIN) ideally one on top and one on the bottom of the opposite quadrant'.
 - Special labels: A special double label with a tear-out bar code may be applied to large, heavy, or bulky items that are too heavy or awkward to pick up and pass over a fixed

scanner. This label has one section that is permanently adhered to the item's box (or to a hang-tag or card if the item is not boxed). This section has a Non-HRI text (number and item description) printed above a full-size bar code. Beneath a perforation, a second section contains exactly the same Non-HRI text and an identical full-size bar code. The two sections are virtually identical except that the section below the perforation has no adhesive on its back.

Figure 6.4.9 – 1

SAMPLE ILLUSTRATION OF THE DOUBLE LABEL WITH TEAR-OUT UPC



- When the item is brought to the Point-of-Sale, the lower half of the label below the perforation is removed. The cashier then either scans the label or, if the symbol cannot be scanned, the cashier key-enters the human readable interpretation beneath the symbol. The top label remains attached to the item or its box.

In instances where the large, heavy, or bulky item is displayed and sold in its shipping container, a third section of label is recommended. Beneath the tear-out label, a second perforation and a 12 millimetres (0.50 inch) section with permanent adhesive SHALL be added. This provides a more secure vehicle for the tear-out section and makes it less likely to tear off in transit.

- Human Readable Interpretation: Human readable interpretation on large, heavy, or bulky items should be a minimum of 16 millimetres (5/8 inch) high. This facilitates easier capture of the number by the cashier without having to pick up the product and move it across the scanner.
- Bar code placement: Identify the front of the package/container (See Section 6.3.2, Identifying the Back of the Trade Item, for instructions on how to identify the package front).
- Preferred placement:
 - Bags: Two bar codes are required, one on the front of the bag, at the top of the upper right quadrant, near the edge, and the other on the back of the bag, centred in the lower right quadrant, near the edge (to accommodate settling of contents).

Figure 6.4.9 - 2 Symbol placement on large, heavy, or bulky bags





Figure 6.4.9 - 3 Symbol placement on large, heavy, or bulky jars, cans, jugs, or tubs




- ❑ Undesirable alternative: On the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
- ❑ Edge rule: See Section [6.3.3.3](#).

6.4.10. Multipacks

Multipacks are single items that are packaged together as one unit or trade item. Multipacks provide convenience to the consumer and/or may represent a price reduction compared to purchasing items individually. Typical multipacks contain bottles, cans, jars, and tubs.

- Package characteristics: multiple single items bound together to create one package
- Unique considerations: as a general rule, a bar code MUST be placed on every consumer package traded through the supply chain. Consequently, items sold in multipacks as well as those sold individually must carry a unique bar code for each consumer package variation or aggregation. To avoid confusion at the Point-of-Sale, the multipack bar code SHALL be the only visible symbol when both the multipack and individual items are symbol-marked. The binder of the multipack acts as a screen to obscure the symbols on the individual items.
 - Special note for can multipacks: Avoid placing the symbol on the top or bottom of the container, since cans have a tendency to cause impressions in the corrugated cardboard and distort the symbol. These can impressions in the symbol may reduce scannability.
- Bar code placement: identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: on the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: on the lower right quadrant of another side, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: see Section [6.3.3.3](#).

Figure 6.4.10 - 1 Symbol placement on multipacks




6.4.11. Publishing Items

Publishing items represent printed materials sold individually for consumer use including books, magazines, newspapers, and tabloids. Bar code placement on published items varies depending on type. In addition, the main bar codes on books and paperbacks must appear on the outside cover of the book (to facilitate payment).


- Package characteristics: printed paper media that is bound, stapled, or folded
- Unique considerations: in addition to the regular bar code, some publishing items have Add-On Symbols that carry supplementary information such as an Issue Code. Bar code placement on published items varies depending on the media type. If an Add-On Symbol is used, it must be located to the right of the regular bar code and parallel to it.
- Bar code placement: identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement:
 - Books: on the lower right quadrant of the back, near the spine, respecting the proper Quiet Zone areas around the bar code

Figure 6.4.11 – 1




- Magazines: On the lower left quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code

Figure 6.4.11 – 2




- Newspapers: when displayed for sale as shown on the left in Figure 6.4.11 - 3, place the symbol on the lower left quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code. If an Add-On Symbol is used, it must be located to the right of the regular bar code and parallel to it.

Figure 6.4.11 – 3



When displayed for sale as shown in Figure 6.4.11 - 4, place the symbol on the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code. If an Add-On Symbol is used, it must be located to the right of the regular bar code and parallel to it.

Figure 6.4.11 – 4



- Undesirable alternative: The undesirable alternative is not feasible for this package type.
- Edge rule: See Section [6.3.3.3](#).

6.4.12. Thin Items or Containers

This package type is so named because items and containers in this category have one physical dimension less than 25 millimetres (1 inch). Items such as these, particularly those without a significant bottom surface, should be marked on the lower right quadrant of the back side. Boxes of pizza, compact disk boxes, packages of powdered drink mix, and writing pads are examples.

- Package characteristics: items or containers with one dimension less than 25 millimetres (1 inch)
- Unique considerations: there are no unique considerations that apply to this package type.
- Bar code placement: identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: on the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: on the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.12 - 1 Symbol placement on thin items or containers





Figure 6.4.12 - 2 Unpackaged item without room for bottom marking




6.4.13. Trays

This package type includes thin square, rectangular, or circular trays holding items that are covered with over-wrap of clear shrink-film or that are vacuum-sealed. Examples include meats, pastries, snacks, and pies or piecrusts.

- Package characteristics: Flat, formed receptacles holding product covered with over-wrap
- Unique considerations: When placing bar codes on trays, it is important to ensure that the bar code is placed on a flat surface. In addition, do not place the symbol over any perforations or other obstructions on the package.
- Bar code placement: Identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: On the lower right corner of the top, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.13 - 1 Symbol placement on trays




6.4.14. Tubes

Tubes are cylindrical shaped items or containers that are either sealed at both ends, such as sausage or refrigerated dough, or that are sealed at one end and have a cap or valve on the other end, such as toothpaste or caulk.

- Package characteristics: Firmly packed cylinders sealed at both ends, or sealed at one end with a cap or valve on the other end
- Unique considerations: When a bar code is printed onto a curved surface it is sometimes possible for the extremes of the symbol to disappear around the curve. See Section [6.2.3.2](#) for the rules on the relationship between the diameter of the item and the X-dimension.

- Bar code placement: Identify the front of the package/container. (Refer to Section [6.3.2](#), Identifying the Back of the Trade Item, for instructions on how to identify the package front.)
 - Preferred placement: On the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: On the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.14 - 1 Symbol placement on tubes




6.4.15. Tubs

Tubs are circular containers (usually made of paper, plastic, or metal) that have removable lids. In most cases, they have spot labels that do not cover the entire surface of the container. Examples include margarine, butter, ice cream, and whipped topping.

- Package characteristics: Deep vessels with removable lids
- Unique considerations: When a bar code is printed onto a curved surface it is sometimes possible for the extremes of the symbol to disappear around the curve. See Section [6.2.3.2](#) for the rules on the relationship between the diameter of the item and the X-dimension.
- Bar code placement: Identify the front of the package/container. (See Section [6.3.2](#), [Identifying the Back of the Trade Item](#), for instructions on how to identify the package front.)
 - Preferred placement: On the lower right quadrant of the back, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Undesirable alternative: On the lower right quadrant of the front, near the edge, respecting the proper Quiet Zone areas around the bar code
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.15 - 1 Symbol placement on tubs



6.4.16. Unpackaged Items

These are square, rectangular, circular, concave, or convex shaped items, including bowls, pots, pans, skillets, cups, vases, and other products (with or without contents), that lack an upright surface suitable for symbol placement.

- Package characteristics: These are items that are unpackaged and sold with spot labels, hangtags or carded sleeves.
- Unique considerations: When selecting symbol placement, consider the product's concave shape on the inside or irregular curvature on the outside while respecting the scanning distances defined in the edge rule below.
- The general marking guideline for a table and giftware items is to use a hangtag. This avoids any damage to the item that could be caused by the spot label adhesive. If this is not practical, the spot label SHALL be applied to the bottom of the item and below the backstamp (where present).
- Bar code placement: Bar code placement on unpackaged items depends on the shape and type of the item. The following examples illustrate symbol placements appropriate to specific item types.
 - Preferred placement: The figures that follow indicate acceptable placement locations for other shaped items.
 - Undesirable alternative: The undesirable alternative is not applicable.
 - Edge rule: See Section [6.3.3.3](#).

Figure 6.4.16 - 1




Figure 6.4.16 - 2




Figure 6.4.16 - 3




Figure 6.4.16 - 4





Figure 6.4.16 - 5 Giftware using hangtag. Option 5



Figure 6.4.16 - 6 Tableware using spot label below backstamp. Option 6




6.4.17. Sets (Grouping of Individually Bar Coded Items)

For bar coding purposes, sets are defined as two or more items that are packaged and sold together as one unit, regardless of whether those items can be sold separately as well. If the items are packaged together for shipping purposes but are not intended to be sold as a single unit, they do not qualify as a set. Examples of sets include a pair of candlesticks, a set of four soup bowls, and a five-piece dinner place setting.


If a set is not intended to be sold as individual components, only the package for the set needs to include a bar code.

Figure 6.4.17 - 1 Example of a set where individual components are not sold separately




If the set is made up of components that can be ordered as separate trade items, then the components of the set must be marked. If the set can be sold as individual components or as the set, then both the package and the components need to be marked with unique symbols. The bar codes on the inner products must be totally obscured so that they cannot be read by the Point-of-Sale system when sold as a set. (See Section 6.3.3.7 for over-wrap special considerations.)

Figure 6.4.17 - 2 Example of a multi-piece set sold as a set or as individual components



If an item is made up of multiple components that cannot be sold separately, such as a teapot with lid, the main piece only SHALL be marked with one symbol. Such items are not considered sets.

Figure 6.4.17 - 3 Items with multiple pieces that are not sold separately (these are not considered sets)



6.4.18. Sporting Goods


Sporting goods is a category composed of many irregular sized and shaped goods. An understanding of each product type, the logistics involved in the supply chain, and the sales floor presentation are key to improving the overall Point-of-Sale efficiency. Of particular importance is consistent bar code placement for sporting goods as presented at the retail Point-of-Sale. This enables the Point-of-Sale operator to accurately predict the symbol location and thereby improve efficiency.

The following examples, while not exhaustive, provide the general principles that are applied to similar product types.

6.4.18.1. Archery Bows, Arrows

- Preferred placement:
 - If packaged in boxes, see Section [6.4.4.](#)
 - If packaged using a hangtag, see Section [6.5.2.](#)
- Edge rule: See Section [6.3.3.3.](#)


Figure 6.4.18.1 - 1 Example bar code location on an archery bow



6.4.18.2. Balls, Team Sports

- Preferred placement:
 - If packaged individually, placement on the shrink wrap.
 - If packaged in boxes or boxed sets, see Section 6.4.4 and Section 6.4.17. If a master SKU is not utilized for a boxed set of balls or a pack set of ball and pump, each product type within the pack set SHALL have a screened bar code.
 - If not packaged, screen the bar code on the opposite side of the logo on the ball.
- Edge rule: See Section 6.3.3.3


Figure 6.4.18.2 - 1 Example bar code locations on a box of balls & separate balls



6.4.18.3. Bats, Team Sports

- Preferred placement: On the barrel handle of the bat, respecting the proper Quiet Zone areas around the bar code.
- Edge rule: See Section 6.3.3.3


Figure 6.4.18.3 - 1 Example bar code location on a baseball bat



6.4.18.4. Bicycles

- Preferred placement: On the right hand fork of the bike, respecting the proper Quiet Zone areas around the bar code.
- Undesirable alternative: On a hangtag around the right hand brake cable, respecting the proper Quiet Zone areas around the bar code.
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.4 - 1 Example bar code location on a bicycle



6.4.18.5. Climbing Gear

- Preferred placement:
 - If packaged in boxes, see Section [6.4.4](#)
 - If packaged using a hangtag, see Section [6.5.2](#)
 - If packaged as carded items, see Section [6.4.6](#)
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.5 - 1 Example bar code locations on climbing gear



6.4.18.6. Fishing Rods:

- **Preferred placement:** On the grip of the fishing rod near the sealed end, respecting the proper Quiet Zone areas around the bar code. When a bar code is printed onto a curved surface, it is sometimes possible for the extremes of the symbol to disappear around the curve. See Section [6.2.3.2](#) for the rules on the relationship between the diameter of the item and the X-dimension.
- **Undesirable alternative:** On a cardboard wrap or a hangtag on the shaft of the fishing rod, respecting the proper Quiet Zone areas around the bar code.
- **Edge rule:** See Section [6.3.3.3](#)


Figure 6.4.18.6 - 1 Example bar code location on a fishing rod



6.4.18.7. Fitness Accessories

- Preferred placement:
 - If packaged in boxes, see Section [6.4.4](#)
 - If packaged using a hangtag, see Section [6.5.2](#)
 - If packaged as carded items, see Section [6.4.6](#)
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.7 - 1 Example bar code location on a box of fitness accessories



6.4.18.8. Gloves, Mitts (Sports)

- Preferred placement:
 - If packaged in boxes, see Section [6.4.4](#)
 - If packaged using a hangtag, see Section [6.5.2](#)
 - If packaged in bags, see Section [6.4.1](#)
 - If not packaged, see Section [6.4.9](#)
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.8 - 1 Example bar code locations on gloves



6.4.18.9. Golf Club:

- Preferred placement: On the shaft of the club located near the club head, respecting the proper Quiet Zone areas around the bar code. When a bar code is printed onto a curved surface, it is sometimes possible for the extremes of the symbol to disappear around the curve. See Section [6.2.3.2](#) for the rules on the relationship between the diameter of the item and the X-dimension. Symbols SHALL not be located on the head of the golf club as symbols located on this flat area (normally preferable to locating bar codes on a curved surface) are easily damaged due to customer trials.
- Undesirable alternative: On the grip of the club near the sealed end, respecting the proper Quiet Zone areas around the bar code.
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.9 - 1 Example bar code location on a golf club



6.4.18.10. Guns

- Preferred placement:
 - If packaged using a hangtag, see Section [6.5.2](#)
 - If packaged as a blister pack, see Section [6.4.2](#)
 - If not packaged, placement near serial number
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.10 - 1 Example bar code locations on a rifle and paint ball gun



6.4.18.11. Helmets, Masks (Sports)

- Preferred placement:
 - If packaged in boxes, see Section [6.4.4](#)
 - If packaged using a hangtag, see Section [6.5.2](#)
 - If not packaged, see Section [6.4.9](#)
- Edge rule: See Section [6.3.3.3](#)

Figure 6.4.18.11 - 1 Example bar code location on a helmet




6.4.18.12. Ice-Hockey and Field Hockey:

- Preferred placement: On the flat blade of the stick, respecting the proper Quiet Zone areas around the bar code.

- Undesirable alternative: At the very top of the shaft of the stick, respecting the proper Quiet Zone areas around the bar code. When a bar code is printed onto a curved surface, it is sometimes possible for the extremes of the symbol to disappear around the curve. See Section [6.2.3.2](#) for the rules on the relationship between the diameter of the item and the X-dimension.
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.12 - 1 Example bar code location on an ice-hockey stick



6.4.18.13. Multi-Sports-Product Pack Sets

- Preferred placement:
 - For placement on bags, see Section [6.4.1](#)
 - For placement on hangtags, see Section [6.5.2](#)
- Edge rule: See Section [6.3.3.3](#)

Figure 6.4.18.13 - 1 Example bar code location on a product pack




6.4.18.14. Pressure Gauges and Sports Pumps

- Preferred placement:

- If packaged as carded items, see Section [6.4.6](#)
- If packaged in bags, see Section [6.4.1](#)
- If not packaged, placement on the wrap band securing the tip/needles, etc.
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.14 - 1 Example bar code location on a carded item



6.4.18.15. Protective Gear, Guards, Vests

- Preferred placement:
 - If packaged as a carded item, see Section [6.4.6](#)
 - If not packaged, see Section [6.4.9](#)
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.15 - 1 Example bar code location on guards



6.4.18.16. Racquets:

- Preferred placement: On the grip of the racquet near the sealed end, respecting the proper Quiet Zone areas around the bar code. When a bar code is printed onto a curved surface it is sometimes possible for the extremes of the symbol to disappear around the curve. See Section [6.2.3.2](#) for the rules on the relationship between the diameter of the item and the X-dimension.
- Undesirable alternative: On the cardboard wrap placed over the head of the racquet near the edge of the racquet head, respecting the proper Quiet Zone areas around the bar code.
- Edge rule: See Section [6.3.3.3](#)

Figure 6.4.18.16 - 1 Example bar code location on a racquet




6.4.18.17. Skateboards:

Skateboards are often displayed in their packages. See Section [6.2.3](#), Orientation, to determine the back of the package. For unpackaged items:

- Preferred placement: On the bottom side of the skateboard on the top above the wheels, respecting the proper Quiet Zone areas around the bar code.
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.17 - 1 Example bar code location on a skateboard



6.4.18.18. Skates

- Preferred placement:
 - If packaged in boxes, see Section [6.4.4](#)
 - If packaged using hangtags, see Section [6.5.2](#).
- Edge rule: See Section [6.3.3.3](#)

Figure 6.4.18.18 - 1 Example bar code location on a box of skates




6.4.18.19. Skis

Skis are displayed without their packaging. The front of the ski is the side where the ski boots are placed and the back of the ski is the opposite side.

- Preferred placement: One bar code is placed on the back of the ski near the top of the ski, respecting the proper Quiet Zone areas around the bar code. Only one bar code is required per pair.
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.19 - 1 Example bar code location on a ski



6.4.18.20. Water Bottles (Sports)

- Preferred placement:
 - If packaged in boxes, see Section [6.4.4](#)
 - If packaged using hangtags, see Section [6.5.2](#)
 - If not packaged, placement on the side of the bottle.
- Edge rule: See Section [6.3.3.3](#)


Figure 6.4.18.20 - 1 example bar code location on a water bottle



6.4.18.21. Water Sports Crafts

- Preferred placement:
 - If packaged in boxes, see Section [6.4.4](#)
 - If packaged using hangtags, see Section [6.5.2](#)
 - If not packaged, see Section [6.4.9](#), Large, Heavy, or Bulky Items
- Edge rule: See Section [6.3.3.3](#)

Figure 6.4.18.21 - 1 Example bar code location on a canoe



6.4.19. Textured Surfaces

Some merchandise may not allow for application of bar code labels due to rough or textured surfaces. These surfaces can distort the label and thus the bar code. Alternative labelling options such as hang tags or loop tags may be necessary.


6.5. Symbol Placement for Clothing and Fashion Accessories

The following examples show recommended placement of symbols on clothing and fashion accessories. To view illustrative images, please visit:

http://www.gs1.org/docs/barcodes/GenSpec_Fashion_symbol_location.pdf

Clothing is displayed in a variety of ways, such as loose (e.g., hanging garments), in boxes, or in bags. In many cases, a relatively small label must carry all the pertinent information relevant to the product. A retail label normally carries not only product-specific information important to the retailer (e.g., die lot, batch) and consumer related information (e.g., style, size, colour), but also the bar code itself.

Figure 6.5 - 1 Example bar code location on boxes



The correct general layout for a retail label is indicated below. Because there are many clothing types on the retail market, detailed label formats are presented at:

- **Layout of label:** The label is divided into three portions:
 - **Manufacturer/retailer information:** The upper portion of the format is the preferred location for Non-HRI product information. This information is important to manufacturers and retailers, but usually not to the consumer.
 - **Bar code:** The centre portion of the format is the best location for the bar code. Symbols in this location are the least likely to present obstructions to scanners because a natural boundary exists between the manufacturer/retailer information (upper portion) and the consumer information (lower portion).
 - **Consumer information:** The lower portion of the format is the preferred location for information that is provided for the consumer, such as price, size, and fabric content.

Label placement on clothing and fashion accessories: To determine the placement of the printed label on clothing and fashion accessories, please visit:

http://www.gs1.org/docs/barcodes/GenSpec_Fashion_symbol_location.pdf.

6.5.1. Information Zones Concept

There are seven information zones that carry product information needed for the vendor, retailer, and consumer. Some information is optional based upon the type of label.

6.5.1.1. General Label Information Zones

Zones	Information Type	Description	Status: Required/Optional
Zone 1	Merchandise identification	This is the primary human readable merchandise identifier, usually the style number, although it may be pattern, model, or garment type. The merchandise identifier is located in the upper left-hand portion of Zone 1.	Always required (see Note)
Zone 2	Vendor information	This includes optional vendor production information, such as vendor Stock Keeping Unit (SKU), cut number, dye lot, colour, and pattern. (Vendor information helps ensure that the correct bar code is attached to the product.)	Optional
Zone 3	Data structure (GTIN-13, GTIN-12, GTIN-8)	Bar code	Always required
Zone 4	Consumer information	This includes optional product information for the consumer, such as fibre content, fire retardancy, and country of origin.	Optional
Zone 5	Size/dimension	Size/dimension is a key requirement for the consumer. Size information can be emphasised in large bold print and is located in the right-hand portion of Zone 5. Vendors may optionally include a style name as a selection aid for the consumer.	Usually required unless defined by the product (e.g., towels)
Zone 6	Retail price	Allow space to print the price with minimum dimension characters of 25 mm (1 in.) x 32 mm (1.25 in.). For plastic packaged, boxed, and banded products, the required space for price can be provided by several methods: For bar code marking on an adhesive label, the space for price can be included as part of the label. For bar code marking designed into the packaging, the space for price can be included on the package artwork. Providing package space adjacent to Zone 5 that is reserved for retail item pricing creates an implied space for price. Implied space replaces the requirement for actual space on labels or package artwork. If implied space for price is used, no information of importance SHALL be printed in the area that might be covered by adhesive item price labels.	Usually required unless defined by the ticket format (e.g., sewn-in tickets)
Zone 7	Manufacturer's suggested retail price	This is for use only if merchandise is pre-priced or the suggested retail price is printed on the tag. If provided, the area must be perforated for optional removal.	Optional



Note: Size and colour are optional in Zone 1 if vendor usage requires this information to define the product.

6.5.1.2. General Label Format

See the Figures 6.5.1.2 - 1 and 6.5.1.2 - 2 for examples of how the zones appear in a typical vertical and horizontal label format.

Figure 6.5.1.2 - 1 Vertical label format





Figure 6.5.1.2 - 2 Horizontal label format



KEY

Required	Optional
----------	----------

6.5.2. Hangtag (Hanging Label) Format

Although hangtags (hanging labels) are primarily associated with hanging ready-to-wear apparel, a wide variety of products are identified with hangtags. Flat-folded apparel, jewellery, belts, handbags, lamps, and furniture are all identified by some form of hangtag. Therefore, the voluntary hangtag format guidelines outlined in this section provide for flexibility in hangtag design while maintaining the overall concept of the information zones.

Hangtags serve a dual purpose. First, they provide brand identification to the consumer. Second, because the back of a hangtag is frequently used for product information and product identification codes, it SHALL carry the bar code that identifies the product.

The typical hangtag layout features the vendor's logo on the front and product identification codes and the bar code on the back. Vendors may optionally include an additional logo on the back of the hangtags. However, a logo SHALL not appear at the bottom because a retail price label may obscure it or it could be torn off if a manufacturer's suggested retail price is removed. Background printing of logos SHALL be avoided, because this may obscure required information or important consumer information. Logos must never obscure the bar code.

6.5.2.1. Hangtag Label Information Zones


Zones	Information Type	Description	Status: Required/ Optional
Zone 1	Merchandise identification	This is the primary human readable merchandise identifier, usually the style number, although it may be pattern, model, or garment type. The merchandise identifier SHALL be located in the upper left-hand portion of Zone 1.	Always required (see Note)
Zone 2	Vendor information	This includes optional vendor production information, such as vendor Stock Keeping Unit (SKU), cut number, dye lot, colour, and pattern. (Vendor information helps ensure that the correct bar code is attached to the product.)	Optional
Zone 3	Data structure (GTIN-13, GTIN-12, GTIN-8)	Bar code	Always required
Zone 4	Consumer information	This includes optional product information for the consumer, such as fibre content, fire retardancy, and country of origin.	Optional
Zone 5	Size/dimension	Size/dimension is a key requirement for the consumer. Size information can be emphasised in large bold print and is located in the right-hand portion of Zone 5. Vendors may optionally include a style name as a selection aid for the consumer.	Usually required unless defined by the product (e.g., towels)
Zone 6	Retail price	Allow space to print the price with minimum dimension characters of 25 mm (1 in.) x 32 mm (1.25 in.).	Usually required unless defined by the ticket format (e.g., sewn-in tickets)
Zone 7	Manufacturer's suggested retail price	This is for use only if merchandise is pre-priced or the suggested retail price is printed on the tag. If provided, the area must be perforated for optional removal.	Optional



Note: Size and colour are optional in Zone 1 if vendor usage requires this information to define the product.

6.5.2.2. Hanging Tag Label Examples

Figure 6.5.2.2 – 1



6.5.3. Sewn-On (Joker) Label Format


Used almost exclusively for apparel merchandise, joker labels are similar in format to hangtags, but differ in one important respect: They are sewn directly onto the product instead of hung from the product. Because it is sewn on, only one side of the label is available for the vendor's logo, the bar code, and merchandise identification information.

Inclusion of a vendor logo on the label is optional. If it is included, it SHALL not appear at the bottom, because it may be obscured by a retail price label, or it could be torn off by the removal of a manufacturer's suggested retail price. Background printing of logos SHALL be avoided, because this may obscure required information or important consumer information. Logos must never obscure the bar code.

6.5.3.1. Sewn-On (Joker) Label Information Zones

Zones	Information Type	Description	Status: Required / Optional
Zone 1	Merchandise identification	This is the primary human readable merchandise identifier, usually the style number, although it may be pattern, model, or garment type. The merchandise identifier is located in the upper left-hand portion of Zone 1.	Always required (see Note)
Zone 2	Vendor information	This includes optional vendor production information, such as vendor Stock Keeping Unit (SKU), cut number, dye lot, colour, and pattern. (Vendor information helps ensure that the correct bar code is attached to the product.)	Optional
Zone 3	Data structure (GTIN-13, GTIN-12, GTIN-8)	Bar code	Always required

Zones	Information Type	Description	Status: Required / Optional
Zone 4	Consumer information	This includes optional product information for the consumer, such as fibre content, fire retardancy, and country of origin.	Optional
Zone 5	Size/dimension	Size/dimension is a key requirement for the consumer. Size information can be emphasised in large bold print and SHALL be located in the right-hand portion of Zone 5. Vendors may optionally include a plain language style name on the size line as a selection aid for the consumer.	Usually required unless defined by the product (e.g., towels)
Zone 6	Retail price	Allow space to print the price with minimum dimension characters of 25 mm (1 in.) x 32 mm (1.25 in.).	Usually required unless defined by the ticket format (e.g., sewn-in tickets)
Zone 7	Manufacturer's suggested retail price	This is for use only if merchandise is pre-priced or the suggested retail price is printed on the tag. If provided, the area must be perforated for optional removal.	Optional

 **Note:** Size and colour are optional in Zone 1 if vendor usage requires this information to define the product.

6.5.3.2. Sewn-On (Joker) Label Examples

Figure 6.5.3.2 - 1 Vertical layout





Figure 6.5.3.2 - 2 Horizontal layout



6.5.4. Sewn-In Label Formats

Sewn-in labels are often used for towel products. Sewn-in labels may be paper based, for removal by the consumer, or cloth based and more permanent.

Because a portion of the sewn-in label is normally covered by a hem, the label SHALL be designed with sufficient blank space on the end that will be attached to the product. Care must be taken to ensure that the product identification information on the label is not obscured by the hem and that it does not interfere with the readability of the bar code at the Point-of-Sale.

6.5.4.1. Sewn-In Label Information Zones

Zones	Information Type	Description	Status: Required/Optional
Zone 1	Merchandise identification	This is the primary human readable merchandise identifier, usually the style number, although it may be pattern, model, or garment type. The merchandise identifier is located in the upper left-hand portion of Zone 1.	Always required (see Note)
Zone 2	Vendor information	This includes optional vendor production information, such as vendor Stock Keeping Unit (SKU), cut number, dye lot, colour, and pattern. (Vendor information helps ensure that the correct bar code is attached to the product.)	Optional
Zone 3	Data structure (GTIN-13, GTIN-12, GTIN-8)	Bar code	Always required
Zone 4	Consumer information	This includes optional product information for the consumer, such as fibre content, fire retardancy, and country of origin.	Optional
Zone 5	Size/dimension	Size or dimension is optional for sewn-in labels. Size or dimension may assist the consumer with product selection or may help the vendor ensure that the correct label and bar code are attached to the product.	Usually required unless defined by the product (e.g., towels) and readily apparent to the consumer.

Zones	Information Type	Description	Status: Required/Optional
Zone 6	Retail price	Allow space to print the price with minimum dimension characters of 25 mm (1 in.) x 32 mm (1.25 in.).	Usually required unless defined by the ticket format (e.g., sewn-in tickets)
Zone 7	Manufacturer's suggested retail price	This is for use only if merchandise is pre-priced or the suggested retail price is printed on the tag. If provided, the area must be perforated for optional removal.	Optional

Note: Size and colour are optional in Zone 1 if vendor usage requires this information to define the product.

6.6. Plastic Packaged Products Label Location Guidelines

The plastic packaged category covers a wide assortment of merchandise, including sheets, pillowcases, table linens, pantyhose, underwear, stationery supplies, pillows, bedspreads, and numerous types of flat-folded apparel that are plastic packaged.

There are two methods of marking plastic packaged products with bar codes:

- Incorporate the bar code and other merchandise identification information into the packaging's artwork.
- Print the bar code and other merchandise identification information on an adhesive label that can be press-applied to the product.

Inclusion of a vendor logo on the label is optional. If it is included, the logo SHALL not appear at the bottom, because it may be obscured by a retail price label, or it could be torn off by the removal of a manufacturer's suggested retail price. Background printing of logos SHALL be avoided, because this may obscure required information or important consumer information. Logos must never obscure the bar code.

6.6.1.1. Plastic Packaged Products Label Information Zones

Zones	Information Type	Description	Status: Required/Optional
Zone 1	Merchandise identification	This is the primary human readable merchandise identifier, usually the style number, although it may be pattern, model, or garment type. The merchandise identifier is located in the upper left-hand portion of Zone 1.	Always required (see Note 1)
Zone 2	Vendor information	This includes optional vendor production information, such as vendor Stock Keeping Unit (SKU), cut number, dye lot, colour, and pattern. (Vendor information helps to ensure that the appropriate bar code is attached to the product.)	Optional
Zone 3	Data structure (GTIN-13, GTIN-12, GTIN-8)	Bar code	Always required
Zone 4	Consumer information	This includes optional product information for the consumer, such as fibre content, fire retardancy, and country of origin.	Optional (see Note 2)

Zones	Information Type	Description	Status: Required/Optional
Zone 5	Size/dimension	Size/dimension is a key requirement for the consumer. Size information can be emphasised in large bold print and is located in the right-hand portion of Zone 5. Vendors may optionally include a style name as a selection aid for the consumer.	Usually required (see Note 3)
Zone 6	Retail price	Allow space to print the price with 25 mm (1 in.) x 32 mm (1.25 in.) minimum dimension characters. For plastic packaged products, this required space for price can be provided by several methods: For bar code marking on an adhesive label, the space for price can be included as part of the label. For bar code marking designed into the packaging, the space for price can be included on the package artwork. Providing package space adjacent to Zone 5 that is reserved for retail item pricing creates an implied space for price. Implied space replaces the requirement for actual space on labels or package artwork. If implied space for price is used, no information of importance SHALL be printed in the area that might be covered by adhesive item price labels.	Usually required
Zone 7	Manufacturer's suggested retail price	This is for use only if merchandise is pre-priced or the suggested retail price is printed on the tag. If provided, the area must be perforated for optional removal.	Optional

- Note 1:** Size and colour are optional in Zone 1 if vendor usage requires this information to define the product.
- Note 2:** Some jurisdictions require that certain products include a permanently affixed statement of information of this type in Zone 4 that may not be satisfied by inclusion on the package.
- Note 3:** Size may be omitted from Zone 5 if the size information is readily available on the product packaging.

6.6.1.2. Plastic Packaged Products Label Placement Guidelines

Consistent bar code placement is required for successful scanning at the Point-of-Sale. The symbol placement guidelines for plastic packaged products have been designed with the flexibility to accommodate differences that may arise from industry to industry:

- On plastic packaged products, the front top right-hand corner is the preferred placement for the bar code and other product identification information.
- The bar code and other product identification information may be located on the front or back of plastic packaged products. However, all products within a particular merchandise category must have their bar codes placed on the same side of the package.

Caution: Placement of the bar code on the back of a product may result in the presentation of the product on the display counter in a backside up orientation by some retailers so that the bar code and retail price appear together in full view by the customer.

- The orientation of the bar code and other product identification information SHALL be consistent with any graphics or descriptive data on the plastic package.
 - Where possible, the symbol and other product identification information, whether built into the package artwork or an adhesive label, must not be closer than 8 millimetres (0.3 inch) or farther than 100 millimetres (4 inches) from the nearest edge of the package. Experience has shown that the previously recommended minimum distance of 5 millimetres (0.2 inch) is inadequate. Also, cashiers often grab packages on the edge with their thumbs. Avoid placing the bar code too close to the edge. Such placement reduces Point-of-Sale efficiency and may cause distortion of the symbol. (See Section [6.3.3.3, Edge Rule.](#))
 - The bar code and other product identification information on plastic packaged products is normally to be located on the front top right-hand corner. However, for very large, bulky, or unusually shaped products, this may be impractical or inappropriate. See Section 6.4.9 for information on large, heavy, and bulky items.
- ✔ **Note:** Section 6.4 specifies the lower right quadrant of the back of the package or container as the recommended location for the bar code. This recommendation applies to plastic packaged products that are sold in a grocery store environment.

6.6.1.3. Plastic Packaged Products Label Example

Figure 6.6.1.3 – 1



6.6.2. Boxed Products Label Formats

Some boxed products may be sold in or out of the box. Other boxed products are actually sets that may also be sold as individual items. Some boxes carry significant amounts of design graphics, while others are plain boxes containing the product.

Box size can range from very small, as in jewellery or cosmetics, to very large, as in home furnishings. For extremely large boxed products, consider using a two-part tear-off bar code label to facilitate scanning at the Point-of-Sale while leaving one label on the box.

There are two methods of marking boxed products with bar codes:

- Incorporate the bar code and other merchandise identification information the box's artwork.

- Print the bar code and other merchandise identification information on an adhesive label that can be affixed to the box.

Inclusion of a vendor logo in the box marking format is optional. If the logo is included, it SHALL not appear at the bottom, because it may be obscured by a retail price label, or it could be torn off if a manufacturer's suggested retail price is removed. Background printing of logos SHALL be avoided, because this may obscure required information or important consumer information.

6.6.2.1. Boxed Products Label Information Zones

Zones	Information Type	Description	Status: Required/Optional
Zone 1	Merchandise identification	This is the primary human readable merchandise identifier, usually the style number, although it may be pattern, model, or garment type. The merchandise identifier is located in the upper left-hand portion of Zone 1.	Always required (see Note 1)
Zone 2	Vendor information	This includes optional vendor production information, such as vendor Stock Keeping Unit (SKU), cut number, dye lot, colour, and pattern. (Vendor information helps ensure that the correct bar code is attached to the product.)	Optional
Zone 3	Data structure (GTIN-13, GTIN-12, GTIN-8)	Bar code	Always required
Zone 4	Consumer information	This includes optional product information for the consumer, such as fibre content, fire retardancy, and country of origin.	Optional (see Note 2)
Zone 5	Size/dimension	Size/dimension is a key requirement for the consumer. Size information can be emphasised in large bold print and is located in the right-hand portion of Zone 5. Vendors may optionally include a style name as a selection aid for the consumer.	Usually required (see Note 3)
Zone 6	Retail price	Allow space to print the price with minimum dimension characters of 25 mm (1 in.) x 32 mm (1.25 in.). For boxed products, this required space for price can be provided by several methods: For bar code marking on an adhesive label, the space for price can be included as part of the label. For bar code marking designed into the packaging, the space for price can be included on the package artwork. Providing package space adjacent to Zone 5 that is reserved for retail item pricing creates an implied space for price. Implied space replaces the requirement for actual space on labels or package artwork. If implied space for price is used, no information of importance is printed in the area that might be covered by adhesive item price labels.	Usually required
Zone 7	Manufacturer's suggested retail price	For use only if merchandise is pre-priced or the suggested retail price is printed on the tag. If provided, the area must be perforated for optional removal.	Optional

- ✓ **Note 1:** Size and colour are optional in Zone 1 if vendor usage requires this information to define the product.
- ✓ **Note 2:** Some jurisdictions require that certain products include a permanently affixed statement of information of this type in Zone 4 that may not be satisfied by inclusion on the package.
- ✓ **Note 3:** Size may be omitted from Zone 5 if the size information is readily available on the product packaging.

6.6.2.2. Packaged Versus Freestanding Single Selling Units

Certain single selling units (trade items) may be sold as freestanding items, or they may be sold in a package. This creates a dilemma for the supplier: to mark the item or mark the package? For GTIN Allocation Rules pertaining to this scenario, see Section 2.1.


6.6.2.3. Boxed Products Label Placement Guidelines

Consistent bar code placement within an industry or product category is required if merchandise carrying a bar code is to successfully scan at the Point-of-Sale. Since the category of boxed products includes a diverse merchandise group, location guidelines have been designed with considerable flexibility to accommodate differences that may arise from industry to industry:

- The exposed surface of the box is the preferred location for bar codes and other product identification information on boxed products sold primarily in the department or specialty store environment.
 - The orientation of the bar code and other product identification information SHALL be consistent with any graphics or descriptive data on the box.
 - Where possible, the symbol and other product identification information, whether built into the package artwork or an adhesive label, must not be closer than 8 millimetres (0.3 inch) or farther than 100 millimetres (4 inches) from the nearest edge of the package. Experience has shown that the previously recommended minimum distance of 5 millimetres (0.2 inch) is inadequate. Also, cashiers often grab packages on the edge with their thumbs. Avoid placing the bar code too close to the edge. Such placement reduces Point-of-Sale efficiency and may cause distortion of the symbol. (See Section [6.3.3.3, Edge Rule.](#))
 - The bar code and other product identification information on plastic packaged products is normally to be located on the front top right-hand corner. However, for very large, bulky, or unusually shaped products, this may be impractical or inappropriate. See Section [6.4.9](#) for information on large, heavy, and bulky items.
- ✓ **Note:** Section [6.4](#) specifies the lower right quadrant of the back of the package or container as the recommended location of the bar code. This recommendation applies to plastic packaged products that are sold in a grocery store environment.

6.6.2.4. Boxed Products Label Examples

Figure 6.6.2.4 – 1 Label example for boxed products



6.6.3. Banded Products Label Formats

Banded packaging involves a specialised group of products. This type of packaging is most commonly associated with hosiery (socks) or yarn products.

There are the two methods of marking banded products with bar codes:

- Incorporate the bar code and other merchandise identification information into the band's artwork.
- Print the bar code and other merchandise identification information on an adhesive label that can be applied to the band.

The typical banded product label has the vendor's logo on the front and the product identification codes, consumer information, and bar code on the back. The vendor's logo can also be printed on the back of the band as part of the band marking format. However, care **MUST** be taken to ensure that there is no obstruction of the bar code or other important product identification information. Background printing of logos **SHALL** be avoided.

6.6.3.1. Banded Products Label Information Zones

Zones	Information Type	Description	Status: Required/Optional
Zone 1	Merchandise identification	This is the primary human readable merchandise identifier, usually the style number, although it may be pattern, model, or garment type. The merchandise identifier is located in the upper left-hand portion of Zone 1.	Always required (see Note 1)
Zone 2	Vendor information	This includes optional vendor production information, such as vendor Stock Keeping Unit (SKU), cut number, dye lot, colour, and pattern. (Vendor information helps ensure that the correct bar code is attached to the product.)	Optional
Zone 3	Data structure (GTIN-13, GTIN-12, GTIN-8)	Bar code	Always required
Zone 4	Consumer information	This includes optional product information for the consumer, such as fibre content, fire retardancy, and country of origin.	Optional (see Note 2)
Zone 5	Size/dimension	Size/dimension is a key requirement for the consumer. Size information can be emphasised in large bold print and is located in the right-hand portion of Zone 5. Vendors may optionally include a style name as an aid to the consumer in selection.	Usually required (see Note 3)
Zone 6	Retail price	Allow space to print the price with minimum dimension characters of 25 mm (1 in.) x 32 mm (1.25 in.). For banded products, this required space for price can be provided by several methods: For bar code marking on an adhesive label, the space for price can be included as part of the label. For bar code marking designed into the packaging, the space for price can be included on the package artwork. Providing package space adjacent to Zone 5 that is reserved for retail item pricing creates an implied space for price. Implied space replaces the requirement for actual space on labels or package artwork. If implied space for price is used, no information of importance is printed in the area that might be covered by adhesive item price labels.	Usually required
Zone 7	Manufacturer's suggested retail price	This is for use only if merchandise is pre-priced or the suggested retail price is printed on the tag. If provided, the area must be perforated for optional removal.	Optional



Note 1: Size and colour are optional in Zone 1 if vendor usage requires this information to define the product.

- ✔ **Note 2:** Some jurisdictions require that certain products include a permanently affixed statement of information of this type in Zone 4 that may not be satisfied by inclusion on the package.
- ✔ **Note 3:** Size may be omitted from Zone 5 if the size information is readily available on the product packaging.

6.7. GS1 Logistics Label Design

These specifications constitute the basis for all GS1 logistics labels. Other sections, most notably Section 3, GS1 Application Identifier Definitions, and Section 5.4, GS1-128 Symbology Specifications, MUST be read in conjunction with the following sub-sections.

6.7.1. Scope

These specifications detail the structure and layout of GS1 logistics labels. Emphasis is given to the basic requirements for practical application in an open trade environment. Primary topics include:

- The unambiguous identification of logistic units
- The efficient presentation of text and machine readable data
- The information requirements of the key partners in the supply chain: suppliers, customers, and carriers
- Technical parameters to ensure systematic and stable interpretation of labels


6.7.2. Concepts

6.7.2.1. Logistics Information Flow

As a logistic unit moves through the supply chain, a series of events occurs that defines the information related to the unit. The whole supply chain process of manufacturing, finished goods distribution, transportation, and deployment into the marketplace adds layers of information related to the logistic unit.

For example, the physical content of the unit is typically defined at finished goods distribution. At that point in time the identification of the logistic unit as an entity is possible. Other elements of information, such as final destination or the composition of a multi-unit shipment, are not typically known until later in the supply chain process. In a trading relationship, different elements of information are generally known and applied by the supplier, carrier, and customer.

Figure 6.7.2.1 – 1



6.7.2.2. Representation of Information

The information included on a GS1 logistics label comes in two basic forms. Non-HRI text is used by people and is comprised of text and graphics. Machine readable information is designed for data capture by a machine. Bar codes are machine readable and are a secure and efficient method for

conveying structured data, while Non-HRI text allows people general access to basic information at any point in the supply chain. Both methods add value to GS1 logistics labels, and often co-exist on the same label.

The GS1 logistics label has three sections. The top section of the label contains free format information. The middle section contains Non-HRI text information and the Human Readable Interpretation of the bar code(s) using data titles rather than AIs. The lowest section contains the bar code(s) including human readable information.

6.7.3. Label Design

The layout of the GS1 logistics label groups information into three logical sections for the supplier, customer, and carrier. Each label section may be applied at a different point in time as relevant information becomes known. Additionally, within each section, bar codes are segregated from text information to facilitate interpretation by both machines and people.

The labeller, the organisation responsible for printing and applying the label, determines the content, format, and dimensions of the label. The SSCC is the single mandatory element for all GS1 logistics labels. Other information, when required, SHALL comply with the specifications of this document and with the proper use of Application Identifiers.

6.7.3.1. Supplier, Customer, Carrier Sections

A section is a logical grouping of information that is generally known at a particular time. There are three label sections on a GS1 logistics label, each representing a group of information. Generally, the order of the sections, from top to bottom, is: carrier, customer, and supplier. However, this order and top/down alignment may vary depending on the size of the logistic unit and the business process being served.

6.7.3.1.1. Supplier Section

The supplier section of the label contains information that is generally known at the time of packaging by the supplier. The SSCC is applied here as the unit identifier, along with the Global Trade Item Number (GTIN) if used. If several logistics or transport units are assembled to be transported under one despatch advice or BOL to one customer the GSIN, AI (402) may also be applied in this supplier section.

Other information that may be of interest to the supplier but might also be useful for customers and carriers can be applied. This includes product-related information such as product variant; dates such as production, packaging, expiration, and best-before dates; and lot, batch, and serial numbers.

6.7.3.1.2. Customer Section

The customer section of the label contains information that is generally known at the time of order and order processing by the supplier. Typical information includes the ship to location, purchase order number, and customer-specific routing and handling information.

6.7.3.1.3. Carrier Section

The carrier section of the label contains information that is generally known at the time of shipment and is typically related to transport. Typical information includes ship to postal codes, AI (420), Global Identification Number for Consignment, AI (401), and carrier-specific routing and handling information.

6.7.3.2. Bar code and Human Readable Interpretation Layout

Bar codes with Human Readable Interpretation are represented in the lower part of each section, while Non-HRI text is shown in the upper part of the section. This facilitates access to each component.

Figure 6.7.3.2 – 1



6.7.3.3. Label Dimensions

The physical dimensions of the label are determined by the labeller, but the size of the label should be consistent with the data requirements for all sections of the label. Factors influencing label dimensions include the amount of data required, the content and X-dimension of the bar codes used, and the dimensions of the logistic unit to be labelled. The business requirements for most users of GS1 Logistic Labels are met by using one of following:

- A6 (105 mm x 148 mm), which is particularly suitable when only the SSCC, or the SSCC and limited additional data, is encoded
- 4 x 6 inch, which is particularly suitable when only the SSCC, or the SSCC and limited additional data, is encoded

-or-

- A5 (148 mm x 210 mm)
- 6 x 8 inch

6.7.4. Technical Specifications

6.7.4.1. Bar codes

6.7.4.1.1. Orientation and Placement

Bar Codes placed relative to the base of a logistic for use for general distribution must be placed in a picket fence orientation, this means, the bars and spaces are perpendicular to the base on which the logistic unit stands. In all cases, the GS1-128 Bar Code encoding the SSCC shall be placed in the lowest portion of the label.

6.7.4.1.2. Human Readable Interpretation

As a back up key entry and diagnostic aid, a Human Readable Interpretation of each bar code shall be provided above or below the symbol. It includes Application Identifiers (AIs), data content, and a Check Digit, but no representation of special symbol characters or the Symbol Check Character.

To facilitate key entry, AIs should be set apart from the data by parentheses.

This Human Readable Interpretation characters shall be no less than 3 millimetres high and clearly legible and preferably below the symbol.

6.7.4.2. Text

6.7.4.2.1. Plain Text

Text that has no bar code equivalent is often required on a label. The name and address of the sender and receiver are typical examples. In many instances companies may also wish to add specific text to a label (e.g., company logos). All text shall be clearly legible and no less than 3 millimetres high.

6.7.4.2.2. Human Readable Interpretation

Human Readable Interpretation is text designed to support manual operations and to facilitate key entry in menu driven systems. It is the equivalent of data elements represented in bar codes and is comprised of data titles and data content. The data content should be at least 7 millimetres in height. If there is no language agreed between trading partners, data titles must be printed in English. As an option left at the discretion of the labeller, a second language can be added. Application Identifiers are not included in Human Readable Interpretation.

6.7.4.2.3. Data Titles

Data titles are the standard abbreviated descriptions of data fields used to denote the Human Readable Interpretation of encoded data. They are prefixes of the Human Readable Interpretation to support manual interpretation of data fields. They can also be used adjacent to other text or bar codes to clarify content, such as the word “from” adjacent to a sender’s address.

All data titles are shown in Section 3.2.

6.7.4.3. Label Location

Label placement specifications are maintained in Section 6.8.

6.7.5. Label Examples

Figure 6.7.5 - 1 The basic label: an SSCC



Figure 6.7.5 - 2 Label with supplier and carrier sections

<p>Von/From</p> <p>Mustermann GmbH Herr Schmidt Hauptstr. 35 60100 Frankfurt Germany</p>	<p>An/To</p> <p>Edificio de Servicios Generales Ms Alicia Romero Calle Centella 18 08820 Barcelona Spain</p>
<p>SSCC: 353708431300012501</p> <p>Route: 72408820+04000002</p> <p>Dimensions/Weight: 80x20x20 cm / 50,0 kg</p> <p>Billing No.: 5020613963 69 01 001/999</p>	
 <p>(403) 72408820+04000002</p>  <p>(00) 3 5370834 130001250 1</p>	

Figure 6.7.5 - 3 Label with supplier and carrier sections

FROM	TO
BIG SUPPLIER 5 th AVENUE NEW YORK USA	GREAT VALUE 8163 NEW CAJUN DAYTON, OHIO USA
	SHIP TO POST 45458 B/L 853930 PRO 2895769860
SSCC 0 0614141 123456789 0	
	
(00) 006141411234567890	

Figure 6.7.5 - 4 Label with supplier section with concatenated data

GRAND SUPPLIER COFFEE

SSCC
0 0614141 1234567890

CONTENT	COUNT
00614141000418	20
BEST BEFORE (ddmmyy)	BATCH
14.02.00	4512XA



(02)00614141000418(15)000214(10)4512XA(37)20



(0 0) 0 0 6 1 4 1 4 1 1 2 3 4 5 6 7 8 9 0

Figure 6.7.5 - 5 Labels with supplier, customer, and carrier sections



6.7.6. EPCglobal Seal Application Guidelines

If using EPC Tags on products it is important to make supply chain partners aware of their presence. This is achieved by using the latest version of the EPCglobal Seal that can be found on:

<http://www.gs1.org/gsm/kc/epcglobal>

6.8. Placement Labels Used in General Distribution

General Distribution Scanning items include any item handled as a single unit in the transport and distribution process. This definition covers a wide variety of package types, such as pallets, cartons, cases, bins, and totes. These items can be trade items and/or logistic units.

Bar code scanning may be carried out manually or automatically, and the recommended symbol location cannot be optimised for one or the other in an open supply chain scenario. These guidelines

have been prepared with the objective to reduce overall supply chain cost but in the full knowledge that implementation will only be driven by a proven (supply chain) business-case.

6.8.1. General Rule

The bar codes on units intended for General Distribution SHALL be upright (i.e. in picket fence orientation) and placed on the sides of the unit. Each item shall have at least one bar code, and two are recommended when these symbols are pre-printed (see Section 6.8.3).

As not all products are packed in an identical way, this general rule may not apply to unusual packaging types (e.g., low height items, display cases, bags).


The bar codes SHALL be kept away from any vertical edges so that the bar codes are less likely to be accidentally damaged in transit.

6.8.1.1. Symbol Placement on Pallets

For all types of pallets, including full pallets containing individual trade items and single trade items, (such as a refrigerator or washing machine), the target height for the bottom of the bar code is between 400 millimetres (16 inches) and 800 millimetres (32 inches) from the base of the pallet. For pallet less than 400 millimetres (16 inches) high, the bar code SHALL be placed as high as possible while protecting the bar code.

The symbol including, its Quiet Zones, SHALL be at least 50 millimetres (2.0 inches) from any vertical edge to avoid damage.


Figure 6.8.1.1 - 1



6.8.1.2. Symbol Placement on Cartons and Outer Cases

For cartons and outer cases, symbol placement will vary slightly in practice, however the target placement for the bottom of the bar code is 32 millimetres (1.25 inches) from the natural base of the item. The symbol including, its Quiet Zones, should be at least 19 millimetres (0.75 inch) from any vertical edge to avoid damage.

Figure 6.8.1.2 - 1 Symbol placement on cartons and outer cases




6.8.1.3. Symbol Location on Shallow Trays and Cases

If the height of a case or tray is less than 50 millimetres (2.0 inches), making it impossible to print a full height bar code with the Human Readable Interpretation below the bars (see Section 4.12 for HRI Rules), or if the construction of the unit is such that the full symbol height cannot be accommodated, the following options SHALL be considered in this order of preference:

- Place the Human Readable Interpretation adjacent to the symbol, outside the compulsory Quiet Zones.

Figure 6.8.1.3 - 1 Human readable interpretation to left of symbol



- When the height of the unit is less than 32 millimetres, the symbol may be placed on the top of the package. The symbol SHALL be placed with the bars perpendicular to the shortest side, no closer than 19 millimetres (0.75 inch) from any edge.

Figure 6.8.1.3 – 2



Sometimes two bar codes are used on variable measure units. If it is necessary to remove the Human Readable Interpretation from beneath the unit, the human readable interpretation of the main symbols SHALL be placed to the left of the bars of the main symbol. The Human Readable Interpretation of the Add-On Symbol SHALL be placed to the right of the bars of the Add-On Symbol.


6.8.2. Recommendation to Include a Bar Code on Two Sides

Although at least one side of all General Distribution Scanning items shall display the bar code information, it is recommended that two (or more) sides of the item carry a bar code with the exact same data when:

- The printing process makes this cost effective (e.g. pre-printed corrugated cartons).
- The supply chain requirement is that one symbol is always visible (e.g., pallets that are stored either long or short edge facing).

Figure 6.8.2 - 1 Two (or more) identical bar codes


Two identical labels improves scanning performance



6.8.3. Add-On Symbols

If the unit is already marked with a symbol, any Add-On Symbol shall be placed so as not to obscure the primary bar code. The preferred location for the symbol in this case is to the side of the primary bar code so that a consistent horizontal location is maintained. Maintain Quiet Zones for both symbols.

Figure 6.8.3 – 1



When it is possible for both parts of the data content to be represented in a GS1-128 Bar code, concatenation into one symbol **MUST** be considered. Bar codes for General Distribution scanning containing data essential for complete product identification (e.g., trade measurements) **SHALL** always be aligned with and to the right of the bar code containing the Global Trade Item Number (GTIN) (the primary symbol).

6.9. Symbol Placement for Regulated Healthcare Trade Items

In addition to the general rules in Section 6, the following symbol placement rules SHALL be added for regulated healthcare products.

6.9.1. Blister Cells

Blister cells are pre-formed clear plastic bubbles, or blisters, containing a product.

6.9.1.1. Perforated Blister Cells

- Placement:
 - At the primary packaging level for pharmaceutical products packaged with perforated blister cells, a bar code shall be placed on each blister cell.

6.9.1.2. Non-Perforated Blister Cells

- Placement:
 - At the primary packaging level for pharmaceutical products packaged with non-perforated blister cells, a bar code shall be placed once on the grouping of blister cells (e.g. blister card). The bar code may be placed anywhere on the blister card.
 - If random printing (e.g. no one to one correlation between printing impression and blister cell position) is used, the symbol may be placed multiple times to ensure that the symbol remains scannable until each blister has been used.

6.9.2. Products Requiring Variable Data On Primary and Secondary Packaging

Where such marking is feasible from a production and marking standpoint, the bar code carrying variable data (e.g. batch/lot number or expiry date) shall be marked on the primary and secondary packaging.

- Placement:
 - The bar code shall be placed only on one side of the packaging , which may be either the face, side or end panel.



7. AIDC Validation Rules

- Introduction
- Synopsis of Message Processing
- Validation of the Electronic Message Regarding System Consistency
- Validation of the Electronic Message Regarding User Requirements
- Conversion of Weights and Measures in User Applications
- Linkage of GTINs in a Database
- Elements Strings Represented in Data Carriers
- Secondary Data for specific Health Industry Products
- Processing of Data from a GS1 Symbology using GS1 Application Identifiers
- Check Digit Calculations
- GTIN-12 and RCN-12 in a UPC-E

7.1. Introduction

The purpose of entering data transmitted from a reading device into a system is to record a transaction. In the GS1 System, a transaction is an Electronic Message to be processed according to the meaning and content of the data fields contained in the message. This should be possible without requiring any human intervention to determine the data's meaning and content.


First, an item must be physically present in order to produce a Bar Code or RFID reader message about the item. Only the data present in the data carrier on the item, and therefore relevant to it, can be recorded.

The standardised Element Strings of the GS1 System are the basis for the identification of items of every kind. They identify a particular item in an unambiguous manner and supply relevant attribute information.

When these Element Strings are printed on items, the scanned and transmitted data refers to that item and identifies its physical presence at a given location. When the message read from the scanned data carrier is coupled with an internally assigned designation of the type of item movement (e.g., warehouse entry, stock taking, sales), it is possible to automatically record data related to each movement of items. This provides security in two ways. First, an item must be physically present in order to produce a Bar Code reader message about the item, and, second, only the data in the Bar Code on the item and, therefore, relevant to it, can be recorded. False notification of movements is thereby largely eliminated.

When Element Strings are used in administrative areas (e.g., in order entry) they also can be used for automatic, error-free data capture. Because of the considerable length of many GS1 System ID numbers, automatic reading has great significance. By using a Check Digit, a digit that ensures the data has been correctly composed, the accuracy of the reading is verified.

7.2. Synopsis of Message Processing



For details on any of the actions in Figure 7.2 - 1, see the following subsections.

7.2.2. Symbology Identification

Each transmitted full string consists of a symbology identifier and one or more Element Strings (see Section 3). The identifiers of Bar Code symbologies are stated in Section 5.

7.2.3. Prefix in Internal Table

System users may generate an internal table showing the GS1 Prefixes of Element Strings they wish to process. This table also serves to sort out the Element Strings representing item identification numbers in order to check their presence in the data file. Details on the respective prefixes are stated in Section 3.

7.2.4. Item Identification

The symbols in the EAN/UPC Symbology family contain identification data for trade items and special data structures (e.g., coupons). Whether an Element String contains the identification of a trade item is determined by the GS1 Prefix. System users must determine the specific structure and meaning of prefixes 20 to 29 as defined by their GS1 Member Organisation.

7.2.5. Application Identifier (AI) in Internal Table

The Element Strings using Application Identifiers cover a wide range of applications. In order to keep the amount of programming on a reasonable level, it is possible to ignore processing of unwanted Element Strings. This is achieved by establishing an internal table with only the Application Identifiers intended for processing.

7.2.6. Length of Data 14 Digits

ITF-14 Bar Codes are used to represent trade item identification numbers. As the use of the general ITF symbology is not exclusive to the GS1 System a check to ensure the symbol encodes 14-digit reference field is recommended.

7.2.7. Check Digit Calculation and other system checks

In EAN/UPC Symbology, the Check Digit verifies reading and decoding of Bar Codes as well as Global Trade Item Numbers (GTINs). This is performed automatically by the Bar Code reader.

Bar Code readers processing ITF-14 Symbols may be programmed to verify the GTIN's Check Digit as well. If this recommended verification has been performed, it is indicated by the symbology identifier] | 1 (see Section 5). For data transmitted from ITF-14 Symbols with symbology identifier] | 0, the GTIN's Check Digit SHALL be verified separately.

GS1-128 and GS1 DataBar have an integral Symbol Check Character that verifies correct decoding of scanned data while GS1 DataMatrix and GS1 QR Code have a Reed Solomon error checking and correction feature. If an Element String encoded in one of these symbol types includes a Check Digit, the Check Digit will not normally be verified by the Bar Code reader and SHALL be verified separately. While the data security provided by the Symbol Check Character or error checking guarantees proper decoding of the entire Element String, correctness of the contained identification number is achieved by having the application software verify the ID number's Check Digit.

Other logical tests checks are recommended for reasonable data content, such as verifying:

- Data field ranges (e.g., month < 13 and > 00)
- The maximum length of a variable length Element String
- No alphanumeric characters in numeric only fields
- Correct GS1 Prefixes

7.2.8. Move Element String to Message Field

Several Element Strings may be scanned in a single transaction. In order to verify the correctness and completeness of the transmitted data, each Element String is transferred to a message record. If an Element String does not include an Application Identifier, verification of the message is simplified if an Application Identifier is internally assigned. Global Trade Item Numbers (GTINs) that are carried by EAN-13, UPC-A, UPC-E or ITF-14 Bar Codes may be denoted with an internally assigned AI (01). Other Element Strings may be assigned "ghost" Application Identifiers.

7.3. Validation of the Electronic Message Regarding System Consistency

The GS1 System enables system users to process scanned data without human intervention. This implies that the electronic message generated from data scanned and transmitted from data carriers needs to substitute for all human activities during a particular transaction. In other words, the transmitted data must provide all information required for its correct processing.

The GS1 System is designed to fulfill these requirements. Section 4 describes the association of Element Strings to form valid messages.

Validation of system consistency refers to the verification of the correct composition of the electronic message by a system processing the transaction messages. Whether the message is adequate in business application terms is dealt with by the application software.

Only messages containing a valid set of Element Strings defined in the GS1 System can be unambiguously processed. The processing of invalid messages may lead to data file errors because the meaning and relationship of the Element Strings are not defined. This is illustrated in Figures 7.3 - 1 and 7.3 - 2.

Figure 7.3 - 1 Examples of Valid Messages

Element Strings in Message			Comment
AI 00	AI 33nn		Identification of a logistic unit + logistic weight
AI 00	AI 01		Identification of an entity as a logistic unit and as a Fixed Measure Trade Item
AI 00	AI 01 '9'	AI 31nn	Identification of an entity as a logistic unit and as a Variable Measure Trade Item
AI 00	AI 02	AI 37	Identification of a logistic unit and its contained Fixed Measure Trade Items
AI 01	AI 10	AI 15	Identification of a trade item + lot number + best before date
AI 00	AI 401		Identification of a logistic unit as part of a consignment
AI 01 '9'	AI 31nn	AI 33nn	Identification of a Variable Measure Trade Item + logistic weight
AI 00	AI 01	AI 33nn	Identification of an entity as a logistic unit and a Fixed Measure Trade Item; the logistic weight is associated with the identification number of the logistic unit
AI 01	AI 710		Identification of a trade item + National Healthcare Reimbursement Number
AI 01	AI 711		Identification of a trade item + National Healthcare Reimbursement Number
AI 01	AI 712		Identification of a trade item + National Healthcare Reimbursement Number

Figure 7.3 - 2 Examples of Invalid Messages

Element Strings in Message			Comment
AI 00	AI 01	AI 37	Invalid identification of an entity as a logistic unit and as a Fixed Measure Trade Item; AI 37 (quantity of items contained) must be used with AI 02 only
AI 01	AI 10	AI 33nn	Invalid identification of a Fixed Measure Trade Item + lot number; AI 33nn is incorrect because logistic measures of a Fixed Measure Trade Item are fixed attributes stored in the data file
AI 01'9'	AI 33nn		Invalid identification of a Variable Measure Trade Item + logistic weight; the mandatory Element String with a trade measure is missing
AI 00	AI 11		Invalid identification of a logistic unit; AI 11 is incorrect because a production date must be associated with the identification number of a trade item
AI 00	AI 01	AI 02/37	Invalid identification of an entity as a logistic unit and as a Fixed Measure Trade Item; AI 02/37 must not be associated with AI 01
AI 01	AI 30		Invalid identification of a Fixed Measure Trade Item; AI 30 must only be associated with the identification number of a Variable Measure Trade Item
AI 02	AI 37		Invalid identification of the fixed measure trade units contained in an unidentified logistic unit; AI 00 is missing
AI 00	AI 02		Invalid identification of a logistic unit and of the contained Fixed Measure Trade Items; AI 02 requires the mandatory presence of AI 37 to complete the identification of the content

7.4. Validation of the Electronic Message Regarding User Requirements

Some industry groups and organisations specify the use of particular Element Strings for attributes and other information not directly identifying the item. Contrary to the validation of messages for system conformity, GS1 does not define the rules for the validation and application of these particular Element Strings. Validation of messages containing these Element Strings in these environments (e.g., trade item identification with best before date and batch number) is left to the discretion of the particular system user community.

Validation of the correctness of a message may be performed differently for each Global Trade Item Number (GTIN), and instructions must be stored in the data file. System users should include the Application Identifiers and their specific application rules in the stored instructions.

Validation of the user requirements must be performed after validation of system consistency. Missing elements in consistent messages may be by-passed or completed in given instances. Inconsistent messages can never be processed properly.

7.5. Conversion of Weights and Measures in User Applications

All weights and measures that are encoded in the Element Strings with the Application Identifiers (31nn) to (36nn) are structured according to the same mathematical rules. The determination of basic units of measurement and the freedom to choose the number of decimal positions will lead to variations in data representation. Suppliers will choose the value that best suits the respective trade item in terms of weight/size and the degree of accuracy required (e.g., grams) for the representation of weights and measures in the six-position data field.

The recipient of such goods also may want to store these details in a standardised form in his data file. This requirement is easily fulfilled through programming with the conversion formula shown below.

As described in Section 3, the Application Identifier in position A₄ denotes the position of the implied decimal point, called the Inverse Exponent.

The three-step formula to convert weights and measures is as follows:

1. Define the company's internal inverse exponent in accordance with the basic unit of measure of the company's internal field structure (e.g., for an AI expressing weight in kilograms, inverse exponent 0 could signify kilograms and inverse exponent 3 could signify grams).
2. Subtract the company's internal inverse exponent from the value of the position A₄ of the Application Identifier in the decoded Element String. Call the result X.
3. Divide the amount of the six-digit applicable value field from the decoded data string by 10^x. The result is the value required in the company's data structure.

In the examples in Figure 7.5 - 1, the company's system uses internal weight fields eight digits in length (format: **nnnnnnn.n**) with a unit of measure equal to grams. Thus, the company uses the internal inverse exponent of 3.


Figure 7.5 - 1

Decoded Data String				Conversion	Internal Weight Field
Application Identifier A ₁ A ₂ A ₃ A ₄	Weight				Eight-Digit Data Field Defined as Grams with One Decimal Position
3 1 0 0	005097 (= 5097 kg)	Step 2: X = 0 minus 3 = -3 Step 3: 005097 divided by 10 ⁻³ (.001) =	5 0 9 7 0 0 0		
3 1 0 2	005097 (= 50.97 kg)	Step 2: X = 2 minus 3 = -1 Step 3: 005097 divided by 10 ⁻¹ (.1) =	0 0 5 0 9 7 0		
3 1 0 3	045250 (= 45.250 kg)	Step 2: X = 3 minus 3 = 0 Step 3: 045250 divided by 10 ⁰ (1) =	0 0 4 5 2 5 0		
3 1 0 4	012347 (= 1234.7 g)	Step 2: X = 4 minus 3 = 1 Step 3: 012347 divided by 10 ¹ (10) =	0 0 0 1 2 3 4 7	↑ Decimal point	

7.6.1. The Principle

The hierarchy for the example in Figure 7.6.1 - 1 is basic product = A; 10 x A = product B; 5 x B = product C.


Figure 7.6.1 - 1



See Figure 7.6.2 - 1 for the mechanism of linkage for the various types of trade items.


7.6.2. Extended Example of a Trade Item Hierarchy

Figure 7.6.2 - 1



Note: For reasons of simplicity, Global Trade Item Numbers (GTINs) are expressed in letters in this example, signifying that they may be of any standardised structure.

Figure 7.6.2 – 2



* Quantity of items numbered A contained in item C



Note: The columns "GTIN in Database" and "GTIN of Relation" are sufficient to establish the links between the different items. The column "Quantity of Items Contained" provides additional information, which may be useful in particular business applications. The column "Relation is Mixed Trade Item" provides the relations pointing to all trade items contained in a mixed trade item.

7.6.3. Linkage of GTINs in a Non-Relational Database by Trade Item Manufacturer

Many types of items are produced and distributed in fixed measure standard nested packaging configurations (e.g., consumer unit, carton, case, pallet) with fixed quantity relationships. The various packaging configurations are often broken into lower levels at various points in the supply chain, and, therefore, each level of the packaging may be a trade item. Computer systems must be capable of understanding the relationships of the units or trade items in the configuration and treating inventory of all levels of the configuration as one SKU (stock keeping unit).

The first digit Indicator (values 1 to 8) of the GTIN-14 Data Structure can be used to identify levels of a standard packaging configuration. This allows digits 2 to 13 to remain constant for all levels of the standard packaging configurations for an item. If this method of numbering item configurations is used when necessary to support business processes or when driven by system constraints, the non-relational database construct defined below may be appropriate.

The item database is constructed with a base item record (table) and segments (tables) for each level of the item packaging configuration. Properly designed, this type of system can support pricing, ordering, and shipping of any level of the packaging configuration (trade item) with appropriate dimension and weight information. It enables inventories to be maintained by packaging level and in total for the base item. It also provides channel partners or customers the choice of ordering and invoicing units. Meeting these requirements often makes this approach a good business solution for manufacturers, because it meets the most critical needs in the supply chain and is practical to implement, particularly in distributed and small systems where performance is critical.

Using the GTIN-14 Data Structure, the base item record contains the base GTIN-8, GTIN-12, or GTIN-13 ID Number (digits 2 to 13) as a key, with all information relating to the base unit and the item in total (including total inventory balance). Each of the packaging segments contains information unique to the respective packaging configuration (e.g., Indicator, Check Digit, quantity relationship to next lower level of the configuration, dimensions, weight, prices). After accessing the item record using the GTIN of the base item (digits 2 to 13), the packaging segments are accessed using the Indicator (first digit).

This construct demands that:

- The trade item must be fixed in measure.
- There must be a single Global Trade Item Number (GTIN) for the base item of the related packaging configurations that is a GTIN-8, GTIN-12, or GTIN-13.
- Each related packaging configuration is limited to eight levels of packaging for the base item using Indicator values 1 to 8.

When storing GTIN-8s, GTIN-12s, or GTIN-13s in a 14-digit reference field or 14-digit data carrier, they must be stored based on rules that ensure their uniqueness.

Companies that receive trade items with GTINs must be able to process the complete GTIN without regard to how it was constructed.

7.7. Elements Strings Represented in Data Carriers

Scanned Element Strings are decoded as a full string by the reading device and are then transmitted for processing in the application software. The full string is composed of a symbology identifier and one or more Element Strings. The meaning of an Element String is also determined by the data carrier in which it is represented.

A synopsis by data carrier of the Element Strings described in these specifications is shown in Figure 7.7.1 - 1, which also provides an overview of the sequential number range of trade items by data carrier.

7.7.1. Element Strings Represented in GS1 System Data Carriers

See figure on next page.

Figure 7.7.1 - 1

ITF-14 or GS1-128 Bar Code													
EAN-13 Bar Code													
UPC-A or UPC-E Bar Code													
										EAN-8 Bar Code			
2.	*	*	*	*	*	*	0	0	0	0	0	0	C
							0	9	9	9	9	9	C
1.	*	*	*	*	*	*	1	0	0	0	0	0	C
							1	3	9	9	9	9	C
2.	*	*	*	*	*	*	2	0	0	0	0	0	C
							2	9	9	9	9	9	C
1.	*	*	*	*	*	*	3	0	0	0	0	0	C
							9	6	9	9	9	9	C
1.	0	0	0	0	0	1	0	0	0	0	0	0	C
	0	0	0	0	0	9	9	9	9	9	9	9	C
2.	*	*	0	0	1	0	0	0	0	0	0	0	C
			0	0	7	9	9	9	9	9	9	9	C
1.	0	0	0	0	8	0	0	0	0	0	0	0	C
	0	0	1	9	9	9	9	9	9	9	9	9	C
4.	*	0	2	0	0	0	0	0	0	0	0	0	C
		0	2	9	9	9	9	9	9	9	9	9	C
1.	0	0	3	0	0	0	0	0	0	0	0	0	C
	0	0	3	9	9	9	9	9	9	9	9	9	C
2.	*	0	4	0	0	0	0	0	0	0	0	0	C
		0	4	9	9	9	9	9	9	9	9	9	C
5.	*	0	5	0	0	0	0	0	0	0	0	0	C
		0	5	9	9	9	9	9	9	9	9	9	C
1.	0	0	6	0	0	0	0	0	0	0	0	0	C
	0	0	9	9	9	9	9	9	9	9	9	9	C
1.	0	1	0	0	0	0	0	0	0	0	0	0	C
	0	1	3	9	9	9	9	9	9	9	9	9	C
2.4.	*	2	0	0	0	0	0	0	0	0	0	0	C
	*	2	9	9	9	9	9	9	9	9	9	9	C
1.	0	3	0	0	0	0	0	0	0	0	0	0	C
	0	9	6	9	9	9	9	9	9	9	9	9	C
7.	*	9	7	7	0	0	0	0	0	0	0	0	C
		9	7	9	9	9	9	9	9	9	9	9	C
8.	*	9	7	8	0	0	0	0	0	0	0	0	C
	*	9	7	9	9	9	9	9	9	9	9	9	C
5.6.	*	9	8	0	0	0	0	0	0	0	0	0	C
		9	8	2	9	9	9	9	9	9	9	9	C
5.	*	9	9	0	0	0	0	0	0	0	0	0	C
		9	9	9	9	9	9	9	9	9	9	9	C
1.	1	0	0	0	0	0	1	0	0	0	0	0	C
	8	0	0	0	0	0	1	3	9	9	9	9	C
1.	1	0	0	0	0	0	3	0	0	0	0	0	C
	8	0	0	0	0	0	9	6	9	9	9	9	C
1.3.	1	0	0	0	0	1	0	0	0	0	0	0	C
	9	0	0	0	0	9	9	9	9	9	9	9	C
1.3.	1	0	0	0	9	0	0	0	0	0	0	0	C
	9	0	1	9	9	9	9	9	9	9	9	9	C
1.3.	1	0	3	0	0	0	0	0	0	0	0	0	C
	9	0	3	9	9	9	9	9	9	9	9	9	C
1.3.	1	0	6	0	0	0	0	0	0	0	0	0	C
	9	0	9	9	9	9	9	9	9	9	9	9	C
1.3.	1	1	0	0	0	0	0	0	0	0	0	0	C
	9	1	3	9	9	9	9	9	9	9	9	9	C
1.3.	1	3	0	0	0	0	0	0	0	0	0	0	C
	9	9	6	9	9	9	9	9	9	9	9	9	C
8.	1	9	7	8	0	0	0	0	0	0	0	0	C
	8	9	7	9	9	9	9	9	9	9	9	9	C

1. Fixed measure; 2. Fixed measure restricted distribution; 3. Variable measure; 4. Variable measure restricted distribution (not a GTIN); 5. Coupons (not a GTIN); 6. Refund Receipts (not a GTIN); 7. ISSN; 8. ISBN

7.7.2. Element Strings Represented in a GS1 Symbology using GS1 Application Identifiers

The Element Strings encoded in any GS1 Symbology that uses GS1 Application Identifiers (such as GS1-128, GS1 DataMatrix, GS1 DataBar, GS1 QR Code and GS1 Composite) are composed of one or more GS1 Application Identifiers and one or several data fields. The Application Identifier denotes the contents and structure of the respective data fields. Full details are contained in Section 3.

7.8. Secondary Data for specific Health Industry Products

Figures 7.8 - 1 and 7.8 - 2 show the correct data formats for secondary data for specific health industry products. If a column in Figure 7.8 - 3 is left blank, then that data format information is not used.

Figure 7.8 - 1

Format	Description
MM	two-digit expiration date month indicator (fixed length of two numeric digits)
YY	two-digit expiration date year indicator (fixed length of two numeric digits)
DD	two-digit expiration date day indicator (fixed length of two numeric digits)
HH	two-digit expiration date hour indicator (fixed length of two, G.M.T. format)
JJJ	three-digit expiration date Julian day indicator (fixed length of three numeric digits)
LOT	up to 13-digit alphanumeric lot number
L	1-digit link character (GTIN Check Digit)
QQ	two-digit quantity (fixed length of two numeric digits)
QQQQQ	five-digit quantity (fixed length of five numeric digits)

The data in Figure 7.8 - 2 is used in the example in Figure 7.8 - 3.

Figure 7.8 - 2

GTIN	10312345678903
Lot number	3C001
Link character	3
Expiration date	September 28, 1995, at 10 p.m.
Two-digit quantity	24
Five-digit quantity	00100

Quantity represents the quantity of items contained within the trade item where the inside item is assigned the GTIN **00312345678906**.

The data formats in Figure 7.8 - 3 show all combinations of the sub-fields possible within the Element String.


Figure 7.8 - 3

Row	Application Identifier	Quantity Format Digit	Quantity Format	Expiration Date Format Digit	Expiration Date Format	Lot Field	Link Digit	Example Data
1	22				MMYY	LOT	L	2209953C0013
2	22			2	MMDDYY	LOT	L	2220928953C0013
3	22			3	YYMMDD	LOT	L	2239509283C0013
4	22			4	YYMMDDHH	LOT	L	224950928223C0013
5	22			5	YYJJJ	LOT	L	225952713C0013
6	22			6	YYJJJHH	LOT	L	22695271223C0013
7	22			7		LOT	L	2273C0013
8	22	8	QQ		MMYY	LOT	L	2282409953C0013
9	22	8	QQ	2	MMDDYY	LOT	L	2282420928953C0013
10	22	8	QQ	3	YYMMDD	LOT	L	2282439509283C0013
11	22	8	QQ	4	YYMMDDHH	LOT	L	228244950928223C0013
12	22	8	QQ	5	YYJJJ	LOT	L	228245952713C0013
13	22	8	QQ	6	YYJJJHH	LOT	L	22824695271223C0013
14	22	8	QQ	7		LOT	L	2282473C0013
15	22	8	QQ			LOT	L	228243
16	22	9	QQQQQ		MMYY	LOT	L	2290010009953C0013
17	22	9	QQQQQ	2	MMDDYY	LOT	L	2290010020928953C0013
18	22	9	QQQQQ	3	YYMMDD	LOT	L	2290010039509283C0013
19	22	9	QQQQQ	4	YYMMDDHH	LOT	L	229001004950928223C0013
20	22	9	QQQQQ	5	YYJJJ	LOT	L	229001005952713C0013
21	22	9	QQQQQ	6	YYJJJHH	LOT	L	22900100695271223C0013
22	22	9	QQQQQ	7		LOT	L	2290010073C0013
23	22	9	QQQQQ			LOT	L	229001003

As an example, row 8 in Figure 7.8 - 3, using the required AI (01) and AI (22), would create the full string]C1 01 10312345678903 22 82409953C0013.

7.9. Processing of Data from a GS1 Symbology using GS1 Application Identifiers

Figure 7.9 - 1



This system logic holds true for any GS1 Symbology using GS1 Application Identifiers. The Symbology Identifiers listed in Figure 7.9-1 are:

1. Jc1 = GS1-128
2. Je0 = GS1 DataBar and GS1 Composite Symbols
3. Jd2 = GS1 DataMatrix
4. JQ3 = GS1 QR Code

7.9.1. General

Any GS1 Symbology using GS1 Application Identifiers may represent several Element Strings in concatenated form (see Section 5). For processing as shown in Figure 7.3 - 1, it is necessary to separate each Element String, which is performed by the processing routine illustrated in Figure 7.9 - 1.

7.9.2. Element Strings with Pre-Defined Lengths Using Application Identifiers

Representation of more than one Element String in a GS1 Symbology using GS1 Application Identifiers requires the use of a Separator Character between the different Element Strings to mark their end. This is normally the Function 1 Symbol Character (FNC1) or, in the case of some types of GS1 DataBar, is part of the symbology specification. For details, see Section 5.

However, in order to enable printing of shorter Bar Codes, some Element Strings have been pre-defined in length, so that their end is determined, and the FNC1 is not needed. These Element Strings are shown in the pre-defined table shown in Section 5.10.

7.9.3. The Function 1 Symbol Character (FNC1)

Only when used as a Separator Character is the Function 1 Symbol Character (FNC1) transmitted in the decoded data string as <GS> (ASCII character 29, seven-bit character set ISO 646). All Element Strings of variable length and those of fixed length not stated in the pre-defined table shown in Section 5.10 must be delimited when followed by another Element String in a single Bar Code. The delimiter shall be a Function 1 Symbol Character in GS1-128 Symbology, GS1 DataBar Expanded Versions and GS1 Composite Symbology and should be a Function 1 Symbol Character in GS1 DataMatrix Symbology and GS1 QR Code Symbology. A delimiter is not required at the end of the last Element String represented in a Bar Code or for certain AI combinations defined by the symbology specification (e.g., some types of GS1 DataBar).

7.9.4. National Healthcare Reimbursement Number (NHRN)

Some national or regional regulatory organizations may require pharmaceuticals and/or medical devices be identified with locally specific National Healthcare Reimbursement Numbers (NHRNs). For compliance with these national/regional regulatory or industry requirements where the GTIN does not meet current need, the trade item shall be identified with GTIN and AIs (710), (711), and (712) National Healthcare Reimbursement Number.

One or more NHRNs may be associated with a single GTIN and encoded within the appropriate GS1 Data Carrier in order to meet multiple market business needs. See Figure 7.9.4. - 1 for examples of multiple NHRNs.

Additional individual NHRN AIs can only be assigned by GS1 and only in response to a work request being submitted into the GSMP system.

Figure 7.9.4. - 1 Examples of Valid Messages

Element Strings in Message				Comment
AI 01	AI 710			GTIN Identification of a trade item + Country "A" NHRN
AI 01	AI 710	AI 711		GTIN Identification of a trade item + Country "A" NHRN + Country "B" NHRN
AI 01	AI 710	AI 711	AI 712	GTIN Identification of a trade item + Country "A" NHRN + Country "B" NHRN + Country "C" NHRN

7.10. Check Digit Calculations

7.10.1. Standard Check Digit Calculations for GS1 Data Structures

This algorithm is identical for all fixed length numeric GS1 Data Structures that require a Check Digit.

Figure 7.10.1 - 1

Digit Positions																		
GTIN-8											N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈
GTIN-12							N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂
GTIN-13						N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃
GTIN-14				N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃	N ₁₄	
17 digits		N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃	N ₁₄	N ₁₅	N ₁₆	N ₁₇
18 digits	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃	N ₁₄	N ₁₅	N ₁₆	N ₁₇	N ₁₈
Multiply value of each position by																		
	x3	x1	x3	x1	x3	x1	x3	x1	x3	x1	x3	x1	x3	x1	x3	x1	x3	
Accumulated results = sum																		
Subtract sum from nearest equal or higher multiple of ten = Check Digit →																		

Figure 7.10.1 - 2

Example of a Check Digit Calculation for the 18-Digit Field																		
Positions	N ₁	N ₂	N ₃	N ₄	N ₅	N ₆	N ₇	N ₈	N ₉	N ₁₀	N ₁₁	N ₁₂	N ₁₃	N ₁₄	N ₁₅	N ₁₆	N ₁₇	N ₁₈
Number without Check Digit	3	7	6	1	0	4	2	5	0	0	2	1	2	3	4	5	6	
Step 1: multiply by	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	
	3	1	3	1	3	1	3	1	3	1	3	1	3	1	3	1	3	
Step 2: add up results to sum	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=
	9	7	18	1	0	4	6	5	0	0	6	1	6	3	12	5	18	= 101
Step 3: Subtract sum from nearest equal or higher multiple of ten (110) = Check Digit (9)																		
Number with Check Digit	3	7	6	1	0	4	2	5	0	0	2	1	2	3	4	5	6	9

7.10.2. Check Digit Calculation for Price/Weight Fields

To increase the security of reading a price or weight from a Bar Code, the Check Digit for these fields is not only calculated according to the methods described in the previous section, but also according to the procedure described in this section.

The basic principle of the Check Digit calculation is that each digit position in a price/weight field is assigned a weighting factor. Weighting factors are **2-**, **3**, **5+**, and **5-**. Each weighting factor affects the particular calculation for the position concerned. The result of such a calculation is called a weighted product.

The figures that follow show the weighted products of the various weighting factors.

Figure 7.10.2 - 1

Weighting Factor 2										
Calculation rule: The digit is multiplied by 2. If the result has two digits, the tens digit is subtracted from the units digit. The units digit resulting is the weighted product.										
Digit	0	1	2	3	4	5	6	7	8	9
Weighted product	0	2	4	6	8	9	1	3	5	7

Figure 7.10.2 - 2

Weighting Factor 3										
Calculation rule: The digit is multiplied by 3. The unit's digit of the result is the weighted product.										
Digit	0	1	2	3	4	5	6	7	8	9
Weighted product	0	3	6	9	2	5	8	1	4	7

Figure 7.10.2 - 3

Weighting Factor 5+										
Calculation rule: The digit is multiplied by 5. The units digit and the tens digit of the result are added together. The result of this sum is the weighted product.										
Digit	0	1	2	3	4	5	6	7	8	9
Weighted product	0	5	1	6	2	7	3	8	4	9

Figure 7.10.2 - 4

Weighting Factor 5-										
Calculation rule: The digit is multiplied by 5. The tens digit of the result is subtracted from the result. The units digit of the result of this subtraction is the weighted product.										
Digit	0	1	2	3	4	5	6	7	8	9
Weighted product	0	5	9	4	8	3	7	2	6	1

7.10.3. Check Digit Calculation for the Four-Digit Price Field

Figure 7.10.3 - 1

Assigned Weighting Factors				
Digit position	1	2	3	4
Weighting factor	2-	2-	3	5-

- **Calculation step 1:** Determine the weighted product for each number in Positions One to Four according to the assigned weighting factors.
- **Calculation step 2:** Add the products of step 1.
- **Calculation step 3:** Multiply the result of step 2 by the factor 3. The unit's digit of the result is the Check Digit.

Figure 7.10.3 – 2

Example of a Check Digit Calculation					
Position of price field	1	2	3	4	
Assigned weighting factor	2-	2-	3	5-	
Amount	2	8	7	5	
Step 1: weighted product according to figure	4	5	1	3	
Step 2: sum	+	+	+	+	= 13
Step 3: multiply by 3					= 39

Unit position is the Check Digit



7.10.4. Check Digit Calculation for the Five-Digit Price Field

Figure 7.10.4 – 1

Assigned Weighting Factors					
Digit positions	1	2	3	4	5
Weighting factor	5+	2-	5-	5+	2-

- **Calculation step 1:** Determine the weighted product for each number in Positions one to five according to the assigned weighting factors.
- **Calculation step 2:** Add the products of step 1.
- **Calculation step 3:** Subtract the result from the nearest equal or higher multiple of 10.
- **Calculation step 4:** Take the result and search for the same number in the weighted product row of Figure 7.10.2 – 4. The Check Digit is the number in the digit row of the same column.

Figure 7.10.4 – 2

Example of a Check Digit Calculation						
Price field positions	1	2	3	4	5	
Assigned weighting factor	5+	2-	5-	5+	2-	
Amount	1	4	6	8	5	
Step 1: weighted product according to figure	5	8	7	4	9	
Step 2: sum	+	+	+	+	+	= 33
Step 3: result of subtraction (40 - 33)						= 7
Step 4: weighted product 7 in the figure weighting factor 5- shows number 6 to be the Check Digit.						

7.11. GTIN-12 and RCN-12 in a UPC-E Bar Code

Some of the GTIN-12 and RCN-12 number ranges beginning with the U.P.C. Prefix 0 may be represented in a small symbol called the UPC-E Bar Code (see section 2.1.).


The GTIN-12 or RCN-12 is condensed into a Bar Code consisting of six symbol character positions. For application processing, the GTIN-12 or RCN-12 must be transformed into its full length by the Bar Code reader software or by the application software. There is no six-digit UPC-E Bar Code.

It is possible to create false UPC-E Bar Codes if the encodation rules are not properly observed. Whether the digits represented in a UPC-E Bar Code can be expanded correctly to a GTIN-12 is verified by the following tests.

Test 1:

Verify the digits encoded in Positions 1 to 6 of the UPC-E Bar Code according to the diagram in Figure 7.11 - 1.

Figure 7.11 -1



Note: These UPC-E Bar Codes were valid in previous specifications. Provision for accepting them must be made during decoding only.

Test 2:

Expand the digits encoded in the UPC-E Bar Code to the first 11 digits of the full length GTIN-12, calculate the Check Digit, and compare it with the Check Digit decoded from the UPC-E Bar Code. If they do not match, it signifies an invalid symbol.

7.12. The GS1 Subset of International Standard ISO/IEC 646

The following figure 7.12 - 1 lists all characters allowed for use in GS1 Application Identifier (AI) Element Strings. It corresponds to ISO/IEC 646 Table 1. All other characters that are not listed here are not allowed in GS1 Application Identifier (AI) Element Strings.

Figure 7.12 - 1 GS1 AI Encodable Character Set

Graphic Symbol	Name	Hexa-decimal	Decimal	Graphic Symbol	Name	Hexa-decimal	Decimal
!	Exclamation mark	21	33	M	Capital letter M	4D	77
"	Quotation mark	22	34	N	Capital letter N	4E	78
%	Percent sign	25	37	O	Capital letter O	4F	79
&	Ampersand	26	38	P	Capital letter P	50	80
'	Apostrophe	27	39	Q	Capital letter Q	51	81
(Left parenthesis	28	40	R	Capital letter R	52	82
)	Right parenthesis	29	41	S	Capital letter S	53	83
*	Asterisk	2A	42	T	Capital letter T	54	84
+	Plus sign	2B	43	U	Capital letter U	55	85
,	Comma	2C	44	V	Capital letter V	56	86
-	Hyphen/Minus	2D	45	W	Capital letter W	57	87
.	Full stop	2E	46	X	Capital letter X	58	88
/	Solidus	2F	47	Y	Capital letter Y	59	89
0	Digit zero	30	48	Z	Capital letter Z	5A	90
1	Digit one	31	49	_	Low line	5F	95
2	Digit two	32	50	a	Small letter a	61	97
3	Digit three	33	51	b	Small letter b	62	98
4	Digit four	34	52	c	Small letter c	63	99
5	Digit five	35	53	d	Small letter d	64	100
6	Digit six	36	54	e	Small letter e	65	101
7	Digit seven	37	55	f	Small letter f	66	102
8	Digit eight	38	56	g	Small letter g	67	103
9	Digit nine	39	57	h	Small letter h	68	104
:	Colon	3A	58	i	Small letter i	69	105
;	Semicolon	3B	59	j	Small letter j	6A	106
<	Less-than sign	3C	60	k	Small letter k	6B	107
=	Equals sign	3D	61	l	Small letter l	6C	108
>	Greater-than sign	3E	62	m	Small letter m	6D	109
?	Question mark	3F	63	n	Small letter n	6E	110
A	Capital letter A	41	65	o	Small letter o	6F	111

Graphic Symbol	Name	Hexa-decimal	Decimal	Graphic Symbol	Name	Hexa-decimal	Decimal
B	Capital letter B	42	66	p	Small letter p	70	112
C	Capital letter C	43	67	q	Small letter q	71	113
D	Capital letter D	44	68	r	Small letter r	72	114
E	Capital letter E	45	69	s	Small letter s	73	115
F	Capital letter F	46	70	t	Small letter t	74	116
G	Capital letter G	47	71	u	Small letter u	75	117
H	Capital letter H	48	72	v	Small letter v	76	118
I	Capital letter I	49	73	w	Small letter w	77	119
J	Capital letter J	4A	74	x	Small letter x	78	120
K	Capital letter K	4B	75	y	Small letter y	79	121
L	Capital letter L	4C	76	z	Small letter z	7A	122


7.13. Determination of Century in Dates

Element Strings are available for the following types of dates:

- Production date: AI (11)
- Due date: AI (12)
- Packaging date: AI (13)
- Best before date (quality): AI (15)
- Expiration date (safety): AI (17)
- Date and time of production: AI (8008)

It is left to the discretion of the user to interpret a particular date type in the sense of his business practices. Such interpretation may change according to the product range for which a date is being applied.

Since the year data field consists of two positions, the century is established by following the procedure in Figure 7.13 - 1.



Note: The Element String can only specify a date in the range from 49 years in the past to 50 years in the future of the current year.



8. GS1 Standards Glossary of Terms

- GS1 Glossary Terms and Definitions
- GS1 Abbreviations
- Legacy (Retired) Terms

8.1. GS1 Glossary Terms and Definitions

The following glossary was updated for the Jan-2013 publication of this document. Please refer to the GS1 General Specification glossary in the GS1 GDD (<http://gdd.gs1.org/GDD/public/searchableglossary.asp>) for the latest version.

Term	Definition
2-Dimensional Symbology	Optically readable symbols that must be examined both vertically and horizontally to read the entire message. Two-dimensional symbols may be one of two types: matrix symbols and multi-row symbols. Two dimensional symbols have error detection and may include error correction features.
Active Potency	Represents the measured actual (“Active”) potency of a biologic such as haemophilia products.
Add-On Symbol	A bar code used to encode information supplementary to that in the main bar code.
Adjacent Symbols	Multiple bar codes placed next to one another without infringing on quiet zones.
AIDC Data Validation	Verification of scanned/read data from bar codes or RFID tags to determine whether it meets the application rules for system logic and consistency and/or a particular user's requirements, prior to processing in applications.
alphanumeric (an)	Describes a character set that contains alphabetic characters (letters), numeric digits (numbers), and other characters, such as punctuation marks.
Aperture	A physical opening that is part of the optical path in a device such as a scanner, photometer, or camera. Most apertures are circular, but they may be rectangular or elliptical.
Asset Type	A component of the Global Returnable Asset Identifier (GRAI) assigned by the owner of the GS1 Company Prefix to create a unique GRAI.
Attribute	An Element String that provides additional information about an entity identified with a GS1 Identification Key, such as Batch Number associated with a Global Trade Item Number (GTIN).
autodiscrimination	The capability of a reader to automatically recognise and decode multiple bar code symbologies.
Automatic Identification and Data Capture	A technology used to automatically capture data. AIDC technologies include bar codes, smart cards, biometrics and RFID.
auxiliary patterns	Components of the EAN/UPC Symbology. The centre guard bar pattern, the left guard bar pattern, and the right guard bar pattern are examples of these.
bar code	A symbol that encodes data into a machine readable pattern of adjacent, varying width, parallel, rectangular dark bars and pale spaces.
Bar Code Verification	The assessment of the printed quality of a bar code based on ISO/IEC standards using ISO/IEC compliant bar code verifiers.
bar gain/loss	The increase/decrease in bar width due to effects of the reproduction and printing processes.
Batch / Lot	The batch or lot number associates an item with information the manufacturer considers relevant for traceability of the trade item. The data may refer to the trade item itself or to items contained in it.
Bearer Bars	Bar abutting the tops and bottoms of the bars in a bar code or a frame surrounding the entire symbol, intended to equalize the pressure exerted by the printing plate over the entire surface of the symbol and/or to prevent a short scan by the bar code reader.

Term	Definition
brand owner	The party that is responsible for allocating GS1 System Identification Keys. The administrator of a GS1 Company Prefix.
Carrier	The party that provides freight transportation services or a physical or electronic mechanism that carries business information.
Character Set 39	The set of characters found in ISO 646: Unique Graphic Character Allocations which includes numeric, alphabetic upper-case, plus the characters “#”, “-“, and “/”.
Character Set 82	The set of characters found in ISO 646: Unique Graphic Character Allocations which includes numeric, alphabetic upper-case and lower-case, plus twenty special characters but excluding “space”
Check Digit	A final digit calculated from the other digits of some GS1 Identification Keys. This digit is used to check that the data has been correctly composed. (See GS1 Check Digit Calculation.)
Company Number	A component of the GS1 Company Prefix.
Component/Part	An item that is intended to undergo at least one further transformation process to create finished goods for the purpose of downstream consumption
Component/Part identifier	The unique identifier for a Components / Parts, comprising a GS1 Company Prefix and a Component / Part reference
Composite Component	This term is used to refer to the 2D symbol component within a composite symbol.
Composite Symbology	A GS1 System composite symbol consists of a linear component (encoding the item's primary identification) associated with an adjacent Composite Component (encoding attribute data, such as a batch number or expiration date). The composite symbol always includes a linear component so that the primary identification is readable by all scanning technologies, and so that imager scanners can use the linear component as a finder pattern for the adjacent 2D Composite Component. The composite symbol always includes one of three multi-row 2D Composite Component versions (e.g., CC-A, CC-B, CC-C) for compatibility with linear- and area-CCD scanners and with linear and rastering laser scanners.
Concatenation	The representation of several Element Strings in one bar code.
Configuration Level	Assignment or grouping of trade items that includes one or more of the same trade item.
Consignment	A grouping of logistic or transport units assembled by a freight forwarder or carrier to be transported under one transport document (e.g. HWB)
Country Subdivision	Principle administrative divisions, or similar areas, of a country included in ISO 3166-1. Examples are a state in the US, a region in France, a canton in Swiss.
Coupon	A voucher that can be redeemed at the Point-of-Sale for a cash value or free item.
Coupon Extended Bar Code	A supplemental bar code, used only in North America, that can be printed on a coupon to provide additional information, such as Offer Codes, expiration dates, and household identification numbers.
Coupon Instance ID	The identification of a unique instance of a digital coupon.
Coupon Issuer	Party issuing the coupons, bearing the commercial and financial responsibility for the coupons.
Coupon-12	A 12-digit GS1 System Restricted Circulation Number for coupons structured according to the rules defined in the target market.

Term	Definition
Coupon-13	A 13-digit GS1 System Restricted Circulation Number for coupons structured according to the rules defined in the target market .
Customer	The party that receives, buys, or consumes an item or service.
data character	A letter, digit, or other symbol represented in the data field(s) of an Element String.
Data Matrix	A standalone, two-dimensional matrix symbology that is made up of square modules arranged within a perimeter finder pattern. Data Matrix ISO version ECC 200 is the only version that supports GS1 System identification numbers, including Function 1 Symbol Character. Data Matrix Symbols are read by two-dimensional imaging scanners or vision systems.
data field	A field that contains a GS1 Identification Key, an RCN, or attribute information
data titles	Data titles are the abbreviated descriptions of Element Strings which are used to support manual interpretation of bar codes.
Default Front	The side of a retail consumer trade item that is used as the starting point to capture dimensional attributes for the purpose of data alignment.
Digital Coupon	A digital coupon is an electronic presentation, that is distributed and presented without manifesting as “paper” or in other hard-copy form, and that can be exchanged for a financial discount or for loyalty points when making a purchase.
Direct mode	Mobile device information retrieval function when the bar code contains either the address (URL) of the content or service, or the content itself, in-line.
Direct Part Marking	Direct part marking refers to the process of marking a symbol on an item using an intrusive or non-intrusive method.
direct print	A process in which the printing apparatus prints the symbol by making physical contact with a substrate (e.g., flexography, ink jet, dot peening).
Document Type	A component of a Global Document Type Identifier (GDTI) assigned by the brand owner to create a unique GDTI.
Dynamic Assortment	A standard trade item grouping that comprises a fixed count of a changing assortment of two or more different retail consumer trade items, each identified with a unique GTIN. The retailer has accepted that the supplier may change the assortment without any prior notice.
EAN/UPC Composite Symbology Family	A family of bar codes comprising the UPC-A Composite Symbology, UPC-E Composite Symbology, EAN-8 Composite Symbology, and EAN-13 Composite Symbology.
EAN/UPC Symbology	A family of bar codes including EAN-8, EAN-13, UPC-A, and UPC-E Bar Codes. Although UPC-E Bar Codes do not have a separate symbology identifier, they act like a separate symbology through the scanning application software. See also EAN-8 Bar Code, EAN-13 Bar Code, UPC-A Bar Code, and UPC-E Bar Code.
EAN-8 Bar Code	A bar code of the EAN/UPC Symbology that encodes GTIN-8 or RCN-8.
EAN-13 Bar Code	A bar code of the EAN/UPC Symbology that encodes GTIN-13, Coupon-13, RCN-13, and VMN-13.
EANCOM	The GS1 standard for Electronic Data Interchange (EDI) that is a detailed implementation guideline of the UN/EDIFACT standard messages using the GS1 Identification Keys.
Electronic Commerce	The conduct of business communications and management through electronic methods, such as Electronic Data Interchange (EDI) and automated data collection systems.
Electronic Message	A composition of Element Strings from scanned data and transaction information assembled for data validation and unambiguous processing in a user application.

Term	Definition
Electronic Product Code	An identification scheme for universally identifying physical objects (e.g. trade items, assets, and locations) via RFID tags and other means. The standardised EPC data consists of an EPC (or EPC Identifier) that uniquely identifies an individual object, as well as an optional Filter Value when judged to be necessary to enable effective and efficient reading of the EPC tags.
Element	A single bar or space of a bar code.
Element String	The combination of a GS1 Application Identifier and GS1 Application Identifier Data Field.
Encounter	Situation on the uninterrupted course of which one or more Healthcare Provider or Individual Providers delivers healthcare services to a Subject of Care
Enhanced Level of AIDC Marking (for Regulated Healthcare Trade Items)	A level within a graduated system of AIDC trade item marking that provides GTIN plus attribute information
Episode of Care	An encounter or series of encounters related to the detection and subsequent care for a particular healthcare requirement.
even parity	A characteristic of the encodation of a symbol character whereby the symbol character contains an even number of dark modules.
Extended Packaging	An approach to giving consumers access to additional information or services about trade items through their mobile device. It is the ability to retrieve additional information about the trade item through mobile devices or in general between link a trade item with virtual information or services.
Extension digit	The first digit within the SSCC (Serial Shipping Container Code) which is allocated by the user and is designed to increase the capacity of the SSCC.
Final filled consumer trade item package	A trade item as it is distributed to the consumer or end-user.
finished consumer trade item	A product after all production and packaging processes are completed and it is ready for distribution to the end consumer.
fixed length	Term used to describe a data field in an Element String with an established number of characters.
Fixed Measure Trade Item	An item always produced in the same pre-defined version (e.g., type, size, weight, contents, design) that may be sold at any point in the supply chain.
Freight Forwarder	The party that arranges the carriage of goods including connected services and/or associated formalities on behalf of the shipper (consignor) or consignee.
Fresh Foods	Trade items in the following product categories: fruits, vegetables, meats, seafood, bakery and ready to serve food such as cheeses, cold cooked or cured meats, and salad, etc. Fresh Foods is defined as food that is not preserved by canning, dehydration, freezing or smoking.
Full String	The data transmitted by the bar code reader from reading a data carrier, including the symbology identifier as well as the encoded data.
Function 1 Symbol Character (FNC1)	A symbology character used in some GS1 data carriers for specific purposes.
General Distribution Scanning	Scanning environments that include bar coded trade items packaged for transport, logistic units, assets, and location tags.
General Retail Consumer Trade Item	A retail consumer trade item identified with a GTIN-13, GTIN-12 or GTIN-8 utilizing omnidirectional linear bar codes that can be scanned by high-volume, omnidirectional scanners.

Term	Definition
Global Electronic Party Information Registry (GEPiR)	A web-browser interface and a machine to machine set of protocols for GS1 Member Organization (MO) membership databases to communicate company information for selected GS1 Keys including information about the allocation of the GS1 Company Prefixes used to create GS1 Keys and/or individually assigned GS1 Keys. Created in 1997 as a tool for MO staff, GEPiR's initial scope was to provide a search engine for Member addresses and phone numbers using MO GS1 Company Prefix (GCP) databases as the source of information. In more recent versions, GEPiR also provides a very limited set of information on Parties (GLNs) and Trade Items (GTINs).
GINC	See Global Identification Number for Consignment.
GLN Extension Component	The GLN extension component is used to identify internal physical locations within a location which is identified with a GLN (stores, factories, buildings, etc.).
Global Coupon Number (GCN)	A GS1 Identification Key that provides a globally unique identification for a coupon, with an optional serial number
Global Document Type Identifier (GDTI)	The GS1 Identification Key used to identify a document type. The key comprises a GS1 Company Prefix, Document Type, Check Digit, and optional serial number.
Global Identification Number for Consignment	The GS1 Identification Key used to identify a logical grouping of logistic or transport units that are assembled to be transported under one transport document (e.g. HWB). The key comprises a GS1 Company Prefix and the Freight Forwarder's or Carrier's transport reference.
Global Individual Asset Identifier (GIAI)	The GS1 Identification Key used to identify an Individual Asset. The key comprises a GS1 Company Prefix and Individual Asset Reference.
Global Location Number (GLN)	The GS1 Identification Key used to identify physical locations or parties. The key comprises a GS1 Company Prefix, Location Reference, and Check Digit.
Global Returnable Asset Identifier (GRAI)	The GS1 Identification Key used to identify Returnable Assets. The key comprises a GS1 Company Prefix, Asset Type, Check Digit, and optional serial number.
Global Service Relation Number (GSRN)	The Global Service Relation Number is the GS1 Identification Key used to identify the relationship between an organisation offering services and the recipient or provider of services. The key is comprised of a GS1 Company Prefix, Service Reference and Check Digit.
Global Shipment Identification Number (GSIN)	The GS1 Identification Key used to identify a logical grouping of logistic or transport units that are assembled by the consignor (seller) for a transport shipment from that consignor to one consignee (buyer) referencing a despatch advice and/or BOL. The key comprises a GS1 Company Prefix, Shipper Reference and Check Digit.
Global Standards Management Process	GS1 created the Global Standards Management Process (GSMP) to support standards development activity for the GS1 System. The GSMP uses a global consensus process to develop supply chain standards that are based on business needs and user-input
Global Trade Item Number (GTIN)	The GS1 Identification Key used to identify trade items. The key comprises a GS1 Company Prefix, an Item Reference and Check Digit.
GS1 AIDC data carrier	A means to represent data in a machine readable form; used to enable automatic reading of the Element Strings as specified for use by GS1.
GS1 Application Identifier	The field of two or more digits at the beginning of an Element String that uniquely defines its format and meaning.
GS1 Application Identifier data field	The data used in a business application defined by one application identifier.

Term	Definition
GS1 B2C Trusted Source of Data (TSD)	A GS1 managed network concept that leverages GTIN (product identification) and GDSN (product information) and would support the communication of authentic product data provided by brand owners to retailers, internet application providers, government, and consumers and shoppers using internet and mobile devices (phones, laptops, etc).
GS1 Check Digit Calculation	An algorithm used by the GS1 System for the calculation of a Check Digit to verify accuracy of data. (e.g. Modulo 10 check digit, Price check digit).
GS1 Common Currency Coupon Code	An identification number for coupons issued in a common currency area (e.g., the euro currency) that uses the Coupon Code-13 Data Structure.
GS1 Company Prefix	Part of the GS1 System identification number consisting of a GS1 Prefix and a Company Number, both of which are allocated by GS1 Member Organisations. See also U.P.C. Company Prefix. GS1 Member Organisations assign GS1 Company Prefixes to entities that administer the allocation of GS1 System identification numbers. These entities may be, for example, commercial companies, not for profit organisations, governmental agencies, and business units within organisations. Criteria to qualify for the assignment of a GS1 Company Prefix are set by the GS1 Member Organisations.
GS1 DataBar Composite Symbology Family	A family of symbols comprising all the GS1 DataBar bar codes when an accompanying Composite Component is printed directly above the linear component.
GS1 DataBar Expanded Bar Code	A bar code that encodes any GS1 Identification Key plus Attribute data, such as weight and "best before" date, in a linear symbol that can be scanned omnidirectionally by suitably programmed Point-of-Sale scanners.
GS1 DataBar Expanded Stacked Bar Code	A bar code that is a variation of the GS1 DataBar Expanded Bar Code that is stacked in multiple rows and is used when the normal symbol would be too wide for the application.
GS1 DataBar Limited Bar Code	A bar code that encodes a GTIN with a leading digit of zero or Indicator digit of one in a linear symbol; for use on small items that will not be scanned at the Point-of-Sale.
GS1 DataBar Omnidirectional Bar Code	A bar code that encodes a GTIN. It is designed to be read by omnidirectional scanners.
GS1 DataBar	A family of bar codes, including GS1 DataBar Omnidirectional; GS1 DataBar Stacked Omnidirectional; GS1 DataBar Expanded; GS1 DataBar Expanded Stacked GS1 DataBar Truncated, GS1 DataBar Limited, and GS1 DataBar Stacked symbols.
GS1 DataBar Retail POS Family	The members of the GS1 DataBar Symbology family designed to be read in segments by omnidirectional scanners at retail POS: GS1 DataBar Omnidirectional; GS1 DataBar Stacked Omnidirectional; GS1 DataBar Expanded; GS1 DataBar Expanded Stacked.
GS1 DataBar Stacked Bar Codel	A bar code that is a variation of the GS1 DataBar Truncated Bar Code that is stacked in two rows and is used when the GS1 DataBar Truncated Bar Code would be too wide for the application.
GS1 DataBar Stacked Omnidirectional Bar Code	A bar code that is a variation of the GS1 DataBar Symbology that is stacked in two rows and is used when the GS1 DataBar Omnidirectional Symbol would be too wide for the application. It is designed to be read by omnidirectional checkout scanners.
GS1 DataBar Truncated Bar Code	A bar code that is a truncated version of the GS1 DataBar Omnidirectional Bar Code. It is used when the GS1 DataBar Omnidirectional Bar Code would be too tall for small item marking applications. It is not intended for omnidirectional checkout scanning.
GS1 DataMatrix	GS1 implementation specification for use of Data Matrix

Term	Definition
GS1 Global Data Dictionary	A repository tool used to record GS1 member standards agreements on business terms and definitions used by all business units.
GS1	Based in Brussels, Belgium, and Princeton, USA, it is the organisation that manages the GS1 System. Its members are GS1 Member Organisations.
GS1 Identification Key	A numeric or alphanumeric data field defined by GS1 to ensure the global, unambiguous uniqueness of the identifier in the open demand or supply chain.
GS1 Identification Keys	A globally managed system of numbering used by all GS1 Business Units to identify trade items, logistic units, locations, legal entities, assets, service relationships, consignment, shipments and more. Any identification number that combines GS1 member company identifiers (GS1 Company Prefix) with standards based rules for allocating reference numbers is a key.
GS1 Member Organisation	A member of GS1 that is responsible for administering the GS1 System in its country (or assigned area). This task includes, but is not restricted to, ensuring brand owners make correct use of the GS1 System, have access to education, training, promotion and implementation support and have access to play an active role in GSMP.
GS1 Prefix	A number with two or more digits, administered by GS1 that is allocated to GS1 Member Organisations or for Restricted Circulation Numbers.
GS1 QR Code	GS1 implementation specification for use of QR Code
GS1 Symbologies using GS1 Application Identifiers	All GS1 endorsed bar code symbologies that can encode more than a GTIN namely GS1-128, GS1 DataMatrix, GS1 DataBar and Composite).
GS1 System	The specifications, standards, and guidelines administered by GS1.
GS1 XML	The GS1 standard for Extensible Markup Language schemas providing users with a global business messaging language of e-business to conduct efficient Internet-based electronic commerce.
GS1-128 Symbology	A subset of Code 128 that is utilised exclusively for GS1 System data structures.
GS1-8 Prefix	A one-, two-, or three-digit index number, administered by GS1, that is allocated to GS1 Member Organisations for the creation of GTIN-8s or for Restricted Circulation Numbers (see RCN-8).
GSIN	See Global Shipment Identification Number.
GTIN Application Format	A format for a GTIN-8, GTIN-12, or GTIN-13 used when a GTIN application uses a fixed field length, for example, when a GTIN-13 is encoded in symbology using Application Identifier (01).
GTIN Plus Attribute(s) Flag	A trigger in systems to determine if additional processing is required by a bar code user for a given GTIN.
GTIN-8	The 8-digit GS1 Identification Key composed of a GS1-8 Prefix, Item Reference, and Check Digit used to identify trade items.
GTIN-12	The 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items.
GTIN-13	The 13-digit GS1 Identification Key composed of a GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.
GTIN-14	The 14-digit GS1 Identification Key composed of an Indicator digit (1-9), GS1 Company Prefix, Item Reference, and Check Digit used to identify trade items.
Guard Bar Pattern	An auxiliary pattern of bars and spaces corresponding to start or stop patterns in bar code symbologies, and serving to separate the two halves of EAN-8, EAN-13, and UPC-A Symbols.

Term	Definition
Hanging Item	Any retail consumer trade item that is normally presented in the store in a hanging position.
Healthcare Primary Packaging	The first level of packaging for the product marked with an AIDC data carrier either on the packaging or on a label affixed to the packaging. For non-sterile packaging, the first level of packaging can be the packaging in direct contact with the product. For sterile packaging, the first level of packaging can be any combination of the sterile packaging system, May consist of a single item or group of items for a single therapy such as a Kit. For packaging configurations that include a retail consumer trade item, primary packaging is a packaging level below the retail consumer trade item.
Healthcare Provider	An organisation or facility that delivers healthcare to a Subject of Care. Corresponds to "Care Delivery Organisation", "Healthcare Organisation", etc
Healthcare Secondary Packaging	A level of packaging marked with an AIDC carrier that may contain one or more primary packages or a group of primary packages containing a single item.
Highest Level of AIDC Marking (for Regulated Healthcare Trade Items)	A level within a graduated system of AIDC trade item marking that provides GTIN, serialization, and potentially other attribute information.
House Way Bill Number	A freight forwarder's document used mainly as a control for the goods within the freight forwarder's own service system.
Human Readable Interpretation(HRI)	Characters, such as letters and numbers, which can be read by persons and are encoded in GS1 AIDC data carriers confined to a GS1 standard structure and format. The Human Readable Interpretation is a one-to-one illustration of the encoded data. However Start, Stop, shift and function characters, as well as the Symbol Check Character, are not shown in the human readable interpretation.
Identification number	A numeric or alphanumeric field intended to enable the recognition of one entity versus another.
Indicator	A digit from 1 to 9 in the leftmost position of the GTIN-14.
Indirect mode	Mobile device information retrieval function when the code contains an identifier, which needs to be resolved to obtain the content or service. Resolving an identifier means looking it up, typically at a network service, to determine the corresponding content or service.
Individual Asset	An entity that is part of the inventory of assets for a given company. (See also Returnable Asset.)
Individual Asset Reference	A component of the Global Individual Asset Identifier (GIAI) assigned by the brand owner to create a unique GIAI.
Individual Provider	Any person who provides or is a potential provider of a health care service to a Subject of Care
Inner Trade Item Grouping	Intermediate package of multiples of the same trade item or a pre-defined assortment of trade items. An inner trade item grouping may or may not be sold at POS. (In some regions may also be referred to as Inner Pack).
Interleaved 2 of 5 Symbology	Bar code symbology used for the ITF-14 Bar Code.
Inverse Exponent	The Application Identifier digit that denotes the implied decimal point position in an Element String.
Item Reference	A component of the Global Trade Item Number (GTIN) assigned by the brand owner to create a unique GTIN.
ITF Symbology	See Interleaved 2 of 5 Symbology.

Term	Definition
ITF-14 Bar Code	ITF-14 (A subset of Interleaved 2-of-5) Bar Codes carry GTINs only on trade items that are not expected to pass through the Point-of-Sale.
Kit	A collection of different regulated healthcare items assembled for use in a single therapy.
Leading Zero(s)	Digits (always zeroes) which must be placed in the leftmost position(s) of a data string when GTIN-8, GTIN-12, or GTIN-13 are encoded in an GS1 AIDC data carrier that requires 14-digits (see also GTIN Application Format) or when used for the same intent in other data structures such as but not limited to Extended Coupon Codes, GRAI.
Levels of AIDC Marking	A graduated system of AIDC marking. The graduated system is defined as minimum, enhanced and highest levels of AIDC marking.
Linear Bar Code	Bar code symbology using bars and spaces in one dimension.
Local Assigned Code	A particular use of the UPC-E Bar Code for restricted distribution.
Location Reference	A component of a Global Location Number (GLN) assigned by the brand owner to create a unique GLN.
Logistic measures	Measures indicating the outside dimensions, total weight, or volume inclusive of packing material of a logistic unit. Also known as gross measures.
Logistic unit	An item of any composition established for transport and/or storage that needs to be managed through the supply chain. It is identified with an SSCC.
Loose Produce	Fruits and vegetables which are delivered to the store loose, in boxes or cases, and then put into a bag or selected individually by the customer for purchase.
Magnification	Different sizes of bar codes based on a nominal size and a fixed aspect ratio; stated as a percentage or decimal equivalent of a nominal size.
Measure verifier-digit	A digit calculated from the measure field of a Variable Measure Number encoded using the EAN/UPC Symbology. Used to check that the data has been correctly composed.
Minimum Level of AIDC Marking (for Regulated Healthcare Trade Items)	A level within a graduated system of AIDC trade item marking that provides GTIN with no attribute information.
Module	The narrowest nominal width unit of measure in a bar code. In certain symbologies, element widths may be specified as multiples of one module. Equivalent to X-dimension.
Modulo 10	The name of the algorithm – a simple checksum formula in the public domain – used to create a check digit for those GS1 Identification Keys that require one.
Modulo 103 GS1-128 Symbol Check Character	A number, which results from a modulo calculation, that is encoded in the GS1-128 Bar Code as a self-checking symbol character. It is created automatically by software as a symbol overhead character and is not expressed in the Human Readable Interpretation.
National Healthcare Reimbursement Number (NHRN)	National and/or regional identification numbers used on pharmaceutical and/or medical devices where required by national or regional regulatory organizations for product registration purposes and/or for the management of healthcare provider reimbursement.
Natural Base	The side of a non-retail consumer trade item package that is used as a reference point for capturing dimensional attributes for the purpose of data alignment.
Non-GTIN Packs	A packaging level for trade items where there is no trading partner requirement for GTIN identification. If a GTIN is required, then this item becomes a retail consumer trade item or standard trade item grouping.

Term	Definition
Non-HRI Text	Characters such as letters and numbers that can be read by persons and may or may not be encoded in GS1 AIDC data carriers and are not confined to a structure and format based on GS1 standards (e.g., a date code expressed in a national format that could be used to encode a date field in a GS1 AIDC data carrier, brand owner name, consumer declarations).
Object Class	Similar to a stock keeping unit SKU or trade item level.
Odd parity	A characteristic of the encodation of a symbol character whereby the symbol character contains an odd number of dark modules.
Omnidirectional Linear Bar Code	A linear bar code symbol designed to be omnidirectionally read in segments by suitably programmed high-volume Omnidirectional Point-of-Sale (POS) scanners.
Packaging Component	Entities such as bottles, caps, and labels to package a consumer trade item.
Packaging Component Number	GTIN attribute used to establish a relationship between a finished consumer trade item and packaging components.
Payment slip	The end customer's notification of a demand for payment for a billable service (e.g., utility bill) comprising an amount payable and payment conditions.
Platform	Pallet or slip sheet or other device used to store or move a unit load, whether a logistics unit or a GTIN.
Point-of-Care (POC)	Dispensing or use of a non-retail, regulated healthcare pharmaceutical or medical device to a patient based on right product, dose, and route of administration
Point-of Sale (POS)	Refers to the retail checkout where omnidirectional bar codes must be used to enable very rapid scanning or low volume checkout where linear or 2D matrix bar codes are used with image-based scanners.
Price check digit	A digit calculated from the price element of a Variable Measure Number encoded using the EAN/UPC Symbology. Used to check that the data has been correctly composed.
Price verifier digit	See Price check digit.
Primary bar code	The bar code containing the identification number of the item (e.g. GTIN, SSCC). Used to determine the placement of any additional bar code information.
Quiet Zone	A clear space which precedes the Start Character of a bar code and follows the Stop Character. Formerly referred to as "Clear Area" or "Light Margin".
Quiet Zone Indicator	A greater than (>) or less than (<) character, printed in the human readable field of the bar code, with the tip aligned with the outer edge of the Quiet Zone.
QR Code	A two-dimensional matrix symbology consisting of square modules arranged in a square pattern. The symbology is characterized by a unique finder pattern located at three corners of the symbol. QR Code Version 2005 is the only version that supports GS1 System identification numbers, including Function 1 Symbol Character. QR Code Symbols are read by two-dimensional imaging scanners or vision systems.
Radio frequency	Any frequency within the electromagnetic spectrum associated with radio wave propagation. When a radio frequency current is supplied to an antenna, an electromagnetic field is created that then is able to propagate through space. Many wireless technologies are based on radio frequency field propagation.
Radio Frequency Identification (RFID)	A data carrier technology that transmits information via signals in the radio frequency portion of the electromagnetic spectrum. A Radio Frequency Identification system consists of an antenna and a transceiver, which read the radio frequency and transfer the information to a processing device, and a transponder, or tag, which is an integrated circuit containing the radio frequency circuitry and information to be transmitted.

Term	Definition
RCN-8	An 8-digit Restricted Circulation Number (see Restricted Circulation Number) beginning with GS1-8 Prefix 0 or 2.
RCN-12	A 12-digit Restricted Circulation Number (see Restricted Circulation Number).
RCN-13	A 13-digit Restricted Circulation Number (see Restricted Circulation Number).
Refund Receipt	A voucher produced by equipment handling empty containers (bottles and crates).
Regulated Healthcare Retail Consumer Trade Item	A regulated healthcare trade item to be sold to the end consumer at a regulated healthcare retail Point-of Sale (Pharmacy). They are identified with a GTIN-13, GTIN-12 or GTIN-8 utilizing linear or 2D matrix bar codes that can be scanned by image-based scanners.
Regulated Healthcare Non-Retail Consumer Trade Item	A consumer trade item not intended for scanning at POS and identified with a GTIN-14, GTIN-13, GTIN-12 or GTIN-8 utilizing linear or 2D matrix bar codes that can be scanned by image-based scanners.
Regulated Healthcare Trade Item	Pharmaceuticals or medical devices that are sold or dispensed in a controlled environment (e.g. retail pharmacy, hospital pharmacy).
Restricted Circulation Number (RCN)	Signifies a GS1 identification number used for special applications in restricted environments, defined by the local GS1 Member Organisation (e.g., restricted within a country, company, industry). They are allocated by GS1 for either internal use by companies or to GS1 Member Organisations for assignment based on business needs in their country (e.g., variable measure product identification, couponing).
Retailer Zero-Suppression Code	A group of ID numbers (separate from Local Assigned Codes), that enable the use of UPC-E Bar Codes in a closed system environment (not for open supply chain applications).
Returnable Asset	A reusable entity owned by a company that is used for transport and storage of goods. It is identified with a GRAI.
Scanner	An electronic device to read bar code and convert them into electrical signals understandable by a computer device.
Separator Character	Function 1 Symbol Character used to separate certain concatenated Element Strings, dependent on their positioning in the GS1 Bar Codes.
Serial number	A code, numeric or alphanumeric, assigned to an individual instance of an entity for its lifetime. Example: Microscope model AC-2 with serial number 1234568 and microscope model AC-2 with serial number 1234569. A unique individual item may be identified with the combined Global Trade Item Number (GTIN) and serial number.
Serial Reference	A component of the Serial Shipping Container Code (SSCC) assigned by the brand owner to create a unique SSCC.
Serial Shipping Container Code	The GS1 Identification Key used to identify logistics units. The key comprises an Extension digit, GS1 Company Prefix, Serial Reference, and Check Digit.
Service Reference	A component of the Global Service Relation Number (GSRN) assigned by the brand owner to create a unique GSRN.
Service Relation Instance Number	An attribute to the GSRN which allows to distinguish different encounters during the same episode, or the reuse of the same GSRN in different episodes.
Shipment	A grouping of logistics and transport units assembled and identified by the seller (sender) of the goods travelling under one despatch advice and/or Bill of Lading to one customer (recipient).
Short Life Items	An item, preparation or reconstituted product with limited use / shelf life, such as in healthcare a cytotoxic medicine, that has undergone some manipulation, such as addition of a diluent, in order to make it administerable to a specified patient.

Term	Definition
Single Shipping / Retail Consumer Trade Item	A retail consumer trade item that is also regarded as a shipping item and is one to a carton (e.g. a bicycle or a television).
Special characters	Special characters that are designated by the symbology specification.
Standard trade item grouping	A standard composition of trade item(s) that is not intended for Point-of-Sale scanning. They are identified with a GTIN-14, GTIN-13, or GTIN-12.
Sterile Packaging System	A combination of the sterile barrier system (the minimum package that prevents ingress of microorganisms and allows aseptic presentation of the product at the point of use) and the protective packaging (configuration of materials designed to prevent damage to the sterile barrier system and its contents until the point of use).
Substrate	The material on which a bar code is printed.
Subject of Care	Any person who uses or is a potential user of a health care service, subjects of care may also be referred to as patients or health care consumers
Supplier	The party that produces, provides, or furnishes an item or service.
Symbol	The combination of symbol characters and features required by a particular symbology, including Quiet Zone, Start and Stop Characters, data characters, and other auxiliary patterns, which together form a complete scannable entity; an instance of a symbology and a data structure.
Symbol character	A group of bars and spaces in a symbol that is decoded as a single unit. It may represent an individual digit, letter, punctuation mark, control indicator, or multiple data characters.
Symbol Check Character	A symbol character or set of bar/space patterns included within a GS1-128 or GS1 DataBar Symbol, the value of which is used by the bar code reader for the purpose of performing a mathematical check to ensure the accuracy of the scanned data. It is not shown in Human Readable Interpretation. It is not input to the bar code printer and is not transmitted by the bar code reader.
Symbol Contrast	An ISO/IEC 15416 parameter that measures the difference between the largest and smallest reflectance values in a Scan Reflectance Profile (SRP).
Symbology	A defined method of representing numeric or alphabetic characters in a bar code; a type of bar code.
Symbology element	A character or characters in a bar code used to define the integrity and processing of the symbol itself (e.g., start and stop patterns). These elements are symbology overhead and are not part of the data conveyed by the bar code.
Symbology identifier	A sequence of characters generated by the decoder (and prefixed to the decoded data transmitted by the decoder) that identifies the symbology from which the data has been decoded.
Trade item	Any item (product or service) upon which there is a need to retrieve pre-defined information and that may be priced, or ordered, or invoiced at any point in any supply chain.
Trade measures	Net measures of Variable Measure Trade Items as used for invoicing (billing) the trade item.
Truncation	Printing a symbol shorter than the symbology specification's minimum height recommendations. Truncation can make the symbol difficult for an operator to scan.
U.P.C. Company Prefix	A special representation of a GS1 Company Prefix constructed from a U.P.C. Prefix and a Company Number. The U.P.C. Company Prefix is only used to create GTIN-12, Coupon-12, RCN-12, and VMN-12, which are encoded in a UPC-A Bar Code.

Term	Definition
U.P.C. Prefix	A special representation of the GS1 Prefixes '00 – 09' with the leading zero removed. Used when representing the GTIN-12, Coupon-12, RCN-12, and VMN-12 in a UPC-A Bar Code.
Unit Load	One or more transport packages or other items contained on a platform making them suitable for transport, stacking, and storage as a unit.
Unrestricted distribution	Signifies that such system data may be applied on goods to be processed anywhere in the world without restraint as to such things as country, company, and industry.
UPC-A Bar Code	A bar code of the EAN/UPC Symbology that encodes GTIN-12, Coupon-12, RCN-12, and VMN-12.
UPC-E Bar Code	A bar code of the EAN/UPC Symbology representing a GTIN-12 in six explicitly encoded digits using zero-suppression techniques.
Variable Measure Number (VMN)	A Restricted Circulation Number used to identify variable measure products for scanning at Point of Sale. It is defined per GS1 Member Organisation rules in their country (see VMN-12 and VMN-13).
Variable Measure Trade Item	A trade item which may be traded without a pre-defined measure, such as its weight or length.
VMN-12	The 12-digit Restricted Circulation Number encoded in UPC-A Symbols to allow scanning of variable measure products at Point of Sale. It is defined per target market specific rules that are associated with U.P.C. Prefix 2.
VMN-13	The 13-digit Restricted Circulation Number encoded in EAN-13 Symbols to allow scanning of variable measure products at Point of Sale. It is defined per target market specific rules that are associated with GS1 Prefixes 20 through 29.
Weight check digit	See Measure verifier digit.
Wide-to-narrow ratio	The ratio between the wide elements and the narrow elements in a bar code symbology such as ITF-14 that has two different element widths.
X-dimension	The specified width of the narrowest element of a bar code.

8.2. GS1 Abbreviations

Abbreviation	Term
ADC	Automatic Data Capture
AI	Application Identifier
AIDC	Automatic Identification and Data Capture
DPM	Direct Part Marking
EAN	EAN International, now called GS1
EDI	Electronic Data Interchange
EPC	Electronic Product Code
FNC1	Function 1 Symbol Character
GCN	Global Coupon Number
GDD	Global Data Dictionary
GDSN	Global Data Synchronization Network
GDTI	Global Document Type Identifier

Abbreviation	Term
GEPIR	Global Electronic Party Information Registry
GIAI	Global Individual Asset Identifier
GINC	Global Identification Number for Consignment
GLN	Global Location Number
GPC	Global Product Classification
GRAI	Global Returnable Asset Identifier
GRCTI	General Retail Consumer Trade Item
GS1 Key	GS1 Identification Key
GSIN	Global Shipment Identification Number
GSMP	Global Standards Management Process
GSRN	Global Service Relation Number
GTIN	Global Trade Item Number
HRI	Human Readable Interpretation
ISBN	International Standard Book Number
ISO	International Organization for Standardization
ISSN	International Standard Serial Number
LAC	Local Assigned Code
NHRN	National Healthcare Reimbursement Number
RCN	Restricted Circulation Number
RFID	Radio Frequency Identification
RHRCTI	Regulated Healthcare Retail Consumer Trade Item
RHTI	Regulated Healthcare Trade Item
RSS	Reduced Space Symbology
RZSC	Retailer Zero-Suppression Code.
SRIN	Service Relation Instance Number
VMN	Variable Measure Number

8.3. Legacy (Retired) Terms

When terms are replaced or retired by GS1, they are maintained within this section for a minimum of five years. The legacy terms are supplied to point GS1 stakeholders to new terminology. The period of five years ensures harmonization with external standards bodies whose standards make normative reference to the GS1 General Specifications.

Legacy Term	Current Term
EAN	GS1
EAN International	GS1 Global Office
EAN Member Organisation	GS1 Member Organisation
EAN.UCC Company Prefix	GS1 Company Prefix

Legacy Term	Current Term
EAN.UCC Prefix	GS1 Prefix
EAN.UCC XML	GS1 XML
EAN/UCC-8 Data Structure	GTIN-8
EAN/UCC-8 Identification Number	GTIN-8
EAN/UCC-12 Data Structure	See GTIN-12, Coupon-12, RCN-12, and VMN-12
EAN/UCC-12 Identification Number	See GTIN-12, GLN, GDTI, Coupon-12, RCN-12, and VMN-12
EAN/UCC-13 Data Structure	See GTIN-13, Coupon-13, RCN-13, and VMN-13
EAN/UCC-13 Identification Number	See GTIN-13, GLN, GDTI, Coupon-13, RCN-13, and VMN-13
EAN/UCC-14 Data Structure	GTIN-14
EAN/UCC-14 Identification Number	GTIN-14
Interleaved 2 of 5	ITF-14 Symbol
Item Number	Item Reference
Item Reference Number	Item Reference
Manufacturer's ID	No longer used
Manufacturer's Number	GS1Company Prefix
Number System Character	See U.P.C. Prefix
Numbering Organisation (NO)	GS1 Member Organisation
print gain/loss	bar gain/loss
Reduced Space Symbology	GS1 DataBar Symbology
RSS Composite Symbology Family	GS1 DataBar Composite Symbology Family
RSS Expanded Bar Code Symbol	GS1 DataBar Expanded Symbol
RSS Expanded Composite Symbology	GS1 DataBar Expanded Composite Symbology
RSS Expanded Stacked Bar Code Symbol	GS1 DataBar Expanded Stacked Symbol
RSS Expanded Stacked Composite Bar Code Symbol	GS1 DataBar Expanded Stacked Composite Symbology
RSS Limited Bar Code symbol	GS1 DataBar Limited Symbol
RSS Limited Composite Symbology	GS1 DataBar Limited Composite Symbology
RSS Omnidirectional	GS1 DataBar Retail POS Family
RSS-14 Bar Code Symbol	GS1 DataBar Omnidirectional Symbol
RSS-14 Composite Symbology	GS1 DataBar Composite Symbology
RSS-14 Stacked Bar Code Symbol	GS1 DataBar Stacked Symbol
RSS-14 Stacked Composite Symbology	GS1 DataBar Stacked Composite Symbology
SCC-14	Global Trade Item Number
SSCC Serial Number	Serial Reference
standard numbering structures	data structure
Symbol Control Character	symbology element



Legacy Term	Current Term
UCC	GS1 US
UCC Company Prefix	U.P.C. Company Prefix
UCC Prefix	U.P.C. Prefix
UCC-12 Data Structure	See GTIN-12, GDTI-12, Coupon -12, RCN-12, and VMN-12
UCC-12 Identification Number	See GTIN-12, GDTI-12, Coupon -12, RCN-12, and VMN-12
Uniform Code Council, Inc	GS1 US
Variable Measure Retail Item	See RCN